Oracle® Fusion Middleware

RESTful Server Runtime Reference for Oracle WebLogic Server Multitenant

12*c* (12.2.1.2.0)

E78021-01

September 2016

This reference describes the RESTful server runtime resources that are used to manage WebLogic Server Multitenant.

ORACLE

Oracle Fusion Middleware RESTful Server Runtime Reference for Oracle WebLogic Server Multitenant, 12*c* (12.2.1.2.0)

E78021-01

Copyright © 2015, 2016 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in preproduction status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

Contents

Preface lxxv

1 Resources

/management/weblogic 1-2

/management/weblogic/{version} 1-5

/management/weblogic/{version}/currentUser 1-9

/management/weblogic/{version}/serverRuntime 1-12

/management/weblogic/{version}/serverRuntime/bootPartition 1-14

/management/weblogic/{version}/serverRuntime/forceRestartPartition 1-16

/management/weblogic/{version}/serverRuntime/getRgState 1-18

/management/weblogic/{version}/serverRuntime/partitionRuntimes 1-20

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} 1-22

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes 1-27

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} 1-29

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime 1-33

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime 1-35

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks 1-37

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} 1-39

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel 1-41

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio

nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks 1-43

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks /{name} 1-45

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks /{name}/cancel 1-47

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks /{name}/subTasks 1-49

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks /{name}/subTasks/{name} 1-51

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks /{name}/subTasks/{name}/cancel 1-53

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/classRedefinitionRuntime/redefineClasses 1-55

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/coherenceClusterRuntime 1-58

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes 1-60

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes/{name} 1-62

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes 1-64

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} 1-66

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capac ityRuntime 1-68

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxT hreadsConstraintRuntime 1-70

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio

nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-72

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-74

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime 1-76

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache 1-78

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes 1-80

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} 1-82

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-84

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-86

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes 1-88

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} 1-90

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager 1-92

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-94

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-96

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-98

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-100

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes 1-102

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} 1-104

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager
1-106

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager
/capacityRuntime 1-108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager
/maxThreadsConstraintRuntime 1-110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager
/minThreadsConstraintRuntime 1-112

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager
/requestClassRuntime 1-114

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedThreadFactoryRuntimes 1-116

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/managedThreadFactoryRuntimes/{name} 1-118

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/maxThreadsConstraintRuntimes 1-120

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-122

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/minThreadsConstraintRuntimes 1-124

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-126

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/optionalPackageRuntimes 1-128

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio
nRuntimes/{name}/optionalPackageRuntimes/{name} 1-130

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes 1-132

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} 1-134

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes 1-136

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} 1-138

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes 1-140

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name} 1-142

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools 1-144

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes 1-146

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name} 1-148

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes 1-150

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} 1-152

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-154

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-156

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-158

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-160

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes 1-162

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} 1-164

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime 1-166

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports 1-168

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} 1-170

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations 1-173

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations 1-175

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} 1-177

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting 1-179

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers 1-181

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} 1-183

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc 1-185

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations 1-187

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} 1-189

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy 1-191

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm 1-193

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime 1-195

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime 1-197

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes 1-199

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} 1-201

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager 1-203

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-205

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-207

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-209

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-211

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes 1-213

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} 1-215

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-217

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-219

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-221

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-223

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-225

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes 1-227

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} 1-229

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime 1-231

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs 1-234

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} 1-236

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-239

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-241

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-244

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-246

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-248

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-250

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-252

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-254

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-256

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-258

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-260

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-262

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-264

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-266

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-268

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-272

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime 1-274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections 1-277

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA 1-279

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs 1-281

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-283

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-286

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-288

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-291

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-293

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-295

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-297

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-299

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-301

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-303

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-305

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-307

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-309

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-311

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-313

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-315

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-317

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-319

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-321

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-323

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-325

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-327

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-329

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-331

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-333

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-335

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name} 1-337

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-340

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-342

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resources 1-344

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-346

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resume 1-348

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/suspend 1-350

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-352

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
1-354

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-356

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resu
me 1-358

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resu
meAll 1-360

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/susp
end 1-362

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-364

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-366

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-368

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-370

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-372

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-374

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-376

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-378

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-380

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-382

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-384

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-386

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs 1-388

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} 1-390

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-393

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-395

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-398

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-400

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-402

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-404

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-406

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-408

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-410

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-412

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-414

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-416

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-418

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-420

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-422

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-424

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-426

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-428

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-430

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-432

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-434

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-436

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-438

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-440

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes 1-442

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name} 1-444

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/poolRuntime 1-447

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-449

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/resources 1-451

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/resources/{name} 1-453

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/resume 1-455

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/suspend 1-457

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/timerRuntime 1-459

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-461

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundCon
nections/{name}/MDBRuntimes/{name}/transactionRuntime 1-463

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume
1-465

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll
1-467

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-469

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-471

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-473

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-475

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-477

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-479

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-481

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-483

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-485

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-487

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-489

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-491

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-493

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume 1-495

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll 1-497

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend 1-499

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll 1-501

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-503

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-505

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-507

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-509

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-511

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-513

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-515

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-517

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-519

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-522

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-524

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-526

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-528

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-530

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-532

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-534

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-536

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-538

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-540

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-542

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-544

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-546

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-548

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-550

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-552

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-554

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-556

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-558

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-560

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-562

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-564

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-566

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-568

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections 1-570

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA 1-572

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs 1-574

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-576

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-579

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-581

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-584

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-586

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-588

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-590

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-592

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-594

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-596

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-598

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-600

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-602

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-604

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-606

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-608

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-610

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-612

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime 1-614

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs 1-617

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-619

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-622

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-624

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-627

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-629

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-631

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-633

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-635

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-637

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-639

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-641

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-643

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-645

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-647

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-649

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-651

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-653

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-655

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-657

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-659

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-661

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-663

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-665

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections 1-667

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name} 1-669

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes 1-671

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name} 1-673

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-676

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-678

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resources 1-680

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-682

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/resume 1-684

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/suspend 1-686

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-688

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers
1-690

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inbo
undConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-692

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-694

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-696

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-698

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-700

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-702

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-704

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-706

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-708

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-710

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-712

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-714

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-716

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-718

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-720

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-722

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections 1-724

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA 1-726

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs 1-728

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} 1-730

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-733

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-735

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-738

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-740

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-742

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-744

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-746

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/ensureLogOpened 1-748

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/flushLog 1-750

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/forceLogRotation 1-752

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/forceReset 1-754

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/logRuntime 1-756

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/logRuntime/ensureLogOpened 1-758

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/logRuntime/flushLog 1-760

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/logRuntime/forceLogRotation 1-762

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/reset 1-764

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectio nPools/{name}/testPool 1-766

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connector WorkManagerRuntime 1-768

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfig uration 1-770

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-772

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-774

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-776

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-778

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-780

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-782

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-784

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-787

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-789

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-791

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-793

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-795

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-797

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-799

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-801

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-803

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume 1-805

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-807

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-809

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-811

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-813

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-815

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-817

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-819

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-821

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes 1-823

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes/{name} 1-825

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes/{name}/capacityRuntime 1-827

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes/{name}/maxThreadsConstraintRuntime 1-829

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes/{name}/minThreadsConstraintRuntime 1-831

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan
agerRuntimes/{name}/requestClassRuntime 1-833

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume 1-835

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll 1-837

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend 1-839

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll 1-841

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-843

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/getConfiguration 1-845

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-847

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-849

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector
ServiceRuntime/inactiveRAs/{name}/getSchema 1-851

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-853

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-855

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-857

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-859

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-862

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-864

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-866

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-868

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-870

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-872

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-874

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-876

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-878

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-880

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-882

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-884

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-886

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-888

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-890

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-892

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-894

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-896

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-898

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-900

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-902

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-904

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-906

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-908

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs 1-910

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} 1-912

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-915

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-917

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-920

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-922

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-924

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-926

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-928

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-930

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-932

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-934

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-936

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-938

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-940

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-942

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-944

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-946

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-948

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime 1-950

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs 1-953

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-955

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-958

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-960

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-963

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-965

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-967

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-969

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-971

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-973

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-975

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-977

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-979

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-981

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-983

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-985

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-987

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-989

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-991

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-993

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-995

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-997

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-999

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-1001

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-1003

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-1005

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1007

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1009

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1012

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1014

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1016

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1018

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1020

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1022

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1024

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1026

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1028

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-1030

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-1032

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-1034

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-1036

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-1038

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-1040

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1042

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1044

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-1046

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-1048

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-1050

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1052

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1054

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1056

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1058

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections 1-1060

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA 1-1062

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs 1-1064

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-1066

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-1069

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-1071

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-1074

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-1076

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-1078

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-1080

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-1082

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-1084

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-1086

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-1088

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-1090

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-1092

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-1094

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-1096

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-1098

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-1100

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectio nPools/{name}/testPool 1-1102

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connector WorkManagerRuntime 1-1104

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfig uration 1-1106

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnec tionPool 1-1108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboun dConnection 1-1110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-1112

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections 1-1114

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections/{name} 1-1116

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections/{name}/MDBRuntimes 1-1118

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections/{name}/MDBRuntimes/{name} 1-1120

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1123

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC onnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1125

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1127

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1129

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1131

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1133

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1135

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1137

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1139

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-1141

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-1143

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-1145

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-1147

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-1149

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-1151

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1153

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1155

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-1157

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-1159

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-1161

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1163

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1165

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1167

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1169

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume 1-1171

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll 1-1173

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend 1-1175

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll 1-1177

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-1179

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-1181

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-1183

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-1185

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-1187

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-1189

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-1191

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1193

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1195

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1198

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1200

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1202

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1204

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1206

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1208

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1210

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1212

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1214

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume 1-1216

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-1218

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-1220

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-1222

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-1224

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-1226

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1228

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1230

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-1232

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-1234

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-1236

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1238

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1240

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1242

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1244

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume 1-1246

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll 1-1248

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend 1-1250

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll 1-1252

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown 1-1254

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup 1-1256

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend 1-1258

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup 1-1260

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState 1-1262

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt..... 1-1264

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime 1-1266

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans 1-1268

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-1270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown 1-1274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend 1-1276

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache 1-1278

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool 1-1280

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile 1-1282

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown 1-1284

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend 1-1286

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime 1-1288

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean 1-1290

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics 1-1292

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics 1-1294

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes 1-1296

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} 1-1298

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime 1-1300

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart

itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1302

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1304

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime 1-1306

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists 1-1308

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset 1-1310

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume 1-1312

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink 1-1314

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown 1-1316

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start 1-1318

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend 1-1320

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks 1-1322

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} 1-1324

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel 1-1326

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks 1-1328

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} 1-1330

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart

itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel 1-1332

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks 1-1334

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} 1-1336

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-1338

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool 1-1340

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1342

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1344

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1346

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1348

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1350

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1352

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans 1-1354

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} 1-1356

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1358

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1360

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1362

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1364

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1366

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1368

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime 1-1370

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections 1-1372

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} 1-1374

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy 1-1376

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions 1-1378

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} 1-1380

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers 1-1382

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} 1-1384

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers 1-1386

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} 1-1388

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers 1-1390

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} 1-1392

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/closeCursor 1-1395

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations 1-1397

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} 1-1399

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor 1-1402

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber 1-1404

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages 1-1406

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers 1-1408

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} 1-1410

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1413

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1415

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1417

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1420

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1422

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-1424

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1426

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-1428

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-1430

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-1432

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-1435

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-1437

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-1439

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-1441

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-1443

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-1445

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1447

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti

me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEnd Position 1-1449

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1451

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStar tPosition 1-1453

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages 1-1455

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort 1-1458

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/getCursorEndPosition 1-1460

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/getCursorSize 1-1462

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/getCursorStartPosition 1-1464

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/getMessages 1-1466

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/pauseConsumption 1-1469

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/pauseInsertion 1-1471

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/pauseProduction 1-1473

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/resumeConsumption 1-1475

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/resumeInsertion 1-1477

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/resumeProduction 1-1479

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti me/JMSServers/{name}/destinations/{name}/sort 1-1481

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceCommit 1-1483

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceRollback 1-1485

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorEndPosition 1-1487

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorSize 1-1489

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorStartPosition 1-1491

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getMessages 1-1493

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getTransactionStatus 1-1495

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime 1-1497

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened 1-1499

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog 1-1501

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation 1-1503

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseConsumption 1-1505

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseInsertion 1-1507

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction 1-1510

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption 1-1512

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion 1-1514

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction 1-1516

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes 1-1518

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} 1-1520

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers 1-1522

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} 1-1524

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer 1-1526

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor 1-1530

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations 1-1532

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} 1-1534

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor 1-1537

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber 1-1539

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages 1-1541

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers 1-1543

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} 1-1545

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti

me/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1548

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1550

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1552

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1556

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1558

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-1560

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1562

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-1564

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-1566

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-1568

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-1571

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-1573

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-1575

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-1577

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-1579

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-1581

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1583

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-1585

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1587

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-1589

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages 1-1591

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort 1-1594

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition 1-1596

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize 1-1598

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition 1-1600

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRunti

me/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages 1-1602

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption 1-1605

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion 1-1607

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction 1-1609

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption 1-1611

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion 1-1613

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction 1-1615

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort 1-1617

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit 1-1619

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback 1-1621

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition 1-1623

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize 1-1625

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition 1-1627

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages 1-1629

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus 1-1631

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime 1-1633

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened 1-1635

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog 1-1637

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation 1-1639

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption 1-1641

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion 1-1643

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction 1-1646

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption 1-1648

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion 1-1650

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction 1-1652

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort 1-1654

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sort 1-1656

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime 1-1658

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans 1-1660

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} 1-1662

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans 1-1664

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name} 1-1666

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans 1-1668

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} 1-1670

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes 1-1672

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} 1-1674

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-1676

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-1678

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes 1-1680

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name} 1-1682

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes 1-1684

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-1686

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes 1-1688

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name} 1-1690

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes 1-1692

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-1694

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime 1-1696

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime 1-1698

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime 1-1700

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime 1-1702

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime 1-1704

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes 1-1706

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} 1-1708

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies 1-1710

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} 1-1712

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor 1-1714

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition 1-1716

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize 1-1718

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition 1-1720

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries 1-1722

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove 1-1724

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes 1-1726

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} 1-1728

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections 1-1730

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name} 1-1732

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes 1-1734

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name} 1-1736

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime 1-1738

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes 1-1740

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} 1-1742

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime 1-1744

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes 1-1746

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name} 1-1748

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume ... 1-1750

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup 1-1752

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime 1-1754

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents 1-1756

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} 1-1758

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations 1-1761

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} 1-1763

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy 1-1765

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime 1-1767

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened 1-1769

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog 1-1771

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation 1-1773

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding 1-1775

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming 1-1777

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving 1-1779

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints 1-1781

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} 1-1783

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor 1-1786

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll 1-1788

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition 1-1790

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize 1-1792

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition 1-1794

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages 1-1796

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding 1-1798

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming 1-1800

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge 1-1802

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding 1-1804

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming 1-1806

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort 1-1808

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding 1-1810

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming 1-1812

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving 1-1814

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown 1-1816

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup 1-1819

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup 1-1822

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin 1-1824

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend.. 1-1826

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup 1-1828

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime 1-1831

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime 1-1833

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes 1-1835

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name} 1-1837

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor 1-1839

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords 1-1841

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount 1-1843

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData 1-1846

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor 1-1848

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime 1-1853

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes 1-1855

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name} 1-1857

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive 1-1859

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime 1-1861

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime 1-1863

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage 1-1865

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks 1-1867

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks 1-1869

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} 1-1871

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel 1-1873

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks 1-1875

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} 1-1877

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel 1-1879

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks 1-1881

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} 1-1883

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-1885

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages 1-1887

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout 1-1889

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime 1-1891

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm 1-1893

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource 1-1895

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes 1-1897

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} 1-1899

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1901

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1903

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1905

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1907

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime 1-1909

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting 1-1911

/management/weblogic/{version}/serverRuntime/search 1-1913

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime 1-1915

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole 1-1917

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes 1-1919

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} 1-1921

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes 1-1923

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes/{name} 1-1925

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime 1-1927

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/clearLockout 1-1929

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure 1-1931

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount 1-1933

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut 1-1935

/management/weblogic/{version}/serverRuntime/threadPoolRuntime 1-1937

/management/weblogic/{version}/serverRuntime/WLDFRuntime 1-1939

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime 1-1941

2 Entities

[3] com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean 2-1
[3] com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean 2-2
[3] java.lang.Throwable 2-3
[3] java.util.Date 2-4
[3] java.util.Properties 2-4
[3] weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean 2-4
[3] weblogic.health.HealthState 2-5
n weblogic.health.Symptom 2-5
n weblogic.management.rest.bean.model.CurrentUser 2-6
n weblogic.management.rest.bean.model.Version 2-6
n weblogic.management.runtime.ApplicationRuntimeMBean 2-7
n weblogic.management.runtime.AuthenticatorRuntimeMBean 2-8

- weblogic.management.runtime.BatchJobRepositoryRuntimeMBean 2-9
- weblogic.management.runtime.CapacityRuntimeMBean 2-9
- weblogic.management.runtime.ClassLoaderRuntimeMBean 2-9
- weblogic.management.runtime.CoherenceClusterRuntimeMBean 2-12
- weblogic.management.runtime.ComponentRuntimeMBean 2-13
- weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean 2-14
- weblogic.management.runtime.ConnectorComponentRuntimeMBean 2-15
- weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean 2-18
- weblogic.management.runtime.ConnectorConnectionRuntimeMBean 2-24
- weblogic.management.runtime.ConnectorInboundRuntimeMBean 2-26
- weblogic.management.runtime.ConnectorServiceRuntimeMBean 2-27
- weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean 2-27
- weblogic.management.runtime.EJBPoolRuntimeMBean 2-28
- weblogic.management.runtime.EJBTimerRuntimeMBean 2-29
- weblogic.management.runtime.EJBTransactionRuntimeMBean 2-30
- weblogic.management.runtime.FairShareConstraintRuntimeMBean 2-31
- weblogic.management.runtime.JDBCDataSourceRuntimeMBean 2-32
- weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean 2-37
- weblogic.management.runtime.JDBCDriverRuntimeMBean 2-39
- weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean 2-39
- weblogic.management.runtime.JDBCPartitionRuntimeMBean 2-40
- weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean 2-41
- weblogic.management.runtime.JMSConnectionRuntimeMBean 2-43
- weblogic.management.runtime.JMSConsumerRuntimeMBean 2-44
- weblogic.management.runtime.JMSDestinationRuntimeMBean 2-46
- weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean 2-49
- weblogic.management.runtime.JMSProducerRuntimeMBean 2-52
- weblogic.management.runtime.JMSRuntimeMBean 2-52
- weblogic.management.runtime.JMSServerRuntimeMBean 2-53
- weblogic.management.runtime.JMSSessionPoolRuntimeMBean 2-58
- weblogic.management.runtime.JMSSessionRuntimeMBean 2-58
- weblogic.management.runtime.JTAPartitionRuntimeMBean 2-60
- weblogic.management.runtime.LibraryRuntimeMBean 2-63
- weblogic.management.runtime.LogRuntimeMBean 2-64
- weblogic.management.runtime.MailSessionRuntimeMBean 2-65
- weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean 2-65
- weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean . 2-67
- weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean 2-68
- weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean 2-69
- weblogic.management.runtime.MessageDrivenEJBRuntimeMBean 2-70
- weblogic.management.runtime.MessagingBridgeRuntimeMBean 2-72
- weblogic.management.runtime.MinThreadsConstraintRuntimeMBean 2-72
- weblogic.management.runtime.NonXAResourceRuntimeMBean 2-74
- weblogic.management.runtime.PSAssemblyRuntimeMBean 2-75
- weblogic.management.runtime.PartitionFairShareRuntimeMBean 2-75
- weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean . 2-76
- weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean 2-77

- weblogic.management.runtime.PartitionRuntimeMBean 2-79
- weblogic.management.runtime.PartitionWorkManagerRuntimeMBean 2-80
- weblogic.management.runtime.PathServiceRuntimeMBean 2-81
- weblogic.management.runtime.PersistenceUnitRuntimeMBean 2-82
- weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean 2-82
- weblogic.management.runtime.PersistentStoreRuntimeMBean 2-83
- weblogic.management.runtime.QueryCacheRuntimeMBean 2-84
- weblogic.management.runtime.RealmRuntimeMBean 2-86
- weblogic.management.runtime.RequestClassRuntimeMBean 2-87
- weblogic.management.runtime.ResourceManagerRuntimeMBean 2-88
- weblogic.management.runtime.ResourceRuntimeMBean 2-88
- weblogic.management.runtime.RuntimeMBean 2-89
- weblogic.management.runtime.SAFAgentRuntimeMBean 2-89
- weblogic.management.runtime.SAFConversationRuntimeMBean 2-92
- weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean 2-93
- weblogic.management.runtime.SAFRuntimeMBean 2-96
- weblogic.management.runtime.ServerRuntimeMBean 2-96
- weblogic.management.runtime.ServerSecurityRuntimeMBean 2-98
- weblogic.management.runtime.TaskRuntimeMBean 2-98
- weblogic.management.runtime.ThreadPoolRuntimeMBean 2-100
- weblogic.management.runtime.TransactionNameRuntimeMBean 2-100
- weblogic.management.runtime.TransactionResourceRuntimeMBean 2-103
- weblogic.management.runtime.TriggerRuntimeMBean 2-104
- weblogic.management.runtime.UserLockoutManagerRuntimeMBean 2-106
- weblogic.management.runtime.WLDFDataAccessRuntimeMBean 2-107
- weblogic.management.runtime.WLDFHarvesterRuntimeMBean 2-108
- weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean 2-108
- weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean 2-110
- weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean 2-110
- weblogic.management.runtime.WLDFPartitionImageRuntimeMBean 2-111
- weblogic.management.runtime.WLDFPartitionRuntimeMBean 2-112
- weblogic.management.runtime.WLDFRuntimeMBean 2-112
- weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean 2-113
- weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean 2-117
- weblogic.management.runtime.WorkManagerRuntimeMBean 2-117
- weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean 2-119
- weblogic.management.runtime.WseeBaseOperationRuntimeMBean 2-122
- weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean 2-125
- weblogic.management.runtime.WseeClusterRoutingRuntimeMBean 2-126
- weblogic.management.runtime.WseeHandlerRuntimeMBean 2-127
- weblogic.management.runtime.WseeMcRuntimeMBean 2-127
- weblogic.management.runtime.WseeOperationRuntimeMBean 2-128
- weblogic.management.runtime.WseePolicyRuntimeMBean 2-131
- weblogic.management.runtime.WseePortPolicyRuntimeMBean 2-132
- weblogic.management.runtime.WseePortRuntimeMBean 2-134
- weblogic.management.runtime.WseeV2RuntimeMBean 2-135
- weblogic.management.runtime.WseeWsrmRuntimeMBean 2-137

Preface

This preface describes the document accessibility features and conventions used in this guide, *RESTful Server Runtime Reference for Oracle WebLogic Server Multitenant*.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
`monospace`	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

1

Resources

This documentation describes the Oracle WebLogic Server Multitenant RESTful server runtime resources that are used to monitor the Administration Server in the specified domain partition.

For a complete listing of the WLS REST reference documents and descriptions of their use, see *Administering Oracle WebLogic Server with RESTful Management Services*.

/management/weblogic

This resource is used to access the different versions of the resources in this domain.

The latest version is 12.2.1.2.0. The other versions, which are deprecated, are 12.2.1.0.0, 12.2.1.1.0.

For future releases, `latest` always refers to the most recent release.

All new and non-deprecated MBean features are available in all versions. Any MBean features that were deprecated in a version will not be available in that version or later versions, but will still be available using earlier versions.

To always use the latest resources, use `latest` in the URLs. Note that this might require updating a client when moving to a newer version of WebLogic Server. To fix the version so that an update is not required, use `12.2.1.2.0` in the URLs.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.rest.bean.model.Version instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.rest.bean.model.Version entities.

This method can return the following links:

- **uri**=/management/weblogic **rel**=canonical

  This resource.

- **uri**=/management/weblogic/12.2.1.2.0 **rel**=current

  Access the latest version of the WLS resources in the this domain.

- **uri**=/management/weblogic **rel**=self

  This resource.

Example

Example 1 View the versions collection.

This example uses the GET method to display the version instances in this collection.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic
```

Example Response

```
HTTP/1.1 200 OK

Response Body:
{
    "links": [
        {
            "rel": "self",
            "href": "http:\//localhost:7001/management/weblogic"
        },
        {
            "rel": "canonical",
            "href": "http:\//localhost:7001/management/weblogic"
        },
        {
            "rel": "current",
            "href": "http:\//localhost:7001/management/weblogic/12.2.1.2.0"
        }
    ],
    "items": [
        {
```

```
                "links": [
                    {
                        "rel": "self",
                        "href": "http:\//localhost:7001/management/12.2.1.0.0"
                    },
                    {
                        "rel": "canonical",
                        "href": "http:\//localhost:7001/management/12.2.1.0.0"
                    }
                ],
                "version": "12.2.1.0.0",
                "isLatest": false,
                "lifecycle": "deprecated"
            },
            {
                "links": [
                    {
                        "rel": "self",
                        "href": "http:\//localhost:7001/management/12.2.1.1.0"
                    },
                    {
                        "rel": "canonical",
                        "href": "http:\//localhost:7001/management/12.2.1.1.0"
                    }
                ],
                "version": "12.2.1.1.0",
                "isLatest": false,
                "lifecycle": "deprecated"
            },
            {
                "links": [
                    {
                        "rel": "self",
                        "href": "http:\//localhost:7001/management/12.2.1.2.0"
                    },
                    {
                        "rel": "canonical",
                        "href": "http:\//localhost:7001/management/12.2.1.2.0"
                    }
                ],
                "version": "12.2.1.2.0",
                "isLatest": true,
                "lifecycle": "active"
            }
        ]
    }
```

/management/weblogic/{version}

This resource describes the resource trees that are used to manage a WebLogic Server domain and its managed servers. The resource trees mimic the bean trees in WLST and allow you to view and edit configuration and monitor runtime behavior.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.rest.bean.model.Version instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.rest.bean.model.Version entity.

This method can return the following links:

- **uri**=/management/weblogic/{version} **rel**=canonical

  This resource.
- **uri**=/management/weblogic/{version}/currentUser **rel**=currentUser
- **uri**=/management/weblogic/{version}/domainConfig **rel**=domainConfig
- **uri**=/management/weblogic/{version}/domainRuntime **rel**=domainRuntime
- **uri**=/management/weblogic/{version}/edit **rel**=edit
- **uri**=/management/weblogic **rel**=parent

  The parent resource of this resource.
- **uri**=/management/weblogic/{version} **rel**=self

  This resource.
- **uri**=/management/weblogic/{version}/serverConfig **rel**=serverConfig
- **uri**=/management/weblogic/{version}/serverRuntime **rel**=serverRuntime

Example

Example 1 View the latest version.

This example uses the GET method to display the latest version.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/latest
```

Example Response

```
HTTP/1.1 200 OK

Response Body:
{
    "links": [
        {
            "rel": "parent",
            "href": "http:\//localhost:7001/management/weblogic"
        },
        {
```

```
            "rel": "self",
            "href": "http:\//localhost:7001/management/weblogic/latest"
        },
        {
            "rel": "canonical",
            "href": "http:\//localhost:7001/management/weblogic/latest"
        },
        {
            "rel": "edit",
            "href": "http:\//localhost:7001/management/weblogic/latest/edit"
        },
        {
            "rel": "domainConfig",
            "href":
"http:\//localhost:7001/management/weblogic/latest/domainConfig"
        },
        {
            "rel": "domainRuntime",
            "href":
"http:\//localhost:7001/management/weblogic/latest/domainRuntime"
        },
        {
            "rel": "serverRuntime",
            "href":
"http:\//localhost:7001/management/weblogic/latest/serverRuntime"
        },
        {
            "rel": "serverConfig",
            "href":
"http:\//localhost:7001/management/weblogic/latest/serverConfig"
        },
        {
            "rel": "currentUser",
            "href":
"http:\//localhost:7001/management/weblogic/latest/currentUser"
        }
    ],
    "version": "12.2.1.2.0",
    "isLatest": true,
    "lifecycle": "active"
}
```

Example 2 View a specific version.

This example uses the GET method to display a specific version.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/12.2.1.2.0
```

Example Response

```
HTTP/1.1 200 OK

Response Body:
{
    "links": [
```

```
            {
                "rel": "parent",
                "href": "http:\//localhost:7001/management/weblogic"
            },
            {
                "rel": "self",
                "href": "http:\//localhost:7001/management/weblogic/12.2.1.2.0"
            },
            {
                "rel": "canonical",
                "href": "http:\//localhost:7001/management/weblogic/12.2.1.2.0"
            },
            {
                "rel": "edit",
                "href": "http:\//localhost:7001/management/weblogic/12.2.1.2.0/edit"
            },
            {
                "rel": "domainConfig",
                "href":
"http:\//localhost:7001/management/weblogic/12.2.1.2.0/domainConfig"
            },
            {
                "rel": "domainRuntime",
                "href":
"http:\//localhost:7001/management/weblogic/12.2.1.2.0/domainRuntime"
            },
            {
                "rel": "serverRuntime",
                "href":
"http:\//localhost:7001/management/weblogic/12.2.1.2.0/serverRuntime"
            },
            {
                "rel": "serverConfig",
                "href":
"http:\//localhost:7001/management/weblogic/12.2.1.2.0/serverConfig"
            },
            {
                "rel": "currentUser",
                "href":
"http:\//localhost:7001/management/weblogic/12.2.1.2.0/currentUser"
            }
        ],
        "version": "12.2.1.2.0",
        "isLatest": true,
        "lifecycle": "active"
}
```

/management/weblogic/{version}/currentUser

This resource represents an authenticated user in the domain.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.rest.bean.model.CurrentUser instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.rest.bean.model.CurrentUser entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/currentUser **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/currentUser **rel**=self

  This resource.

Example

Example 1 Viewing the weblogic.management.rest.bean.model.CurrentUser Instance

This example uses the GET method to view this weblogic.management.rest.bean.model.CurrentUser instance.

Example Request

```
curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/latest/currentUser
```

Example Response

```
HTTP/1.1 200 OK

Response Body:
{
    "links": [
        {
            "rel": "parent",
            "href": "http:\//localhost:7001/management/weblogic/latest"
        },
        {
            "rel": "self",
            "href":
"http:\//localhost:7001/management/weblogic/latest/currentUser"
        },
        {
            "rel": "canonical",
            "href":
"http:\//localhost:7001/management/weblogic/latest/currentUser"
```

```
            }
        ],
        "partitionId": "0",
        "partitionName": "DOMAIN",
        "user": "admin"
    }
```

/management/weblogic/{version}/serverRuntime

This resource is used to monitor the administration server and managed servers.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ServerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ServerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=WLDFRuntime

  This resource's WLDFRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/bootPartition **rel**=action **title**=bootPartition

  This resource's bootPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceRestartPartition **rel**=action **title**=forceRestartPartition

  This resource's forceRestartPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getRgState **rel**=action **title**=getRgState

  This resource's getRgState action resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=partitionRuntimes

  This resource's partitionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/search **rel**=search

  This resource's search resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime **rel**=serverSecurityRuntime

  This resource's serverSecurityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/threadPoolRuntime **rel**=threadPoolRuntime

  This resource's threadPoolRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/bootPartition

The resource supports the following methods:

- POST

POST

Boots the partition

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

partitionName
name of the partition to boot

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/forceRestartPartition

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Performs a forced restart of the specified partition, waiting the specified time after the halt completes before executing the operation to return the partition to its state in this server at the time the `forceRestartPartition` method was invoked.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

partitionName
the partition to be restarted

Type: string

restartDelayMillis
time in milliseconds to wait after halt before restarting

Type: long

Response Body

Contains an empty JSON object.

POST

Performs a forced restart of the specified partition.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

partitionName
partitionName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/getRgState

The resource supports the following methods:

- POST

POST

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes

This resource manages a collection of weblogic.management.runtime.PartitionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PartitionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PartitionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}

This resource manages a weblogic.management.runtime.PartitionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PartitionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PartitionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=JDBCPartitionRuntime

  This resource's JDBCPartitionRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime **rel**=JMSRuntime

  This resource's JMSRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=JTAPartitionRuntime

  This resource's JTAPartitionRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime **rel**=SAFRuntime

  This resource's SAFRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=WLDFPartitionRuntime

  This resource's WLDFPartitionRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown **rel**=action **title**=forceShutdown

  This resource's forceShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup **rel**=action **title**=forceShutdownResourceGroup

  This resource's forceShutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend **rel**=action **title**=forceSuspend

  This resource's forceSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup **rel**=action **title**=forceSuspendResourceGroup

  This resource's forceSuspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState **rel**=action **title**=getRgState

  This resource's getRgState action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt **rel**=action **title**=halt

This resource's halt action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup **rel**=action **title**=resumeResourceGroup

  This resource's resumeResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown **rel**=action **title**=shutdown

  This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup **rel**=action **title**=shutdownResourceGroup

  This resource's shutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup **rel**=action **title**=startResourceGroup

  This resource's startResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin **rel**=action **title**=startResourceGroupInAdmin

  This resource's startResourceGroupInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup **rel**=action **title**=suspendResourceGroup

  This resource's suspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=applicationRuntimes

  This resource's applicationRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=batchJobRepositoryRuntime

  This resource's batchJobRepositoryRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=concurrentManagedObjectsRuntime

  This resource's concurrentManagedObjectsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=mailSessionRuntimes

  This resource's mailSessionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes

  This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=messagingBridgeRuntimes

  This resource's messagingBridgeRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes

  This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime **rel**=partitionResourceMetricsRuntime

  This resource's partitionResourceMetricsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=partitionWorkManagerRuntime

  This resource's partitionWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=pathServiceRuntimes

  This resource's pathServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=persistentStoreRuntimes

  This resource's persistentStoreRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes

  This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=resourceManagerRuntime

  This resource's resourceManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=wseeClusterFrontEndRuntime

This resource's wseeClusterFrontEndRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes

This resource manages a collection of weblogic.management.runtime.ApplicationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ApplicationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ApplicationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}

This resource manages a weblogic.management.runtime.ApplicationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ApplicationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ApplicationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime **rel**=action **title**=getPersistenceUnitRuntime

  This resource's getPersistenceUnitRuntime action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache **rel**=action **title**=hasApplicationCache

  This resource's hasApplicationCache action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools **rel**=action **title**=reInitializeApplicationCachesAndPools

  This resource's reInitializeApplicationCachesAndPools action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime **rel**=classLoaderRuntime

  This resource's classLoaderRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=classRedefinitionRuntime

  This resource's classRedefinitionRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=coherenceClusterRuntime

  This resource's coherenceClusterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=componentRuntimes

  This resource's componentRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

  This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes
  rel=managedExecutorServiceRuntimes

  This resource's managedExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes
  rel=managedScheduledExecutorServiceRuntimes

  This resource's managedScheduledExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes
  rel=managedThreadFactoryRuntimes

  This resource's managedThreadFactoryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes
  rel=maxThreadsConstraintRuntimes

  This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes
  rel=minThreadsConstraintRuntimes

  This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes
  rel=optionalPackageRuntimes

  This resource's optionalPackageRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes
  rel=persistenceUnitRuntimes

  This resource's persistenceUnitRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=queryCacheRuntimes

  This resource's queryCacheRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes

  This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes
  rel=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=wseeV2Runtimes

  This resource's wseeV2Runtimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime

This resource manages a weblogic.management.runtime.ClassLoaderRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ClassLoaderRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ClassLoaderRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime

This resource manages a com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses **rel**=action **title**=redefineClasses

  This resource's redefineClasses action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=classRedefinitionTasks

  This resource's classRedefinitionTasks collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks

This resource manages a collection of com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}

This resource manages a com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Initiate a class redefinition cycle, which will identify classes which may have changed and then attempt to redefine them. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Response Body

Contains a JSON object with a com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean reference return field.

POST

Initiate a class redefinition cycle, to redefine only the specified classes from given module. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task. If specified module name is null, any classes within the application (scoped to any modules as well as globally scoped classes) which are included in the list will be redefined.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

moduleName
Module from which the classes are to be redefined.

Type: string

classNames
Classes to be redefined.

Type: array of string

Response Body

Contains a JSON object with a com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime

This resource manages a weblogic.management.runtime.CoherenceClusterRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CoherenceClusterRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CoherenceClusterRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes

This resource manages a collection of weblogic.management.runtime.ComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}

This resource manages a weblogic.management.runtime.ComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime

The resource supports the following methods:

- POST

POST

Provides the PersistenceUnitRuntimeMBean for the application with the specified name.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

unitName
unitName

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.PersistenceUnitRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache

The resource supports the following methods:

- POST

POST

Returns true if the application has an (EJB) Application Level Cache

Roles

Admin, Operator

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes

This resource manages a collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.LibraryRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}

This resource manages a weblogic.management.runtime.LibraryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LibraryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LibraryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

  This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=workManager

  This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=workManager

  This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime
  rel=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime
  rel=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes

This resource manages a collection of weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes

This resource manages a collection of weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes

This resource manages a collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.LibraryRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}

This resource manages a weblogic.management.runtime.LibraryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LibraryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LibraryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

  This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes

This resource manages a collection of weblogic.management.runtime.PersistenceUnitRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PersistenceUnitRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PersistenceUnitRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name}

This resource manages a weblogic.management.runtime.PersistenceUnitRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PersistenceUnitRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PersistenceUnitRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes

This resource manages a collection of weblogic.management.runtime.QueryCacheRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.QueryCacheRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.QueryCacheRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}

This resource manages a weblogic.management.runtime.QueryCacheRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.QueryCacheRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.QueryCacheRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools

The resource supports the following methods:

- POST

POST

If the application has an (EJB) Application Level Cache, then this method will reinitialize the cache and any of its associated pools to their startup time states if possible.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes

This resource manages a collection of weblogic.management.runtime.RequestClassRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RequestClassRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RequestClassRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes

This resource manages a collection of weblogic.management.runtime.WseeV2RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WseeV2RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WseeV2RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}

This resource manages a weblogic.management.runtime.WseeV2RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeV2RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeV2RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=policyRuntime

  This resource's policyRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=ports

  This resource's ports collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime

This resource manages a weblogic.management.runtime.WseePolicyRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseePolicyRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseePolicyRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports

This resource manages a collection of weblogic.management.runtime.WseePortRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WseePortRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WseePortRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}

This resource manages a weblogic.management.runtime.WseePortRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseePortRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseePortRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations **rel**=aggregatedBaseOperations

  This resource's aggregatedBaseOperations singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=baseOperations

  This resource's baseOperations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=clusterRouting

  This resource's clusterRouting singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=handlers

  This resource's handlers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=mc

  This resource's mc singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=operations

  This resource's operations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=portPolicy

This resource's portPolicy singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=wsrm

  This resource's wsrm singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations

This resource manages a weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations

This resource manages a collection of weblogic.management.runtime.WseeBaseOperationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WseeBaseOperationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WseeBaseOperationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name}

This resource manages a weblogic.management.runtime.WseeBaseOperationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeBaseOperationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeBaseOperationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting

This resource manages a weblogic.management.runtime.WseeClusterRoutingRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeClusterRoutingRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeClusterRoutingRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers

This resource manages a collection of weblogic.management.runtime.WseeHandlerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WseeHandlerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WseeHandlerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}

This resource manages a weblogic.management.runtime.WseeHandlerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeHandlerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeHandlerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc

This resource manages a weblogic.management.runtime.WseeMcRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeMcRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeMcRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations

This resource manages a collection of weblogic.management.runtime.WseeOperationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WseeOperationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WseeOperationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}

This resource manages a weblogic.management.runtime.WseeOperationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeOperationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeOperationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy

This resource manages a weblogic.management.runtime.WseePortPolicyRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseePortPolicyRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseePortPolicyRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm

This resource manages a weblogic.management.runtime.WseeWsrmRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeWsrmRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeWsrmRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime

This resource manages a weblogic.management.runtime.BatchJobRepositoryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.BatchJobRepositoryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.BatchJobRepositoryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime

This resource manages a weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes **rel**=managedExecutorServiceRuntimes

  This resource's managedExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes **rel**=managedScheduledExecutorServiceRuntimes

  This resource's managedScheduledExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes **rel**=managedThreadFactoryRuntimes

  This resource's managedThreadFactoryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=workManager

  This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime
  rel=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime
  rel=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=workManager

  This resource's workManager singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes

This resource manages a collection of weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}

This resource manages a weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime

This resource manages a weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=RAs

  This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

  This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

  This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

  This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

  This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools
  rel=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime
  rel=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime
  rel=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections
  rel=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime
  rel=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes
  rel=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections

  This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime

This resource manages a weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs **rel**=RAs

  This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

  This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

  This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

  This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

  This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- POST

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a array of weblogic.management.runtime.ConnectorInboundRuntimeMBean references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- POST

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key
The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorComponentRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactive

RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs
  rel=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs
  rel=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{na

me}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

  This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- POST

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a array of weblogic.management.runtime.ConnectorInboundRuntimeMBean references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- POST

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key
The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorComponentRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools
  rel=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime
  rel=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime
  rel=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections
  rel=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime
  rel=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes
  rel=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

  This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime

This resource manages a weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=RAs

  This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

  This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

  This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

  This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

  This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/active

RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- POST

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a array of weblogic.management.runtime.ConnectorInboundRuntimeMBean references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- POST

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key
The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorComponentRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs
  rel=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs
  rel=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
  rel=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
  rel=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

  This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

  This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime

This resource manages a weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/RAs **rel**=RAs

  This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

  This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

  This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

  This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

  This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{na

me}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime
rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime
rel=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections

The resource supports the following methods:

- POST

POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a array of weblogic.management.runtime.ConnectorInboundRuntimeMBean references return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA

The resource supports the following methods:

- POST

POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

key
The JNDI name of the resource adapter.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorComponentRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs

This resource manages a collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorComponentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorComponentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}

This resource manages a weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorComponentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorComponentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

  This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

  This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

  This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

  This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

  This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

  This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

  This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

  This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

  This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

  This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

  This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

  This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections

This resource manages a collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}

This resource manages a weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

  This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

  This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

  This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete

The resource supports the following methods:

- POST

POST

Provides a way to manually close a connection through the console.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError

The resource supports the following methods:

- POST

POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection

The resource supports the following methods:

- POST

POST

Test the connection. Returns true if the test was successful.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset

The resource supports the following methods:

- POST

POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset

The resource supports the following methods:

- POST

POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool

The resource supports the following methods:

- POST

POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false it at least one failed the test.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
  rel=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}
  rel=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime

This resource manages a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration

The resource supports the following methods:

- POST

POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool

The resource supports the following methods:

- POST

POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

key
JNDI name or resource-link name of the connection pool.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection

The resource supports the following methods:

- POST

POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

messageListenerType
Message listener type.

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.ConnectorInboundRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema

The resource supports the following methods:

- POST

POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

version
String

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections

This resource manages a collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ConnectorInboundRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ConnectorInboundRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}

This resource manages a weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ConnectorInboundRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ConnectorInboundRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

  This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes

This resource manages a collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}

This resource manages a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessageDrivenEJBRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

  This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

  This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

  This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

  This resource's transactionRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime

This resource manages a weblogic.management.runtime.EJBPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

  This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool

The resource supports the following methods:

- POST

POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resumes the specific type of MDB by calling start on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

Roles

Admin

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime

This resource manages a weblogic.management.runtime.EJBTimerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTimerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTimerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

  This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers

The resource supports the following methods:

- POST

POST

Activate any temporarily disabled timers.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime

This resource manages a weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.EJBTransactionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.EJBTransactionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspend a particular type of activity for this resource adapter

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll

The resource supports the following methods:

- POST

POST

Resumes all activities of this resource adapter.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Resumes all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the specified type of activity for all RAs

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

props
Properties to pass on to the RA or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends the specified type of activity for all RAs.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

type
int The type of activity(ies), see weblogic.connector.extensions.Suspendable

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

props
Properties to be passed to the resource adapters or null

Type: java.util.Properties

Response Body

Contains an empty JSON object.

POST

Suspends all activities of all resource adapters.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown

The resource supports the following methods:

- POST

POST

Force shutdown the partition. Causes the partition to reject new requests and fail pending requests.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup

The resource supports the following methods:

- POST

POST

Force shutdown the resource group. Causes the resource group to reject new requests and fail pending requests.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend

The resource supports the following methods:

- POST

POST

Transitions the partition from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are transitioned to admin mode. This forcefully suspends the partition and transitions it to `ADMIN` state.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup

The resource supports the following methods:

- POST

POST

Transitions the resource group from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This forcefully suspends the resource group and transitions it `ADMIN` state.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState

The resource supports the following methods:

- POST

POST

The current state of the named resource group MBean

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
the resource group name

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt

The resource supports the following methods:

- POST

POST

Halts the partition.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime

This resource manages a weblogic.management.runtime.JDBCPartitionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCPartitionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCPartitionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans
  rel=JDBCDataSourceRuntimeMBeans

  This resource's JDBCDataSourceRuntimeMBeans collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans
  rel=JDBCMultiDataSourceRuntimeMBeans

  This resource's JDBCMultiDataSourceRuntimeMBeans collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans

This resource manages a collection of weblogic.management.runtime.JDBCDataSourceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JDBCDataSourceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JDBCDataSourceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}

This resource manages a weblogic.management.runtime.JDBCDataSourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCDataSourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=JDBCDriverRuntime

  This resource's JDBCDriverRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=JDBCReplayStatisticsRuntimeMBean

  This resource's JDBCReplayStatisticsRuntimeMBean singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown **rel**=action **title**=asyncShutdown

  This resource's asyncShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend **rel**=action **title**=asyncSuspend

  This resource's asyncSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache **rel**=action **title**=clearStatementCache

  This resource's clearStatementCache action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool **rel**=action **title**=dumpPool

  This resource's dumpPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile **rel**=action **title**=dumpPoolProfile

  This resource's dumpPoolProfile action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown **rel**=action **title**=forceShutdown

  This resource's forceShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend **rel**=action **title**=forceSuspend

  This resource's forceSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists **rel**=action **title**=poolExists

  This resource's poolExists action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset **rel**=action **title**=reset

  This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume **rel**=action **title**=resume

  This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink **rel**=action **title**=shrink

  This resource's shrink action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown **rel**=action **title**=shutdown

  This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start **rel**=action **title**=start

  This resource's start action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend **rel**=action **title**=suspend

  This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool **rel**=action **title**=testPool

  This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=canonical

  This resource.

- **rel**=lastTask

  This resource's lastTask reference to a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=tasks

  This resource's tasks collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown

The resource supports the following methods:

- POST

POST

Gracefully, asynchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

Setting IgnoreInUseConnectionsEnabled to false causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

operationSecs
The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use Inactive Connection Timeout Seconds if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: int

Response Body

Contains a JSON object with a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend

The resource supports the following methods:

- POST

POST

Asynchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later. These connections remain in the pool and are not closed because the pool may be resumed.

Setting IgnoreInUseConnectionsEnabled to false causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

operationSecs
The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use Inactive Connection Timeout Seconds if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: int

Response Body

Contains a JSON object with a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache

The resource supports the following methods:

- POST

POST

For each connection in the connection pool, clears the statement cache of Prepared and Callable Statements.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool

The resource supports the following methods:

- POST

POST

Prints out information about all the connections in the connection pool in the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile

The resource supports the following methods:

- POST

POST

Prints out profile information about the data source.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown

The resource supports the following methods:

- POST

POST

Forcefully shuts down a data source that has a health state of `Running`, including forcing the disconnection of all current connection users.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend

The resource supports the following methods:

- POST

POST

Forcefully suspends a data source that has the health state of `Running`, including disconnecting all current connection users. All current connections are closed and recreated.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime

This resource manages a weblogic.management.runtime.JDBCDriverRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCDriverRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCDriverRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean

This resource manages a weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics **rel**=action **title**=clearStatistics

  This resource's clearStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics **rel**=action **title**=refreshStatistics

  This resource's refreshStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics

The resource supports the following methods:

- POST

POST

Clear the statistics on all connections.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics

The resource supports the following methods:

- POST

POST

Update the snapshot

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists

The resource supports the following methods:

- POST

POST

Specifies whether a data source with the given name exists.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

poolName
Name of the pool being looked for

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset

The resource supports the following methods:

- POST

POST

Resets the connection pool in the data source by shutting down and recreating all available database connections in the pool.

Use when a data source is in the health state of `Unhealthy` and needs to be reinitialized.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume

The resource supports the following methods:

- POST

POST

Restores all access to and operations on a data source that has a health state of `Suspended`

If successful, the health state is set to `Running`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink

The resource supports the following methods:

- POST

POST

Shrinks the database connection pool in the data source to either the current number of reserved connections or the initial size of the connection pool, which ever is greater.

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown

The resource supports the following methods:

- POST

POST

Gracefully, synchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start

The resource supports the following methods:

- POST

POST

Starts a data source that has a health state of `Shutdown`

If successful, the health state is set to `Running`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend

The resource supports the following methods:

- POST

POST

Synchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later. If graceful suspend is done as part of a graceful shutdown operation, connections are immediately closed when no longer reserved or at the end of the timeout period. If not done as part of a shutdown operation, these connections remain in the pool and are not closed because the pool may be resumed.

By default, the timeout period is 60 seconds. You can change the value of this timeout period by configuring or dynamically setting Inactive Connection Timeout Seconds to a non-zero value.

Setting IgnoreInUseConnectionsEnabled to false causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks

This resource manages a collection of weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}

This resource manages a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool

The resource supports the following methods:

- POST

POST

Tests the connection pool in the data source by reserving and releasing a connection from it.

If the pool configuration attribute TestConnectionsOnReserve is enabled, the acquired connection is also tested as part of the reserve operation.

Roles

Admin

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime
  rel=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime
  rel=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans

This resource manages a collection of weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}

This resource manages a weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes

  This resource's workManagerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime

This resource manages a weblogic.management.runtime.JMSRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=JMSServers

  This resource's JMSServers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections **rel**=connections

  This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections

This resource manages a collection of weblogic.management.runtime.JMSConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}

This resource manages a weblogic.management.runtime.JMSConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy **rel**=action **title**=destroy

  This resource's destroy action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions **rel**=sessions

  This resource's sessions collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy

The resource supports the following methods:

- POST

POST

Destroys server side context for the connection.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions

This resource manages a collection of weblogic.management.runtime.JMSSessionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSSessionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSSessionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}

This resource manages a weblogic.management.runtime.JMSSessionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSSessionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSSessionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=consumers

  This resource's consumers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers **rel**=producers

  This resource's producers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers

This resource manages a collection of weblogic.management.runtime.JMSConsumerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSConsumerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSConsumerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}

This resource manages a weblogic.management.runtime.JMSConsumerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSConsumerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSConsumerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers

This resource manages a collection of weblogic.management.runtime.JMSProducerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSProducerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSProducerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}

This resource manages a weblogic.management.runtime.JMSProducerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSProducerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSProducerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers

This resource manages a collection of weblogic.management.runtime.JMSServerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSServerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSServerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}

This resource manages a weblogic.management.runtime.JMSServerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSServerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSServerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceCommit **rel**=action **title**=forceCommit

  This resource's forceCommit action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceRollback **rel**=action **title**=forceRollback

  This resource's forceRollback action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getTransactionStatus **rel**=action **title**=getTransactionStatus

  This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseConsumption **rel**=action **title**=pauseConsumption

  This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseInsertion **rel**=action **title**=pauseInsertion

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=destinations

  This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=sessionPoolRuntimes

  This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations

This resource manages a collection of weblogic.management.runtime.JMSDestinationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSDestinationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSDestinationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}

This resource manages a weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDestinationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

  This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption **rel**=action **title**=pauseConsumption

  This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion

  This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=durableSubscribers

  This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber

The resource supports the following methods:

- POST

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID
An identifier that uniquely identifies a client connection.

Type: string

subscriptionName
The name used to identify this subscription.

Type: string

selector
Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal
If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers

This resource manages a collection of weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}

This resource manages a weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

  This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime

This resource manages a weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDestinationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

  This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action **title**=pauseConsumption

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion

  This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers

  This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- POST

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID
An identifier that uniquely identifies a client connection.

Type: string

subscriptionName
The name used to identify this subscription.

Type: string

selector
Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal
If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceCommit

The resource supports the following methods:

- POST

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceRollback

The resource supports the following methods:

- POST

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getMessages

The resource supports the following methods:

- POST

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/getTransactionStatus

The resource supports the following methods:

- POST

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the appearance of any messages on all the destinations of the JMSServer, that are result of the in-flight work completion on all the destinations hosted by this JMSServer.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

    Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

    These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

    These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

    These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

    These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

    These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

    If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

  These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

  These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operation on all the destinations hosted by the JMSSever.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are alloed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes

This resource manages a collection of weblogic.management.runtime.JMSSessionPoolRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSSessionPoolRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSSessionPoolRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}

This resource manages a weblogic.management.runtime.JMSSessionPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSSessionPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSSessionPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=JMSServer

  This resource's JMSServer singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=connectionConsumers

  This resource's connectionConsumers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers

This resource manages a collection of weblogic.management.runtime.JMSConsumerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSConsumerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSConsumerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}

This resource manages a weblogic.management.runtime.JMSConsumerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSConsumerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSConsumerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer

This resource manages a weblogic.management.runtime.JMSServerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSServerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSServerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit **rel**=action **title**=forceCommit

  This resource's forceCommit action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback **rel**=action **title**=forceRollback

  This resource's forceRollback action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus **rel**=action **title**=getTransactionStatus

  This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption **rel**=action **title**=pauseConsumption

  This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion **rel**=action **title**=pauseInsertion

  This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=destinations

  This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sessionPoolRuntimes **rel**=sessionPoolRuntimes

  This resource's sessionPoolRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations

This resource manages a collection of weblogic.management.runtime.JMSDestinationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.JMSDestinationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.JMSDestinationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}

This resource manages a weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDestinationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

  This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption **rel**=action **title**=pauseConsumption

  This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion

  This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=durableSubscribers

  This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber

The resource supports the following methods:

- POST

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID
An identifier that uniquely identifies a client connection.

Type: string

subscriptionName
The name used to identify this subscription.

Type: string

selector
Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal
If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers

This resource manages a collection of weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of
weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of
weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}

This resource manages a weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

  This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime

This resource manages a weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JMSDestinationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JMSDestinationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

  This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

  This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action **title**=pauseConsumption

  This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion

  This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction

  This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption

  This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion

  This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction

  This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers

  This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber

The resource supports the following methods:

- POST

POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

ClientID
An identifier that uniquely identifies a client connection.

Type: string

subscriptionName
The name used to identify this subscription.

Type: string

selector
Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

noLocal
If set, inhibits the delivery of messages published by its own connection.

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages

The resource supports the following methods:

- POST

POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A JMS message selector to identify which messages to delete.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

state
A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

Type: int

Response Body

Contains a JSON object with a string return field.

POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector.

Type: string

timeout
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the insertion on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the production on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the insertion operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the production operations on the destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit

The resource supports the following methods:

- POST

POST

Causes the work associated with the specified transaction branch to be committed.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback

The resource supports the following methods:

- POST

POST

Causes the work associated with the specified transaction branch to be rolled back.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages

The resource supports the following methods:

- POST

POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An Xid in string representation for a JMS transaction branch.

Type: string

timeoutSeconds
The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus

The resource supports the following methods:

- POST

POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

xid
An Xid in string representation for a JMS transaction branch.

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption

The resource supports the following methods:

- POST

POST

Pauses the consumption operation on all the destinations hosted by the JMSServer.

When the JMSServer is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion

The resource supports the following methods:

- POST

POST

Pauses the appearance of any messages on all the destinations of the JMSServer, that are result of the in-flight work completion on all the destinations hosted by this JMSServer.

Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

    Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

    These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

    These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

    These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

    These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

    These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

    If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

  These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

  These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction

The resource supports the following methods:

- POST

POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption

The resource supports the following methods:

- POST

POST

Resumes the consumption operation on all the destinations hosted by the JMSSever.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion

The resource supports the following methods:

- POST

POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are alloed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction

The resource supports the following methods:

- POST

POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor.

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The JMS header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime

This resource manages a weblogic.management.runtime.JTAPartitionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.JTAPartitionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.JTAPartitionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans **rel**=nonXAResourceRuntimeMBeans

  This resource's nonXAResourceRuntimeMBeans collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans **rel**=transactionNameRuntimeMBeans

  This resource's transactionNameRuntimeMBeans collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans **rel**=transactionResourceRuntimeMBeans

  This resource's transactionResourceRuntimeMBeans collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans

This resource manages a collection of weblogic.management.runtime.NonXAResourceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.NonXAResourceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.NonXAResourceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name}

This resource manages a weblogic.management.runtime.NonXAResourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.NonXAResourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.NonXAResourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans

This resource manages a collection of weblogic.management.runtime.TransactionNameRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TransactionNameRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TransactionNameRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}

This resource manages a weblogic.management.runtime.TransactionNameRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TransactionNameRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TransactionNameRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans

This resource manages a collection of weblogic.management.runtime.TransactionResourceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TransactionResourceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TransactionResourceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name}

This resource manages a weblogic.management.runtime.TransactionResourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TransactionResourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TransactionResourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes

This resource manages a collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.LibraryRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.LibraryRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}

This resource manages a weblogic.management.runtime.LibraryRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LibraryRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LibraryRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

  This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of weblogic.management.runtime.RuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}

This resource manages a weblogic.management.runtime.RuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes

This resource manages a collection of weblogic.management.runtime.MailSessionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MailSessionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MailSessionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}

This resource manages a weblogic.management.runtime.MailSessionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MailSessionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MailSessionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes

This resource manages a collection of weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes

This resource manages a collection of weblogic.management.runtime.MessagingBridgeRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MessagingBridgeRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MessagingBridgeRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}

This resource manages a weblogic.management.runtime.MessagingBridgeRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MessagingBridgeRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MessagingBridgeRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes

This resource manages a collection of weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime

This resource manages a weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime

This resource manages a weblogic.management.runtime.PartitionWorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PartitionWorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PartitionWorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime **rel**=fairShareRuntime

  This resource's fairShareRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime **rel**=minThreadsConstraintCapRuntime

  This resource's minThreadsConstraintCapRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **el**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime

This resource manages a weblogic.management.runtime.PartitionFairShareRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PartitionFairShareRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PartitionFairShareRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime

This resource manages a weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes

This resource manages a collection of weblogic.management.runtime.PathServiceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PathServiceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PathServiceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **el**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}

This resource manages a weblogic.management.runtime.PathServiceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PathServiceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PathServiceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies **rel**=assemblies

  This resource's assemblies collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies

This resource manages a collection of weblogic.management.runtime.PSAssemblyRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PSAssemblyRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PSAssemblyRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}

This resource manages a weblogic.management.runtime.PSAssemblyRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PSAssemblyRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PSAssemblyRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries **rel**=action **title**=getMapEntries

  This resource's getMapEntries action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove **rel**=action **title**=remove

  This resource's remove action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries

The resource supports the following methods:

- POST

POST

Returns all entries in a persistent map's assembly.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

timeout
how many seconds till operatoin times out. Zero is an infinite timeout.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove

The resource supports the following methods:

- POST

POST

Remove the path service entry referenced by this object.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
the handle to the cursor

Type: string

itemHandle
the handle to a specific item in the cursor

Type: int

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes

This resource manages a collection of weblogic.management.runtime.PersistentStoreRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PersistentStoreRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PersistentStoreRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}

This resource manages a weblogic.management.runtime.PersistentStoreRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PersistentStoreRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PersistentStoreRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections **rel**=connections

  This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections

This resource manages a collection of weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}

This resource manages a weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes

This resource manages a collection of weblogic.management.runtime.RequestClassRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RequestClassRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RequestClassRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime

This resource manages a weblogic.management.runtime.ResourceManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ResourceManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ResourceManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes **rel**=resourceRuntimes

  This resource's resourceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes

This resource manages a collection of weblogic.management.runtime.ResourceRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.ResourceRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.ResourceRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}

This resource manages a weblogic.management.runtime.ResourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ResourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ResourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime **rel**=fairShareConstraintRuntime

  This resource's fairShareConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes **rel**=triggerRuntimes

  This resource's triggerRuntimes collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime

This resource manages a weblogic.management.runtime.FairShareConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.FairShareConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.FairShareConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes

This resource manages a collection of weblogic.management.runtime.TriggerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TriggerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TriggerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}

This resource manages a weblogic.management.runtime.TriggerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TriggerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TriggerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}
  rel=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}
  rel=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume

The resource supports the following methods:

- POST

POST

Resume a suspended partition. Allow new requests. This operation transitions the partition into `RUNNING` state.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup

The resource supports the following methods:

- POST

POST

Resume suspended resource group. Allow new requests. This operation transitions the resource group into `RUNNING` state.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime

This resource manages a weblogic.management.runtime.SAFRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.SAFRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.SAFRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents **rel**=agents

  This resource's agents collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents

This resource manages a collection of weblogic.management.runtime.SAFAgentRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.SAFAgentRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.SAFAgentRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}

This resource manages a weblogic.management.runtime.SAFAgentRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.SAFAgentRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.SAFAgentRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding **rel**=action **title**=pauseForwarding

  This resource's pauseForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming **rel**=action **title**=pauseIncoming

  This resource's pauseIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving **rel**=action **title**=pauseReceiving

  This resource's pauseReceiving action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding **rel**=action **title**=resumeForwarding

  This resource's resumeForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming **rel**=action **title**=resumeIncoming

  This resource's resumeIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving **rel**=action **title**=resumeReceiving

  This resource's resumeReceiving action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=conversations

  This resource's conversations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=logRuntime

  This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=remoteEndpoints

  This resource's remoteEndpoints collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations

This resource manages a collection of weblogic.management.runtime.SAFConversationRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.SAFConversationRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.SAFConversationRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}

This resource manages a weblogic.management.runtime.SAFConversationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.SAFConversationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.SAFConversationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy **rel**=action **title**=destroy

  This resource's destroy action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy

The resource supports the following methods:

- POST

POST

Destroys the conversation and purges all the messages.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime

This resource manages a weblogic.management.runtime.LogRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.LogRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.LogRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

  This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

  This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

  This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened

The resource supports the following methods:

- POST

POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog

The resource supports the following methods:

- POST

POST

Flushes the buffer to the log file on disk.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation

The resource supports the following methods:

- POST

POST

Forces the rotation of the underlying log immediately.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding

The resource supports the following methods:

- POST

POST

Pauses the sending agent on forwarding messages so that the agent will not forward messages but will accept new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming

The resource supports the following methods:

- POST

POST

Pauses the sending agent on accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving

The resource supports the following methods:

- POST

POST

Pauses the receiving agent on receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints

This resource manages a collection of weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}

This resource manages a weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll **rel**=action **title**=expireAll

  This resource's expireAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

  This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize **rel**=action **title**=getCursorSize

  This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

  This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages **rel**=action **title**=getMessages

  This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding **rel**=action **title**=pauseForwarding

  This resource's pauseForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming **rel**=action **title**=pauseIncoming

  This resource's pauseIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge **rel**=action **title**=purge

  This resource's purge action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding **rel**=action **title**=resumeForwarding

  This resource's resumeForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming **rel**=action **title**=resumeIncoming

  This resource's resumeIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort **rel**=action **title**=sort

  This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll

The resource supports the following methods:

- POST

POST

All pending messages for a remote destination are processed according to the policy specified by the associated Error Handling configuration and then removed.

- When selected, `expireAll` is performed asynchronously by the server.
- Oracle recommends that the remote endpoint is paused for incoming messages prior to expiring messages. When all pending messages are processed and removed, the remote endpoint can be set to resume and accept new messages.
- The state of the `expireAll` operation can be determined by the `getOperationState` method.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition

The resource supports the following methods:

- POST

POST

Returns the cursor end position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize

The resource supports the following methods:

- POST

POST

Returns the number of items in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition

The resource supports the following methods:

- POST

POST

Returns the cursor start position in the result set.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The cursor handle.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages

The resource supports the following methods:

- POST

POST

Queries messages on the queue according to the message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. If the cursor expires, the associated resources are released.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

selector
A valid JMS message selector or SAF message selector.

Type: string

timeout
Specifies the amount of time the message cursor is valid. A value of 0 indicates the cursor does not expire.

Type: int

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding

The resource supports the following methods:

- POST

POST

Pauses the forwarding of messages for a remote endpoint. The agent accepts new messages but does not forward them.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming

The resource supports the following methods:

- POST

POST

Pauses a remote endpoint so that new messages are not accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge

The resource supports the following methods:

- POST

POST

Destroys all conversations and purges all the pending messages for a remote destination.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding

The resource supports the following methods:

- POST

POST

Resumes the forwarding of messages for the remote endpoint.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming

The resource supports the following methods:

- POST

POST

Resumes a remote endpoint so that new messages are accepted.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort

The resource supports the following methods:

- POST

POST

Sorts the entire message result set managed by the cursor according to the SAF header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

Roles

Admin, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorHandle
The handle of the cursor on which to perform the sort operation

Type: string

start
The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

Type: long

fields
The SAF header attributes on which to sort.

Type: array of string

ascending
Determines whether the sort of the corresponding fields element is in ascending or descending order.

Type: array of boolean

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding

The resource supports the following methods:

- POST

POST

Resumes the sending agent for forwarding messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming

The resource supports the following methods:

- POST

POST

Resumes the sending agent for accepting new messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving

The resource supports the following methods:

- POST

POST

Resumes the receiving agent for receiving messages.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST
- POST

POST

Gracefully shuts down the partition after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the partition is completing inflight work. For example, a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown is taking too long to complete.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout
Number of seconds to wait before aborting inflight work and shutting down the partition.

Type: int

ignoreSessions
`true` indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions
`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout
timeout

Type: int

ignoreSessions
ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST
- POST

POST

Gracefully shuts down the resource group after handling inflight work.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work. Optionally, ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown takes a long time.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

timeout
Number of seconds to wait before aborting inflight work and shutting down the partition.

Type: int

ignoreSessions
`true` indicates ignore pending HTTP sessions during inflight work handling.

Type: boolean

waitForAllSessions
`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

Type: boolean

Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

timeout
timeout

Type: int

ignoreSessions
ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup

The resource supports the following methods:

- POST

POST

starts the resource group.

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
The resource group name

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin

The resource supports the following methods:

- POST

POST

Starts the resource group in ADMIN state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends the partition. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Response Body

Contains an empty JSON object.

POST

Transitions the partition from `RUNNING` to `ADMIN` state gracefully.

Applications are in admin mode. Inflight work is completed. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

timeout
Seconds to wait for partition to transition gracefully. The forceSuspend() is called after timeout.

Type: int

ignoreSessions
drop inflight HTTP sessions during graceful suspend

Type: boolean

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

timeout
timeout

Type: int

ignoreSessions
ignoreSessions

Type: boolean

Response Body

Contains an empty JSON object.

POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

Roles

Admin, Operator

Request Body

Must contain a JSON object with the following fields:

resourceGroupName
resourceGroupName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime

This resource manages a weblogic.management.runtime.WLDFPartitionRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFPartitionRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFPartitionRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime
  rel=WLDFPartitionAccessRuntime

  This resource's WLDFPartitionAccessRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime
  rel=WLDFPartitionHarvesterRuntime

  This resource's WLDFPartitionHarvesterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime
  rel=WLDFPartitionImageRuntime

  This resource's WLDFPartitionImageRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime
  rel=WLDFWatchNotificationRuntime

  This resource's WLDFWatchNotificationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}
  rel=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime

This resource manages a weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes **rel**=WLDFDataAccessRuntimes

  This resource's WLDFDataAccessRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime **rel**=action **title**=lookupWLDFDataAccessRuntime

  This resource's lookupWLDFDataAccessRuntime action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes **rel**=dataAccessRuntimes

  This resource's dataAccessRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes

This resource manages a collection of weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}

This resource manages a weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor **rel**=action **title**=closeCursor

  This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords **rel**=action **title**=deleteDataRecords

  This resource's deleteDataRecords action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount **rel**=action **title**=getDataRecordCount

  This resource's getDataRecordCount action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData **rel**=action **title**=hasMoreData

  This resource's hasMoreData action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor **rel**=action **title**=openCursor

  This resource's openCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor

The resource supports the following methods:

- POST

POST

Disposes of the cursor once the client has fetched all the records.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName
cursorName

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords

The resource supports the following methods:

- POST

POST

Delete records within the specified time range that match the specified query. If the query is null or empty, all records within the time range will be deleted.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Not all archives support a deletion feature. If not supported, this method will throw an UnsupportedOperationException exception.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime
Start time of the interval (inclusive)

Type: long

endTime
End time of the interval (exclusive)

Type: long

queryString
Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST
- POST

POST

The number of records that match the specified query and time range.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startTime
Start time of the interval (inclusive)

Type: long

endTime
End time of the interval (exclusive)

Type: long

query
Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number of records that match the specified query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query
Query expression

Type: string

Response Body

Contains a JSON object with a int return field.

POST

The number that match the specified query and record-ID range, and whose timestamp (if it is available) is earlier than the specified end time.

The end time is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

startRecordId
Record id of the first record

Type: long

endRecordId
Look at records whose record-ids are smaller than specified endrecordId

Type: long

endTime
Look at records which were entered prior to endTime

Type: long

query
Query criterion

Type: string

Response Body

Contains a JSON object with a int return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData

The resource supports the following methods:

- POST

POST

Determines whether the specified cursor has more data to be fetched.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

cursorName
cursorName

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST
- POST
- POST
- POST
- POST

POST

Opens a cursor with the specified timeout value, in milliseconds.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query
The query expression to filter the result set from the underlying diagnostic log.

Type: string

cursorTimeout
The timeout interval after which the cursor will become invalid if not invoked.

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor for records that meet the specified time range and query condition. The timeout value for the cursor is also specified.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp
beginTimestamp

Type: long

endTimestamp
endTimestamp

Type: long

query
query

Type: string

cusorTimeout
cusorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor on the server side for the query.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

query
The query expression to filter the result set from the underlying diagnostic log.

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with the specified query and time range.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginTimestamp
beginTimestamp

Type: long

endTimestamp
endTimestamp

Type: long

query
query

Type: string

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor using the specified record-ID range, end timestamp, and query. The timeout value for the cursor is also specified.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId
Record id of the first record (inclusive) in the result set

Type: long

endRecordId
Record id of the last record (exclusive) in the result set

Type: long

endTimestamp
Include only those records whose timestamp is earlier than this value

Type: long

query
Query criterion

Type: string

cusorTimeout
cusorTimeout

Type: long

Response Body

Contains a JSON object with a string return field.

POST

Opens a cursor with a given query and a record-id range.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

beginRecordId
Record id of the first record (inclusive) in the result set

Type: long

endRecordId
Record id of the last record (exclusive) in the result set

Type: long

endTimestamp
Include only those records whose timestamp is earlier than this value

Type: long

query
Query criterion

Type: string

Response Body

Contains a JSON object with a string return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime

The resource supports the following methods:

- POST

POST

An instance of a WLDFDataAccessMBean defined by its logical name. The name is constructed from the specific type of log data requested.

Roles

Admin, Deployer, Monitor, Operator

Request Body

Must contain a JSON object with the following fields:

logicalName
logicalName

Type: string

Response Body

Contains a JSON object with a weblogic.management.runtime.WLDFDataAccessRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes

This resource manages a collection of weblogic.management.runtime.WLDFDataAccessRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WLDFDataAccessRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WLDFDataAccessRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}

This resource manages a weblogic.management.runtime.WLDFDataAccessRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFDataAccessRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFDataAccessRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive **rel**=action **title**=closeArchive

  This resource's closeArchive action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive

The resource supports the following methods:

- POST

POST

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime

This resource manages a weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime

This resource manages a weblogic.management.runtime.WLDFPartitionImageRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFPartitionImageRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFPartitionImageRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage **rel**=action **title**=captureImage

  This resource's captureImage action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks **rel**=action **title**=clearCompletedImageCaptureTasks

  This resource's clearCompletedImageCaptureTasks action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages **rel**=action **title**=purgeCapturedImages

  This resource's purgeCapturedImages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout **rel**=action **title**=resetImageLockout

  This resource's resetImageLockout action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks **rel**=imageCaptureTasks

  This resource's imageCaptureTasks collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the configured lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Response Body

Contains a JSON object with a weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean reference return field.

POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

lockoutMinutes
number of minutes before the next image capture request will be accepted

Type: int

Response Body

Contains a JSON object with a weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean reference return field.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks

The resource supports the following methods:

- POST

POST

Removes all completed image capture tasks.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks

This resource manages a collection of weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}

This resource manages a weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks

This resource manages a collection of weblogic.management.runtime.TaskRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.TaskRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.TaskRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}

This resource manages a weblogic.management.runtime.TaskRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.TaskRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.TaskRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

  This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=parent

  The parent resource of this resource.

- **rel**=parentTask

  This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

  This resource's subTasks collection resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel

The resource supports the following methods:

- POST

POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages

The resource supports the following methods:

- POST

POST

Delete captured images specified by the age criteria.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

age
Purge diagnostic images older than specified age specified in the format Days:Hours:Minutes. If empty or null all existing image files on disk are purged. The hours and minutes components are optional.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout

The resource supports the following methods:

- POST

POST

Reset the lockout period, thus allowing image capture requests to be accepted.

Roles

Admin

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime

This resource manages a weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource **rel**=WLDFWatchJMXNotificationSource

  This resource's WLDFWatchJMXNotificationSource singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm **rel**=action **title**=resetWatchAlarm

  This resource's resetWatchAlarm action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm

The resource supports the following methods:

- POST

POST

Resets a policy alarm.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

watchName
the name of the policy to reset

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource

This resource manages a weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes

This resource manages a collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.WorkManagerRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.WorkManagerRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}

This resource manages a weblogic.management.runtime.WorkManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WorkManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WorkManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

  This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

  This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

  This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

  This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime

This resource manages a weblogic.management.runtime.CapacityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.CapacityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.CapacityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime

This resource manages a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.MinThreadsConstraintRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime

This resource manages a weblogic.management.runtime.RequestClassRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RequestClassRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RequestClassRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime

This resource manages a weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting **rel**=clusterRouting

  This resource's clusterRouting singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting

This resource manages a weblogic.management.runtime.WseeClusterRoutingRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WseeClusterRoutingRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WseeClusterRoutingRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/search

The resource supports the following methods:

- POST

POST

Search the serverRuntime tree.

Request Body

The search request body includes the search criteria.

Response Body

The search response includes the results of the search.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime

This resource manages a weblogic.management.runtime.ServerSecurityRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ServerSecurityRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ServerSecurityRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole **rel**=action **title**=checkRole

  This resource's checkRole action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes **rel**=realmRuntimes

  This resource's realmRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Checks whether current Subject has the specified role.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

roleName
Name of the role to check if the Subject has the specified role.

Type: string

Response Body

Contains a JSON object with a boolean return field.

POST

Checks whether current Subject has any of the required roles.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

roleNames
Names of the roles to check if the Subject has one of the specified roles.

Type: array of string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes

This resource manages a collection of weblogic.management.runtime.RealmRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.RealmRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.RealmRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}

This resource manages a weblogic.management.runtime.RealmRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.RealmRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.RealmRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes **rel**=authenticatorRuntimes

  This resource's authenticatorRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} **rel**=self

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime **rel**=userLockoutManagerRuntime

  This resource's userLockoutManagerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes

This resource manages a collection of weblogic.management.runtime.AuthenticatorRuntimeMBean instances.

The resource supports the following methods:

- GET

GET

Get this collection of weblogic.management.runtime.AuthenticatorRuntimeMBean instances.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a list of weblogic.management.runtime.AuthenticatorRuntimeMBean entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes/{name}

This resource manages a weblogic.management.runtime.AuthenticatorRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.AuthenticatorRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.AuthenticatorRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes/{name} **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes/{name} **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime

This resource manages a weblogic.management.runtime.UserLockoutManagerRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.UserLockoutManagerRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.UserLockoutManagerRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/clearLockout **rel**=action **title**=clearLockout

  This resource's clearLockout action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure **rel**=action **title**=getLastLoginFailure

  This resource's getLastLoginFailure action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount **rel**=action **title**=getLoginFailureCount

  This resource's getLoginFailureCount action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut **rel**=action **title**=isLockedOut

  This resource's isLockedOut action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/clearLockout

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains an empty JSON object.

POST

Unlocks a user account.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain
- The identity domain of the user. May be null.

Type: string

Response Body

Contains an empty JSON object.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns a string that indicates the time of the last invalid login for this user.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain
- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains a JSON object with a long return field.

POST

Returns the current count of login failures for a specific user. This value returns to

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain
- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a long return field.

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut

The resource supports the following methods:

- POST

POST

The resource supports the following methods:

- POST
- POST

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

identityDomain
- The identity domain of the user. May be null.

Type: string

Response Body

Contains a JSON object with a boolean return field.

POST

Indicates whether a user is locked out.

Roles

Admin

Request Body

Must contain a JSON object with the following fields:

userName
- A user name. If the user does not exist, this method returns `false`.

Type: string

Response Body

Contains a JSON object with a boolean return field.

/management/weblogic/{version}/serverRuntime/threadPoolRuntime

This resource manages a weblogic.management.runtime.ThreadPoolRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.ThreadPoolRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.ThreadPoolRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/threadPoolRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/threadPoolRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime

This resource manages a weblogic.management.runtime.WLDFRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime **rel**=WLDFHarvesterRuntime

  This resource's WLDFHarvesterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=self

  This resource.

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime

This resource manages a weblogic.management.runtime.WLDFHarvesterRuntimeMBean instance.

The resource supports the following methods:

- GET

GET

Get this weblogic.management.runtime.WLDFHarvesterRuntimeMBean instance.

Roles

Admin, Deployer, Monitor, Operator

Response Body

Contains a weblogic.management.runtime.WLDFHarvesterRuntimeMBean entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime **rel**=canonical

  This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime **rel**=parent

  The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime **rel**=self

  This resource.

2
Entities

The following sections describe the data models on which the REST resources operate. These data models describe the information exchanged in REST resources.

com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean

This interface provides functionality to monitor the class redefinition process. It also provides methods to explicitly initiate class redefinition.

The properties of the com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean entity are as follows:

classRedefinitionCount
Number of class redefinitions executed so far.

Type: int

Constraints: Read Only, Restart Required

failedClassRedefinitionCount
Number of failed redefinition operations since the application was deployed.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

processedClassesCount
Number of classes processed since the application was deployed.

Type: int

Constraints: Read Only, Restart Required

totalClassRedefinitionTime
Total time spent processing classes, in nano seconds since the application was deployed.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean

This interface provides functionality to monitor and control a class redefinition request.

The properties of the com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean entity are as follows:

candidateClassesCount
Estimated number of candidate classes to be redefined in the current change-list. Returns -1 if the number is not yet estimated.

Type: int

Constraints: Read Only, Restart Required

completed
This property indicates whether an asynchronous job has completed.

Type: boolean

description
A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime
This property indicates the time when the asynchronous job ended.

Type: java.util.Date

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask
The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

processedClassesCount
Number of classes processed so far.

Type: int

Constraints: Read Only, Restart Required

progress
The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running
Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime
This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong
The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask
Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError
Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus
The status of this task.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

java.lang.Throwable

This entity represents errors and exceptions.

The properties of the java.lang.Throwable entity are as follows:

cause
This property contains the stack trace of errors and exceptions.

Type: java.lang.Throwable

message
This property contains the reason why the error or exception was thrown.

Type: string

java.util.Date

This entity represents a date as a string in ISO 8601 format, yyyy-MM-ddTHH:mm:ss.SSSX

java.util.Properties

This entity represents a JSONObject with a property for each property in the properties object, where the key is the property's name the the value is a string containing the property's value.

weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean entity are as follows:

earliestAvailableTimestamp
The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the earliest record in the diagnostic data log.

Type: long

Constraints: Read Only, Restart Required

latestAvailableTimestamp
The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the newest record in the diagnostic data log.

Type: long

Constraints: Read Only, Restart Required

latestRecordId
The latest known record ID for the underlying archive.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timestampAvailable
Returns true, if timestamp information is available with the underlying archive.

Type: boolean

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.health.HealthState

This entity represents the health of the services that are in a WebLogic server domain. Selected subsystems within each WebLogic Server instance monitor their health status based on criteria specific to the subsystem.

The properties of the weblogic.health.HealthState entity are as follows:

partitionName
This property indicates the partition name for which the health state is reported.

Type: string

state
This property indicates the reported state as:

- OK - Service is healthy.
- WARN - Service could have problems in the future
- CRITICAL - Something must be done now to prevent service failure
- FAILED - Service has failed and must be restarted
- OVERLOADED - Service is functioning normally but there is too much work in it
- UNKNOWN - Service state cannot be determined

Type: string

subsystemName
This property indicates the service for which the health state is reported.

Type: string

symptoms
This property idicates the cause ot the reported state.

Type: array of weblogic.health.Symptom

weblogic.health.Symptom

This entity represents an observation reported by a service with its health state. A symptom can be used to determine the reason for the current health state of a WebLogic server.

The properties of the weblogic.health.Symptom entity are as follows:

info
This property provides additional information about the symptom if available.

Type: string

instanceId
This property represents an identifier for the symptom.

Type: string

severity
This property indicates a low, medium, or high severity level.

Type: string

type
This property represents the cause of the symptom (low memory, network error, stuck threads, and so on).

Type: string

weblogic.management.rest.bean.model.CurrentUser

The authenticated user that is making the request.

The properties of the weblogic.management.rest.bean.model.CurrentUser entity are as follows:

partitionId
The ID of the partition where the component that is being invoked resides.

Type: string

partitionName
The human readable name of the partition ID.

Type: string

user
The login of the user making this request, if the user has been authenticated, or `null` if the user has not been authenticated.

Type: string

weblogic.management.rest.bean.model.Version

A Version entity describes a version of the WebLogic Server resources.

The properties of the weblogic.management.rest.bean.model.Version entity are as follows:

isLatest
`True` if this is the default version.

Type: boolean

lifecycle
The lifecycle of this version: `active` or `deprecated`

Type: string

version
The name of this version.

Type: string

weblogic.management.runtime.ApplicationRuntimeMBean

An application represents a Java EE enterprise application packaged in an EAR file or EAR exploded directory. The EAR file or directory contains a set of components such as WAR, EJB, and RAR connector components, each of which can be deployed on one or more targets. A target is a server or a cluster. Modules in the application can have one of the following states:

- UNPREPARED - Indicates that none of the modules in this application are currently prepared or active.
- PREPARED - Indicates that none of the modules in this application are currently prepared or active.
- ACTIVATED - Indicates that at least one module in this application is currently active.

ApplicationRuntimeMBean encapsulates runtime information about a deployed enterprise application.

The properties of the weblogic.management.runtime.ApplicationRuntimeMBean entity are as follows:

activeVersionState

Specifies whether this application version is the currently active version.

An application can be the only version currently deployed, or it can have more than one version currently deployed, using the side-by-side deployment feature. If more than one version is deployed, only one version can be active. This attribute specifies the state the current application version is in.

An application can be in an INACTIVE state, which means that it has not been activated yet, or that there is more than one version of the application deployed (using side-by-side deployment) and this version is retiring.

An application can be in ACTIVE_ADMIN state, which means that it is the currently active version for administrative channel requests.

An application can be in ACTIVE state, which means that it is the currently active version for normal (non-administrative) channel requests.

Type: int

Constraints: Read Only, Restart Required

applicationName

The name of the application.

Type: string

Constraints: Read Only, Restart Required

applicationVersion

The application's version identifier.

This is particularly useful, when using the side-by-side deployment feature, to differentiate between two different versions of the same application that are deployed at the same time.

Type: string

Constraints: Read Only, Restart Required

healthState
The HealthState MBean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

internal
Indicates whether this application is an internal application. Such applications are not displayed in the console or persisted in the config.xml.

Type: boolean

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overallHealthState
The overall health of the application including that of some of the components that report health. Currently, only connector modules report health status and are the only ones considered in the overall health state of the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

partitionName
The application's partition.

Returns the partition to which this application is deployed.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.AuthenticatorRuntimeMBean

This class is used to monitor and manage authentication provider runtime information.

The properties of the weblogic.management.runtime.AuthenticatorRuntimeMBean entity are as follows:

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.BatchJobRepositoryRuntimeMBean

The properties of the weblogic.management.runtime.BatchJobRepositoryRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.CapacityRuntimeMBean

Monitoring information for Capacity which defines the maximum number of requests that can be enqueued by all the work managers that share it.

The properties of the weblogic.management.runtime.CapacityRuntimeMBean entity are as follows:

count
Total number of requests that can be enqueued.

Type: int

Constraints: Read Only, Has Default Value: -1

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ClassLoaderRuntimeMBean

Provides methods for retrieving runtime information about class loading

The properties of the weblogic.management.runtime.ClassLoaderRuntimeMBean entity are as follows:

afterIndexingFindClassCount
Type: long

Constraints: Read Only, Restart Required

afterIndexingFindClassTime
Type: long

Constraints: Read Only, Restart Required

afterIndexingLoadClassCount
Type: long

Constraints: Read Only, Restart Required

afterIndexingLoadClassTime
Type: long

Constraints: Read Only, Restart Required

afterIndexingResourceCount
Type: long

Constraints: Read Only, Restart Required

afterIndexingResourceTime
Type: long

Constraints: Read Only, Restart Required

beforeIndexingFindClassCount
Type: long

Constraints: Read Only, Restart Required

beforeIndexingFindClassTime
Type: long

Constraints: Read Only, Restart Required

beforeIndexingLoadClassCount
Type: long

Constraints: Read Only, Restart Required

beforeIndexingLoadClassTime
Type: long

Constraints: Read Only, Restart Required

beforeIndexingResourceCount
Type: long

Constraints: Read Only, Restart Required

beforeIndexingResourceTime
Type: long

Constraints: Read Only, Restart Required

defineClassCount
Type: long

Constraints: Read Only, Restart Required

defineClassTime
Type: long

Constraints: Read Only, Restart Required

duringIndexingFindClassCount
Type: long

Constraints: Read Only, Restart Required

duringIndexingFindClassTime
Type: long

Constraints: Read Only, Restart Required

duringIndexingLoadClassCount
Type: long

Constraints: Read Only, Restart Required

duringIndexingLoadClassTime
Type: long

Constraints: Read Only, Restart Required

duringIndexingResourceCount
Type: long

Constraints: Read Only, Restart Required

duringIndexingResourceTime
Type: long

Constraints: Read Only, Restart Required

findClassCount
Type: long

Constraints: Read Only, Restart Required

findClassTime
Type: long

Constraints: Read Only, Restart Required

indexingTime
Type: long

Constraints: Read Only, Restart Required

loadClassCount
Type: long

Constraints: Read Only, Restart Required

loadClassTime
Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentDelegationCount
Type: long

Constraints: Read Only, Restart Required

parentDelegationTime
Type: long

Constraints: Read Only, Restart Required

resourceCount
Type: long

Constraints: Read Only, Restart Required

resourceTime
Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.CoherenceClusterRuntimeMBean

Coherence cluster run-time information.

The properties of the weblogic.management.runtime.CoherenceClusterRuntimeMBean entity are as follows:

clusterName
The name of the Coherence cluster.

Type: string

Constraints: Read Only, Restart Required

clusterSize
The size of the Coherence cluster.

Type: int

Constraints: Read Only, Restart Required

licenseMode
The license mode for the Coherence cluster. Possible values are Evaluation, Development, or Production.

Type: string

Constraints: Read Only, Restart Required

members
Identifiers for the available Coherence cluster members.

Type: array of string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

version
The Coherence cluster version.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ComponentRuntimeMBean

Base class for all runtime mbeans that provide status of running modules.

The properties of the weblogic.management.runtime.ComponentRuntimeMBean entity are as follows:

deploymentState
The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

moduleId
Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean

Concurrent Managed Objects Runtime information for the global/domain partition or a common partition.

The properties of the weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests
The number of long-running requests that have been rejected by managed executor services and managed scheduled executor services in this partition on the current server.

Type: long

Constraints: Read Only, Restart Required

rejectedNewThreadRequests
The number of newThread method invocations that have been rejected by managed thread factories in this partition on the current server.

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests
The number of running long-running requests submitted to managed executor services and managed scheduled executor services in this partition on the current server.

Type: int

Constraints: Read Only, Restart Required

runningThreadsCount
The number of running threads created by managed thread factories in this partition on the current server.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorComponentRuntimeMBean

Generates notifications about the deployment state of resource adapters. (Each resource adapter is represented by an instance of weblogic.management.configuration.ConnectorComponentMBean.)

In 2-phase deployment, if a resource adapter's state is `PREPARED` then it has achieved the first phase of deployment (everything is set up and all that remains is to enable a reference to the adapter). When the resource adapter is in an `ACTIVATED` state, it has achieved the second phase of deployment, in which applications can obtain a reference to the adapter.

A server instance creates an instance of this interface when it creates an instance of `weblogic.management.configuration.ConnectorComponentMBean`

The properties of the weblogic.management.runtime.ConnectorComponentRuntimeMBean entity are as follows:

EISResourceId
Returns the EISResourceId for the component.

Type: string

Constraints: Read Only, Restart Required

EISType
Get the EIS type.

Type: string

Constraints: Read Only, Restart Required

activeVersion
Return true if this version is the active version. Returns true if this resource adapter is not versioned.

Type: boolean

Constraints: Read Only, Restart Required

activeVersionId
Get the active version Id.

Type: string

Constraints: Read Only, Restart Required

componentName
Get the name of the connector component.

Type: string

Constraints: Read Only, Restart Required

configuration
Return the xml string representing the RA configuration. The xml corresponding to the latest schema is returned. The current supported version is "1.0"

Type: string

Constraints: Read Only, Restart Required

configurationVersion
Return the latest configuration version.

Type: string

Constraints: Read Only, Restart Required

configuredProperties
Gets a subset of the resource adapter descriptor information.

Type: java.util.Properties

Constraints: Read Only, Restart Required

connectionPoolCount
The number of connection pools.

Type: int

Constraints: Read Only, Restart Required

deploymentState
The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

description
Get the Description for the resource adapter.

Type: string

Constraints: Read Only, Restart Required

descriptions
Get the Descriptions for the resource adapter.

Type: array of string

Constraints: Read Only, Restart Required

healthState
The HealthState mbean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

inboundConnectionsCount
The number of inbound connections for the resource adapter.

Type: int

Constraints: Read Only, Restart Required

jndiName
Get the Jndi name of the resource adapter.

Type: string

Constraints: Read Only, Restart Required

linkref
Get the linkref.

Type: string

Constraints: Read Only, Restart Required

moduleId
Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

schema
Get the latest schema for RA configuration.

Type: string

Constraints: Read Only, Restart Required

specVersion
Get the spec version.

Type: string

Constraints: Read Only, Restart Required

state
Get the state of the resource adapter.

Type: string

Constraints: Read Only, Restart Required

suspendedState
Gets the suspended state information of the resource adapter.

If getState() returns SUSPENDED then getSuspendedState() returns an integer describing which functions of the resource adapter are suspended: one or more of INBOUND, OUTBOUND or WORK (or ALL) or 0 for nothing suspended

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

vendorName
Get the vendor name.

Type: string

Constraints: Read Only, Restart Required

version
Get the version.

Type: string

Constraints: Read Only, Restart Required

versionId
Get the version Id.

Type: string

Constraints: Read Only, Restart Required

versioned
Check if the resource adapter is versioned. Returns true if it is.

Type: boolean

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean

This class is used for monitoring a WebLogic Connector Connection Pool

The properties of the weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity are as follows:

EISResourceId
The EISResourceId of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

MCFClassName
Get the MCF class name.

Type: string

Constraints: Read Only, Restart Required

activeConnectionsCurrentCount
The current total active connections.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsHighCount
The high water mark of active connections in this Connector Pool since the pool was instantiated.

Type: int

Constraints: Read Only, Restart Required

averageActiveUsage
The running average usage of created connections that are active in the Connector Pool since the pool was last shrunk.

Type: int

Constraints: Read Only, Restart Required

capacityIncrement
The initial capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

closeCount
The number of connections that were closed for the connection pool.

Type: long

Constraints: Read Only, Restart Required

connectionFactoryClassName
The ConnectionFactoryName of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

connectionFactoryName
For 1.0 link-ref resource adapters only, the base resource adapter's connection factory name.

Type: string

Constraints: Read Only, Restart Required

connectionsCreatedTotalCount
The total number of Connector connections created in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedByErrorTotalCount
Return the number of connections that were destroyed because an error event was received.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedByShrinkingTotalCount
Return the number of connections that were destroyed as a result of shrinking.

Type: int

Constraints: Read Only, Restart Required

connectionsDestroyedTotalCount
The total number of Connector connections destroyed in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsMatchedTotalCount
The total number of times a request for a Connector connections was satisfied via the use of an existing created connection since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectionsRejectedTotalCount
The total number of rejected requests for a Connector connections in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

connectorEisType
The EIS type of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

currentCapacity
The PoolSize of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

freeConnectionsCurrentCount
The current total free connections.

Type: int

Constraints: Read Only, Restart Required

freeConnectionsHighCount
The high water mark of free connections in this Connector Pool since the pool was instantiated.

Type: int

Constraints: Read Only, Restart Required

freePoolSizeHighWaterMark
The FreePoolSizeHighWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

freePoolSizeLowWaterMark
The FreePoolSizeLowWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

healthState
The HealthState mbean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

highestNumWaiters
Gets the highest number of waiters.

Type: long

Constraints: Read Only, Restart Required

initialCapacity
The initial capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

key
The configured Key for the Connection Factory using this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

lastShrinkTime
Return the last time that the pool was shrunk.

Type: long

Constraints: Read Only, Restart Required

logFileName
The Log File used by the Resource Adapter for this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

logFileStreamOpened
Gets the opened state of the log file stream represented by this instance.

Type: boolean

Constraints: Read Only, Restart Required

loggingEnabled
Indicates whether logging is enabled for this Connector connection pool.

Type: boolean

Constraints: Read Only, Restart Required

managedConnectionFactoryClassName
The ManagedConnectionFactoryName of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

maxCapacity
The maximum capacity configured for this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

numUnavailableCurrentCount
Return the number of unavailable connections.

Type: int

Constraints: Read Only, Restart Required

numUnavailableHighCount
Return the highest unavailable number of connections at any given time.

Type: int

Constraints: Read Only, Restart Required

numWaiters
Gets the current number of waiters.

Type: long

Constraints: Read Only, Restart Required

numWaitersCurrentCount
Return the number of waiters.

Type: int

Constraints: Read Only, Restart Required

poolName
The configured Logical Name for the Connection Factory using this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

poolSizeHighWaterMark
The PoolSizeHighWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

poolSizeLowWaterMark
The PoolSizeLowWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

proxyOn
Return a flag indicating if the proxy is on. Returns true if it is.

Type: boolean

Constraints: Read Only, Restart Required

recycledTotal
The total number of Connector connections that have been recycled in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

runtimeTransactionSupport
The real transaction support level in use at runtime.

Type: string

Constraints: Read Only, Restart Required

shrinkCountDownTime
The amount of time left (in minutes) until an attempt to shrink the pool will be made.

Type: int

Constraints: Read Only, Restart Required

shrinkPeriodMinutes
The Shrink Period (in minutes) of this Connector connection pool.

Type: int

Constraints: Read Only, Restart Required

shrinkingEnabled
Specifies whether shrinking of this Connector connection pool is enabled.

Type: boolean

Constraints: Read Only, Restart Required

state
Get the state of the pool.

Type: string

Constraints: Read Only, Restart Required

testable
This indicates whether the connection pool is testable or not.

Type: boolean

Constraints: Read Only, Restart Required

transactionSupport
The static transaction support level, either configured in ra.xml or in @Conector annotation, for the Resource Adapter for this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorConnectionRuntimeMBean

This class is used for monitoring individual WebLogic Connector connections

The properties of the weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity are as follows:

EISProductName
Returns the EISProductName associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

EISProductVersion
Returns the EISProductVersion associated with the ManagedConnection's MetaData.

Type: string

Constraints: Read Only, Restart Required

activeHandlesCurrentCount
The current total active connection handles for this connection.

Type: int

Constraints: Read Only, Restart Required

activeHandlesHighCount
The high water mark of active connection handles for this connection since the connection was created.

Type: int

Constraints: Read Only, Restart Required

connectionFactoryClassName
Returns the connection factory class name.

Type: string

Constraints: Read Only, Restart Required

creationDurationTime
Return the time taken to create the connection.

Type: long

Constraints: Read Only, Restart Required

currentlyInUse
Indicates whether the connection is currently in use.

Type: boolean

Constraints: Read Only, Restart Required

deletable
Indicates whether the connection can be closed manually through the console.

Type: boolean

Constraints: Read Only, Restart Required

handlesCreatedTotalCount
The total number of connection handles created for this connection since the connection was created.

Type: int

Constraints: Read Only, Restart Required

inTransaction
Indicates whether the connection is currently in use in a transaction.

Type: boolean

Constraints: Read Only, Restart Required

managedConnectionFactoryClassName
Returns the managed connection factory class name.

Type: string

Constraints: Read Only, Restart Required

maxConnections
Returns the MaxConnections associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

reserveDurationTime
Get the time taken to reserve this connection.

Type: long

Constraints: Read Only, Restart Required

reserveTime
Return the last time the connection was reserved.

Type: long

Constraints: Read Only, Restart Required

shared
Indicates whether the connection is currently being shared by more than one invoker.

Type: boolean

Constraints: Read Only, Restart Required

transactionId
Get the Transaction ID of the transaction that this connection is being used with.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

userName
Returns the UserName associated with the ManagedConnection's MetaData

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorInboundRuntimeMBean

This class is used for monitoring inbound connections of resource adapters.

The properties of the weblogic.management.runtime.ConnectorInboundRuntimeMBean entity are as follows:

activationSpecClass
The activation spec class.

Type: string

Constraints: Read Only, Restart Required

msgListenerType
The message listener type.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

state
Return the state of the Inbound connection. The values that are returned are : "Running" and "Suspended".

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorServiceRuntimeMBean

This interface defines the runtime information that can be accessed at a connector service level. Runtime information can be accessed at a per resource adapter level or at an overall level.

The properties of the weblogic.management.runtime.ConnectorServiceRuntimeMBean entity are as follows:

RACount
Returns the number of resource adapters that have been deployed in the server. This count includes active RAs and Non-active RAs (in the case of versioned RAs that are being replaced by a new version)

Type: int

Constraints: Read Only, Restart Required

activeRACount
Returns the number of resource adapters that are active.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean

This class is used for monitoring Connector Work Manager of resource adapters.

The properties of the weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity are as follows:

activeLongRunningRequests
Return The number of current active long-running work requests.

Type: int

Constraints: Read Only, Restart Required

completedLongRunningRequests
The number of completed long-running work requests.

Type: int

Constraints: Read Only, Restart Required

maxConcurrentLongRunningRequests
The maximum number of allowed concurrent long-running work requests. New work submission will be rejected if current running long-running work requests exceed the limit.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBPoolRuntimeMBean

This interface contains accessor methods for all free pool runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBPoolRuntimeMBean entity are as follows:

accessTotalCount
Provides a count of the total number of times an attempt was made to get an instance from the free pool.

Type: long

Constraints: Read Only, Restart Required

beansInUseCurrentCount
Provides a count of the number of bean instances currently being used from the free pool.

Type: int

Constraints: Read Only, Restart Required

destroyedTotalCount
Provides a count of the total number of times a bean instance from this pool was destroyed due to a non-application Exception being thrown from it.

Type: long

Constraints: Read Only, Restart Required

missTotalCount
Provides a count of the total number of times a failed attempt was made to get an instance from the free pool. An Attempt to get a bean from the pool will fail if there are no available instances in the pool.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pooledBeansCurrentCount
Provides a count of the current number of available bean instances in the free pool.

Type: int

Constraints: Read Only, Restart Required

timeoutTotalCount
Provides a count of the total number of Threads that have timed out waiting for an available bean instance from the free pool.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

waiterCurrentCount
Provides a count of the number of Threads currently waiting for an available bean instance from the free pool.

Type: int

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBTimerRuntimeMBean

This interface contains accessor methods for all EJB Timer runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBTimerRuntimeMBean entity are as follows:

activeTimerCount
Provides the current number of active timers for this EJB

Type: int

Constraints: Read Only, Restart Required

cancelledTimerCount
Provides the total number of timers that have been explicitly cancelled for this EJB.

Type: long

Constraints: Read Only, Restart Required

disabledTimerCount

Provides the current number of timers temporarily disabled for this EJB

Type: int

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timeoutCount

Provides the total number of successful timeout notifications that have been made for this EJB.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.EJBTransactionRuntimeMBean

This interface contains accessor methods for all transaction runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBTransactionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

transactionsCommittedTotalCount

Provides a count of the total number of transactions that have been committed for this EJB.

Type: long

Constraints: Read Only, Restart Required

transactionsRolledBackTotalCount

Provides a count of the total number of transactions that have been rolled back for this EJB.

Type: long

Constraints: Read Only, Restart Required

transactionsTimedOutTotalCount
Provides a count of the total number of transactions that have timed out for this EJB.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.FairShareConstraintRuntimeMBean

The properties of the weblogic.management.runtime.FairShareConstraintRuntimeMBean entity are as follows:

activated
Returns true if trigger was successfully executed.

Type: boolean

Constraints: Read Only, Restart Required

initiated
Returns true if trigger execution has begun.

Type: boolean

Constraints: Read Only, Restart Required

lastTimeExecuted
Return last trigger execution date and time.

Type: java.util.Date

Constraints: Read Only, Restart Required

name
Return name of the Resource.

Type: string

Constraints: Read Only, Restart Required

recourseActionEventsHistory
Return details of trigger execution in the past.

Type: array of weblogic.management.runtime.RecourseActionEventVBean

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Data Source and its associated connection pool.

The properties of the weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity are as follows:

activeConnectionsAverageCount

Average number of active connections in this instance of the data source.

Active connections are connections in use by an application. This value is only valid if the resource is configured to allow shrinking.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsCurrentCount

The number of connections currently in use by applications.

Type: int

Constraints: Read Only, Restart Required

activeConnectionsHighCount

Highest number of active database connections in this instance of the data source since the data source was instantiated.

Active connections are connections in use by an application.

Type: int

Constraints: Read Only, Restart Required

connectionDelayTime

The average amount of time, in milliseconds, that it takes to create a physical connection to the database.

The value is calculated as summary of all times to connect divided by the total number of connections.

Type: int

Constraints: Read Only, Restart Required

connectionsTotalCount

The cumulative total number of database connections created in this data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

currCapacity

The current count of JDBC connections in the connection pool in the data source.

Type: int

Constraints: Read Only, Restart Required

currCapacityHighCount

Highest number of database connections available or in use (current capacity) in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

databaseProductName

The product name of the database that this data source is connected to.

Type: string

Constraints: Read Only, Restart Required

databaseProductVersion

The product version of the database that this data source is connected to.

Type: string

Constraints: Read Only, Restart Required

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

driverName

The product name of the JDBC driver that this data source is configured to use.

Type: string

Constraints: Read Only, Restart Required

driverVersion

The version of the JDBC driver that this data source is configured to use.

Type: string

Constraints: Read Only, Restart Required

enabled

Indicates whether the data source is enabled or disabled:

- `true` if the data source is enabled.
- `false` if the data source is disabled.

Type: boolean

Constraints: Read Only, Restart Required

failedReserveRequestCount

The cumulative, running count of requests for a connection from this data source that could not be fulfilled.

Type: long

Constraints: Read Only, Restart Required

failuresToReconnectCount

The number of times that the data source attempted to refresh a database connection and failed.

Failures may occur when the database is unavailable or when the network connection to the database is interrupted.

Type: int

Constraints: Read Only, Restart Required

highestNumAvailable

Highest number of database connections that were idle and available to be used by an application at any time in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

highestNumUnavailable

Highest number of database connections that were in use by applications or being tested by the system in this instance of the data source since the data source was deployed.

Type: int

Constraints: Read Only, Restart Required

lastTask

Get the last datasource Task

Type: weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean reference

Constraints: Read Only, Restart Required

leakedConnectionCount

The number of leaked connections. A leaked connection is a connection that was reserved from the data source but was not returned to the data source by calling `close()`

Type: int

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

numAvailable

The number of database connections that are currently idle and available to be used by applications in this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

numUnavailable

The number of connections currently in use by applications or being tested in this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheAccessCount

The cumulative, running count of the number of times that the statement cache was accessed.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheAddCount

The cumulative, running count of the number of statements added to the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements added to the caches for all connections in the connection pool.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheCurrentSize

The number of prepared and callable statements currently cached in the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements in the caches for all connections in the connection pool.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheDeleteCount

The cumulative, running count of statements discarded from the cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements that were discarded from the caches for all connections in the connection pool.

Type: long

Constraints: Read Only, Restart Required

prepStmtCacheHitCount

The cumulative, running count of the number of times that statements from the cache were used.

Type: int

Constraints: Read Only, Restart Required

prepStmtCacheMissCount

The number of times that a statement request could not be satisfied with a statement from the cache.

Type: int

Constraints: Read Only, Restart Required

properties

The list of properties for a data source that are passed to the JDBC driver when creating database connections.

This is a privileged operation that can only be invoked by an authorized user.

Type: java.util.Properties

Constraints: Read Only, Restart Required

reserveRequestCount

The cumulative, running count of requests for a connection from this data source.

Type: long

Constraints: Read Only, Restart Required

state

The current state of the data source.

Possible states are:

- `Running` - the data source is enabled (deployed and not `Suspended`). This is the normal state of the data source. This state includes conditions when the database server is not available and the data source is created (creation retry must be enabled) or when all connections have failed connection tests (on creation, on reserve, or periodic testing).
- `Suspended` - the data source has been disabled.
- `Shutdown` - the data source is shutdown and all database connections have been closed.
- `Overloaded` - all resources in pool are in use.
- `Unknown` - the data source state is unknown.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

versionJDBCDriver

The driver class name of the JDBC driver used to create database connections.

Type: string

Constraints: Read Only, Restart Required

waitSecondsHighCount

The highest number of seconds that an application waited for a connection (the longest connection reserve wait time) from this instance of the connection pool since the connection pool was instantiated.

This value is updated when a completed `getConnection` request takes longer to return a connection than any previous request.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionCurrentCount

The number of connection requests waiting for a database connection.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionFailureTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually failed to get a connection.

Waiting connection requests can fail for a variety of reasons, including waiting for longer than the ConnectionReserveTimeoutSeconds.

Type: long

Constraints: Read Only, Restart Required

waitingForConnectionHighCount

Highest number of application requests concurrently waiting for a connection from this instance of the data source.

Type: int

Constraints: Read Only, Restart Required

waitingForConnectionSuccessTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually succeeded in getting a connection.

Type: long

Constraints: Read Only, Restart Required

waitingForConnectionTotal

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection, including those that eventually got a connection and those that did not get a connection.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean

The properties of the weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean entity are as follows:

completed
This property indicates whether an asynchronous job has completed.

Type: boolean

description
A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime
This property indicates the time when the asynchronous job ended.

Type: java.util.Date

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask
The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

progress
The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running
Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime
This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong
The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask
Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError
Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus
The status of this task.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCDriverRuntimeMBean

This class maps to a JDBCDriver JMO

The properties of the weblogic.management.runtime.JDBCDriverRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Multi Data Source and its associated data sources.

The properties of the weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean entity are as follows:

deploymentState
The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.

- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

maxCapacity

The maximum capacity of this multi data source. The maximum capacity is: - Maximum capacity of first available (not suspended) data source in the list, if the multi data source is using the FAILOVER algorithm (the `FailoverRequestIfBusy` flag is not set). - Sum of maximum capacities of all available (not suspended) data sources, if the multi data source is using other algorithms.

Type: int

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCPartitionRuntimeMBean

Partition monitoring of WebLogic JDBC resources

The properties of the weblogic.management.runtime.JDBCPartitionRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean

This class is used to get replay statics for an Oracle replay datasource aggregated across all connections in the pool.

The properties of the weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean entity are as follows:

deploymentState

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

Type: int

Constraints: Read Only, Restart Required

failedReplayCount

Obtains the number of replays that failed.

When replay fails, it rethrows the original SQLRecoverableException to the application, with the reason for the failure chained to that original exception. Application can call `getNextException` to retrieve the reason.

Type: long

Constraints: Read Only, Restart Required

moduleId

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

replayDisablingCount

Obtains the number of times that replay is disabled. When replay is disabled in the middle of a request, the remaining calls in that request are no longer protected by AC.

In case an outage strikes one of those remaining calls, no replay will be attempted, and application simply gets an SQLRecoverableException.

Type: long

Constraints: Read Only, Restart Required

successfulReplayCount

Obtains the number of replays that succeeded. Successful replays mask the outages from applications.

Type: long

Constraints: Read Only, Restart Required

totalCalls

Obtains the total number of JDBC calls executed so far.

Type: long

Constraints: Read Only, Restart Required

totalCallsAffectedByOutages

Obtains the number of JDBC calls affected by outages. This includes both local calls and calls that involve roundtrip(s) to the database server.

Type: long

Constraints: Read Only, Restart Required

totalCallsAffectedByOutagesDuringReplay

Obtains the number of JDBC calls affected by outages in the middle of replay. Outages may be cascaded and strike a call multiple times when replay is ongoing. AC automatically reattempts replay when this happens, unless it reaches the maximum retry limit.

Type: long

Constraints: Read Only, Restart Required

totalCallsTriggeringReplay

Obtains the number of JDBC calls that triggered replay. Not all the calls affected by an outage trigger replay, because replay can be disabled for some requests.

Type: long

Constraints: Read Only, Restart Required

totalCompletedRequests

Obtains the total number of completed requests so far.

Type: long

Constraints: Read Only, Restart Required

totalProtectedCalls

Obtains the total number of JDBC calls executed so far that are protected by AC.

Type: long

Constraints: Read Only, Restart Required

totalReplayAttempts

Obtains the number of replay attempts. AC automatically reattempts when replay fails, so this number may exceed the number of JDBC calls that triggered replay.

Type: long

Constraints: Read Only, Restart Required

totalRequests
Obtains the total number of successfully submitted requests so far.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSConnectionRuntimeMBean

This class is used for monitoring a WebLogic JMS connection.

The properties of the weblogic.management.runtime.JMSConnectionRuntimeMBean entity are as follows:

clientID
The client ID for this connection.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy
The ClientIDPolicy on this connection or durable subscriber.

Values are:

- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular `ClientID`
- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any `ClientID`, even when other restricted or unrestricted connections already use the same `ClientID`

Type: string

Constraints: Read Only, Restart Required

hostAddress
The host address of the client JVM as a string.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sessionsCurrentCount
The current number of sessions for this connection.

Type: long

Constraints: Read Only, Restart Required

sessionsHighCount
The peak number of sessions for this connection since the last reset.

Type: long

Constraints: Read Only, Restart Required

sessionsTotalCount
The number of sessions on this connection since the last reset.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSConsumerRuntimeMBean

This class is used for monitoring a WebLogic JMS consumer.

The properties of the weblogic.management.runtime.JMSConsumerRuntimeMBean entity are as follows:

active
Indicates whether the consumer active. A consumer is active if it has a message listener set up or a synchronous receive in progress.

Type: boolean

Constraints: Read Only, Restart Required

bytesPendingCount
The number of bytes pending (uncommitted and unacknowledged) by this consumer.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount
The number of bytes received by this consumer since the last reset.

Type: long

Constraints: Read Only, Restart Required

clientID
The client ID for this connection.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy

The ClientIDPolicy on this connection or durable subscriber.

Valid values are:

- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular `ClientID`
- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any `ClientID`, even when other restricted or unrestricted connections already use the same `ClientID`

Type: string

Constraints: Read Only, Restart Required

destinationName

The name of the destination for this consumer. In case of a distributed destination, it is the name of the distributed destination, instead of the member destination.

Type: string

Constraints: Read Only, Restart Required

durable

Indicates whether the consumer is durable.

Type: boolean

Constraints: Read Only, Restart Required

memberDestinationName

The name of the destination for this consumer. In case of a distributed destination, it is the name of the member destination.

Type: string

Constraints: Read Only, Restart Required

messagesPendingCount

The number of messages pending (uncommitted and unacknowledged) by this consumer.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount

The number of messages received by this consumer since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

selector
The selector associated with this consumer, if any.

Type: string

Constraints: Read Only, Restart Required

subscriptionSharingPolicy
The Subscription Sharing Policy on this subscriber.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSDestinationRuntimeMBean

This class is used for monitoring a WebLogic JMS destination (topic or queue).

The properties of the weblogic.management.runtime.JMSDestinationRuntimeMBean entity are as follows:

bytesCurrentCount
The current number of bytes stored in the destination. This does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount
The peak number of bytes stored in the destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount
The number of pending bytes stored in the destination.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount
The number of bytes received in this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime
The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersCurrentCount
The current number of consumers accessing this destination.

Type: long

Constraints: Read Only, Restart Required

consumersHighCount
The peak number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersTotalCount
The total number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumptionPaused
Indicates the consumption Pause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

consumptionPausedState
The current consumption pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

destinationType
The destination type, either `weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_QUEUE` or `weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_TOPIC` depending upon whether the destination is a queue or topic.

Type: string

Constraints: Read Only, Restart Required

insertionPaused
Indicates the InsertionPause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

insertionPausedState
The current insertion pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

messagesCurrentCount
The current number of messages in the destination. This does not include the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesDeletedCurrentCount
Returns the number of messages that have been deleted from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount
The peak number of messages in the destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesMovedCurrentCount
Returns the number of messages that have been moved from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
The number of pending messages in the destination.

Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or that has been received and not committed or acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received in this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime
The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

productionPaused
Indicates the ProductionPause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

productionPausedState
The current production pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

state
The operational state of the destination as a String.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean

This class is used for monitoring a WebLogic JMS durable subscriber.

The properties of the weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entity are as follows:

active
Indicates whether this subscription is being used by a durable subscriber.

Type: boolean

Constraints: Read Only, Restart Required

bytesCurrentCount
The number of bytes received by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount
The number of bytes pending by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

clientID
A unique client identifier for this durable subscriber.

Note: The client ID is not necessarily equivalent to the WebLogic Server username; that is, a name used to authenticate a user in the WebLogic security realm. You can set the client ID to the WebLogic Server username if it is appropriate for your JMS application.

Type: string

Constraints: Read Only, Restart Required

clientIDPolicy
The policy for the client identifier for this durable subscriber.

Note: The client ID policy is either `Restricted` or `Unrestricted`.

Type: string

Constraints: Read Only, Restart Required

lastMessagesReceivedTime
The time when the last time a subscriber received a message from the subscription. The returned value is a standard java absolute time, which is measured in milliseconds since midnight, January 1, 1970 UTC

This returns the JMS durable subscription boot time if there were no messages that were successfully delivered to any subscriber on this subscription since the subscription was booted. We define the boot time of a durable subscription to be the time the subscription is originally created or recovered during a server reboot or jms migration, which ever is latest.

Type: long

Constraints: Read Only, Restart Required

messagesCurrentCount
The number of messages still available by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

messagesDeletedCurrentCount
Returns the number of messages that have been deleted from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount
The peak number of messages for the durable subscriber since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesMovedCurrentCount
Returns the number of messages that have been moved from the destination.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
The number of messages pending (uncommitted and unacknowledged) by this durable subscriber.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received by the durable subscriber since that reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

noLocal
Specifies whether this durable subscriber receives local messages that it has published.

To prevent this, set the `noLocal` parameter to `true`

Type: boolean

Constraints: Read Only, Restart Required

selector
The message selector defined for this durable subscriber.

Type: string

Constraints: Read Only, Restart Required

subscribersCurrentCount
The number of subscribers that currently share this subscription.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscribersHighCount
The highest number of subscribers that have shared this subscription at the same time since the creation or the last reboot of the subscription, which ever is later.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscribersTotalCount
The total number of subscribers that have accessed this subscription since the creation or the last reboot of the subscription, whichever is later.

Type: int

Constraints: Read Only, Restart Required, Has Default Value: 0

subscriptionName
The subscription name for this durable subscriber. This name must be unique for each client ID.

Valid durable subscription names cannot include the following characters: comma ",", equals "=", colon ":", asterisk "*", percent "%", or question mark"?".

Type: string

Constraints: Read Only, Restart Required

subscriptionSharingPolicy
The SubscriptionSharingPolicy on this subscriber.

Type: string

Constraints: Read Only, Restart Required, Has Default Value: Exclusive

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSProducerRuntimeMBean

This class is used for monitoring a WebLogic JMS producer.

The properties of the weblogic.management.runtime.JMSProducerRuntimeMBean entity are as follows:

bytesPendingCount
The number of bytes pending (uncommitted and unacknowledged) by this producer.

Type: long

Constraints: Read Only, Restart Required

bytesSentCount
The number of bytes sent by this producer since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
The number of messages pending (uncommitted and unacknowledged) by this producer.

Type: long

Constraints: Read Only, Restart Required

messagesSentCount
The number of messages sent by this producer since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSRuntimeMBean

This class is used for monitoring a WebLogic JMS service.

The properties of the weblogic.management.runtime.JMSRuntimeMBean entity are as follows:

JMSServersCurrentCount
The current number of JMS servers that are deployed on this WebLogic Server instance.

Type: long

Constraints: Read Only, Restart Required

JMSServersHighCount
The highest number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

Type: long

Constraints: Read Only, Restart Required

JMSServersTotalCount
The total number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

Type: long

Constraints: Read Only, Restart Required

connectionsCurrentCount
The current number of connections to WebLogic Server server.

Type: long

Constraints: Read Only, Restart Required

connectionsHighCount
The highest number of connections to this WebLogic Server since the last reset.

Type: long

Constraints: Read Only, Restart Required

connectionsTotalCount
The total number of connections made to this WebLogic Server since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState
The health state of this JMS service.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSServerRuntimeMBean

This class is used for monitoring a WebLogic JMS server.

The properties of the weblogic.management.runtime.JMSServerRuntimeMBean entity are as follows:

bytesCurrentCount
The current number of bytes stored on this JMS server.

This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount
The peak number of bytes stored in the JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPageableCurrentCount
Return the total number of bytes in all the messages that are currently available to be paged out, but which have not yet been paged out. The JMS server attempts to keep this number smaller than the "MessageBufferSize" parameter.

Type: long

Constraints: Read Only, Restart Required

bytesPagedInTotalCount
Return the total number of bytes that were read from the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

bytesPagedOutTotalCount
Return the total number of bytes that were written to the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount
The current number of bytes pending (unacknowledged or uncommitted) stored on this JMS server.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount
The number of bytes received on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime
The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumptionPaused
Returns the current consumption paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

consumptionPausedState
Returns the current consumption paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

destinationsCurrentCount
The current number of destinations for this JMS server.

Type: long

Constraints: Read Only, Restart Required

destinationsHighCount
The peak number of destinations on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

destinationsTotalCount
The number of destinations instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState
The health state of this JMS server.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

insertionPaused
Returns the current insertion paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

insertionPausedState
Returns the current insertion paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

messagesCurrentCount
The current number of messages stored on this JMS server. This number does not include the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount
The peak number of messages stored in the JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPageableCurrentCount
Return the number of messages that are currently available for paging in this JMS server but have not yet been paged out. Note that due to internal implementation details, this count may be zero even if "PageableByteCurrentCount" is zero.

Type: int

Constraints: Read Only, Restart Required

messagesPagedInTotalCount
Return the total number of messages that were read from the paging directory since the JMS server was started.

Type: int

Constraints: Read Only, Restart Required

messagesPagedOutTotalCount
Return the total number of messages that were written to the paging directory since the JMS server was started.

Type: int

Constraints: Read Only, Restart Required

messagesPendingCount
The current number of messages pending (unacknowledged or uncommitted) stored on this JMS server.

Pending messages are over and above the current number of messages.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received on this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime
The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pagingAllocatedIoBufferBytes
See PersistentStoreRuntimeMBean.AllocatedIoBufferBytes

Type: long

Constraints: Read Only, Restart Required

pagingAllocatedWindowBufferBytes
See PersistentStoreRuntimeMBean.AllocatedWindowBufferBytes

Type: long

Constraints: Read Only, Restart Required

pagingPhysicalWriteCount
See PersistentStoreRuntimeMBean.PhysicalWriteCount

Type: long

Constraints: Read Only, Restart Required

pendingTransactions
Returns an array of Xids representing transaction branches that exist onthis JMS server in the pending state, i.e. branches that have been prepared by the transaction manager but not yet committed or rolled back.

Type: array of string

Constraints: Read Only, Restart Required

productionPaused
Returns the current production paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

productionPausedState
Returns the current production paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

sessionPoolsCurrentCount
The current number of session pools instantiated on this JMS server.

Type: long

Constraints: Read Only, Restart Required

sessionPoolsHighCount
The peak number of session pools instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

sessionPoolsTotalCount
The number of session pools instantiated on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

transactions
Returns an array of Xids representing transaction branches that exist on this JMS server in any state.

Type: array of string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSSessionPoolRuntimeMBean

This class is used for monitoring a WebLogic JMS session pool.

The properties of the weblogic.management.runtime.JMSSessionPoolRuntimeMBean entity are as follows:

connectionConsumersCurrentCount
The current number of connection consumers for this session pool.

Type: long

Constraints: Read Only, Restart Required

connectionConsumersHighCount
The peak number of simultaneous connection consumers for this session pool.

Type: long

Constraints: Read Only, Restart Required

connectionConsumersTotalCount
The total number of connection consumers made by this session pool since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JMSSessionRuntimeMBean

This class is used for monitoring a WebLogic JMS session.

The properties of the weblogic.management.runtime.JMSSessionRuntimeMBean entity are as follows:

acknowledgeMode
The acknowledge mode as one of the following:

- `AUTO_ACKNOWLEDGE`
- `CLIENT_ACKNOWLEDGE`
- `DUPS_OK_ACKNOWLEDGE`
- `NO_ACKNOWLEDGE`

Type: string

Constraints: Read Only, Restart Required

bytesPendingCount
The number of bytes pending (uncommitted and unacknowledged) for this session.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount
The number of bytes received by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesSentCount
The number of bytes sent by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersCurrentCount
The current number of consumers for this session.

Type: long

Constraints: Read Only, Restart Required

consumersHighCount
The peak number of consumers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

consumersTotalCount
The number of consumers instantiated by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
The number of messages pending (uncommitted and unacknowledged) for this session.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesSentCount
The number of bytes sent by this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

producersCurrentCount
The current number of producers for this session.

Type: long

Constraints: Read Only, Restart Required

producersHighCount
The peak number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

producersTotalCount
The number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

transacted
Indicates whether the session is transacted.

Type: boolean

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.JTAPartitionRuntimeMBean

This interface is used for accessing transaction runtime characteristics within a WebLogic server.

The properties of the weblogic.management.runtime.JTAPartitionRuntimeMBean entity are as follows:

activeTransactionsTotalCount
The number of active transactions on the server.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

registeredNonXAResourceNames
An array of NonXA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

registeredResourceNames
An array of XA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

secondsActiveTotalCount
The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

transactionAbandonedTotalCount
The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionCommittedTotalCount
The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount
The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionLLRCommittedTotalCount
The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionNoResourcesCommittedTotalCount
The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionOneResourceOnePhaseCommittedTotalCount
The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionReadOnlyOnePhaseCommittedTotalCount
The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackAppTotalCount
The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackResourceTotalCount
The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackSystemTotalCount
The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTimeoutTotalCount
The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount
The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount
The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedLoggedTotalCount
The total number of two phase commit transactions that were committed with TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedNotLoggedTotalCount
The total number of two phase commited transactions that were committed without TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedTotalCount
The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.LibraryRuntimeMBean

RuntimeMBean for library deployments.

The properties of the weblogic.management.runtime.LibraryRuntimeMBean entity are as follows:

implementationVersion
Returns the library implementation version. If not set, this value is null.

Type: string

Constraints: Read Only, Restart Required

libraryIdentifier
Returns the library identifier.

The library identifier uniquely identifies this library version across all versions of all deployed applications and deployed libraries. If the library is not versioned, the library identifier is the same as the library name.

Type: string

Constraints: Read Only, Restart Required

libraryName
Returns the library name.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName
The library's partition.

Returns the partition to which this library is deployed.

Type: string

Constraints: Read Only, Restart Required

referenced
Returns true if this library is referenced by one or more referencers. Typically, a library referencer is a deployed application.

Type: boolean

Constraints: Read Only, Restart Required

specificationVersion
Returns the library specification version. If not set, this value is null.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.LogRuntimeMBean

This interface defines the control operations for a log in the WebLogic Server.

The properties of the weblogic.management.runtime.LogRuntimeMBean entity are as follows:

logFileStreamOpened
Gets the opened state of the log file stream represented by this instance.

Type: boolean

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MailSessionRuntimeMBean

RuntimeMBean for JavaMail Sessions

The properties of the weblogic.management.runtime.MailSessionRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean

ManagedExecutorService Runtime information. It can be the information of a partition level MES, an application level MES or a regular JSR236 MES.

The properties of the weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entity are as follows:

applicationName
Get the name of the application this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

completedLongRunningRequests
Total number of long running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

completedShortRunningRequests
Total number of short running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

failedRequests
Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

Type: long

Constraints: Read Only, Restart Required

moduleName
Get the name of the module this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName
Get the name of the partition this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests
Total number of long running tasks rejected by max-concurrent-long-running-requests

Type: long

Constraints: Read Only, Restart Required

rejectedShortRunningRequests
Total number of short running tasks rejected by workmanager overload policy

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests
Total number of long running tasks which is currently running.

Type: long

Constraints: Read Only, Restart Required

submitedShortRunningRequests
Total number of submitted short running tasks

Type: long

Constraints: Read Only, Restart Required

submittedLongRunningRequests
Total number of submitted long running tasks

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean

ManagedScheduledExecutorService Runtime information. It can be the information of a partition level MSES, an application level MSES or a regular JSR236 MSES.

The properties of the weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entity are as follows:

applicationName
Get the name of the application this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

completedLongRunningRequests
Total number of long running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

completedShortRunningRequests
Total number of short running tasks which is successfully completed.

Type: long

Constraints: Read Only, Restart Required

failedRequests
Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

Type: long

Constraints: Read Only, Restart Required

moduleName
Get the name of the module this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName
Get the name of the partition this ManagedExecutor is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedLongRunningRequests
Total number of long running tasks rejected by max-concurrent-long-running-requests

Type: long

Constraints: Read Only, Restart Required

rejectedShortRunningRequests
Total number of short running tasks rejected by workmanager overload policy

Type: long

Constraints: Read Only, Restart Required

runningLongRunningRequests
Total number of long running tasks which is currently running.

Type: long

Constraints: Read Only, Restart Required

submitedShortRunningRequests
Total number of submitted short running tasks

Type: long

Constraints: Read Only, Restart Required

submittedLongRunningRequests
Total number of submitted long running tasks

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean

ManagedThreadFactory Runtime information. It can be the information of a partition level MTF, an application level MTF or a regular JSR236 MTF.

The properties of the weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entity are as follows:

applicationName
Get the name of the application this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

completedThreadsCount
The number of completed threads.

Type: long

Constraints: Read Only, Restart Required

moduleName
Get the name of the module this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName
Get the name of the partition this ManagedThreadFactory is associated with

Type: string

Constraints: Read Only, Restart Required

rejectedNewThreadRequests
The number of newThread method invocations that have been rejected because the limit of running threads was exceeded.

Type: long

Constraints: Read Only, Restart Required

runningThreadsCount
The number of running threads.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean

Runtime information for MaxThreadsConstraint

The properties of the weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity are as follows:

configuredCount
The configured count, or maximum concurrency value.

Type: int

Constraints: Read Only, Restart Required

count
The current maximum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed maximum concurrency value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

deferredRequests
Number of requests that are denied a thread for execution because the constraint is exceeded.

Type: int

Constraints: Read Only, Restart Required

executingRequests
Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MessageDrivenEJBRuntimeMBean

This interface contains accessor methods for all EJB runtime information collected for a Message Driven Bean.

The properties of the weblogic.management.runtime.MessageDrivenEJBRuntimeMBean entity are as follows:

EJBName
Provides the name for this EJB as defined in the javax.ejb.EJB annotation, or the ejb-name when * using the ejb-jar.xml deployment descriptor.

Type: string

Constraints: Read Only, Restart Required

JMSConnectionAlive
Provides information about whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

Returns whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

Type: boolean

Constraints: Read Only, Restart Required

MDBStatus
Provides the Message Driven Bean status. MDBStatus is used after the MDB is connected to the destination. MDBStatus can be Running or Suspended.

Type: string

Constraints: Read Only, Restart Required

connectionStatus
Provides the connection status for the Message Driven Bean. ConnectionStatus can be Connected or Reconnecting.

Type: string

Constraints: Read Only, Restart Required

destination
Provides a count of the Message Driven Bean destination

Type: string

Constraints: Read Only, Restart Required

healthState
The health state of this MDB.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

jmsClientID
Provides a count of the Message Driven Bean jmsClientID

Type: string

Constraints: Read Only, Restart Required

lastException
Provides the last exception this MDB encountered

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

lastExceptionAsString
Provides the last exception as String this MDB encountered

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

processedMessageCount
Provides a count of the total number of messages processed by this Message Driven Bean.

Type: long

Constraints: Read Only, Restart Required

suspendCount
Provides a count of the total number of times this MDB is suspended by the user or the EJB container.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MessagingBridgeRuntimeMBean

This class is used for monitoring a WebLogic messaging bridge.

The properties of the weblogic.management.runtime.MessagingBridgeRuntimeMBean entity are as follows:

description
The reason, if the messaging bridge is not running.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

state
The state of the messaging bridge.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.MinThreadsConstraintRuntimeMBean

Monitoring information for MinThreadsConstraint

The properties of the weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity are as follows:

completedRequests
Completed request count.

Type: long

Constraints: Read Only, Restart Required

configuredCount
The configured count, or minimum concurrency value.

Type: int

Constraints: Read Only, Restart Required

count
The current minimum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed minimum concurrency value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

currentWaitTime
The last measured time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

Type: long

Constraints: Read Only, Restart Required

executingRequests
Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

maxWaitTime
The max time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

Type: long

Constraints: Read Only, Restart Required

mustRunCount
Number of requests that must be executed to satisfy the constraint.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

outOfOrderExecutionCount
Number of requests executed out of turn to satisfy this constraint.

Type: long

Constraints: Read Only, Restart Required

partitionLimitReached
Whether the partition-level minimum threads constraint limit has reached, which could cause the number of executing requests to be less than the configured value in this minimum threads constraint.

Type: boolean

Constraints: Read Only, Restart Required

pendingRequests
Pending requests that are waiting for an available thread.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.NonXAResourceRuntimeMBean

This represents runtime statistical information about a NonXAResource

The properties of the weblogic.management.runtime.NonXAResourceRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

nonXAResourceName
Returns the resource name.

Type: string

Constraints: Read Only, Restart Required

transactionCommittedTotalCount
The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount
The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount
The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PSAssemblyRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PSAssemblyRuntimeMBean entity are as follows:

mapEntries

Returns all entries in a persistent map's assembly.

Type: string

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionFairShareRuntimeMBean

Monitoring information for PartitionFairShare

The properties of the weblogic.management.runtime.PartitionFairShareRuntimeMBean entity are as follows:

configuredFairShare

The configured fair share value.

Type: int

Constraints: Read Only, Restart Required

fairShare
The current fair share value. This could be different from the configured value as Resource Consumption Management could dynamically adjust the actual fair share value based on configured RCM policies and actual thread usage by the partition

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionAdjuster
The multiplier to be used to adjust the priority of requests from the partition in the request queue.

Type: double

Constraints: Read Only, Restart Required

threadUse
Total amount of thread use time in milliseconds used by the partition during the past period.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean

Monitoring information for PartitionMinThreadsConstraint

The properties of the weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean entity are as follows:

executingRequests
Number of requests that are currently executing.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sumMinThreadsConstraints

Sum of all configured minimum threads constraints in the partition. This is the number of threads that is needed in order to satisfy all configured minimum threads constraints in the partition if all of them have more than that amount of concurrent work requests.

Type: int

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean

The runtime MBean interface for partition specific resource consumption metrics. The resource meters are added lazily for a partition. Therefore, the first time these metrics are queried, it might return zero values. Subsequent gets would return non-zero values based on the resource consumption. These metrics are applicable in the context of a partition since either server start or partition creation/restart, whichever was later.

The properties of the weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean entity are as follows:

RCMMetricsDataAvailable

Checks whether RCM metrics data is available for this partition.

Type: boolean

Constraints: Read Only, Restart Required

allocatedMemory

Total allocated memory in bytes for the partition. This metric value increases monotonically over time, it never decreases. Retained memory should be used to get current net values.

Type: long

Constraints: Read Only, Restart Required

cpuTimeNanos

Total CPU time spent measured in nanoseconds in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

cpuUtilizationHistoricalData

Returns a snapshot of the historical data for CPU usage for the partition. CPU Utilization percentage indicates the percentage of CPU utilized by a partition with respect to available CPU to Weblogic Server. Data is returned as a two-dimensional array for the CPU usage scoped to the partition over time. Each item in the array contains a tuple of [timestamp (long), cpuUsage(long)] values.

Type: array of array of long

Constraints: Read Only, Restart Required

currentOpenFileCount
Number of files currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

currentOpenFileDescriptorCount
Number of file descriptors currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

currentOpenSocketCount
Number of sockets currently open in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

fileBytesRead
Total number of file bytes read in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

fileBytesWritten
Total number of file bytes written in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

networkBytesRead
Total number of bytes read from sockets for a partition.

Type: long

Constraints: Read Only, Restart Required

networkBytesWritten
Total number of bytes written to sockets for a partition.

Type: long

Constraints: Read Only, Restart Required

retainedHeapHistoricalData
Returns a snapshot of the historical data for retained heap memory usage for the partition. Data is returned as a two-dimensional array for the usage of retained heap scoped to the partition over time. Each item in the array contains a tuple of [timestamp (long), retainedHeap(long)] values.

Type: array of array of long

Constraints: Read Only, Restart Required

threadCount
Number of threads currently assigned to the partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedFileCount
Total number of files opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedFileDescriptorCount
Total number of file descriptors opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

totalOpenedSocketCount
Total number of sockets opened in the context of a partition.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionRuntimeMBean

Partition Runtime information.

The properties of the weblogic.management.runtime.PartitionRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overallHealthState
The aggregate health state of the partition as reported by components within the partition

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

partitionID
Partition ID for this partition.

Type: string

Constraints: Read Only, Restart Required

restartRequired
Indicates whether the partition must be restarted in order to activate configuration changes.

Type: boolean

Constraints: Read Only, Restart Required

serverName
The server associated with this configuration.

Type: string

Constraints: Read Only, Restart Required

state
The current state of the partition runtime MBean

Type: string

Constraints: Read Only, Restart Required

subState
The current substate of the partition runtime MBean

Type: string

Constraints: Read Only, Restart Required

subsystemHealthStates
An array of health states for major subsystems in the partition.

Type: array of weblogic.health.HealthState

Constraints: Read Only, Restart Required

systemFileSystemRoot
System file system root directory for this partition.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

userFileSystemRoot
User file system root directory for this partition.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PartitionWorkManagerRuntimeMBean

Monitoring information for PartitionWorkManager

The properties of the weblogic.management.runtime.PartitionWorkManagerRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overloadRejectedRequestsCount
Number of requests rejected due to configured Shared Capacity for work managers have been reached.

Type: int

Constraints: Read Only, Restart Required

pendingUserRequestCount
The number of pending user requests in the priority queue. The priority queue contains requests from internal subsystems and users. This is just the count of all user requests.

Type: int

Constraints: Read Only, Restart Required

sharedCapacityForWorkManagers
Maximum amount of requests that can be accepted in the priority queue. Note that a request with higher priority will be accepted in place of a lower priority request already in the queue even after the threshold is reached. The lower priority request is kept waiting in the queue till all high priority requests are executed. Also note that further enqueues of the low priority requests are rejected right away.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PathServiceRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PathServiceRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistenceUnitRuntimeMBean

This class is used for monitoring JPA specific runtime stats. Base class for all runtime mbeans that provide status of running modules.

The properties of the weblogic.management.runtime.PersistenceUnitRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

persistenceUnitName
Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean

This class is used for monitoring a Persistent Store Connection.

The properties of the weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean entity are as follows:

createCount
Number of create requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

deleteCount
Number of delete requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

objectCount
Number of objects contained in the connection.

Type: long

Constraints: Read Only, Restart Required

readCount
Number of read requests issued by this connection, including requests that occur during store initialization.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

updateCount
Number of update requests issued by this connection.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.PersistentStoreRuntimeMBean

This class is used for monitoring a Persistent Store.

The properties of the weblogic.management.runtime.PersistentStoreRuntimeMBean entity are as follows:

allocatedIoBufferBytes
The amount of off-heap (native) memory, in bytes, reserved for file store use.

When applicable, this is a multiple of the file store configurable attribute `IOBufferSize`. Applies to synchronous write policies `Direct-Write` and `Cache-Flush` policies

Type: long

Constraints: Read Only, Restart Required

allocatedWindowBufferBytes
The amount of off-heap (native) memory, in bytes, reserved for file store window buffer use.

Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled` but only when the native `wlfileio` library is loaded. See file store configurable attribute `MaxWindowBufferSize` for more information

Type: long

Constraints: Read Only, Restart Required

createCount
Number of create requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

deleteCount
Number of delete requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

healthState
Implement the HealthFeedback interface by returning the health state of this store.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

objectCount
Number of objects contained in the store.

Type: long

Constraints: Read Only, Restart Required

physicalWriteCount
Number of times the store flushed its data to durable storage.

Type: long

Constraints: Read Only, Restart Required

readCount
Number of read requests issued by this store, including requests that occur during store initialization.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

updateCount
Number of update requests issued by this store.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.QueryCacheRuntimeMBean

This interface contains accessor methods for all query cache runtime information collected for an EJB. The cache miss counts need some explaining. A query-cache miss can occur due to one of the following reasons:

- The query result was not found in the query-cache

- The query result has timed out
- A bean which satisfies the query wasnot found in the entity cache
- A query with relationship-caching turned on did not find the related-beans query result
- A query which loads multiple EJBs could not load one or more of them

To better aid tuning, there are separate counters provided for each of the last four of the above causes. The fifth counter is a total cache miss counter. This counter takes into account all five causes of a cache miss.

The properties of the weblogic.management.runtime.QueryCacheRuntimeMBean entity are as follows:

cacheAccessCount
Provides a count of the number of accesses of the query cache for this EJB.

Returns the number of accesses of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

cacheHitCount
Provides a count of the number of cache hits of the query cache for this EJB.

Returns the number of cache hits of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

cacheMissByBeanEvictionCount
Provides a count of the number of cache misses of the query cache for this EJB because corresponding beans were not found in the entity cache.

Returns the number of times a cache miss occurred for this EJB because corresponding beans were not found in the entity cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByDependentQueryMissCount
Provides a count of the number of cache misses of the query cache for this EJB because a dependent query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a dependent query was not found in another EJB's query cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByRelatedQueryMissCount
Provides a count of the number of cache misses of the query cache for this EJB because a related query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a related query was not found in another EJB's query cache.

Type: long

Constraints: Read Only, Restart Required

cacheMissByTimeoutCount
Provides a count of the number of cache misses of the query cache for this EJB due to query results timing out.

Returns the number of cache misses due to query result timeout for this EJB.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalCacheMissCount
Provides a count of the total number of cache misses of the query cache for this EJB.

Returns the total number of cache misses of the query cache for this EJB.

Type: long

Constraints: Read Only, Restart Required

totalCachedQueriesCount
Provides a count of the total number of query results for this EJB currently in the query cache.

Returns the total number of query results for this EJB currently in the EJB cache.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.RealmRuntimeMBean

This class is used to monitor and manage per security realm runtime information.

The properties of the weblogic.management.runtime.RealmRuntimeMBean entity are as follows:

name
The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=`*`user-specified-name`*

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.RequestClassRuntimeMBean

RequestClassRuntimeMBean presents runtime information about RequestClasses. A request class represents a class of work. Work using the same request class shares the same priority.

The properties of the weblogic.management.runtime.RequestClassRuntimeMBean entity are as follows:

completedCount

Total number of completions since server start

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pendingRequestCount

Number of requests waiting for a thread to become available.

Type: int

Constraints: Read Only, Restart Required

requestClassType

Returns the type of RequestClass. Either `FAIR_SHARE` or `RESPONSE_TIME` or `CONTEXT`

Type: string

Constraints: Read Only, Restart Required

totalThreadUse

Total amount of thread use time in millisec's used by the request class since server start.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

virtualTimeIncrement

Current priority of the request class. The priority is relative to other request class priorities. The priority is calculated dynamically frequently and can change.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.ResourceManagerRuntimeMBean

The {@code ResourceManagerRuntimeMBean} holds runtime information about a Resource Manager that has been assigned to the current Domain Partition. The {@code ResourceManagerRuntimeMBean} is used for retrieving the runtime state (information about policy evaluation, current resource usage, recourse actions executed) of configured resource management policies established for the current Partition by a system administrator in the current server instance.

The properties of the weblogic.management.runtime.ResourceManagerRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ResourceRuntimeMBean

The {@code ResourceRuntimeMBean} holds runtime state about the policy evaluations that have been performed for a Resource type in the current Domain Partition in the current server instance.

The properties of the weblogic.management.runtime.ResourceRuntimeMBean entity are as follows:

name
The name of the policy defined for this resource as configured in the {@code ResourceManagerMBean} for this MBean's resource type getResourceType().

Type: string

Constraints: Read Only, Restart Required

resourceType
The resource type associated with this MBean.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

usage
The current resource utilization of a Resource by the current Domain Partition, in the current Server instance.

To track or monitor resource consumption for a Domain Partition without creating resource consumption management policies, see weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.RuntimeMBean

The tagging interface for all runtime MBeans.

The properties of the weblogic.management.runtime.RuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFAgentRuntimeMBean

This class is used for monitoring a WebLogic SAF agent.

The properties of the weblogic.management.runtime.SAFAgentRuntimeMBean entity are as follows:

bytesCurrentCount

Returns the current number of bytes. This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount

Returns the peak number of bytes since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount

Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount

The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime
Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

conversationsCurrentCount
Returns the current number of conversations

Type: long

Constraints: Read Only, Restart Required

conversationsHighCount
The peak number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

conversationsTotalCount
The total number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

failedMessagesTotal
Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

healthState
The health state of this JMS server.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

messagesCurrentCount
Returns the current number of messages. This number includes the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount
Returns the peak number of messages since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime
Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

pausedForForwarding
Indicates whether or not the sending agent is paused for forwarding at the current time.

Type: boolean

Constraints: Read Only, Restart Required

pausedForIncoming
Indicates whether or not the sending agent is paused for incoming messages at the current time.

Type: boolean

Constraints: Read Only, Restart Required

pausedForReceiving
Indicates whether or not the receiving agent is paused for receiving at the current time.

Type: boolean

Constraints: Read Only, Restart Required

remoteEndpointsCurrentCount
The current number of remote endpoints to which this SAF agent has been storing and forwarding messages.

Type: long

Constraints: Read Only, Restart Required

remoteEndpointsHighCount
The peak number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

Type: long

Constraints: Read Only, Restart Required

remoteEndpointsTotalCount
The number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFConversationRuntimeMBean

This class is used for monitoring a WebLogic SAF conversation.

The properties of the weblogic.management.runtime.SAFConversationRuntimeMBean entity are as follows:

QOS
The quality of service (QOS) for the SAF conversation.

The quality-of-service values are:

- `weblogic.management.runtime.SAFConstants.QOS_EXACTLY_ONCE`
- `weblogic.management.runtime.SAFConstants.QOS_ATLEAST_ONCE`
- `weblogic.management.runtime.SAFConstants.QOS_ATMOST_ONCE`

Type: string

Constraints: Read Only, Restart Required

conversationName
The name of the conversation.

Type: string

Constraints: Read Only, Restart Required

destinationURL
The URL of the destination.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean

This class is used for monitoring a WebLogic SAF remote endpoint

The properties of the weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean entity are as follows:

URL
The URL of the remote endpoint.

Type: string

Constraints: Read Only, Restart Required

bytesCurrentCount
Returns the current number of bytes. This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

bytesHighCount
Returns the peak number of bytes since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesPendingCount
Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

bytesReceivedCount
The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

bytesThresholdTime
Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

downtimeHigh
Specifies the longest time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

downtimeTotal
Specifies the total time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

endpointType
Specifies if the remote endpoint is a JMS or Web Services (WSRM) destination. The possible values are: weblogic.management.runtime.SAFConstants.JMS_ENDPOINT or weblogic.management.runtime.SAFConstants.WS_ENDPOINT.

Type: string

Constraints: Read Only, Restart Required

failedMessagesTotal
Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

lastException
Specifies the exception thrown when message forwarding failed.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

lastTimeConnected
Specifies the last time that the remote endpoint was connected.

Type: java.util.Date

Constraints: Read Only, Restart Required

lastTimeFailedToConnect
Specifies the last time that the remote endpoint failed to be connected.

Type: java.util.Date

Constraints: Read Only, Restart Required

messagesCurrentCount
Returns the current number of messages. This number includes the pending messages.

Type: long

Constraints: Read Only, Restart Required

messagesHighCount
Returns the peak number of messages since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesPendingCount
Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

Type: long

Constraints: Read Only, Restart Required

messagesReceivedCount
The number of messages received since the last reset.

Type: long

Constraints: Read Only, Restart Required

messagesThresholdTime

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationState

Specifies the state of the most recent `ExireAll` operation.

Type: string

Constraints: Read Only, Restart Required

pausedForForwarding

Indicates if the remote endpoint is currently not forwarding messages.

Type: boolean

Constraints: Read Only, Restart Required

pausedForIncoming

Indicates if a remote endpoint is currently not accepting new messages.

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

uptimeHigh

Specifies the longest time, in seconds, that the remote endpoint has been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

uptimeTotal

Specifies the total time, in seconds, that the remote endpoint has been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.SAFRuntimeMBean

This class is used for monitoring a WebLogic SAF service.

The properties of the weblogic.management.runtime.SAFRuntimeMBean entity are as follows:

healthState
The health state of SAF service.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerRuntimeMBean

Provides methods for retrieving runtime information about a server instance and for transitioning a server from one state to another.

The properties of the weblogic.management.runtime.ServerRuntimeMBean entity are as follows:

adminServerHost
The address on which the Administration Server is listening for connections. For example, this might return the string: santiago

Type: string

Constraints: Read Only, Restart Required

adminServerListenPort
The port on which the Administration Server is listening for connections.

Type: int

Constraints: Read Only, Restart Required

adminServerListenPortSecure
Indicates whether the port that the server uses for administrative traffic is configured to use a secure protocol.

Type: boolean

Constraints: Read Only, Restart Required

defaultURL
The URL that clients use to connect to this server's default network channel.

The returned value indicates the default protocol, listen address and listen port:

protocol://*listen-addresslisten-port*

Note: The default protocol, listen address and listen port are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getDefaultURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

The returned URL will be consistent with dynamic channel updates.

Type: string

Constraints: Read Only, Restart Required

healthState

The health state of the server as reported by the server's self-health monitoring.

For example, the server can report if it is overloaded by too many requests, if it needs more memory resources, or if it will soon fail for other reasons.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

overallHealthState

Determine the overall health state of this server, taking into account the health of each of its subsystems.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

restartRequired

Indicates whether the server must be restarted in order to activate configuration changes.

Type: boolean

Constraints: Read Only, Restart Required

state

The current life cycle state of this server.

For example, a server can be in a RUNNING state in which it can receive and process requests or in an ADMIN state in which it can receive only administrative requests.

Type: string

Constraints: Read Only, Restart Required

stateVal

Returns current state of the server as in integer.
weblogic.management.runtime.ServerStates has more information about the available server states

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogicVersion
The version of this WebLogic Server instance (server).

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ServerSecurityRuntimeMBean

This class is used for monitoring WebLogic Security Info.

The properties of the weblogic.management.runtime.ServerSecurityRuntimeMBean entity are as follows:

name
The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TaskRuntimeMBean

Exposes monitoring information about an ongoing and potentially long-running administrative process. This should be taken to mean, at minimum, any OA&M operation involving I/O. Examples include starting and stopping servers, deploying and undeploying applications, or migrating services.

An MBean operation of this sort should fork a separate thread to perform the actual work and immediately return an instance of `TaskRuntimeMBean` to the caller. The caller can then use this to track the task's progress as desired. Users can also query for all instances of `TaskRuntimeMBean` to get a summary of both currently-running and recently-completed tasks.

Instance of `TaskRuntimeMBean` continue to exist in the MBeanServer after the completion of the work they describe. They will eventually either be explicitly deregistered by the user, or removed by a scavenger process which periodically purges instances of `TaskRuntimeMBean` that have been completed for some time.

The properties of the weblogic.management.runtime.TaskRuntimeMBean entity are as follows:

completed
This property indicates whether an asynchronous job has completed.

Type: boolean

description
A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime
This property indicates the time when the asynchronous job ended.

Type: java.util.Date

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask
The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

progress
The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running
Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime
This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong
The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask
Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError
Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus
The status of this task.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.ThreadPoolRuntimeMBean

This bean is used to monitor the self-tuning queue

The properties of the weblogic.management.runtime.ThreadPoolRuntimeMBean entity are as follows:

executeThreadTotalCount
The total number of threads in the pool.

Type: int

Constraints: Read Only, Restart Required

stuckThreadCount
Number of stuck threads in the thread pool.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TransactionNameRuntimeMBean

This interface represents runtime statistics for a transaction name category.

The properties of the weblogic.management.runtime.TransactionNameRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

secondsActiveTotalCount
The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

transactionAbandonedTotalCount
The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionCommittedTotalCount
The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount
The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionLLRCommittedTotalCount
The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionName
The transaction name.

Type: string

Constraints: Read Only, Restart Required

transactionNoResourcesCommittedTotalCount
The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionOneResourceOnePhaseCommittedTotalCount
The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionReadOnlyOnePhaseCommittedTotalCount
The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackAppTotalCount
The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackResourceTotalCount
The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackSystemTotalCount
The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTimeoutTotalCount
The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount
The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount
The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedLoggedTotalCount
The total number of two phase commit transactions that were committed with TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedNotLoggedTotalCount
The total number of two phase commited transactions that were committed without TLog since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTwoPhaseCommittedTotalCount
The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TransactionResourceRuntimeMBean

This interface represents runtime statistics for a transactional resource.

The properties of the weblogic.management.runtime.TransactionResourceRuntimeMBean entity are as follows:

healthState
The health state of the Resource.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

resourceName
The resource name.

Type: string

Constraints: Read Only, Restart Required

transactionCommittedTotalCount
The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicCommitTotalCount
The number of transactions for which this resource has returned a heuristic commit decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicHazardTotalCount
The number of transactions for which this resource has reported a heuristic hazard decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicMixedTotalCount

The number of transactions for which this resource has reported a heuristic mixed decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicRollbackTotalCount

The number of transactions for which this resource has returned a heuristic rollback decision.

Type: long

Constraints: Read Only, Restart Required

transactionHeuristicsTotalCount

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionRolledBackTotalCount

The number of transactions that were rolled back since the server was started.

Type: long

Constraints: Read Only, Restart Required

transactionTotalCount

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.TriggerRuntimeMBean

The {@code TriggerRuntimeMBean} holds runtime state (for the current Server instance) for a Trigger that has been configured in the Resource Consumption Management policy of the current Domain Partition.

The WebLogic Resource Consumption Management feature automatically initiates the configured recourse action of a Trigger when the Trigger's configured usage limits are exceeded by a Domain Partition. When a usage limit is exceeded, and the configured recourse action has been successfully executed, the Trigger is *Activated*.

When the current resource usage by the Domain Partition falls below the Trigger's configured usage limit, the feature automatically withdraws the recourse action where

possible. When the current usage is below the configured usage limit, and the configured recourse action has been successfully withdrawn, the Trigger is said to be *not Activated*.

The MBean captures the following states for a Trigger when the current resource consumption usage by the Domain Partition exceeds or goes below the configured usage limit for the Domain Partition:

- Whether the Trigger is *Activated* (usage has exceeded the limit and the recourse action was successfully executed) or not
- The time when the last recourse action was executed successfully for the Trigger
- Whether a recourse action has been initiated in response to the resource usage by the Domain Partition exceeding the configured usage limits

The properties of the weblogic.management.runtime.TriggerRuntimeMBean entity are as follows:

activated
Indicates if the Trigger is *Activated*

Type: boolean

Constraints: Read Only, Restart Required

initiated
Indicates if a recourse action has been initiated for this Trigger as a result of the current resource usage by a Domain Partition exceeding its usage limit. A new {@code RecourseActionEventVBean} is added to the array returned by getRecourseActionEventsHistory().

The kind of recourse action initiated (for example, a new recourse action or a withdrawal of an existing recourse action) can be determined through RecourseActionEventVBean#isActive().

Type: boolean

Constraints: Read Only, Restart Required

lastTimeExecuted
The {@code Date} when the last recourse action was successfully executed for the current Trigger.

Type: java.util.Date

Constraints: Read Only, Restart Required

name
The name of the Trigger, as configured in the Resource Consumption Management policy of the Domain Partition.

Type: string

Constraints: Read Only, Restart Required

recourseActionEventsHistory
A list of recourse action events that have been initiated and executed.

Type: array of weblogic.management.runtime.RecourseActionEventVBean

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.UserLockoutManagerRuntimeMBean

This class is used to monitor and manage per security realm user lockout information.

The properties of the weblogic.management.runtime.UserLockoutManagerRuntimeMBean entity are as follows:

invalidLoginAttemptsTotalCount
Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled. In a cluster, this method returns the number of invalid logins attempted that have occured since the cluster has been started because all servers share login failure information.

Type: long

Constraints: Read Only, Restart Required

invalidLoginUsersHighCount
Returns the highest number of users with concurrent unexpired or uncleared invalid login attempts. Invalid login attempts expire as specified by `LockoutResetDuration`. This count is useful in determining whether the `LockoutCacheSize` needs to be modified.

Type: long

Constraints: Read Only, Restart Required

lockedUsersCurrentCount
Returns the number of users that are currently locked out of this server.

Type: long

Constraints: Read Only, Restart Required

loginAttemptsWhileLockedTotalCount
Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

unlockedUsersTotalCount

Returns the number times users have been unlocked since this server has been started.

Type: long

Constraints: Read Only, Restart Required

userLockoutTotalCount

Returns the number of user lockouts that have occured since this server has been started. In a cluster, this method returns the number of user lockouts that have occured since the cluster has been started because all servers share login failure information.

Type: long

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFDataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the weblogic.management.runtime.WLDFDataAccessRuntimeMBean entity are as follows:

earliestAvailableTimestamp

Type: long

Constraints: Read Only, Restart Required

latestAvailableTimestamp

Type: long

Constraints: Read Only, Restart Required

latestRecordId

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

timestampAvailable

Type: boolean

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations, as well as metadata about harvestable and harvested attributes, types, and instances. Harvestable means potentially available for harvesting; harvested means explicitly designated for harvesting. These terms apply to types, instances, and the attributes within those types. In addition, the interface provides access to sampling and snapshot statistics. All statistics are base on data collected during the current server session.

The properties of the weblogic.management.runtime.WLDFHarvesterRuntimeMBean entity are as follows:

knownHarvestableTypes

The set of all known types, regardless of whether the types are currently configured for harvesting. The set includes the WebLogic Server MBeans, which are always present, plus any other types that can be discovered. MBeans that are not WebLogic Server MBeans will require instances to exist in order to discover the type.

Type: array of string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean

Exposes monitoring information about a potentially long-running request for the generation of a diagnostic image. Remote clients, as well as clients running within a server, can access this information.

weblogic.management.runtime.WLDFImageRuntimeMBean
WLDFImageRuntimeMBean supports operations to request the generation of a diagnostic image for capturing a running server's internal state information. These operations will fork a separate thread to perform the actual work and immediately return an instance of this MBean to the caller. The caller can then use that instance to track the task's progress.

The properties of the weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean entity are as follows:

completed

This property indicates whether an asynchronous job has completed.

Type: boolean

description

A description of this task.

Type: string

Constraints: Read Only, Restart Required

endTime

This property indicates the time when the asynchronous job ended.

Type: java.util.Date

imageFileName
Retrieve the name of the image file that was created. If the name is not yet known at the time this is called, this may return null.

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

parentTask
The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

progress
The progress of this task.

Type: string

Constraints: Read Only, Restart Required

running
Indicates whether the task is still running.

Type: boolean

Constraints: Read Only, Restart Required

startTime
This property indicates the time when an asynchronous job was started.

Type: java.util.Date

startTimeAsLong
The time at which this task was started.

Type: long

Constraints: Read Only, Restart Required

systemTask
Indicates whether this task was initiated by the server versus a user.

Type: boolean

Constraints: Read Only, Restart Required

taskError
Returns an exception describing the error, if any, that occurred while performing this task.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

taskStatus
The status of this task.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean

Use this interface to access the different types of diagnostic data generated by a partition.

The properties of the weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean entity are as follows:

availableDiagnosticDataAccessorNames
Type: array of string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations for a partition.

The properties of the weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean entity are as follows:

averageSamplingTime
The average amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

maximumSamplingTime
The maximum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

minimumSamplingTime
The minimum sampling time, in nanoseconds.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalSamplingCycles
The total number of sampling cycles taken thus far.

Type: long

Constraints: Read Only, Restart Required

totalSamplingTime
The total amount of time, in nanoseconds, spent in sampling cycles.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionImageRuntimeMBean

This interface controls diagnostic image creation, and provides access to run-time information about past and current diagnostic image capture requests.

The properties of the weblogic.management.runtime.WLDFPartitionImageRuntimeMBean entity are as follows:

availableCapturedImages
Returns a list of captured images that are available on the Server.

Type: array of string

Constraints: Read Only, Restart Required

imageDir
The default directory where the server stores captured diagnostic images.

Type: string

Constraints: Read Only, Restart Required

imageTimeout
The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFPartitionRuntimeMBean

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFPartitionRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFRuntimeMBean

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFRuntimeMBean entity are as follows:

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean

Provides access to policy and action statistical data for the current instance of this server.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean entity are as follows:

activeAlarmWatches
The names of active alarm policies.

Type: array of string

Constraints: Read Only, Restart Required

averageEventDataWatchEvaluationTime
The average Instrumentation event data evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageHarvesterWatchEvaluationTime
The average Harvester evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

averageLogWatchEvaluationTime
The average Log evaluation cycle time, in milliseconds.

Type: long

Constraints: Read Only, Restart Required

currentActiveAlarmsCount
The number of active alarms of any type.

Type: int

Constraints: Read Only, Restart Required

maximumActiveAlarmsCount
The maximum number of active alarms at any one time.

Type: int

Constraints: Read Only, Restart Required

maximumEventDataWatchEvaluationTime
The maximum time spent evaluating EventData policies.

Type: long

Constraints: Read Only, Restart Required

maximumHarvesterWatchEvaluationTime
The maximum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

maximumLogWatchEvaluationTime
The maximum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumEventDataWatchEvaluationTime
The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

minimumHarvesterWatchEvaluationTime
The minimum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

minimumLogWatchEvaluationTime
The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

totalActiveAutomaticResetAlarms
The total number of active automatically reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalActiveManualResetAlarms
The total number of active manually reset alarms.

Type: long

Constraints: Read Only, Restart Required

totalDIMGNotificationsPerformed
The total number of Diagnostic Image actions fired. Diagnostic Image files are not true actions, but this records the number of image captures requested by the policy component.

Type: long

Constraints: Read Only, Restart Required

totalEventDataEvaluationCycles
The total number of times Instrumentation event data policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchEvaluations
The total number of Instrumentation event data policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Instrumentation event data policies.

Type: long

Constraints: Read Only, Restart Required

totalEventDataWatchesTriggered
The total number of Instrumentation event data policies that have evaluated to `true` and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalFailedDIMGNotifications
The total number of failed Diagnostic Image action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMSNotifications
The total number of failed JMS action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedJMXNotifications
The total number of failed JMX action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedNotifications
The total number of failed action requests.

Type: long

Constraints: Read Only, Restart Required

totalFailedSMTPNotifications
The total number of failed SMTP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalFailedSNMPNotifications
The total number of failed SNMP action attempts.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterEvaluationCycles
The total number of times the Harvester has invoked the Policy and Action component to evaluate Harvester policies. (This number corresponds to the number of sampling cycles.)

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchEvaluations

The total number of Harvester policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Harvester policies.

Type: long

Constraints: Read Only, Restart Required

totalHarvesterWatchesTriggered

The total number of Harvester policies that have evaluated to `true` and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalJMSNotificationsPerformed

The total number of JMS actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalJMXNotificationsPerformed

The total number of JMX actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalLogEvaluationCycles

The total number of times Log policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchEvaluations

The total number of Log policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Log policies.

Type: long

Constraints: Read Only, Restart Required

totalLogWatchesTriggered

The total number of Log policies that have evaluated to `true` and triggered actions.

Type: long

Constraints: Read Only, Restart Required

totalNotificationsPerformed

The total number of actions performed.

Type: long

Constraints: Read Only, Restart Required

totalSMTPNotificationsPerformed

The total number of SMTP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

totalSNMPNotificationsPerformed

The total number of SNMP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean

Attaches an action listener in order to receive action events when a policy evaluates to `true`. Note that the listener will receive all actions; the caller must filter the output.

Unlike the deprecated WLDFWatchJMXNotificationRuntimeMBean, the action generated by this source is a Java Map object comprised of simple JDK types, and does not require a client dependency on any WLDF code.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WorkManagerRuntimeMBean

WorkManager Runtime information.

The properties of the weblogic.management.runtime.WorkManagerRuntimeMBean entity are as follows:

applicationName

Get the name of the application this WorkManager is associated with

Type: string

Constraints: Read Only, Restart Required

completedDaemonRequests
The number of daemon requests that have been processed

Type: long

Constraints: Read Only, Restart Required

completedRequests
The number of requests that have been processed, including daemon requests.

Type: long

Constraints: Read Only, Restart Required

healthState
Returns the HealthState mbean for the work manager.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

moduleName
Get the name of the module this WorkManager is associated with

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

partitionName
Returns the name of the partition that the work manager is associated with.

Type: string

Constraints: Read Only, Restart Required

pendingDaemonRequests
The number of daemon requests in progress.

Type: int

Constraints: Read Only, Restart Required

pendingRequests
The number of waiting requests in the queue, including daemon requests.

Type: int

Constraints: Read Only, Restart Required

stuckThreadCount
The number of threads that are considered to be stuck on the basis of any stuck thread constraints.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean

Describes Web Service operation state, such as deployment state and runtime statistics. The derived MBean determines whether this state is for a single operation or whether it is aggregated across operations.

This MBean can describe the operation(s) on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean entity are as follows:

dispatchTimeAverage
Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh
Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow
Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal
Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount
Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage
Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh
Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow
Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal
Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount
Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError
Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime
Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime
Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError
Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime
Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime
Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

responseCount
Total number of oresponses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount
Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage
Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh
Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow
Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal
Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeBaseOperationRuntimeMBean

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the weblogic.management.runtime.WseeBaseOperationRuntimeMBean entity are as follows:

dispatchTimeAverage
Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh
Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow
Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount

Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage

Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh

Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow

Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal

Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError

Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime
Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime
Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError
Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime
Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime
Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationName
Name of the operation for which runtime information is being provided.

Type: string

Constraints: Read Only, Restart Required

responseCount
Total number of oresponses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount
Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage
Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh
Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow
Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal
Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean

Encapsulates runtime information about a particular Web Service cluster front-end instance. This MBean represents a cluster front-end instance (e.g. HttpClusterServlet) that contains a cluster routing function.

The properties of the weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeClusterRoutingRuntimeMBean

Encapsulates runtime information about a particular Web Service cluster routing instance (whether it be a front-end router or an in-place router).

The properties of the weblogic.management.runtime.WseeClusterRoutingRuntimeMBean entity are as follows:

lastRoutingFailure

The exception that caused the last routing failure, or null if no failures have occurred.

Type: string

Constraints: Read Only, Restart Required

lastRoutingFailureTime

The time (in milliseconds since epoch) of the last routing failure (or 0 if no failures have occurred).

Type: long

Constraints: Read Only, Restart Required

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

requestCount

The number of requests (messages with no RelatesTo header) that have come through this front-end since the server started.

Type: int

Constraints: Read Only, Restart Required

responseCount

The number of responses (messages with a RelatesTo header) that have come through this front-end since the server started.

Type: int

Constraints: Read Only, Restart Required

routedRequestCount

The number of requests that were routed to a specific server instance via routing information in the request (not just load balanced) since the server started.

Type: int

Constraints: Read Only, Restart Required

routedResponseCount

The number of responses that were routed to a specific server instance via routing information in the response (not just load balanced) since the server started.

Type: int

Constraints: Read Only, Restart Required

routingFailureCount
The number of times a message failed to be routed, since the server started.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeHandlerRuntimeMBean

Provides runtime information about a SOAP message handler that has been associated with a Web service.

SOAP message handlers are used to intercept both the inbound (request) and outbound (response) SOAP messages so that extra processing can be done on the messages. Programmers specify SOAP message handlers for a Web Service using the @SOAPMessageHandlers and @HandlerChain JWS annotations.

The properties of the weblogic.management.runtime.WseeHandlerRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeMcRuntimeMBean

Describes the state of MakeConnection pending message lists

The properties of the weblogic.management.runtime.WseeMcRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeOperationRuntimeMBean

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds

The properties of the weblogic.management.runtime.WseeOperationRuntimeMBean entity are as follows:

dispatchTimeAverage
Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeHigh
Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeLow
Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

dispatchTimeTotal
Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

Type: long

Constraints: Read Only, Restart Required

errorCount
Number of errors sending or receiving a request.

Type: int

Constraints: Read Only, Restart Required

executionTimeAverage
Average operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeHigh
Longest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeLow
Shortest operation execution time.

Type: long

Constraints: Read Only, Restart Required

executionTimeTotal
Total time for all operation executions.

Type: long

Constraints: Read Only, Restart Required

invocationCount
Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

Type: int

Constraints: Read Only, Restart Required

lastError
Last error that occurred processing a request.

Type: string

Constraints: Read Only, Restart Required

lastErrorTime
Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastInvocationTime
Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

Type: long

Constraints: Read Only, Restart Required

lastResponseError
Last response error to arrive for this client/service (or null if no errors have occurred).

Type: string

Constraints: Read Only, Restart Required

lastResponseErrorTime
Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

lastResponseTime
Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

Type: long

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

operationName
Name of the operation for which runtime information is being provided.

Type: string

Constraints: Read Only, Restart Required

policyAttachmentSupport
Get attachment support for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectName
Get subject name for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectResourcePattern
The policySubject parameter must uniquely identify what application, module, service, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used: /{domain}/{instance}/{app}/WEBs|EJBs/{module }/WEBSERVICEs/{service}/PORTs/{port}/OPERATIONs/{operation}

Type: string

Constraints: Read Only, Restart Required

policySubjectType
Get subject type for this port MBean.

Type: string

Constraints: Read Only, Restart Required

responseCount
Total number of oresponses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseErrorCount
Total number of errors from responses generated from operation invocations.

Type: int

Constraints: Read Only, Restart Required

responseTimeAverage
Average response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeHigh
Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeLow
Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

responseTimeTotal
Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePolicyRuntimeMBean

Specifies runtime information about the WS-Policy files that are available for the Web Service.

Web Services can have one or more WS-Policy files associated with the endpoint itself or its operations; the WS-Policy files specify configuration options for Web Service message-level security (encryption and digital signatures) and reliable SOAP messaging.

Programmers can use the @Policy JWS annotation to associate a WS-Policy file to a Web Service at development time. Administrators can also associate additional WS-Policy files at runtime.

The properties of the weblogic.management.runtime.WseePolicyRuntimeMBean entity are as follows:

availablePolicies
Type: array of string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePortPolicyRuntimeMBean

Describes the Web service security policy state of a particular Web service port.

The properties of the weblogic.management.runtime.WseePortPolicyRuntimeMBean entity are as follows:

authenticationSuccesses
Total number of authentication successes detected for this port. Only incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

authenticationViolations
Total number of authentication violations generated for this port. Only incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

authorizationSuccesses
Total number of authorization successes detected for this port.

Type: int

Constraints: Read Only, Restart Required

authorizationViolations
Total number of authorization violations generated for this port.

Type: int

Constraints: Read Only, Restart Required

confidentialitySuccesses
Total number of confidentiality successes generated for this port. Both outgoing and incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

confidentialityViolations
Total number of confidentiality violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

integritySuccesses
Total number of integrity successes generated for this port. Both outgoing and incoming message processing can add to the success count.

Type: int

Constraints: Read Only, Restart Required

integrityViolations
Total number of integrity violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyFaults
Total number of policy faults generated for this port.

Type: int

Constraints: Read Only, Restart Required

totalSecurityFaults
Total number of security faults and violations generated for this port.

Type: int

Constraints: Read Only, Restart Required

totalViolations
Total number of authentication, integrity, and confidentialy violations. Both outgoing and incoming message processing can add to the violation count.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseePortRuntimeMBean

Describes the state of a particular Web Service port.

The properties of the weblogic.management.runtime.WseePortRuntimeMBean entity are as follows:

name

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyAttachmentSupport

Get attachment support for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policyFaults

Total number of policy faults.

Type: int

Constraints: Read Only, Restart Required

policySubjectAbsolutePortableExpression

The policySubject AbsolutePortableExpression This is the WSM ResourcePattern AbsolutePortableExpression string

Type: string

Constraints: Read Only, Restart Required

policySubjectName

Get subject name for this port MBean.

Type: string

Constraints: Read Only, Restart Required

policySubjectResourcePattern

The policySubject parameter must uniquely identify what application, module, service or reference-name, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used:
/{domain}/{instance}/{app}/WEBs|EJBs/{module}/WEBSERVICEs/{service}|{reference-name}/PORTs/{port}

Type: string

Constraints: Read Only, Restart Required

policySubjectType

Get subject type for this port MBean.

Type: string

Constraints: Read Only, Restart Required

portName
Name of this port.

This attribute corresponds to the "name" attribute of the "port" element in the WSDL that describes the Web service. Programmers specify the name of the port using the portName attribute of the @WLXXXTransport annotation, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

Type: string

Constraints: Read Only, Restart Required

startTime
Date and time that the Web service endpoint started.

Type: long

Constraints: Read Only, Restart Required

totalSecurityFaults
Total number of security faults and violations.

Type: int

Constraints: Read Only, Restart Required

transportProtocolType
Transport protocol used to invoke this Web service, such as HTTP, HTTPS, or JMS.

This attribute determines the transport that is published in the endpoint address section of the WSDL of the Web Service. Programmers specify the transport by the type of @WLXXXTransport JWS annotation they specify, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

Type: string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeV2RuntimeMBean

Encapsulates runtime information about a particular Web Service. The name attribute of this MBean will be the value of the webservice-description-name element in webservices.xml

The properties of the weblogic.management.runtime.WseeV2RuntimeMBean entity are as follows:

URI
Specifies the URI of this Web service.

This attribute corresponds to the final part of the endpoint address in the WSDL that describes the Web Services. It is specified at development time for JAX-RPC services using the serviceURI attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services, this can be set during compilation.

Type: string

Constraints: Read Only, Restart Required

contextPath
Specifies the context path of this web service.

This attribute corresponds to the initial part of the endpoint address in the WSDL that describes the Web Service. It is specified at development time in JAX-RPC services using the contextPath attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services the context path is set either during compilation of the service, or by the module (web or EJB) hosting the service.

Type: string

Constraints: Read Only, Restart Required

implementationType
Specifies the implementation type of this service.

Valid values include: JAX-WS 2.0 JAX-RPC 1.1

Type: string

Constraints: Read Only, Restart Required

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

policyFaults
Total number of faults generated by security policy handler.

Type: int

Constraints: Read Only, Restart Required

serviceName
Specifies the qualified name of this Web service.

This attribute is calculated based on actual MBean type and of the form:

`WseeRuntimeMBean`: <app name>#<app version>!<service name>.

`WseeV2RuntimeMBean`: <app name>#<app version>!<web WAR name or EJB JAR name>!<service name>.

Type: string

Constraints: Read Only, Restart Required

startTime
Date and time that the Web service starts.

Type: long

Constraints: Read Only, Restart Required

totalSecurityFaults
Total number of faults generated by this endpoint.

Type: int

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

webserviceDescriptionName
webservice description name for this webservice

Type: string

Constraints: Read Only, Restart Required

weblogic.management.runtime.WseeWsrmRuntimeMBean

Encapsulates runtime information about WS-RM functionality. If this MBean is parented by a WseePortRuntimeMBean instance, this MBean represents WS-RM resources contained in a particular Web Service or web service client. If this MBean is parented by ServerRuntimeMBean, this MBean represents WS-RM resources for the entire server/VM (spanning across applications, web services, clients, etc.)

The properties of the weblogic.management.runtime.WseeWsrmRuntimeMBean entity are as follows:

name
The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

sequenceIds
A list of sequence IDs representing active sequences being managed on the WS-RM destination (receiving side).

Type: array of string

Constraints: Read Only, Restart Required

type
Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required