

## **Oracle® Fusion Middleware**

RESTful Server Runtime Reference for Oracle WebLogic  
Server

12c (12.2.1.2.0)

**E78024-01**

September 2016

This reference describes the RESTful server runtime  
resources that are used to manage WebLogic Server.

Copyright © 2015, 2016, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

This documentation is in preproduction status and is intended for demonstration and preliminary use only. It may not be specific to the hardware on which you are using the software. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to this documentation and will not be responsible for any loss, costs, or damages incurred due to the use of this documentation.

The information contained in this document is for informational sharing purposes only and should be considered in your capacity as a customer advisory board member or pursuant to your beta trial agreement only. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described in this document remains at the sole discretion of Oracle.

This document in any form, software or printed matter, contains proprietary information that is the exclusive property of Oracle. Your access to and use of this confidential material is subject to the terms and conditions of your Oracle Master Agreement, Oracle License and Services Agreement, Oracle PartnerNetwork Agreement, Oracle distribution agreement, or other license agreement which has been executed by you and Oracle and with which you agree to comply. This document and information contained herein may not be disclosed, copied, reproduced, or distributed to anyone outside Oracle without prior written consent of Oracle. This document is not part of your license agreement nor can it be incorporated into any contractual agreement with Oracle or its subsidiaries or affiliates.

---

---

# Contents

**Preface** ..... cxli

## 1 Resources

/management/weblogic..... 1-2

/management/weblogic/{version} ..... 1-5

/management/weblogic/{version}/currentUser ..... 1-9

/management/weblogic/{version}/serverRuntime..... 1-12

/management/weblogic/{version}/serverRuntime/applicationRuntimes ..... 1-19

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} ... 1-21

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime 1-24

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime 1-26

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks 1-28

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name} 1-30

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/cancel 1-32

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks 1-34

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name} 1-36

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name}/cancel 1-38

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedeinitionRuntime/classRedeinitionTasks/{name}/subTasks/{name}/subTasks 1-40

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRe  
definitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}  
1-42

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRe  
definitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/  
cancel 1-44

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRe  
definitionRuntime/redefineClasses 1-46

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/cohere  
nceClusterRuntime 1-49

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes 1-51

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name} 1-53

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes 1-55

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes/{name} 1-57

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-59

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
1-61

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
1-63

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/compo  
nentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-65

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPers  
istenceUnitRuntime 1-67

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasAp  
plicationCache 1-69

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/library  
Runtimes 1-71

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name} 1-73

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-75

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-77

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes 1-79

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} 1-81

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager 1-83

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-85

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-87

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-89

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-91

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes 1-93

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} 1-95

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-97

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-99

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-101

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/manag

edScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-103

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-105

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes 1-107

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} 1-109

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes 1-111

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-113

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes 1-115

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-117

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes 1-119

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name} 1-121

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes 1-123

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} 1-125

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes 1-127

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} 1-129

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes 1-131

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name} 1-133

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools 1-135

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes 1-137

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name} 1-139

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes 1-141

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} 1-143

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-145

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-147

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-149

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-151

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes 1-153

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} 1-155

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime 1-157

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports 1-159

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} 1-161

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations 1-164

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations 1-166

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} 1-168

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting 1-170

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers 1-172

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} 1-174

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc 1-176

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations 1-178

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} 1-180

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy 1-182

/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm 1-184

/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime..... 1-186

/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime ... 1-188

/management/weblogic/{version}/serverRuntime/bootPartition..... 1-190

/management/weblogic/{version}/serverRuntime/classLoaderRuntime ..... 1-192

/management/weblogic/{version}/serverRuntime/clusterRuntime ..... 1-194

/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration 1-196

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime 1-198

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs 1-200

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} 1-202

/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel 1-204



/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/getJob 1-206

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime 1-208

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData 1-210

/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} 1-212

/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging..... 1-214

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime.. 1-216

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes 1-218

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} 1-220

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager 1-222

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-224

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-226

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-228

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-230

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes 1-232

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} 1-234

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-236

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime  
1-238

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstr  
aintRuntime 1-240

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstra  
intRuntime 1-242

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRunti  
me 1-244

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedThreadFactoryRuntimes 1-246

/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/  
managedThreadFactoryRuntimes/{name} 1-248

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime..... 1-250

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
1-253

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name} 1-255

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools 1-258

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name} 1-260

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/connections 1-263

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/connections/{name} 1-265

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/connections/{name}/delete 1-267

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/connections/{name}/hasError 1-269

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/connections/{name}/testConnection 1-271

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/ensureLogOpened 1-273

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/flushLog 1-275

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/forceLogRotation 1-277

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/forceReset 1-279

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/logRuntime 1-281

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-283

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/logRuntime/flushLog 1-285

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-287

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/reset 1-289

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectionPools/{name}/testPool 1-291

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime 1-293

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/getInboundConnections 1-296

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/getRA 1-298

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs 1-300

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-302

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-305

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-307

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne  
ctions 1-310

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne  
ctions/{name} 1-312

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne  
ctions/{name}/delete 1-314

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne  
ctions/{name}/hasError 1-316

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/conne  
ctions/{name}/testConnection 1-318

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensur  
eLogOpened 1-320

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flush  
Log 1-322

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/force  
LogRotation 1-324

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/force  
Reset 1-326

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu  
ntime 1-328

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu  
ntime/ensureLogOpened 1-330

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu  
ntime/flushLog 1-332

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRu  
ntime/forceLogRotation 1-334

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset  
1-336

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPo  
ol 1-338

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntim  
e 1-340

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-342

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-344

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-346

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-348

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-350

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}  
1-352

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/  
MDBRuntimes 1-354

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/  
MDBRuntimes/{name} 1-356

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/  
MDBRuntimes/{name}/poolRuntime 1-359

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs

`/ {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / poolRuntime / initializePool 1-361`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / resources 1-363`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / resources / {name} 1-365`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / resume 1-367`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / suspend 1-369`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / timerRuntime 1-371`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / timerRuntime / activateDisabledTimers 1-373`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / inboundConnections / {name} / MDBRuntimes / {name} / transactionRuntime 1-375`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / resume 1-377`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / resumeAll 1-379`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / suspend 1-381`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / suspendAll 1-383`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntime 1-385`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntime / capacityRuntime 1-387`

`/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs`

*/ {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntime / maxThreadsConstraintRuntime 1-389*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntime / minThreadsConstraintRuntime 1-391*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntime / requestClassRuntime 1-393*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes 1-395*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes / {name} 1-397*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes / {name} / capacityRuntime 1-399*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes / {name} / maxThreadsConstraintRuntime 1-401*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes / {name} / minThreadsConstraintRuntime 1-403*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / inactiveRAs / {name} / workManagerRuntimes / {name} / requestClassRuntime 1-405*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / RAs 1-407*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / RAs / {name} 1-409*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / RAs / {name} / connectionPools 1-412*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / RAs / {name} / connectionPools / {name} 1-414*

*/ management / weblogic / {version} / serverRuntime / connectorServiceRuntime / activeRAs / {name} / connectorServiceRuntime / RAs / {name} / connectionPools / {name} / connections 1-417*

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{  
name} 1-419

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{  
name}/delete 1-421

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{  
name}/hasError 1-423

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{  
name}/testConnection 1-425

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOp  
ened 1-427

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog  
1-429

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRota  
tion 1-431

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset  
1-433

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime  
1-435

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/  
ensureLogOpened 1-437

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/f  
lushLog 1-439

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/f  
orceLogRotation 1-441

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-443



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool  
1-445

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime  
1-447

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-449

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-451

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-453

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-455

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-457

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-459

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes 1-461

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name} 1-463

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/poolRuntime 1-466

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/poolRuntime/initializePool 1-468

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/resources 1-470

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/resources/{name} 1-472

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/resume 1-474

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/suspend 1-476

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/timerRuntime 1-478

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/timerRuntime/activateDisabledTimers 1-480

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRu  
ntimes/{name}/transactionRuntime 1-482

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/resume 1-484

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-486

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-488

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-490

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-492

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntim  
e 1-494

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsCo  
nstraintRuntime 1-496

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsCo  
nstraintRuntime 1-498

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRu  
ntime 1-500

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-502

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-504

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capaci  
tyRuntime 1-506

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxT  
hreadConstraintRuntime 1-508

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minT  
hreadConstraintRuntime 1-510

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/reque  
stClassRuntime 1-512

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/resume 1-514

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/resumeAll 1-516

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/suspend 1-518

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorServiceRuntime/suspendAll 1-520

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/connectorWorkManagerRuntime 1-522

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/getConfiguration 1-524

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/getConnectionPool 1-526

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/getInboundConnection 1-528

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/getSchema 1-530

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections 1-532

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name} 1-534

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes 1-536

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-538

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-541

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-543

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-545

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-547

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-549

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-551

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-553

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-555

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-557

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/resume 1-559

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/resumeAll 1-561

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/suspend 1-563

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/suspendAll 1-565

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntime 1-567

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntime/capacityRuntime 1-569

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-571

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-573

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntime/requestClassRuntime 1-575

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes 1-577

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes/{name} 1-579

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes/{name}/capacityRuntime 1-581

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-583

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-585

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs  
/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-587

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections 1-589

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRA .....  
1-591

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs  
1-593

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name} 1-595

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools 1-598

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name} 1-600

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections 1-603

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name} 1-605

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/delete 1-607

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/hasError 1-609

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/connections/{name}/testConnection 1-611

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/ensureLogOpened 1-613

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/flushLog 1-615

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/forceLogRotation 1-617

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/forceReset 1-619

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime 1-621

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-623

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime/flushLog 1-625

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-627

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-629

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-631

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime 1-633

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs 1-636

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-638

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-641

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-643

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-646

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-648

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-650

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-652

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-654

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-656

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-658

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-660

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-662

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-664

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-666

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-668

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-670

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-672

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-674

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-676

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-678

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-680

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-682

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-684

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-686



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}  
1-688

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes 1-690

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name} 1-692

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/poolRuntime 1-695

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/poolRuntime/initializePool 1-697

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/resources 1-699

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/resources/{name} 1-701

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/resume 1-703

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/suspend 1-705

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/timerRuntime 1-707

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-709

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/transactionRuntime 1-711

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-713

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-715

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-717

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-719

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-721

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-723

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-725

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-727

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-729

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-731

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-733

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-735

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-737

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-739

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-741

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections 1-743

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA 1-745

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs 1-747

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} 1-749

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-752

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-754

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-757

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-759

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-761

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-763

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-765

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-767

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-769

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-771

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-773

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-775

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-777

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-779

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-781

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-783

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-785

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-787

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-789

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-791

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-793

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-795

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-797

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-799

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRA

s/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-801

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-803

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-806

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-808

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-810

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-812

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-814

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-816

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-818

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-820

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-822

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume 1-824

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-826

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-828

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-830

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-832

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-834

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-836

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-838

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-840

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-842

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-844

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-846

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-848

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-850

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-852

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume 1-854

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll 1-856

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend 1-858

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll 1-860

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-862

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-864

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-866

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-868

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-870

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-872

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-874

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-876

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-878

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-881

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-883

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-885

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-887

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-889

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-891

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-893

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-895

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-897

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/resume 1-899

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/resumeAll 1-901

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/suspend 1-903

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/suspendAll 1-905

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime 1-907

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime/capacityRuntime 1-909

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-911

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-913

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntime/requestClassRuntime 1-915

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntimes 1-917

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAS/{name}/workManagerRuntimes/{name} 1-919



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-921

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-923

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-925

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-927

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs.....  
1-929

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} 1-931

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools 1-934

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-936

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-939

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-941

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-943

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-945

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-947

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-949

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-951

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-953

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-955

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-957

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-959

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-961

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-963

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-965

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-967

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime 1-969

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs 1-972

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-974

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-977

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-979

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-982

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-984

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-986

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}

e)/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-988

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-990

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-992

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-994

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-996

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-998

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-1000

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-1002

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-1004

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-1006

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-1008

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-1010

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-1012

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration 1-1014

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-1016

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-1018

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-1020

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-1022

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-1024

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times 1-1026

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name} 1-1028

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/poolRuntime 1-1031

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/poolRuntime/initializePool 1-1033

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resources 1-1035

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resources/{name} 1-1037

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/resume 1-1039

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRun times/{name}/suspend 1-1041

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1043

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1045

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1047

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-1049

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-1051

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-1053

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-1055

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-1057

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-1059

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1061

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1063

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-1065

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-1067

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-1069

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1071

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1073

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1075

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1077

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections 1-1079

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA 1-1081

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs 1-1083

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-1085

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools 1-1088

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-1090

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-1093

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-1095

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-1097

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-1099

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-1101

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-1103

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-1105

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-1107

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-1109

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-1111

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-1113

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-1115

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-1117

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-1119

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-1121

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-1123

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-1125

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-1127

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-1129

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-1131

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-1133

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-1135

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1137

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1139

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1142

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1144

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1146

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1148

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1150

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1152

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1154



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1156

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1158

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-1160

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-1162

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-1164

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-1166

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-1168

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-1170

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1172

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1174

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-1176

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-1178

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-1180

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1182

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1184

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1186

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1188

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume 1-1190

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll 1-1192

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend 1-1194

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll 1-1196

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-1198

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration 1-1200

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-1202

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-1204

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema 1-1206

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections 1-1208

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-1210

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-1212

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-1214

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-1216

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-1218

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-1220

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-1222

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-1224

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-1226

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-1228

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-1230

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-1232

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume 1-1234

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll 1-1236

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend 1-1238

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll 1-1240

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-1242

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-1244

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-1246

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-1248

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-1250

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-1252

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-1254

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1256

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1258

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1260

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1262

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume ..... 1-1264

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll 1-1266

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend ... 1-1268

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll 1-1270

/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime..... 1-1272

/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime..... 1-1274

/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime ..... 1-1276

/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime ..... 1-1278

/management/weblogic/{version}/serverRuntime/executeQueueRuntimes ..... 1-1280

/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name} ..... 1-1282

/management/weblogic/{version}/serverRuntime/forceRestartPartition..... 1-1284

/management/weblogic/{version}/serverRuntime/forceShutdown ..... 1-1286

/management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup .....  
 1-1288

/management/weblogic/{version}/serverRuntime/forceSuspend ..... 1-1290

/management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup 1-1292

/management/weblogic/{version}/serverRuntime/getIPv4URL..... 1-1294

/management/weblogic/{version}/serverRuntime/getIPv6URL..... 1-1296

/management/weblogic/{version}/serverRuntime/getRgState ..... 1-1298

/management/weblogic/{version}/serverRuntime/getURL..... 1-1300

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime ..... 1-1302

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans 1-1304

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-1306

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown 1-1310

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend 1-1312

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache 1-1314

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool 1-1316

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile 1-1318

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown 1-1320

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend 1-1322

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime 1-1324

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean 1-1326

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics 1-1328

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSource

ceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics  
1-1330

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
1-1332

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
/{name} 1-1334

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
/{name}/capacityRuntime 1-1336

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
/{name}/maxThreadsConstraintRuntime 1-1338

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
/{name}/minThreadsConstraintRuntime 1-1340

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes  
/{name}/requestClassRuntime 1-1342

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists 1-1344

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset 1-1346

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume 1-1348

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink 1-1350

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown 1-1352

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start 1-1354

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend 1-1356

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks 1-1358

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} 1-1360

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel 1-1362

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks 1-1364

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} 1-1366

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel 1-1368

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks 1-1370

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} 1-1372

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-1374

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool 1-1376

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1378

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1380

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1382

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1384

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1386

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1388

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans 1-1390

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-1392

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans 1-1394

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-1396

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-1398

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} 1-1400

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1402

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1404

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1406

/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1408

/management/weblogic/{version}/serverRuntime/JMSRuntime..... 1-1410  
/management/weblogic/{version}/serverRuntime/JMSRuntime/connections ..... 1-1412  
/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} ..... 1-1414

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy 1-1416

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions 1-1418

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name} 1-1420

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers 1-1422



/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} 1-1424

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers 1-1426

/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} 1-1428

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers..... 1-1430

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} ..... 1-1432

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor 1-1435

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations 1-1437

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} 1-1439

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor 1-1442

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber 1-1444

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages 1-1446

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers 1-1448

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} 1-1450

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1453

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1455

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1457

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1460

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1462

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-1464

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1466

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-1468

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-1470

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-1472

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-1475

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-1477

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-1479

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-1481

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-1483

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-1485

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1487

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-1489

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1491

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-1493

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages 1-1495

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort 1-1498

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition 1-1500

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize 1-1502

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition 1-1504

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages 1-1506

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption 1-1509

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion 1-1511

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction 1-1513

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption 1-1515

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion 1-1517

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction 1-1519

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort 1-1521

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit 1-1523

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceRollback 1-1525

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorEndPosition 1-1527

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorSize 1-1529

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorStartPosition 1-1531

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getMessages 1-1533

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getTransactionStatus 1-1535

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime 1-1537

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened 1-1539

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/flushLog 1-1541

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation 1-1543

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseConsumption 1-1545

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseInsertion 1-1547

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseProduction 1-1550

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeConsumption 1-1552

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeInsertion 1-1554

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeProduction 1-1556

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes 1-1558

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} 1-1560

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers 1-1562

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} 1-1564

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer 1-1566

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor 1-1570

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations 1-1572

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} 1-1574

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor 1-1577

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber 1-1579

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages 1-1581

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers 1-1583

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} 1-1585

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor 1-1588

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/se

sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-1590

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-1592

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-1596

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-1598

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-1600

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-1602

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-1604

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-1606

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-1608

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-1611

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-1613

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-1615

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-1617

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-1619

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-1621

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-1623

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-1625

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-1627

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-1629

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages 1-1631

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort 1-1634

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition 1-1636

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize 1-1638

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition 1-1640

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages 1-1642

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption 1-1645

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion 1-1647

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction 1-1649

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption  
1-1651

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion 1-1653

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction 1-1655

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort 1-1657

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit 1-1659

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback 1-1661

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition 1-1663

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize 1-1665

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition 1-1667

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages 1-1669

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus 1-1671

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime 1-1673

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened 1-1675

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog 1-1677



/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation 1-1679

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption 1-1681

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion 1-1683

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction 1-1686

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption 1-1688

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion 1-1690

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction 1-1692

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort 1-1694

/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort 1-1696

/management/weblogic/{version}/serverRuntime/joltRuntime ..... 1-1698

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools ..... 1-1700

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name} 1-1702

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections 1-1704

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name} 1-1706

/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool 1-1708

/management/weblogic/{version}/serverRuntime/JTARuntime ..... 1-1710

/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean 1-1712

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans 1-1714

/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name} 1-1716

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans 1-1718

/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name} 1-1720

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean 1-1722

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections 1-1724

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name} 1-1726

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans 1-1728

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name} 1-1730

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans 1-1732

/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} 1-1734

/management/weblogic/{version}/serverRuntime/JVMRuntime..... 1-1736

/management/weblogic/{version}/serverRuntime/libraryRuntimes ..... 1-1738

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name} ..... 1-1740

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes 1-1742

/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name} 1-1744

/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime ..... 1-1746

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes ..... 1-1748

/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name} ..... 1-1750

/management/weblogic/{version}/serverRuntime/MANASyncReplicationRuntime ..... 1-1752

/management/weblogic/{version}/serverRuntime/MANReplicationRuntime..... 1-1754

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes ..... 1-1756

/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name} 1-1758  
 /management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes.... 1-1760  
 /management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}.... 1-1762  
 /management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes ..... 1-1764  
  
 /management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name} 1-1766  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes..... 1-1768  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}.... 1-1770  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes 1-1775  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} 1-1777  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime 1-1781  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime 1-1783  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks 1-1785  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} 1-1787  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel 1-1789  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks 1-1791  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} 1-1793  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel 1-1795  
  
 /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/application

nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks  
/{name}/subTasks 1-1797

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks  
/{name}/subTasks/{name} 1-1799

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks  
/{name}/subTasks/{name}/cancel 1-1801

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/classRedefinitionRuntime/redefineClasses 1-1803

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/coherenceClusterRuntime 1-1806

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes 1-1808

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name} 1-1810

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes 1-1812

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}  
1-1814

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capac  
ityRuntime 1-1816

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxT  
hreadsConstraintRuntime 1-1818

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minT  
hreadsConstraintRuntime 1-1820

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/reque  
stClassRuntime 1-1822

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/getPersistenceUnitRuntime 1-1824

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicatio  
nRuntimes/{name}/hasApplicationCache 1-1826

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes 1-1828

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} 1-1830

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-1832

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-1834

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes 1-1836

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} 1-1838

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager 1-1840

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1842

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/threadsConstraintRuntime 1-1844

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1846

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1848

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes 1-1850

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} 1-1852

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-1854

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/application

nRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1856

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1858

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1860

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1862

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes 1-1864

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} 1-1866

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes 1-1868

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-1870

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes 1-1872

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-1874

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes 1-1876

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} 1-1878

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes 1-1880

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} 1-1882

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes 1-1884

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} 1-1886

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes 1-1888

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name} 1-1890

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools 1-1892

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes 1-1894

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name} 1-1896

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes 1-1898

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} 1-1900

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-1902

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-1904

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-1906

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-1908

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes 1-1910

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} 1-1912

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime 1-1914

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports 1-1916

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} 1-1918

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations 1-1921

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations 1-1923

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} 1-1925

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting 1-1927

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers 1-1929

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} 1-1931

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc 1-1933

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations 1-1935

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} 1-1937

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy 1-1939

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm 1-1941

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime 1-1943

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime 1-1945

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes 1-1947

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} 1-1949



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager  
1-1951

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1953

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1955

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1957

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1959

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes 1-1961

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name} 1-1963

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager 1-1965

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime 1-1967

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime 1-1969

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime 1-1971

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime 1-1973

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes 1-1975

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name} 1-1977

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime 1-1979

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs 1-1982

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} 1-1984

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-1987

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-1989

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-1992

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-1994

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-1996

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-1998

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2000

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2002

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-2004

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-2006

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-2008

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-2010

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOp  
ened 1-2012

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog  
1-2014

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotat  
ion 1-2016

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-2018

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-2020

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime 1-2022

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections  
1-2025

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA 1-2027

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs 1-2029

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}  
1-2031

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn  
ectionPools 1-2034

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn  
ectionPools/{name} 1-2036

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/conn  
ectionPools/{name}/connections 1-2039

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} 1-2041

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2043

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2045

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2047

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2049

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-2051

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-2053

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-2055

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-2057

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2059

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2061

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2063

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-2065

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-2067

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-2069

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfig 1-2071

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-2073

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-2075

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-2077

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-2079

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-2081

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2083

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2085

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2088

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2090

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2092

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2094

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2096

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2098

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2100

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2102

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2104

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-2106

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-2108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-2110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-2112

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2114

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2116

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2118

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2120

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-2122

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2124

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2126

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2128

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2130

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2132

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2134

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs 1-2136

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} 1-2138

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools 1-2141

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} 1-2143

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-2146

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-2148

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2150

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2152

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2154

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-2156

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-2158

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-2160

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-2162

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-2164

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2166

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2168



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2170

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2172

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2174

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2176

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2178

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-2180

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-2182

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-2184

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-2186

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2188

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2190

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2192

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2195

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2197

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2199

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2201

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2203

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2205

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2207

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2209

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2211

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume 1-2213

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-2215

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-2217

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-2219

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-2221

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-2223

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2225

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2227

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-2229

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-2231

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-2233

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2235

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2237

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2239

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2241

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume 1-2243

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll 1-2245

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend 1-2247

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll 1-2249

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2251

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/getConfiguration 1-2253

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/getConnectionPool 1-2255

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/getInboundConnection 1-2257

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/getSchema 1-2259

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections 1-2261

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-2263

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes  
1-2265

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
} 1-2267

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/poolRuntime 1-2270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/poolRuntime/initializePool 1-2272

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/resources 1-2274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/resources/{name} 1-2276

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/resume 1-2278

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/suspend 1-2280

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/timerRuntime 1-2282

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/timerRuntime/activateDisabledTimers 1-2284

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name  
}/transactionRuntime 1-2286

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/resume 1-2288

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/resumeAll 1-2290

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/suspend 1-2292

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/suspendAll 1-2294

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntime 1-2296

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-2298

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRunti  
me 1-2300

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRunti  
me 1-2302

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime  
1-2304

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-2306

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-2308

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime  
1-2310

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstr  
aintRuntime 1-2312

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstra  
intRuntime 1-2314

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRunTi  
me 1-2316

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/getInboundConnections 1-2318

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/getRA 1-2320

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs 1-2322

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name} 1-2324

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools 1-2327

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name} 1-2329

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections 1-2332

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}  
1-2334

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/del  
ete 1-2336

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/has  
Error 1-2338

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/test  
Connection 1-2340

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened  
1-2342

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-2344

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation  
1-2346

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-2348

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-2350

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogO  
pened 1-2352

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog  
1-2354

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRot  
ation 1-2356

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-2358

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-2360

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime 1-2362

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs 1-2365

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-2367

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools 1-2370

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} 1-2372

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections 1-2375

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} 1-2377

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete 1-2379

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2381

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2383

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2385

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-2387

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-2389

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-2391

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector



ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-2393

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2395

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2397

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2399

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-2401

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-2403

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2405

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionConfiguration 1-2407

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-2409

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-2411

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-2413

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnections 1-2415

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnections/{name} 1-2417

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2419

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2421

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2424

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2426

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2428

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2430

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2432

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2434

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2436

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2438

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2440

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-2442

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resu  
meAll 1-2444

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/susp  
end 1-2446

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/susp  
endAll 1-2448

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntime 1-2450

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntime/capacityRuntime 1-2452

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntime/maxThreadsConstraintRuntime 1-2454

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntime/minThreadsConstraintRuntime 1-2456

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntime/requestClassRuntime 1-2458

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntimes 1-2460

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntimes/{name} 1-2462

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntimes/{name}/capacityRuntime 1-2464

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2466

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/wor  
kManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2468

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2470

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections 1-2472

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA 1-2474

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs 1-2476

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} 1-2478

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools 1-2481

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name} 1-2483

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections 1-2486

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name} 1-2488

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/delete 1-2490

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/hasError 1-2492

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/connections/{name}/testConnection 1-2494

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionsPools/{name}/ensureLogOpened 1-2496

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-2498

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-2500

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-2502

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-2504

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2506

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2508

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2510

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2512

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2514

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2516

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2518

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-2520

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection 1-2522

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema 1-2524

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections 1-2526

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2528

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2530

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2532

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2535

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2537

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2539

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2541

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2543

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2545

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2547

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundC

onnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers  
1-2549

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2551

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume  
1-2553

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll  
1-2555

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend  
1-2557

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendA  
ll 1-2559

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntime 1-2561

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntime/capacityRuntime 1-2563

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntime/maxThreadsConstraintRuntime 1-2565

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntime/minThreadsConstraintRuntime 1-2567

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntime/requestClassRuntime 1-2569

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntimes 1-2571

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workMan  
agerRuntimes/{name} 1-2573

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2575

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2577

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2579

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2581

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume 1-2583

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll 1-2585

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend 1-2587

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll 1-2589

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime 1-2591

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration 1-2593

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool 1-2595

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection 1-2597

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema 1-2599

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections 1-2601

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} 1-2603



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes  
1-2605

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me} 1-2607

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/poolRuntime 1-2610

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/poolRuntime/initializePool 1-2612

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/resources 1-2614

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/resources/{name} 1-2616

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/resume 1-2618

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/suspend 1-2620

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/timerRuntime 1-2622

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/timerRuntime/activateDisabledTimers 1-2624

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{na  
me}/transactionRuntime 1-2626

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/resume 1-2628

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/resumeAll 1-2630

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/suspend 1-2632

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/suspendAll 1-2634

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2636

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2638

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRun  
time 1-2640

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRun  
time 1-2642

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime  
1-2644

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2646

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2648

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime  
1-2650

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsCons  
traintRuntime 1-2652

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConst  
raintRuntime 1-2654

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRunt  
ime 1-2656

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs 1-2658

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name} 1-2660

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools 1-2663

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name} 1-2665

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections 1-2668

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} 1-2670

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete  
1-2672

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError  
1-2674

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnect  
ion 1-2676

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened 1-2678

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog 1-2680

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation 1-2682

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset 1-2684

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime 1-2686

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened  
1-2688

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2690

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation  
1-2692

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/reset 1-2694

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectionPools/{name}/testPool 1-2696

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime 1-2698

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs 1-2701

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} 1-2703

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools 1-2706

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name} 1-2708

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/connections 1-2711

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/connections/{name} 1-2713

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/connections/{name}/delete 1-2715

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/connections/{name}/hasError 1-2717

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/connections/{name}/testConnection 1-2719

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionP  
ools/{name}/ensureLogOpened 1-2721

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog 1-2723

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation 1-2725

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset 1-2727

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime 1-2729

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2731

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2733

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2735

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset 1-2737

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool 1-2739

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime 1-2741

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnection 1-2743

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool 1-2745

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection 1-2747

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema 1-2749

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections 1-2751

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} 1-2753

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2755

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} 1-2757

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2760

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2762

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources 1-2764

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2766

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2768

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2770

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2772

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2774

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2776

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume 1-2778

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll 1-2780

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend 1-2782

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll 1-2784

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime 1-2786

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime 1-2788

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2790

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2792

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime 1-2794

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes 1-2796

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} 1-2798

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2800

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2802

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2804

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2806

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections 1-2808

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA 1-2810

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs 1-2812

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} 1-2814

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionsPools 1-2817

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionsPools/{name} 1-2819

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionsPools/{name}/connections 1-2822

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionsPools/{name}/connections/{name} 1-2824

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionsPools/{name}/connections/{name}/delete 1-2826



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError 1-2828

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection 1-2830

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened 1-2832

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog 1-2834

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation 1-2836

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset 1-2838

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime 1-2840

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened 1-2842

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog 1-2844

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation 1-2846

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset 1-2848

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool 1-2850

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connector  
WorkManagerRuntime 1-2852

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfig  
uration 1-2854

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnec  
tionPool 1-2856

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboun  
dConnection 1-2858

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema  
1-2860

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections 1-2862

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name} 1-2864

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes 1-2866

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name} 1-2868

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name}/poolRuntime 1-2871

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool 1-2873

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name}/resources 1-2875

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundC  
onnections/{name}/MDBRuntimes/{name}/resources/{name} 1-2877

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume 1-2879

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend 1-2881

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime 1-2883

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2885

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2887

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume 1-2889

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll 1-2891

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend 1-2893

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll 1-2895

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime 1-2897

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime 1-2899

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2901

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2903

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime 1-2905

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes 1-2907

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} 1-2909

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2911

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2913

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2915

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2917

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume 1-2919

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll 1-2921

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend 1-2923

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll 1-2925

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime 1-2927

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration 1-2929

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool 1-2931

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/getInboundConnection 1-2933

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/getSchema 1-2935

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections 1-2937

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name} 1-2939

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes 1-2941

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}  
1-2943

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/pool  
IRuntime 1-2946

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/pool  
IRuntime/initializePool 1-2948

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
1-2950

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
{name} 1-2952

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume  
1-2954

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend  
1-2956

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector  
ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timer  
Runtime 1-2958

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers 1-2960

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime 1-2962

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume 1-2964

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll 1-2966

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend 1-2968

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll 1-2970

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime 1-2972

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime 1-2974

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime 1-2976

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime 1-2978

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime 1-2980

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes 1-2982

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} 1-2984

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime 1-2986

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-2988

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connector

ServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-2990

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-2992

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume 1-2994

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll 1-2996

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend 1-2998

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll 1-3000

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown 1-3002

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup 1-3004

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend 1-3006

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup 1-3008

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState 1-3010

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt..... 1-3012

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime 1-3014

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans 1-3016

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} 1-3018

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown 1-3022

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend 1-3024

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache 1-3026

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool 1-3028

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile 1-3030

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown 1-3032

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend 1-3034

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime 1-3036

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean 1-3038

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics 1-3040

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics 1-3042

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes 1-3044

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} 1-3046

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime 1-3048

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3050

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart



itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3052

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime 1-3054

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists 1-3056

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset 1-3058

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume 1-3060

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink 1-3062

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown 1-3064

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start 1-3066

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend 1-3068

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks 1-3070

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} 1-3072

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel 1-3074

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks 1-3076

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} 1-3078

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel 1-3080

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart

itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}  
/subTasks 1-3082

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}  
/subTasks/{name} 1-3084

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}  
/subTasks/{name}/cancel 1-3086

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool 1-3088

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes 1-3090

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
1-3092

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
/capacityRuntime 1-3094

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
/maxThreadsConstraintRuntime 1-3096

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
/minThreadsConstraintRuntime 1-3098

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
/requestClassRuntime 1-3100

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCMultiDataSourceRuntimeMBeans 1-3102

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} 1-3104

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes  
1-3106

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPart  
itionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{n  
ame} 1-3108

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime 1-3110

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3112

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3114

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-3116

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime 1-3118

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections 1-3120

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} 1-3122

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy 1-3124

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions 1-3126

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} 1-3128

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers 1-3130

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} 1-3132

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers 1-3134

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} 1-3136

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers 1-3138

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} 1-3140

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/closeCursor 1-3143

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations 1-3145

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} 1-3147

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor 1-3150

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber 1-3152

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages 1-3154

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers 1-3156

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} 1-3158

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor 1-3161

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-3163

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-3165

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-3168

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-3170

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-3172

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-3174

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-3176

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-3178

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-3180

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-3183

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-3185

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-3187

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-3189

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-3191

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-3193

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-3195

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-3197

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime

me/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize  
1-3199

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-3201

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages  
1-3203

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort 1-3206

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition 1-3208

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize 1-3210

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition 1-3212

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages 1-3214

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption 1-3217

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion 1-3219

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction 1-3221

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption 1-3223

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion 1-3225

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction 1-3227

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort 1-3229

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/forceCommit 1-3231

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/forceRollback 1-3233

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorEndPosition 1-3235

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorSize 1-3237

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorStartPosition 1-3239

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getMessages 1-3241

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getTransactionStatus 1-3243

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime 1-3245

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened 1-3247

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/flushLog 1-3249

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/forceLogRotation 1-3251

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseConsumption 1-3253

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseInsertion 1-3255

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseProduction 1-3258

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeConsumption 1-3260

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeInsertion 1-3262

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeProduction 1-3264

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes 1-3266

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} 1-3268

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers 1-3270

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} 1-3272

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer 1-3274

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor 1-3278

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations 1-3280

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} 1-3282

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor 1-3285

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber 1-3287

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages 1-3289

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers 1-3291

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} 1-3293

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor 1-3296



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages 1-3298

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime 1-3300

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor 1-3304

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber 1-3306

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages 1-3308

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition 1-3310

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize 1-3312

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition 1-3314

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages 1-3316

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption 1-3319

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion 1-3321

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction 1-3323

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime

me/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption 1-3325

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion 1-3327

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction 1-3329

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort 1-3331

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition 1-3333

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize 1-3335

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition 1-3337

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages 1-3339

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort 1-3342

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition 1-3344

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize 1-3346

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition 1-3348

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages 1-3350

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption 1-3353

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion 1-3355

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction 1-3357

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption 1-3359

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion 1-3361

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction 1-3363

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort 1-3365

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit 1-3367

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback 1-3369

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition 1-3371

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize 1-3373

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition 1-3375

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages 1-3377

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus 1-3379

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime 1-3381

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened 1-3383

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog 1-3385

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation 1-3387

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption 1-3389

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion 1-3391

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction 1-3394

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption 1-3396

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion 1-3398

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction 1-3400

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort 1-3402

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sort 1-3404

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime 1-3406

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans 1-3408

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} 1-3410

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans 1-3412

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name} 1-3414

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans 1-3416

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} 1-3418

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes 1-3420

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name} 1-3422

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes 1-3424

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} 1-3426

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes 1-3428

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name} 1-3430

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes 1-3432

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name} 1-3434

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes 1-3436

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name} 1-3438

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes 1-3440

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name} 1-3442

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime 1-3444

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime 1-3446

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime 1-3448

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime 1-3450

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime 1-3452

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes 1-3454

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} 1-3456

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies 1-3458

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} 1-3460

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor 1-3462

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition 1-3464

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize 1-3466

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition 1-3468

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries 1-3470

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove 1-3472

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes 1-3474

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name} 1-3476

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections 1-3478

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name} 1-3480

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes 1-3482

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name} 1-3484

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime 1-3486

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes 1-3488

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} 1-3490

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime 1-3492

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes 1-3494

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name} 1-3496

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume ... 1-3498

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup 1-3500

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime 1-3502

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents 1-3504

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} 1-3506

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations 1-3509

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name} 1-3511

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy 1-3513

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime 1-3515

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened 1-3517

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog 1-3519

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation 1-3521

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding 1-3523

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming 1-3525

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving 1-3527

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints 1-3529

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} 1-3531

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor 1-3534



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll 1-3536

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition 1-3538

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize 1-3540

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition 1-3542

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages 1-3544

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding 1-3546

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming 1-3548

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge 1-3550

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding 1-3552

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming 1-3554

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort 1-3556

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding 1-3558

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming 1-3560

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving 1-3562

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown 1-3564

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup 1-3567

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup 1-3570

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin 1-3572

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend.. 1-3574

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup 1-3576

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime 1-3579

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime 1-3581

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes 1-3583

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name} 1-3585

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor 1-3587

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords 1-3589

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount 1-3591

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData 1-3594

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor 1-3596

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime 1-3601

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes 1-3603

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}  
1-3605

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/close  
Archive 1-3607

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime 1-3609

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime 1-3611

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage 1-3613

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks  
1-3615

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks 1-3617

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name} 1-3619

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel  
1-3621

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks  
1-3623

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name} 1-3625

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel 1-3627

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks 1-3629

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}

titionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} 1-3631

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-3633

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages 1-3635

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout 1-3637

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime 1-3639

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm 1-3641

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource 1-3643

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes 1-3645

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name} 1-3647

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime 1-3649

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3651

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3653

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime 1-3655

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime 1-3657

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting 1-3659

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes ..... 1-3661

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}..... 1-3663

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies 1-3665

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} 1-3667

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor 1-3669

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition 1-3671

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize 1-3673

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition 1-3675

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries 1-3677

/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove 1-3679

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes..... 1-3681

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}..... 1-3683

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections 1-3685

/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name} 1-3687

/management/weblogic/{version}/serverRuntime/requestClassRuntimes..... 1-3689

/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}..... 1-3691

/management/weblogic/{version}/serverRuntime/restartSSLChannels..... 1-3693

/management/weblogic/{version}/serverRuntime/resume ..... 1-3695

/management/weblogic/{version}/serverRuntime/resumeResourceGroup ..... 1-3697

/management/weblogic/{version}/serverRuntime/SAFRuntime ..... 1-3699

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents..... 1-3701

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} 1-3703

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations 1-3706

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name} 1-3708

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy 1-3710

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime 1-3712

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened 1-3714

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog 1-3716

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation 1-3718

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseForwarding 1-3720

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseIncoming 1-3722

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseReceiving 1-3724

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints 1-3726

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name} 1-3728

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor 1-3731

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll 1-3733

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition 1-3735

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize 1-3737

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition 1-3739

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages 1-3741

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/pauseForwarding 1-3743

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/pauseIncoming 1-3745

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/purge 1-3747

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/resumeForwarding 1-3749

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/resumeIncoming 1-3751

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remote  
Endpoints/{name}/sort 1-3753

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume  
Forwarding 1-3755

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume  
Incoming 1-3757

/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resume  
Receiving 1-3759

/management/weblogic/{version}/serverRuntime/search..... 1-3761

/management/weblogic/{version}/serverRuntime/serverChannelRuntimes ..... 1-3763

/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name} .....  
1-3765

/management/weblogic/{version}/serverRuntime/serverLogRuntime ..... 1-3767

/management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpene  
d 1-3769

/management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog 1-3771

/management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation  
1-3773

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime ..... 1-3775

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole .....  
1-3777

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm  
Runtime 1-3779

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealm  
Runtime/authenticatorRuntimes 1-3781

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name} 1-3783

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime 1-3785

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/clearLockout 1-3787

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLastLoginFailure 1-3789

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLoginFailureCount 1-3791

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/isLockedOut 1-3793

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes 1-3795

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name} 1-3797

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes 1-3799

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/authenticatorRuntimes/{name} 1-3801

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime 1-3803

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/clearLockout 1-3805

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure 1-3807

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount 1-3809

/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut 1-3811

/management/weblogic/{version}/serverRuntime/shutdown ..... 1-3813

/management/weblogic/{version}/serverRuntime/shutdownResourceGroup ..... 1-3816

/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime..... 1-3819



/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish	1-3821
/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime .....	1-3823
/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache	1-3825
/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule	1-3827
/management/weblogic/{version}/serverRuntime/startPartition .....	1-3829
/management/weblogic/{version}/serverRuntime/startPartitionInAdmin .....	1-3831
/management/weblogic/{version}/serverRuntime/startResourceGroup .....	1-3833
/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin	1-3835
/management/weblogic/{version}/serverRuntime/suspend .....	1-3837
/management/weblogic/{version}/serverRuntime/suspendResourceGroup .....	1-3839
/management/weblogic/{version}/serverRuntime/threadPoolRuntime .....	1-3842
/management/weblogic/{version}/serverRuntime/timerRuntime .....	1-3844
/management/weblogic/{version}/serverRuntime/WANReplicationRuntime .....	1-3846
/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase	1-3848
/management/weblogic/{version}/serverRuntime/webServerRuntimes .....	1-3850
/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}.	1-3852
/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime	1-3854
/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened	1-3856
/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog	1-3858
/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation	1-3860
/management/weblogic/{version}/serverRuntime/WLDFRuntime .....	1-3862
/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime	1-3864
/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes	1-3866
/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}	1-3868

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor 1-3870

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords 1-3872

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount 1-3874

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData 1-3877

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor 1-3879

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime 1-3884

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes 1-3886

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name} 1-3888

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive 1-3890

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes 1-3892

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name} 1-3894

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime 1-3896

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls 1-3898

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} 1-3900

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime 1-3902

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime 1-3904

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm 1-3906

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime 1-3908

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch 1-3910

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks 1-3912

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches 1-3914

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches 1-3916

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks 1-3918

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name} 1-3920

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel 1-3922

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks 1-3924

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name} 1-3926

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/cancel 1-3928

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks 1-3930

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} 1-3932

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-3934

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/showDebugPatchInfo 1-3936

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime 1-3938

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime 1-3940

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/captureImage 1-3942

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/clearCompletedImageCaptureTasks 1-3946

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks 1-3948

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name} 1-3950

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/cancel 1-3952

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks 1-3954

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name} 1-3956

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel 1-3958

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks 1-3960

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} 1-3962

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel 1-3964

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/purgeCapturedImages 1-3966

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/resetImageLockout 1-3968

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes 1-3970

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name} 1-3972

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodInvocationStatisticsData 1-3974

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodMemoryAllocationStatisticsData 1-3976

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime 1-3978

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm 1-3980

/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource 1-3982

/management/weblogic/{version}/serverRuntime/workManagerRuntimes ..... 1-3984

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name} ..... 1-3986

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime 1-3988

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime 1-3990

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime 1-3992

/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime 1-3994

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime ..... 1-3996

/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting 1-3998

/management/weblogic/{version}/serverRuntime/wseeWsrnRuntime ..... 1-4000

/management/weblogic/{version}/serverRuntime/WTCRuntime ..... 1-4002

/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus ..... 1-4004

/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService ..... 1-4008

/management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection ..... 1-4012

/management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection ..... 1-4014

/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService ..... 1-4016

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean 1-4020

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInboundFailReqTotalCount 1-4023

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInboundMessageTotalCount 1-4025

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInboundNWMessageTotalSize 1-4028

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInboundSuccessReqTotalCount 1-4031

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInTransactionCommittedTotalCount 1-4033

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getInTransactionRolledBackTotalCount 1-4035

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutboundFailReqTotalCount 1-4037

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutboundMessageTotalCount 1-4039

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutboundNWMessageTotalSize 1-4042

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutboundSuccessReqTotalCount 1-4045

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutstandingNWReqCount 1-4047

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutTransactionCommittedTotalCount 1-4050

/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntime  
MBean/getOutTransactionRolledBackTotalCount 1-4052

## 2 Entities

[3]	com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean .....	2-1
[3]	com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean .....	2-2
[3]	java.lang.Throwable .....	2-3
[3]	java.util.Date .....	2-4
[3]	java.util.Properties .....	2-4

[3]	weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean .....	2-4
[3]	weblogic.health.HealthState .....	2-5
n	weblogic.health.Symptom .....	2-5
n	weblogic.management.rest.bean.model.CurrentUser .....	2-6
n	weblogic.management.rest.bean.model.Version .....	2-6
n	weblogic.management.runtime.ApplicationRuntimeMBean .....	2-7
n	weblogic.management.runtime.AsyncReplicationRuntimeMBean .....	2-8
n	weblogic.management.runtime.AuthenticatorRuntimeMBean .....	2-9
n	weblogic.management.runtime.BatchJobRepositoryRuntimeMBean .....	2-10
n	weblogic.management.runtime.CapacityRuntimeMBean .....	2-10
n	weblogic.management.runtime.ClassLoaderRuntimeMBean .....	2-11
n	weblogic.management.runtime.ClusterRuntimeMBean .....	2-13
n	weblogic.management.runtime.CoherenceClusterRuntimeMBean .....	2-16
n	weblogic.management.runtime.ComponentRuntimeMBean .....	2-16
n	weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean .....	2-17
n	weblogic.management.runtime.ConnectorComponentRuntimeMBean .....	2-18
n	weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean .....	2-22
n	weblogic.management.runtime.ConnectorConnectionRuntimeMBean .....	2-27
n	weblogic.management.runtime.ConnectorInboundRuntimeMBean .....	2-30
n	weblogic.management.runtime.ConnectorServiceRuntimeMBean .....	2-30
n	weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean .....	2-31
n	weblogic.management.runtime.EJBPoolRuntimeMBean .....	2-32
n	weblogic.management.runtime.EJBTimerRuntimeMBean .....	2-33
n	weblogic.management.runtime.EJBTransactionRuntimeMBean .....	2-34
n	weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean .....	2-34
n	weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean .....	2-38
n	weblogic.management.runtime.ExecuteQueueRuntimeMBean .....	2-41
n	weblogic.management.runtime.FairShareConstraintRuntimeMBean .....	2-42
n	weblogic.management.runtime.JDBCDataSourceRuntimeMBean .....	2-42
n	weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean .....	2-48
n	weblogic.management.runtime.JDBCDriverRuntimeMBean .....	2-50
n	weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean .....	2-50
n	weblogic.management.runtime.JDBCPartitionRuntimeMBean .....	2-51
n	weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean .....	2-52
n	weblogic.management.runtime.JDBCServiceRuntimeMBean .....	2-54
n	weblogic.management.runtime.JMSCConnectionRuntimeMBean .....	2-54
n	weblogic.management.runtime.JMSCConsumerRuntimeMBean .....	2-55
n	weblogic.management.runtime.JMSDestinationRuntimeMBean .....	2-57
n	weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean .....	2-60
n	weblogic.management.runtime.JMSProducerRuntimeMBean .....	2-63
n	weblogic.management.runtime.JMSRuntimeMBean .....	2-64
n	weblogic.management.runtime.JMSServerRuntimeMBean .....	2-65
n	weblogic.management.runtime.JMSSessionPoolRuntimeMBean .....	2-69
n	weblogic.management.runtime.JMSSessionRuntimeMBean .....	2-70
n	weblogic.management.runtime.JTAPartitionRuntimeMBean .....	2-72
n	weblogic.management.runtime.JTARecoveryRuntimeMBean .....	2-75
n	weblogic.management.runtime.JTARuntimeMBean .....	2-76

n	weblogic.management.runtime.JVMRuntimeMBean .....	2-78
n	weblogic.management.runtime.JobRuntimeMBean.....	2-80
n	weblogic.management.runtime.JobSchedulerRuntimeMBean .....	2-81
n	weblogic.management.runtime.JoltConnectionPoolRuntimeMBean .....	2-82
n	weblogic.management.runtime.JoltConnectionRuntimeMBean .....	2-82
n	weblogic.management.runtime.JoltConnectionServiceRuntimeMBean .....	2-84
n	weblogic.management.runtime.LibraryRuntimeMBean .....	2-84
n	weblogic.management.runtime.LogBroadcasterRuntimeMBean.....	2-85
n	weblogic.management.runtime.LogRuntimeMBean.....	2-86
n	weblogic.management.runtime.MANAsyncReplicationRuntimeMBean .....	2-86
n	weblogic.management.runtime.MANReplicationRuntimeMBean .....	2-87
n	weblogic.management.runtime.MailSessionRuntimeMBean .....	2-89
n	weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean .....	2-89
n	weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean .....	2-90
n	weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean.....	2-92
n	weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean .....	2-93
n	weblogic.management.runtime.MessageDrivenEJBRuntimeMBean.....	2-94
n	weblogic.management.runtime.MessagingBridgeRuntimeMBean.....	2-96
n	weblogic.management.runtime.MigrationDataRuntimeMBean .....	2-96
n	weblogic.management.runtime.MinThreadsConstraintRuntimeMBean .....	2-98
n	weblogic.management.runtime.NonXAResourceRuntimeMBean.....	2-99
n	weblogic.management.runtime.PSAssemblyRuntimeMBean .....	2-100
n	weblogic.management.runtime.PartitionFairShareRuntimeMBean .....	2-101
n	weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean .....	2-101
n	weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean.....	2-102
n	weblogic.management.runtime.PartitionRuntimeMBean .....	2-104
n	weblogic.management.runtime.PartitionWorkManagerRuntimeMBean .....	2-106
n	weblogic.management.runtime.PathServiceRuntimeMBean.....	2-106
n	weblogic.management.runtime.PersistenceUnitRuntimeMBean.....	2-107
n	weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean.....	2-107
n	weblogic.management.runtime.PersistentStoreRuntimeMBean .....	2-108
n	weblogic.management.runtime.QueryCacheRuntimeMBean .....	2-110
n	weblogic.management.runtime.RealmRuntimeMBean .....	2-112
n	weblogic.management.runtime.RequestClassRuntimeMBean.....	2-112
n	weblogic.management.runtime.ResourceManagerRuntimeMBean .....	2-113
n	weblogic.management.runtime.ResourceRuntimeMBean .....	2-113
n	weblogic.management.runtime.RuntimeMBean .....	2-114
n	weblogic.management.runtime.SAFAgentRuntimeMBean .....	2-114
n	weblogic.management.runtime.SAFConversationRuntimeMBean .....	2-117
n	weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean.....	2-118
n	weblogic.management.runtime.SAFRuntimeMBean .....	2-121
n	weblogic.management.runtime.SNMPAgentRuntimeMBean .....	2-121
n	weblogic.management.runtime.ServerChannelRuntimeMBean .....	2-124
n	weblogic.management.runtime.ServerLogRuntimeMBean .....	2-125
n	weblogic.management.runtime.ServerMigrationRuntimeMBean .....	2-126
n	weblogic.management.runtime.ServerRuntimeMBean .....	2-126
n	weblogic.management.runtime.ServerSecurityRuntimeMBean.....	2-130



n	weblogic.management.runtime.SingleSignOnServicesRuntimeMBean.....	2-130
n	weblogic.management.runtime.TaskRuntimeMBean.....	2-130
n	weblogic.management.runtime.ThreadPoolRuntimeMBean.....	2-132
n	weblogic.management.runtime.TimerRuntimeMBean.....	2-134
n	weblogic.management.runtime.TransactionNameRuntimeMBean.....	2-135
n	weblogic.management.runtime.TransactionResourceRuntimeMBean.....	2-137
n	weblogic.management.runtime.TriggerRuntimeMBean.....	2-139
n	weblogic.management.runtime.UnicastMessagingRuntimeMBean.....	2-140
n	weblogic.management.runtime.UserLockoutManagerRuntimeMBean.....	2-141
n	weblogic.management.runtime.WANReplicationRuntimeMBean.....	2-142
n	weblogic.management.runtime.WLDFAccessRuntimeMBean.....	2-143
n	weblogic.management.runtime.WLDFArchiveRuntimeMBean.....	2-144
n	weblogic.management.runtime.WLDFControlRuntimeMBean.....	2-144
n	weblogic.management.runtime.WLDFDataAccessRuntimeMBean.....	2-145
n	weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean.....	2-145
n	weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean.....	2-147
n	weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean.....	2-148
n	weblogic.management.runtime.WLDFHarvesterRuntimeMBean.....	2-149
n	weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean.....	2-150
n	weblogic.management.runtime.WLDFImageRuntimeMBean.....	2-152
n	weblogic.management.runtime.WLDFInstrumentationRuntimeMBean.....	2-153
n	weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean.....	2-154
n	weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean.....	2-155
n	weblogic.management.runtime.WLDFPartitionImageRuntimeMBean.....	2-155
n	weblogic.management.runtime.WLDFPartitionRuntimeMBean.....	2-156
n	weblogic.management.runtime.WLDFRuntimeMBean.....	2-157
n	weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean.....	2-157
n	weblogic.management.runtime.WLDFWatchManagerRuntimeMBean.....	2-157
n	weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean.....	2-162
n	weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean.....	2-166
n	weblogic.management.runtime.WTCRuntimeMBean.....	2-167
n	weblogic.management.runtime.WTCStatisticsRuntimeMBean.....	2-167
n	weblogic.management.runtime.WebServerRuntimeMBean.....	2-168
n	weblogic.management.runtime.WorkManagerRuntimeMBean.....	2-168
n	weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean...	2-169
n	weblogic.management.runtime.WseeBaseOperationRuntimeMBean.....	2-173
n	weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean.....	2-176
n	weblogic.management.runtime.WseeClusterRoutingRuntimeMBean.....	2-176
n	weblogic.management.runtime.WseeHandlerRuntimeMBean.....	2-178
n	weblogic.management.runtime.WseeMcRuntimeMBean.....	2-178
n	weblogic.management.runtime.WseeOperationRuntimeMBean.....	2-178
n	weblogic.management.runtime.WseePolicyRuntimeMBean.....	2-182
n	weblogic.management.runtime.WseePortPolicyRuntimeMBean.....	2-183
n	weblogic.management.runtime.WseePortRuntimeMBean.....	2-184
n	weblogic.management.runtime.WseeV2RuntimeMBean.....	2-186
n	weblogic.management.runtime.WseeWsruntimeMBean.....	2-188







---

---

# Preface

This preface describes the document accessibility features and conventions used in this guide, *RESTful Server Runtime Reference for Oracle WebLogic Server*.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



---

---

## Resources

This documentation describes the Oracle WebLogic Server RESTful server runtime resources that are used to monitor the Administration Server or a Managed Server.

For a complete listing of the WLS REST reference documents and descriptions of their use, see *Administering Oracle WebLogic Server with RESTful Management Services*.

---

## **/management/weblogic**

This resource is used to access the different versions of the resources in this domain.

The latest version is 12.2.1.2.0. The other versions, which are deprecated, are 12.2.1.0.0, 12.2.1.1.0.

For future releases, `latest` always refers to the most recent release.

All new and non-deprecated MBean features are available in all versions. Any MBean features that were deprecated in a version will not be available in that version or later versions, but will still be available using earlier versions.

To always use the latest resources, use `latest` in the URLs. Note that this might require updating a client when moving to a newer version of WebLogic Server. To fix the version so that an update is not required, use `12.2.1.2.0` in the URLs.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.rest.bean.model.Version](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.rest.bean.model.Version](#) entities.

This method can return the following links:

- **uri=/management/weblogic rel=canonical**  
This resource.
- **uri=/management/weblogic/12.2.1.2.0 rel=current**  
Access the latest version of the WLS resources in the this domain.
- **uri=/management/weblogic rel=self**  
This resource.

## Example

### Example 1 View the versions collection.

This example uses the GET method to display the version instances in this collection.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic
```

#### Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "self",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {  
      "rel": "canonical",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {  
      "rel": "current",  
      "href": "http://localhost:7001/management/weblogic/12.2.1.2.0"  
    }  
  ],  
  "items": [  
    {
```

```
    "links": [
      {
        "rel": "self",
        "href": "http://localhost:7001/management/12.2.1.0.0"
      },
      {
        "rel": "canonical",
        "href": "http://localhost:7001/management/12.2.1.0.0"
      }
    ],
    "version": "12.2.1.0.0",
    "isLatest": false,
    "lifecycle": "deprecated"
  },
  {
    "links": [
      {
        "rel": "self",
        "href": "http://localhost:7001/management/12.2.1.1.0"
      },
      {
        "rel": "canonical",
        "href": "http://localhost:7001/management/12.2.1.1.0"
      }
    ],
    "version": "12.2.1.1.0",
    "isLatest": false,
    "lifecycle": "deprecated"
  },
  {
    "links": [
      {
        "rel": "self",
        "href": "http://localhost:7001/management/12.2.1.2.0"
      },
      {
        "rel": "canonical",
        "href": "http://localhost:7001/management/12.2.1.2.0"
      }
    ],
    "version": "12.2.1.2.0",
    "isLatest": true,
    "lifecycle": "active"
  }
]
}
```

## **/management/weblogic/{version}**

This resource describes the resource trees that are used to manage a WebLogic Server domain and its managed servers. The resource trees mimic the bean trees in WLST and allow you to view and edit configuration and monitor runtime behavior.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.rest.bean.model.Version](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.rest.bean.model.Version](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=currentUser
- **uri**=[/management/weblogic/{version}/domainConfig](#) **rel**=domainConfig
- **uri**=[/management/weblogic/{version}/domainRuntime](#) **rel**=domainRuntime
- **uri**=[/management/weblogic/{version}/edit](#) **rel**=edit
- **uri**=[/management/weblogic](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=self  
This resource.
- **uri**=[/management/weblogic/{version}/serverConfig](#) **rel**=serverConfig
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=serverRuntime

### Example

#### Example 1 View the latest version.

This example uses the GET method to display the latest version.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest
```

#### Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic"  
    },  
    {
```

```

        "rel": "self",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "canonical",
        "href": "http://localhost:7001/management/weblogic/latest"
    },
    {
        "rel": "edit",
        "href": "http://localhost:7001/management/weblogic/latest/edit"
    },
    {
        "rel": "domainConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/domainConfig"
    },
    {
        "rel": "domainRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/domainRuntime"
    },
    {
        "rel": "serverRuntime",
        "href":
"http://localhost:7001/management/weblogic/latest/serverRuntime"
    },
    {
        "rel": "serverConfig",
        "href":
"http://localhost:7001/management/weblogic/latest/serverConfig"
    },
    {
        "rel": "currentUser",
        "href":
"http://localhost:7001/management/weblogic/latest/currentUser"
    }
],
"version": "12.2.1.2.0",
"isLatest": true,
"lifecycle": "active"
}

```

### Example 2 View a specific version.

This example uses the GET method to display a specific version.

#### Example Request

```

curl -v \
--user admin:admin123 \
-H X-Requested-By:MyClient \
-H Accept:application/json \
-X GET http://localhost:7001/management/weblogic/12.2.1.2.0

```

#### Example Response

HTTP/1.1 200 OK

Response Body:

```

{
  "links": [

```

```
{
  "rel": "parent",
  "href": "http://localhost:7001/management/weblogic"
},
{
  "rel": "self",
  "href": "http://localhost:7001/management/weblogic/12.2.1.2.0"
},
{
  "rel": "canonical",
  "href": "http://localhost:7001/management/weblogic/12.2.1.2.0"
},
{
  "rel": "edit",
  "href": "http://localhost:7001/management/weblogic/12.2.1.2.0/edit"
},
{
  "rel": "domainConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0/domainConfig"
},
{
  "rel": "domainRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0/domainRuntime"
},
{
  "rel": "serverRuntime",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0/serverRuntime"
},
{
  "rel": "serverConfig",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0/serverConfig"
},
{
  "rel": "currentUser",
  "href":
"http://localhost:7001/management/weblogic/12.2.1.2.0/currentUser"
}
],
"version": "12.2.1.2.0",
"isLatest": true,
"lifecycle": "active"
}
```

## **/management/weblogic/{version}/currentUser**

---

This resource represents an authenticated user in the domain.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.rest.bean.model.CurrentUser](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/currentUser](#) **rel**=self  
This resource.

### Example

#### Example 1 Viewing the [weblogic.management.rest.bean.model.CurrentUser](#) Instance

This example uses the GET method to view this [weblogic.management.rest.bean.model.CurrentUser](#) instance.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET http://localhost:7001/management/weblogic/latest/currentUser
```

#### Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:
```

```
{  
  "links": [  
    {  
      "rel": "parent",  
      "href": "http://localhost:7001/management/weblogic/latest"  
    },  
    {  
      "rel": "self",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"  
    },  
    {  
      "rel": "canonical",  
      "href":  
"http://localhost:7001/management/weblogic/latest/currentUser"    }  
  ]  
}
```



```
    }  
  ],  
  "partitionId": "0",  
  "partitionName": "DOMAIN",  
  "user": "admin"  
}
```

---

## **/management/weblogic/{version}/serverRuntime**

This resource is used to monitor the administration server and managed servers.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime  
**rel**=JDBCServiceRuntime  
This resource's JDBCServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime  
**rel**=JMSRuntime  
This resource's JMSRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime  
**rel**=JTARuntime  
This resource's JTARuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JVMRuntime  
**rel**=JVMRuntime  
This resource's JVMRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime  
**rel**=MANAsyncReplicationRuntime  
This resource's MANAsyncReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/MANReplicationRuntime  
**rel**=MANReplicationRuntime  
This resource's MANReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime  
**rel**=SAFRuntime  
This resource's SAFRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime  
**rel**=SNMPAgentRuntime  
This resource's SNMPAgentRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WANReplicationRuntime  
**rel**=WANReplicationRuntime  
This resource's WANReplicationRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime  
**rel**=WLDFRuntime  
This resource's WLDFRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime  
**rel**=WTCRuntime

This resource's WTCRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/bootPartition **rel**=action **title**=bootPartition

This resource's bootPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceRestartPartition **rel**=action **title**=forceRestartPartition

This resource's forceRestartPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceShutdown **rel**=action **title**=forceShutdown

This resource's forceShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup **rel**=action **title**=forceShutdownResourceGroup

This resource's forceShutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceSuspend **rel**=action **title**=forceSuspend

This resource's forceSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup **rel**=action **title**=forceSuspendResourceGroup

This resource's forceSuspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getIPv4URL **rel**=action **title**=getIPv4URL

This resource's getIPv4URL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getIPv6URL **rel**=action **title**=getIPv6URL

This resource's getIPv6URL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getRgState **rel**=action **title**=getRgState

This resource's getRgState action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/getURL **rel**=action **title**=getURL

This resource's getURL action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/restartSSLChannels **rel**=action **title**=restartSSLChannels

This resource's restartSSLChannels action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/resumeResourceGroup **rel**=action **title**=resumeResourceGroup

This resource's resumeResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/shutdown **rel**=action **title**=shutdown

This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/shutdownResourceGroup  
**rel**=action **title**=shutdownResourceGroup

This resource's shutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startPartition **rel**=action  
**title**=startPartition

This resource's startPartition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startPartitionInAdmin  
**rel**=action **title**=startPartitionInAdmin

This resource's startPartitionInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startResourceGroup  
**rel**=action **title**=startResourceGroup

This resource's startResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin  
**rel**=action **title**=startResourceGroupInAdmin

This resource's startResourceGroupInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/suspend **rel**=action  
**title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/suspendResourceGroup  
**rel**=action **title**=suspendResourceGroup

This resource's suspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes  
**rel**=applicationRuntimes

This resource's applicationRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime  
**rel**=asyncReplicationRuntime

This resource's asyncReplicationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime  
**rel**=batchJobRepositoryRuntime

This resource's batchJobRepositoryRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/classLoaderRuntime  
**rel**=classLoaderRuntime

This resource's classLoaderRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime  
**rel**=clusterRuntime

This resource's clusterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime  
**rel**=concurrentManagedObjectsRuntime

This resource's concurrentManagedObjectsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime  
**rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime  
**rel**=defaultExecuteQueueRuntime

This resource's defaultExecuteQueueRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime  
**rel**=entityCacheCumulativeRuntime

This resource's entityCacheCumulativeRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime  
**rel**=entityCacheCurrentStateRuntime

This resource's entityCacheCurrentStateRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime  
**rel**=entityCacheHistoricalRuntime

This resource's entityCacheHistoricalRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/executeQueueRuntimes  
**rel**=executeQueueRuntimes

This resource's executeQueueRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/joltRuntime  
**rel**=joltRuntime

This resource's joltRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/libraryRuntimes  
**rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime  
**rel**=logBroadcasterRuntime

This resource's logBroadcasterRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/mailSessionRuntimes  
**rel**=mailSessionRuntimes

This resource's mailSessionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes  
**rel**=maxThreadsConstraintRuntimes

This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes  
**rel**=messagingBridgeRuntimes

This resource's messagingBridgeRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes  
**rel**=minThreadsConstraintRuntimes

This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes  
**rel**=partitionRuntimes

This resource's partitionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes  
**rel**=pathServiceRuntimes

This resource's pathServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes  
**rel**=persistentStoreRuntimes

This resource's persistentStoreRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/requestClassRuntimes  
**rel**=requestClassRuntimes

This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/search **rel**=search

This resource's search resource.

- **uri**=/management/weblogic/{version}/serverRuntime **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverChannelRuntimes  
**rel**=serverChannelRuntimes

This resource's serverChannelRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverLogRuntime  
**rel**=serverLogRuntime

This resource's serverLogRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime  
**rel**=serverSecurityRuntime

This resource's serverSecurityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime  
**rel**=singleSignOnServicesRuntime

This resource's singleSignOnServicesRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/threadPoolRuntime  
**rel**=threadPoolRuntime

This resource's threadPoolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/timerRuntime  
**rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes  
**rel**=webServerRuntimes

This resource's webServerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/workManagerRuntimes  
**rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime  
**rel**=wseeClusterFrontEndRuntime  
This resource's wseeClusterFrontEndRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/wseeWsruntime  
**rel**=wseeWsruntime  
This resource's wseeWsruntime singleton resource.

## Example

### Example 1 Viewing the weblogic.management.runtime.ServerRuntimeMBean Instance

This example uses the GET method to view this weblogic.management.runtime.ServerRuntimeMBean instance.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-X GET  
http://localhost:7001/management/weblogic/latest/serverRuntime?fields=name,openSoc  
ketsCurrentCount,overallHealthState,administrationURL&links=self
```

#### Example Response

HTTP/1.1 200 OK

Response Body:

```
{  
  "links": [{  
    "rel": "self",  
    "href": "http://localhost:7001/management/weblogic/latest/serverRuntime"  
  }],  
  "openSocketsCurrentCount": 1,  
  "administrationURL": "t3://localhost:7001",  
  "overallHealthState": {  
    "state": "ok",  
    "subsystemName": null,  
    "partitionName": null,  
    "symptoms": []  
  },  
  "name": "AdminServer"  
}
```



---

## /management/weblogic/{version}/serverRuntime/applicationRuntimes

This resource manages a collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ApplicationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes](#)  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ApplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPersistenceUnitRuntime **rel**=action **title**=getPersistenceUnitRuntime  
This resource's getPersistenceUnitRuntime action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasApplicationCache **rel**=action **title**=hasApplicationCache  
This resource's hasApplicationCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools **rel**=action **title**=reInitializeApplicationCachesAndPools  
This resource's reInitializeApplicationCachesAndPools action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=classLoaderRuntime  
This resource's classLoaderRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime **rel**=classRedefinitionRuntime  
This resource's classRedefinitionRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=coherenceClusterRuntime  
This resource's coherenceClusterRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes **rel**=componentRuntimes  
This resource's componentRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes  
This resource's libraryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=managedExecutorServiceRuntimes  
This resource's managedExecutorServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes  
**rel**=managedScheduledExecutorServiceRuntimes  
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=managedThreadFactoryRuntimes  
This resource's managedThreadFactoryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes  
This resource's maxThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes  
This resource's minThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=optionalPackageRuntimes  
This resource's optionalPackageRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=persistenceUnitRuntimes  
This resource's persistenceUnitRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes **rel**=queryCacheRuntimes  
This resource's queryCacheRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes  
This resource's requestClassRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}  
**rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes **rel**=wseeV2Runtimes  
This resource's wseeV2Runtimes collection resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime**

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classLoaderRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime**

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses](#) **rel=action** **title=**redefineClasses  
This resource's redefineClasses action resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=classRedefinitionTasks**  
This resource's classRedefinitionTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/classRedefinitionTasks**

This resource manages a collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/classRedefinitionTasks/{name}**

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel **rel**=action  
**title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a weblogic.management.runtime.TaskRuntimeMBean resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=subTasks  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks  
This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks  
This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/  
classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/s  
ubTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ classRedefinitionRuntime/redefineClasses**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Initiate a class redefinition cycle, which will identify classes which may have changed and then attempt to redefine them. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

## Roles

Admin

## Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

## POST

Initiate a class redefinition cycle, to redefine only the specified classes from given module. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task. If specified module name is null, any classes within the application (scoped to any modules as well as globally scoped classes) which are included in the list will be redefined.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**moduleName**

Module from which the classes are to be redefined.

**Type:** string

**classNames**

Classes to be redefined.

**Type:** array of string

## Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime**

This resource manages a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/coherenceClusterRuntime **rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes**

This resource manages a collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/getPersistenceUnitRuntime**

The resource supports the following methods:

- [POST](#)

## POST

Provides the PersistenceUnitRuntimeMBean for the application with the specified name.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**unitName**  
unitName  
Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.PersistenceUnitRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/hasApplicationCache**

The resource supports the following methods:

- [POST](#)

## POST

Returns true if the application has an (EJB) Application Level Cache

### Roles

Admin, Operator

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes**

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ libraryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ libraryRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedScheduledExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/ managedScheduledExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#)  
**rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#)  
**rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#)  
**rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}](#)  
**rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#)  
**rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#)  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes**

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes**

This resource manages a collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of `weblogic.management.runtime.PersistenceUnitRuntimeMBean` instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of `weblogic.management.runtime.PersistenceUnitRuntimeMBean` entities.

This method can return the following links:

- `uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes rel=canonical`

This resource.

- `uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} rel=parent`

The parent resource of this resource.

- `uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes rel=self`

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes**

This resource manages a collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name}**

This resource manages a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools**

The resource supports the following methods:

- [POST](#)

## POST

If the application has an (EJB) Application Level Cache, then this method will reinitialize the cache and any of its associated pools to their startup time states if possible.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes**

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes**

This resource manages a collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WseeV2RuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes rel=self](#)  
This resource.



## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}**

This resource manages a [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeV2RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=policyRuntime

This resource's policyRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=ports

This resource's ports collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime**

This resource manages a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports**

This resource manages a collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WseePortRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}**

This resource manages a [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseePortRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations **rel**=aggregatedBaseOperations

This resource's aggregatedBaseOperations singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=baseOperations

This resource's baseOperations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=clusterRouting

This resource's clusterRouting singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=handlers

This resource's handlers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=mc

This resource's mc singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=operations

This resource's operations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=parent

The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=portPolicy

This resource's portPolicy singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=self

This resource.



- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsm **rel**=wsm

This resource's wsm singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations**

This resource manages a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations**

This resource manages a collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name}**

This resource manages a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting**

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers**

This resource manages a collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}**

This resource manages a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc**

This resource manages a [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeMcRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations**

This resource manages a collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}**

This resource manages a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy**

This resource manages a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm**

This resource manages a [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime**

This resource manages a [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.AsyncReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/asyncReplicationRuntime](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime**

This resource manages a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/batchJobRepositoryRuntime](#)  
**rel**=self  
This resource.

---

## /management/weblogic/{version}/serverRuntime/bootPartition

The resource supports the following methods:

- [POST](#)

## POST

Boots the partition

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**partitionName**

name of the partition to boot

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/classLoaderRuntime**

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/classLoaderRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/classLoaderRuntime](#)  
**rel**=self  
This resource.

---

## /management/weblogic/{version}/serverRuntime/clusterRuntime

This resource manages a [weblogic.management.runtime.ClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ClusterRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ClusterRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration](#) **rel=action** **title=initiateResourceGroupMigration**  
This resource's initiateResourceGroupMigration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=jobSchedulerRuntime**  
This resource's jobSchedulerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime](#) **rel=serverMigrationRuntime**  
This resource's serverMigrationRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging](#) **rel=unicastMessaging**  
This resource's unicastMessaging singleton resource.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/initiateResourceGroupMigration**

The resource supports the following methods:

- [POST](#)

## POST

Provides a synchronous method for initiating resource group migration.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**partitionName**

partitionName

Type: string

**resourceGroupName**

resourceGroupName

Type: string

**targetCluster**

targetCluster

Type: string

**timeout**

timeout

Type: int

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime**

This resource manages a [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JobSchedulerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/getJob](#) **rel=action** **title=getJob**  
This resource's getJob action resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=executedJobs**  
This resource's executedJobs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs**

This resource manages a collection of [weblogic.management.runtime.JobRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JobRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JobRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}**

This resource manages a [weblogic.management.runtime.JobRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JobRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JobRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel **rel**=action **title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/executedJobs/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Cancel this job and prevent it from executing again in any server, not just this server.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/jobSchedulerRuntime/getJob**

The resource supports the following methods:

- [POST](#)

## POST

Return the JobRuntimeMBean corresponding to the specified ID. An ID is recorded in the WebLogic server logs whenever a new job is scheduled with the Job Scheduler.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**id**  
unique ID corresponding to a job  
Type: string

### Response Body

Contains a JSON object with a weblogic.management.runtime.JobRuntimeMBean reference return field.

## /management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime

This resource manages a [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ServerMigrationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData **rel**=migrationData  
This resource's migrationData collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData**

This resource manages a collection of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MigrationDataRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name}**

This resource manages a [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MigrationDataRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MigrationDataRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/clusterRuntime/serverMigrationRuntime/migrationData/{name} **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging

This resource manages a [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.UnicastMessagingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/clusterRuntime/unicastMessaging](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime**

This resource manages a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=managedExecutorServiceRuntimes**  
This resource's managedExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=managedScheduledExecutorServiceRuntimes**  
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=managedThreadFactoryRuntimes**  
This resource's managedThreadFactoryRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=workManager**  
This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime  
**rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime  
**rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime  
**rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime  
**rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=workManager**  
This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maximumThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaximumThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

## /management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#) **rel=self**  
This resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs rel=RAs](#)  
This resource's RAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections rel=action title=getInboundConnections](#)  
This resource's getInboundConnections action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRA rel=action title=getRA](#)  
This resource's getRA action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume rel=action title=resume](#)  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll rel=action title=resumeAll](#)  
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend rel=action title=suspend](#)  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll rel=action title=suspendAll](#)  
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs rel=activeRAs](#)  
This resource's activeRAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs rel=inactiveRAs](#)  
This resource's inactiveRAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#)  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset  
This resource's forceReset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset  
This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool  
This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections  
This resource's connections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime  
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete  
**rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError  
**rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection  
**rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened  
**rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action  
**title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation  
**rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=RAs

This resource's RAs collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections](#) **rel**=action **title**=getInboundConnections

This resource's getInboundConnections action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA](#) **rel**=action **title**=getRA

This resource's getRA action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume](#) **rel**=action **title**=resume

This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll](#) **rel**=action **title**=resumeAll

This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend](#) **rel**=action **title**=suspend

This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll](#) **rel**=action **title**=suspendAll

This resource's suspendAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs](#) **rel**=activeRAs

This resource's activeRAs collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel**=canonical

This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)



## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)



## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)



## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)



## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)



## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)

This resource's timerRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConne](#)

[ctions/{name}/MDBRuntimes/{name}/transactionRuntime](#)  
**rel=transactionRuntime**

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool](#) **rel**=action  
**title**=initializePool

This resource's initializePool action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers  
**rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManager Runtime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime rel=self](#)  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManager Runtimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel**=action **title**=getConfiguration  
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel**=action **title**=getConnectionPool  
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel**=action **title**=getInboundConnection  
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel**=action **title**=getSchema  
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.



- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#)  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this `weblogic.management.runtime.MessageDrivenEJBRuntimeMBean` instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a `weblogic.management.runtime.MessageDrivenEJBRuntimeMBean` entity.

This method can return the following links:

- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume` `rel=action` `title=resume`

This resource's resume action resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend` `rel=action` `title=suspend`

This resource's suspend action resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}` `rel=canonical`

This resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes` `rel=parent`

The parent resource of this resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime` `rel=poolRuntime`

This resource's poolRuntime singleton resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources` `rel=resources`

This resource's resources collection resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}` `rel=self`

This resource.
- `uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime` `rel=timerRuntime`

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/a  
ctiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/  
{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action  
**title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action  
**title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{n

## **POST**

Activate any temporarily disabled timers.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime  
**rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime  
**rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime  
**rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime  
**rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime S

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime  
**s rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime  
**s rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=capacityRuntime](#)

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime rel=requestClassRuntime](#)

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimeS/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)



## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes  
**rel**=MDBRuntimes  
This resource's MDBRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime  
This resource's poolRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources  
This resource's resources collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime  
This resource's timerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers](#) **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=self  
This resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)  
**rel**=self

This resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.



## /management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime** **e**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime** **e**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/i](#)  
[nactiveRAs](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#)  
[rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/i](#)  
[nactiveRAs](#) [rel=self](#)  
This resource.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action**  
**title=ensureLogOpened**  
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**  
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action**  
**title=forceLogRotation**  
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action**  
**title=forceReset**  
This resource's forceReset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**  
This resource's reset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**  
This resource's testPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**  
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime](#) **rel=logRuntime**  
This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened  
**rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action  
**title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation  
**rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=RAs

This resource's RAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections

This resource's getInboundConnections action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA

This resource's getRA action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs

This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs



This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel=action title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel=action title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel=action title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel=action title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel=action title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel=action title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel=action title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel=action title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)



## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/flushLog**

The resource supports the following methods:

- [POST](#)



## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo ols/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPo  
ols/{name}/testPool**

The resource supports the following methods:

- [POST](#)



## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWor kManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfigurati on**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)



## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**  
This resource's timerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConn](#)

[ctions/{name}/MDBRuntimes/{name}/transactionRuntime](#)  
**rel=transactionRuntime**

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in  
activeRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=self](#)  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManager Runtimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/innactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#)  
**rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#)  
**rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#)  
**rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#)  
**rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel**=action  
**title**=resume

This resource's resume action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#)  
**rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel**=action  
**title**=suspend

This resource's suspend action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#)  
**rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime rel=self](#)

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**  
This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action  
**title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers  
**rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

## **POST**

Activate any temporarily disabled timers.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime rel=capacityRuntime](#)  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=requestClassRuntime](#)  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti me/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/in activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRunti mes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)



## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#)  
**rel=MDBRuntimes**  
This resource's MDBRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)  
This resource's timerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime rel=transactionRuntime](#)

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#)  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inaactiveRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/interactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#)  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/R](#)  
[As rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime](#)  
[rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/R](#)  
[As rel=self](#)  
This resource.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration **rel**=action **title**=getConfiguration  
This resource's getConfiguration action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool  
This resource's getConnectionPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection  
This resource's getInboundConnection action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema **rel**=action **title**=getSchema  
This resource's getSchema action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` entity.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened` **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog` **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation` **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset` **rel**=action **title**=forceReset  
This resource's forceReset action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset` **rel**=action **title**=reset  
This resource's reset action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool` **rel**=action **title**=testPool  
This resource's testPool action resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}` **rel**=canonical  
This resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections` **rel**=connections  
This resource's connections collection resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime` **rel**=logRuntime  
This resource's logRuntime singleton resource.
- **uri**=`/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools` **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action  
**title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action  
**title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action  
**title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/RAs **rel**=RAs  
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections  
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA  
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs  
This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs  
This resource's inactiveRAs collection resource.



- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel**=action **title**=getConfiguration  
This resource's getConfiguration action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel**=action **title**=getConnectionPool  
This resource's getConnectionPool action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel**=action **title**=getInboundConnection  
This resource's getInboundConnection action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel**=action **title**=getSchema  
This resource's getSchema action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

## Roles

Admin

## Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{n

## **POST**

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)



## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action  
**title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers](#) **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime  
**rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime  
**rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime  
**rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime  
**rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime  
**rel**=self  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime S**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/capacityRuntime rel=capacityRuntime](#)

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/maxThreadsConstraintRuntime rel=maxThreadsConstraintRuntime](#)

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/minThreadsConstraintRuntime rel=minThreadsConstraintRuntime](#)

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/requestClassRuntime rel=requestClassRuntime](#)

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name} rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimeS/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.



## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action** **title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action** **title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete rel=action title=delete](#)

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError rel=action title=hasError](#)

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection rel=action title=testConnection](#)

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} rel=self](#)

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=self**

This resource.



---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action  
**title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers  
**rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

## **POST**

Activate any temporarily disabled timers.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)



## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=MDBRuntimes**  
This resource's MDBRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#)  
**rel=action title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#)  
**rel=action title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#)  
**rel=poolRuntime**  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)  
**rel=resources**  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#)  
**rel=timerRuntime**  
This resource's timerRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime](#)  
**rel=transactionRuntime**  
This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)



## POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)



## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

**props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

**props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

**props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime

This resource manages a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/defaultExecuteQueueRuntime](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime**

This resource manages a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCumulativeRuntime rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime**

This resource manages a [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheCurrentStateRuntime rel=self](#)  
This resource.

## /management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime

This resource manages a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/entityCacheHistoricalRuntime](#) [rel=self](#)  
This resource.

---

## /management/weblogic/{version}/serverRuntime/executeQueueRuntimes

This resource manages a collection of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ExecuteQueueRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/executeQueueRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/forceRestartPartition**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Performs a forced restart of the specified partition, waiting the specified time after the halt completes before executing the operation to return the partition to its state in this server at the time the `forceRestartPartition` method was invoked.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**partitionName**  
the partition to be restarted

Type: string

**restartDelayMillis**  
time in milliseconds to wait after halt before restarting

Type: long

## Response Body

Contains an empty JSON object.

## POST

Performs a forced restart of the specified partition.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**partitionName**  
partitionName

Type: string

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/forceShutdown**

The resource supports the following methods:

- [POST](#)

## POST

Force shutdown the server. Causes the server to reject new requests and fail pending requests.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/forceShutdownResourceGroup

The resource supports the following methods:

- [POST](#)

## POST

Force shutdown the resource group. Causes the resource group to reject new requests and fail pending requests.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/forceSuspend**

The resource supports the following methods:

- [POST](#)



## POST

Transitions the server from `RUNNING` to `ADMIN` state forcefully cancelling inflight work. Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This is the supported way of force suspending the server and getting it into `ADMIN` state.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/forceSuspendResourceGroup

The resource supports the following methods:

- [POST](#)

## POST

Transitions the resource group from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This is the supported way of force suspending the resource group and getting it into `ADMIN` state.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/getIPv4URL**

The resource supports the following methods:

- [POST](#)

## POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**protocol**  
the desired protocol

Type: string

### Response Body

Contains a JSON object with a string return field.

### Example

#### Example 1 Invoke the getIPv4URL Action

This example uses the POST method to invoke the `getIPv4URL` action.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{ protocol: 'http' }" \  
-X POST http://localhost:7001/management/weblogic/latest/serverRuntime/getIPv4URL
```

#### Example Response

```
HTTP/1.1 200 OK
```

Response Body:

```
{"return": "http://localhost:7001"}
```

## **/management/weblogic/{version}/serverRuntime/getIPv6URL**

The resource supports the following methods:

- [POST](#)

## POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**protocol**

the desired protocol

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/getRgState**

The resource supports the following methods:

- [POST](#)



## POST

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/getURL**

The resource supports the following methods:

- [POST](#)

## POST

The URL that clients use when connecting to this server using the specified protocol.

Note: The listen address and listen port for a given protocol are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**protocol**

the desired protocol

Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime**

This resource manages a [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) [rel=JDBCDataSourceRuntimeMBeans](#)  
This resource's JDBCDataSourceRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDriverRuntimeMBeans](#) [rel=JDBCDriverRuntimeMBeans](#)  
This resource's JDBCDriverRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) [rel=JDBCMultiDataSourceRuntimeMBeans](#)  
This resource's JDBCMultiDataSourceRuntimeMBeans collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime  
**rel**=JDBCDriverRuntime  
This resource's JDBCDriverRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean  
**rel**=JDBCReplayStatisticsRuntimeMBean  
This resource's JDBCReplayStatisticsRuntimeMBean singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown **rel**=action  
**title**=asyncShutdown  
This resource's asyncShutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend **rel**=action  
**title**=asyncSuspend  
This resource's asyncSuspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache **rel**=action  
**title**=clearStatementCache  
This resource's clearStatementCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool **rel**=action **title**=dumpPool  
This resource's dumpPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile **rel**=action  
**title**=dumpPoolProfile  
This resource's dumpPoolProfile action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown **rel**=action  
**title**=forceShutdown  
This resource's forceShutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend **rel**=action **title**=forceSuspend

This resource's forceSuspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists **rel**=action **title**=poolExists

This resource's poolExists action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink **rel**=action **title**=shrink

This resource's shrink action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown **rel**=action **title**=shutdown

This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start **rel**=action **title**=start

This resource's start action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=canonical

This resource.

- **rel**=lastTask

This resource's lastTask reference to a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=tasks

This resource's tasks collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes  
**rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown**

The resource supports the following methods:

- [POST](#)

## POST

Gracefully, asynchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

Setting `IgnoreInUseConnectionsEnabled` to `false` causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

#### **operationSecs**

The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use `Inactive Connection Timeout Seconds` if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: int

### Response Body

Contains a JSON object with a `weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend**

The resource supports the following methods:

- [POST](#)

## POST

Asynchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: `java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later.` These connections remain in the pool and are not closed because the pool may be resumed.

Setting `IgnoreInUseConnectionsEnabled` to `false` causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`.

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **operationSecs**

The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use `Inactive Connection Timeout Seconds` if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: `int`

## Response Body

Contains a JSON object with a `weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearState-

## **POST**

For each connection in the connection pool, clears the statement cache of Prepared and Callable Statements.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool**

The resource supports the following methods:

- [POST](#)

## POST

Prints out information about all the connections in the connection pool in the data source.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile**

The resource supports the following methods:

- [POST](#)

## **POST**

Prints out profile information about the data source.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown**

The resource supports the following methods:

- [POST](#)

## POST

Forcefully shuts down a data source that has a health state of `Running`, including forcing the disconnection of all current connection users.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend**

The resource supports the following methods:

- [POST](#)



## POST

Forcefully suspends a data source that has the health state of `Running`, including disconnecting all current connection users. All current connections are closed and recreated.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime**

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean**

This resource manages a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics **rel**=action **title**=clearStatistics  
This resource's clearStatistics action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics **rel**=action **title**=refreshStatistics  
This resource's refreshStatistics action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics**

The resource supports the following methods:

- [POST](#)

## POST

Clear the statistics on all connections.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics**

The resource supports the following methods:

- [POST](#)



## **POST**

Update the snapshot

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists**

The resource supports the following methods:

- [POST](#)

## POST

Specifies whether a data source with the given name exists.

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**poolName**

Name of the pool being looked for

Type: string

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset**

The resource supports the following methods:

- [POST](#)



## POST

Resets the connection pool in the data source by shutting down and recreating all available database connections in the pool.

Use when a data source is in the health state of `Unhealthy` and needs to be reinitialized.

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Restores all access to and operations on a data source that has a health state of Suspended

If successful, the health state is set to Running

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink**

The resource supports the following methods:

- [POST](#)

## POST

Shrinks the database connection pool in the data source to either the current number of reserved connections or the initial size of the connection pool, whichever is greater.

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown**

The resource supports the following methods:

- [POST](#)

## POST

Gracefully, synchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/start**

The resource supports the following methods:

- [POST](#)



## POST

Starts a data source that has a health state of Shutdown

If successful, the health state is set to Running

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Synchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: `java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later.` If graceful suspend is done as part of a graceful shutdown operation, connections are immediately closed when no longer reserved or at the end of the timeout period. If not done as part of a shutdown operation, these connections remain in the pool and are not closed because the pool may be resumed.

By default, the timeout period is 60 seconds. You can change the value of this timeout period by configuring or dynamically setting `Inactive Connection Timeout Seconds` to a non-zero value.

Setting `IgnoreInUseConnectionsEnabled` to false causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks**

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}**

This resource manages a [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel](#) **rel=action** **title=cancel**  
This resource's cancel action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks](#) **rel=parent**  
The parent resource of this resource.
- **rel=parentTask**  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks](#) **rel=subTasks**  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)



## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel  
**rel**=action **title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks  
**rel**=subTasks  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks](#)  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC  
DataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/  
{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Tests the connection pool in the data source by reserving and releasing a connection from it.

If the pool configuration attribute TestConnectionsOnReserve is enabled, the acquired connection is also tested as part of the reserve operation.

## Roles

Admin

## Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC DriverRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDriverRuntimeMBeans](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCDriverRuntimeMBeans](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC DriverRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC  
DriverRuntimeMBeans/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC  
DriverRuntimeMBeans](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC  
DriverRuntimeMBeans/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=workManagerRuntimes**

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capa cityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/max ThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minT hreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBC MultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requ estClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JDBCServiceRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime**

This resource manages a [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers](#)  
**rel**=JMSServers  
This resource's JMSServers collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)  
**rel**=connections  
This resource's connections collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections**

This resource manages a collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}

This resource manages a [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy **rel**=action **title**=destroy  
This resource's destroy action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions **rel**=sessions  
This resource's sessions collection resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/destroy**

The resource supports the following methods:

- [POST](#)

## **POST**

Destroys server side context for the connection.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions**

This resource manages a collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}**

This resource manages a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel=consumers**  
This resource's consumers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=producers**  
This resource's producers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers**

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}**

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers**

This resource manages a collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}**

This resource manages a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers**

This resource manages a collection of [weblogic.management.runtime.JMServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMServerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMServerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}**

This resource manages a [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMServerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor](#) **rel=action** **title=closeCursor**  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit](#) **rel=action** **title=forceCommit**  
This resource's forceCommit action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceRollback](#) **rel=action** **title=forceRollback**  
This resource's forceRollback action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorEndPosition](#) **rel=action** **title=getCursorEndPosition**  
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorSize](#) **rel=action** **title=getCursorSize**  
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorStartPosition](#) **rel=action** **title=getCursorStartPosition**  
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getMessages](#) **rel=action** **title=getMessages**  
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getTransactionStatus](#) **rel=action** **title=getTransactionStatus**  
This resource's getTransactionStatus action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseConsumption](#) **rel=action** **title=pauseConsumption**  
This resource's pauseConsumption action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseInsertion](#) **rel=action** **title=pauseInsertion**  
This resource's pauseInsertion action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseProduction](#) **rel=action** **title=pauseProduction**

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations **rel**=destinations

This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations**

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor **rel**=action **title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber **rel**=action **title**=createDurableSubscriber  
This resource's createDurableSubscriber action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages **rel**=action **title**=deleteMessages  
This resource's deleteMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize **rel**=action **title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages **rel**=action **title**=getMessages  
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption **rel**=action **title**=pauseConsumption  
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=durableSubscribers

This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)



## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers**

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}**

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages  
This resource's deleteMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages  
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=canonical  
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime  
**rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber rel=action title=createDurableSubscriber](#)

This resource's createDurableSubscriber action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption rel=action title=pauseConsumption](#)

This resource's pauseConsumption action resource.



- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers  
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition**

The resource supports the following methods:

- [POST](#)



## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort**

The resource supports the following methods:

- [POST](#)



## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/destinations/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceCommit**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be committed.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/forceRollback**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be rolled back.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

**Type:** string

**timeoutSeconds**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/getTransactionStatus**

The resource supports the following methods:

- [POST](#)

## POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains a JSON object with a int return field.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime **rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption operation on all the destinations hosted by the JMS Server.

When the JMS Server is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the appearance of any messages on all the destinations of the JMS Server, that are result of the in-flight work completion on all the destinations hosted by this JMS Server.

### Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)



## POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are alloed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes**

This resource manages a collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}**

This resource manages a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=JMSServer

This resource's JMSServer singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=connectionConsumers

This resource's connectionConsumers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers**

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}**

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer**

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor **rel**=action  
**title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit **rel**=action  
**title**=forceCommit  
This resource's forceCommit action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback **rel**=action  
**title**=forceRollback  
This resource's forceRollback action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorEndPosition **rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize **rel**=action  
**title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorStartPosition **rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages **rel**=action  
**title**=getMessages  
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus **rel**=action  
**title**=getTransactionStatus  
This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption **rel**=action **title**=pauseConsumption  
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=destinations  
This resource's destinations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=logRuntime  
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=self  
This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sessionPoolRuntimes  
**rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor**

The resource supports the following methods:

- [POST](#)



## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations**

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor](#) or [rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber](#) [rel=action title=createDurableSubscriber](#)

This resource's createDurableSubscriber action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages](#) [rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition](#) [rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize](#) [rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition](#) [rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages](#) [rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption](#) [rel=action title=pauseConsumption](#)

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=durableSubscribers  
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=self  
This resource.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers**

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}**

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=canonical

This resource.



- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action  
**title**=pauseConsumption  
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action  
**title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action  
**title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action  
**title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action  
**title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action  
**title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers  
**rel**=durableSubscribers  
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=parent



The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition**

The resource supports the following methods:

- [POST](#)



## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort**

The resource supports the following methods:

- [POST](#)



## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursor EndPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be committed.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be rolled back.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

**Type:** string

**timeoutSeconds**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus**

The resource supports the following methods:

- [POST](#)

## POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened  
**rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog  
**rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation  
**rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=self  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption operation on all the destinations hosted by the JMS Server.

When the JMS Server is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the appearance of any messages on all the destinations of the JMS Server, that are result of the in-flight work completion on all the destinations hosted by this JMS Server.

### Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- **RECOVERED MESSAGES**

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- **REDELIVERED MESSAGES**

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeInsertion**

The resource supports the following methods:

- [POST](#)



## POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are alloed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/JMSRuntime/JMSServers/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/joltRuntime**

This resource manages a [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JoltConnectionServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#) **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools**

This resource manages a collection of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/joltRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JoltConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool](#) **rel=action** **title=resetConnectionPool**  
This resource's resetConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections](#) **rel=connections**  
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JoltConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/connections/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/joltRuntime/connectionPools/{name}/resetConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Resets the connection pool.

## Roles

Admin

## Response Body

Contains a JSON object with a int return field.

## **/management/weblogic/{version}/serverRuntime/JTARuntime**

This resource manages a [weblogic.management.runtime.JTARuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JTARuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JTARuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean](#) [rel=action](#) [title=getRecoveryRuntimeMBean](#)  
This resource's `getRecoveryRuntimeMBean` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans](#) [rel=nonXAResourceRuntimeMBeans](#)  
This resource's `nonXAResourceRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) [rel=recoveryRuntimeMBeans](#)  
This resource's `recoveryRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) [rel=self](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) [rel=transactionLogStoreRuntimeMBean](#)  
This resource's `transactionLogStoreRuntimeMBean` singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans](#) [rel=transactionNameRuntimeMBeans](#)  
This resource's `transactionNameRuntimeMBeans` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) [rel=transactionResourceRuntimeMBeans](#)  
This resource's `transactionResourceRuntimeMBeans` collection resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/getRecoveryRuntimeMBean**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime MBean for the Transaction Recovery Service of the specified server. If the Transaction Recovery Service of the specified server is not deployed on this server, null will be returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**serverName**

serverName

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.JTARecoveryRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/nonXAResourceRuntimeMBeans/{name} **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JTARecoveryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JTARuntime/recoveryRuntimeMBeans/{name}](#) **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections](#) **rel=connections**

This resource's connections collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections**

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name}**

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionLogStoreRuntimeMBean/connections/{name} **rel**=self

This resource.

## /management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans

This resource manages a collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionNameRuntimeMBeans/{name} **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/JTARuntime/transactionResourceRuntimeMBeans/{name} **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/JVMRuntime

This resource manages a [weblogic.management.runtime.JVMRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JVMRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JVMRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/JVMRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/JVMRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/libraryRuntimes**

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes](#)  
**rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel**=referencingRuntimes  
This resource's referencingRuntimes collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/libraryRuntimes/{name}/referencingRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime**

This resource manages a [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogBroadcasterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/logBroadcasterRuntime](#)  
**rel**=self  
This resource.

---

## /management/weblogic/{version}/serverRuntime/mailSessionRuntimes

This resource manages a collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MailSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name}** **}**

This resource manages a [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MailSessionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/mailSessionRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime**

This resource manages a [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MANAsyncReplicationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/MANAsyncReplicationRuntime rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/MANReplicationRuntime**

This resource manages a [weblogic.management.runtime.MANReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MANReplicationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MANReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/MANReplicationRuntime](#)  
**l**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/MANReplicationRuntime](#)  
**l**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/maxThreadsConstraintRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/messagingBridgeRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/minThreadsConstraintRuntimes/{name}](#) **rel=self**  
This resource.

---

## /management/weblogic/{version}/serverRuntime/partitionRuntimes

This resource manages a collection of [weblogic.management.runtime.PartitionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PartitionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PartitionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.PartitionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PartitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) **rel**=JDBCPartitionRuntime  
This resource's JDBCPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime](#) **rel**=JMSRuntime  
This resource's JMSRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=JTAPartitionRuntime  
This resource's JTAPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime](#) **rel**=SAFRuntime  
This resource's SAFRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=WLDFPartitionRuntime  
This resource's WLDFPartitionRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown](#) **rel**=action **title**=forceShutdown  
This resource's forceShutdown action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup](#) **rel**=action **title**=forceShutdownResourceGroup  
This resource's forceShutdownResourceGroup action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend](#) **rel**=action **title**=forceSuspend  
This resource's forceSuspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup](#) **rel**=action **title**=forceSuspendResourceGroup  
This resource's forceSuspendResourceGroup action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState](#) **rel**=action **title**=getRgState  
This resource's getRgState action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt](#) **rel**=action **title**=halt

This resource's halt action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup **rel**=action **title**=resumeResourceGroup

This resource's resumeResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown **rel**=action **title**=shutdown

This resource's shutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup **rel**=action **title**=shutdownResourceGroup

This resource's shutdownResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup **rel**=action **title**=startResourceGroup

This resource's startResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin **rel**=action **title**=startResourceGroupInAdmin

This resource's startResourceGroupInAdmin action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup **rel**=action **title**=suspendResourceGroup

This resource's suspendResourceGroup action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=applicationRuntimes

This resource's applicationRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=batchJobRepositoryRuntime

This resource's batchJobRepositoryRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime **rel**=concurrentManagedObjectsRuntime

This resource's concurrentManagedObjectsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes **rel**=mailSessionRuntimes

This resource's mailSessionRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=maxThreadsConstraintRuntimes

This resource's maxThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes **rel**=messagingBridgeRuntimes

This resource's messagingBridgeRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes **rel**=minThreadsConstraintRuntimes

This resource's minThreadsConstraintRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime **rel**=partitionResourceMetricsRuntime

This resource's partitionResourceMetricsRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime **rel**=partitionWorkManagerRuntime

This resource's partitionWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes **rel**=pathServiceRuntimes

This resource's pathServiceRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes **rel**=persistentStoreRuntimes

This resource's persistentStoreRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes

This resource's requestClassRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime **rel**=resourceManagerRuntime

This resource's resourceManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime **rel**=wseeClusterFrontEndRuntime

This resource's wseeClusterFrontEndRuntime singleton resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes**

This resource manages a collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ApplicationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ApplicationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ApplicationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ApplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime **rel**=action  
**title**=getPersistenceUnitRuntime

This resource's getPersistenceUnitRuntime action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache **rel**=action  
**title**=hasApplicationCache

This resource's hasApplicationCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools **rel**=action  
**title**=reInitializeApplicationCachesAndPools

This resource's reInitializeApplicationCachesAndPools action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime **rel**=classLoaderRuntime

This resource's classLoaderRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime  
**rel**=classRedefinitionRuntime

This resource's classRedefinitionRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime  
**rel**=coherenceClusterRuntime

This resource's coherenceClusterRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=componentRuntimes

This resource's componentRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=libraryRuntimes

This resource's libraryRuntimes collection resource.



- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes  
**rel**=managedExecutorServiceRuntimes  
This resource's managedExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes  
**rel**=managedScheduledExecutorServiceRuntimes  
This resource's managedScheduledExecutorServiceRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes  
**rel**=managedThreadFactoryRuntimes  
This resource's managedThreadFactoryRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes  
**rel**=maxThreadsConstraintRuntimes  
This resource's maxThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes  
**rel**=minThreadsConstraintRuntimes  
This resource's minThreadsConstraintRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes  
**rel**=optionalPackageRuntimes  
This resource's optionalPackageRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes  
**rel**=persistenceUnitRuntimes  
This resource's persistenceUnitRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=queryCacheRuntimes  
This resource's queryCacheRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes **rel**=requestClassRuntimes  
This resource's requestClassRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes  
**rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=wseeV2Runtimes

This resource's wseeV2Runtimes collection resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime**

This resource manages a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ClassLoaderRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classLoaderRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime**

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/defineClasses](#)  
**rel**=action **title**=defineClasses

This resource's defineClasses action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)  
**rel**=classRedefinitionTasks

This resource's classRedefinitionTasks collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks**

This resource manages a collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks](#)  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}**

This resource manages a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a `weblogic.management.runtime.TaskRuntimeMBean` resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap  
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{  
name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap  
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{  
name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{ name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap  
plicationRuntimes/{name}/classRedefinitionRuntime/classRedefinitionTasks/{  
name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/classRedefinitionRuntime/redefineClasses**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Initiate a class redefinition cycle, which will identify classes which may have changed and then attempt to redefine them. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

## POST

Initiate a class redefinition cycle, to redefine only the specified classes from given module. Class redefinition will be performed asynchronously. The progress of the class redefinition process can be monitored with the returned task. If specified module name is null, any classes within the application (scoped to any modules as well as globally scoped classes) which are included in the list will be redefined.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**moduleName**

Module from which the classes are to be redefined.

**Type:** string

**classNames**

Classes to be redefined.

**Type:** array of string

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/classRedefinitionRunti

## Response Body

Contains a JSON object with a `com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime**

This resource manages a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CoherenceClusterRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/coherenceClusterRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes**

This resource manages a collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime** **S**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntime/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/componentRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/getPersistenceUnitRuntime**

The resource supports the following methods:

- [POST](#)

## POST

Provides the PersistenceUnitRuntimeMBean for the application with the specified name.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**unitName**

unitName

Type: string

### Response Body

Contains a JSON object with a  
weblogic.management.runtime.PersistenceUnitRuntimeMBean reference return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/hasApplicationCache**

The resource supports the following methods:

- [POST](#)



## **POST**

Returns true if the application has an (EJB) Application Level Cache

## **Roles**

Admin, Operator

## **Response Body**

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes**

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes

This resource's referencingRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes  
**rel**=self  
This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=workManager

This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=workManager  
This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/managedThreadFactoryRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/managedThreadFactoryRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/maxThreadsConstraintRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/minThreadsConstraintRuntimes/{name} **rel**=self

This resource.

---

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=referencingRuntimes  
This resource's referencingRuntimes collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/optionalPackageRuntimes/{name}/referencingRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes**

This resource manages a collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/persistenceUnitRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PersistenceUnitRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/persistenceUnitRuntimes/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes**

This resource manages a collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}**

This resource manages a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.QueryCacheRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.QueryCacheRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/queryCacheRuntimes/{name}](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/reInitializeApplicationCachesAndPools**

The resource supports the following methods:

- [POST](#)

## POST

If the application has an (EJB) Application Level Cache, then this method will reinitialize the cache and any of its associated pools to their startup time states if possible.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes**

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes**

This resource manages a collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeV2RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WseeV2RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}**

This resource manages a [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeV2RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeV2RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=policyRuntime

This resource's policyRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=ports

This resource's ports collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime**

This resource manages a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WseePolicyRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseePolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/policyRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports**

This resource manages a collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseePortRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WseePortRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}**

This resource manages a [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseePortRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseePortRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregatedBaseOperations](#) **rel=aggregatedBaseOperations**  
This resource's aggregatedBaseOperations singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel=baseOperations**  
This resource's baseOperations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel=clusterRouting**  
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#) **rel=handlers**  
This resource's handlers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc](#) **rel=mc**  
This resource's mc singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations](#) **rel=operations**  
This resource's operations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel=portPolicy**

This resource's portPolicy singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsm **rel**=wsm

This resource's wsm singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregated BaseOperations**

This resource manages a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregateDBaseOperations rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/aggregateDBaseOperations rel=self](#)

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperati ons**

This resource manages a collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperati ons/{name}**

This resource manages a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeBaseOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/baseOperations/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouti ng**

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/clusterRouting](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers**

This resource manages a collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers](#)  
**rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name}**

This resource manages a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeHandlerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/handlers/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc**

This resource manages a [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeMcRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeMcRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/mc  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations**

This resource manages a collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name}**

This resource manages a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeOperationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeOperationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/operations/{name} **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy**

This resource manages a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseePortPolicyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/portPolicy](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/ap plicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrcm**

This resource manages a [weblogic.management.runtime.WseeWsrcmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/applicationRuntimes/{name}/wseeV2Runtimes/{name}/ports/{name}/wsrm](#)  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime**

This resource manages a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.BatchJobRepositoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/batchJobRepositoryRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime**

This resource manages a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel=managedExecutorServiceRuntimes**  
This resource's `managedExecutorServiceRuntimes` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntime](#) **s rel=managedScheduledExecutorServiceRuntimes**  
This resource's `managedScheduledExecutorServiceRuntimes` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel=managedThreadFactoryRuntimes**  
This resource's `managedThreadFactoryRuntimes` collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **el=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel=self**  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes](#)  
**rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}](#)  
**rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=workManager

This resource's workManager singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/maxThreadsConstraintRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedScheduledExecutorServiceRuntimes/{name}/workManager/requestClassRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes**

This resource manages a collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/concurrentManagedObjectsRuntime/managedThreadFactoryRuntimes/{name}](#)  
**rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs](#) **rel**=RAs  
This resource's RAs collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections](#) **rel**=action **title**=getInboundConnections  
This resource's getInboundConnections action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA](#) **rel**=action **title**=getRA  
This resource's getRA action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume](#) **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll](#) **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend](#) **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll](#) **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs](#) **rel**=activeRAs  
This resource's activeRAs collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=inactiveRAs  
This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}  
**rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/  
connectorServiceRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration](#) **rel=action**  
**title=getConfiguration**  
This resource's getConfiguration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool](#) **rel=action**  
**title=getConnectionPool**  
This resource's getConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection](#) **rel=action**  
**title=getInboundConnection**  
This resource's getInboundConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema](#) **rel=action**  
**title=getSchema**  
This resource's getSchema action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume](#) **rel=action** **title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll](#) **rel=action**  
**title=resumeAll**  
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend](#) **rel=action** **title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll](#) **rel=action**  
**title=suspendAll**  
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=canonical**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools  
**rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime  
**rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime  
**rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections  
**rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime  
**rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes  
**rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Test the connection. Returns true if the test was successful.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)



## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs  
**rel**=RAs  
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections  
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA  
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs  
This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action**  
**title=ensureLogOpened**  
This resource's ensureLogOpened action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**  
This resource's flushLog action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action**  
**title=forceLogRotation**  
This resource's forceLogRotation action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**  
This resource's forceReset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**  
This resource's reset action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**  
This resource's testPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#)  
**rel=action title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#)  
**rel=action title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#)  
**rel=poolRuntime**

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)  
**rel=resources**

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactive](#)

[RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#)  
**rel=timerRuntime**

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)



## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Activate any temporarily disabled timers.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's getConfiguration action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's getConnectionPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's getInboundConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's getSchema action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's resumeAll action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Test the connection. Returns true if the test was successful.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connect

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)



## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=MDBRuntimes**

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}

[me}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#)  
**rel=timerRuntime**

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel=transactionRuntime**

This resource's transactionRuntime singleton resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/resume  
All**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#) **rel=action** **title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#) **rel=action** **title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#) **rel=poolRuntime**  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#) **rel=resources**  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#) **rel=timerRuntime**  
This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inbound

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action  
**title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime  
**rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime  
**rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime  
**rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime  
**rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassesRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)

## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration](#) **rel=action**  
**title=getConfiguration**  
This resource's getConfiguration action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool](#) **rel=action**  
**title=getConnectionPool**  
This resource's getConnectionPool action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection](#) **rel=action**  
**title=getInboundConnection**  
This resource's getInboundConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema](#) **rel=action**  
**title=getSchema**  
This resource's getSchema action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume](#) **rel=action**  
**title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll](#) **rel=action**  
**title=resumeAll**  
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend](#) **rel=action**  
**title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll](#) **rel=action**  
**title=suspendAll**  
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=canonical**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools  
**rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime  
**rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime  
**rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections  
**rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime  
**rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes  
**rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.



- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action** **title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action** **title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action** **title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)



## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)



## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)



## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs](#)  
**rel=RAs**  
This resource's RAs collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections](#) **rel=action title=getInboundConnections**  
This resource's getInboundConnections action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA](#)  
**rel=action title=getRA**  
This resource's getRA action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume](#)  
**rel=action title=resume**  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll](#)  
**rel=action title=resumeAll**  
This resource's resumeAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend](#)  
**rel=action title=suspend**  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll](#)  
**rel=action title=suspendAll**  
This resource's suspendAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#)  
**rel=activeRAs**  
This resource's activeRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened rel=action title=ensureLogOpened](#)  
This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog rel=action title=flushLog](#)  
This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation rel=action title=forceLogRotation](#)  
This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset rel=action title=forceReset](#)  
This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset rel=action title=reset](#)  
This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool rel=action title=testPool](#)  
This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} rel=canonical](#)  
This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections rel=connections](#)

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened](#) **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog](#) **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation](#) **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime](#) **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=MDBRuntimes**

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel=self**

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume](#)  
**rel=action title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend](#)  
**rel=action title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime](#)  
**rel=poolRuntime**

This resource's poolRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources](#)  
**rel=resources**

This resource's resources collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/active](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime  
e rel=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)



## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)



## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Activate any temporarily disabled timers.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime rel=canonical](#)  
This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime rel=self](#)

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)



## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action**  
**title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action**  
**title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action**  
**title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Test the connection. Returns true if the test was successful.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/conne

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self  
This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)



## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)



## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{

`name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime`  
**rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activeDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of `weblogic.management.runtime.WorkManagerRuntimeMBean` instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of `weblogic.management.runtime.WorkManagerRuntimeMBean` entities.

This method can return the following links:

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes` **rel**=canonical

This resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}` **rel**=parent

The parent resource of this resource.

- **uri**=`/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes` **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume rel=action title=resume](#)  
This resource's resume action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend rel=action title=suspend](#)  
This resource's suspend action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime rel=poolRuntime](#)  
This resource's poolRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources rel=resources](#)  
This resource's resources collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} rel=self](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime rel=timerRuntime](#)  
This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbou

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/M  
DBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action  
**title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inbou

## **POST**

Activate any temporarily disabled timers.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

**props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration](#) **rel=action**  
**title=getConfiguration**

This resource's getConfiguration action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool](#) **rel=action**  
**title=getConnectionPool**

This resource's getConnectionPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection](#) **rel=action**  
**title=getInboundConnection**

This resource's getInboundConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's getSchema action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume](#) **rel=action** **title=resume**

This resource's resume action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's resumeAll action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's suspend action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's suspendAll action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=canonical**

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset

This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset

This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool

This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.



- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime  
**rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)



## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

## **Roles**

Admin

## **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## **POST**

Flushes the buffer to the log file on disk.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)



## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)



## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime**

This resource manages a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/RAs **rel**=RAs  
This resource's RAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections **rel**=action **title**=getInboundConnections  
This resource's getInboundConnections action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA **rel**=action **title**=getRA  
This resource's getRA action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume **rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll **rel**=action **title**=resumeAll  
This resource's resumeAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend **rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll **rel**=action **title**=suspendAll  
This resource's suspendAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=activeRAs  
This resource's activeRAs collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs  
**rel**=inactiveRAs

This resource's inactiveRAs collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration **rel**=action **title**=getConfiguration

This resource's getConfiguration action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool **rel**=action **title**=getConnectionPool

This resource's getConnectionPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection **rel**=action **title**=getInboundConnection

This resource's getInboundConnection action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema **rel**=action **title**=getSchema

This resource's getSchema action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll **rel**=action **title**=resumeAll

This resource's resumeAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll **rel**=action **title**=suspendAll

This resource's suspendAll action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=connectionPools

This resource's connectionPools collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime

This resource's connectorServiceRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime

This resource's connectorWorkManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=inboundConnections

This resource's inboundConnections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=workManagerRuntime

This resource's workManagerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened](#) **rel=action**  
**title=ensureLogOpened**

This resource's ensureLogOpened action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog](#) **rel=action** **title=flushLog**

This resource's flushLog action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation](#) **rel=action**  
**title=forceLogRotation**

This resource's forceLogRotation action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset](#) **rel=action** **title=forceReset**

This resource's forceReset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset](#) **rel=action** **title=reset**

This resource's reset action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool](#) **rel=action** **title=testPool**

This resource's testPool action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel=connections**

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel**=action **title**=delete

This resource's delete action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel**=action **title**=hasError

This resource's hasError action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel**=action **title**=testConnection

This resource's testConnection action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)

## POST

Provides a way to manually close a connection through the console.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## POST

Test the connection. Returns true if the test was successful.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{na

[me}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime](#)  
**rel=timerRuntime**

This resource's timerRuntime singleton resource.

- **uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**  
**rel=transactionRuntime**

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)



## **POST**

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)



## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activeDisabledTimers**

The resource supports the following methods:

- [POST](#)

## **POST**

Activate any temporarily disabled timers.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes all activities of this resource adapter.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/activeRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getInboundConnections**

The resource supports the following methods:

- [POST](#)

## POST

Returns runtime information for the specified inbound connection. A null is returned if the inbound connection is not found.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a array of `weblogic.management.runtime.ConnectorInboundRuntimeMBean` references return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/getRA**

The resource supports the following methods:

- [POST](#)



## POST

Returns the runtime information of the resource adapter specified by the given JNDI name. A null is returned if the resource adapter cannot be found. This function returns the active RA if multiple versions of the resource adapters has been deployed

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**key**

The JNDI name of the resource adapter.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorComponentRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs**

This resource manages a collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}**

This resource manages a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorComponentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration](#) **rel=action** **title=getConfiguration**

This resource's `getConfiguration` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool](#) **rel=action** **title=getConnectionPool**

This resource's `getConnectionPool` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection](#) **rel=action** **title=getInboundConnection**

This resource's `getInboundConnection` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema](#) **rel=action** **title=getSchema**

This resource's `getSchema` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume](#) **rel=action** **title=resume**

This resource's `resume` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll](#) **rel=action** **title=resumeAll**

This resource's `resumeAll` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend](#) **rel=action** **title=suspend**

This resource's `suspend` action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll](#) **rel=action** **title=suspendAll**

This resource's `suspendAll` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=connectionPools  
This resource's connectionPools collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorServiceRuntime **rel**=connectorServiceRuntime  
This resource's connectorServiceRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=connectorWorkManagerRuntime  
This resource's connectorWorkManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=inboundConnections  
This resource's inboundConnections collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=workManagerRuntime  
This resource's workManagerRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=workManagerRuntimes  
This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened **rel**=action **title**=ensureLogOpened  
 This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog **rel**=action **title**=flushLog  
 This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation **rel**=action **title**=forceLogRotation  
 This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset **rel**=action **title**=forceReset  
 This resource's forceReset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset **rel**=action **title**=reset  
 This resource's reset action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool **rel**=action **title**=testPool  
 This resource's testPool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=canonical  
 This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections **rel**=connections

This resource's connections collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete](#) **rel=action**  
**title=delete**

This resource's delete action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError](#) **rel=action**  
**title=hasError**

This resource's hasError action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection](#) **rel=action**  
**title=testConnection**

This resource's testConnection action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}](#) **rel=self**

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/delete**

The resource supports the following methods:

- [POST](#)



## **POST**

Provides a way to manually close a connection through the console.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/hasError**

The resource supports the following methods:

- [POST](#)

## POST

Return a flag indicating whether the connection has an error or not. A "true" is returned if there is an error.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/connections/{name}/testConnection**

The resource supports the following methods:

- [POST](#)

## **POST**

Test the connection. Returns true if the test was successful.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/flushLog**

The resource supports the following methods:

- [POST](#)



## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/forceReset**

The resource supports the following methods:

- [POST](#)

## POST

Force immediately discard all used/unused connections and recreate connection pool (and using new configuration if user update the pool's configuration).

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## **POST**

Flushes the buffer to the log file on disk.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/reset**

The resource supports the following methods:

- [POST](#)

## POST

Reset connection pool Discard all unused connections and recreate connection pool (and using new configuration if user update the pool's configuration) if no connection from pool is reserved by client application. If any connection from the connection pool is currently in use, the operation fails and false will be returned, otherwise all connections will be reset and true will be returned.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectionPools/{name}/testPool**

The resource supports the following methods:

- [POST](#)



## POST

Test all the available connections in the pool. Returns true if all the connections passed the test and false if at least one failed the test.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/connectorWorkManagerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)



## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{

`name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime`  
**rel**=timerRuntime

This resource's timerRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime  
**rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.  
This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources  
**rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the specific type of MDB by calling start on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Suspends the specific type of MDB by calling stop on the JMS Connection.

### Roles

Admin

### Response Body

Contains a JSON object with a boolean return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action **title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activeDisabledTimers**

The resource supports the following methods:

- [POST](#)

## POST

Activate any temporarily disabled timers.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/capacityRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntime/requestClassRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime

This resource's capacityRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime

This resource's maxThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime

This resource's minThreadsConstraintRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime

This resource's requestClassRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/inactiveRAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/connectorWorkManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConfiguration**

The resource supports the following methods:

- [POST](#)

## POST

Return the xml string representing the RA configuration. The xml corresponding to the version specified is returned.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getConnectionPool**

The resource supports the following methods:

- [POST](#)

## POST

Returns a `ConnectorConnectionPoolRuntimeMBean` that represents the statistics for a connection pool. The pool that is accessed in this call must be part of the resource adapter that is being accessed. A null is returned if the JNDI name or resource-link name is not found.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**key**

JNDI name or resource-link name of the connection pool.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getInboundConnection**

The resource supports the following methods:

- [POST](#)

## POST

Runtime information for the specified inbound connection. A null is returned if the inbound connection is not found in the resource adapter.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**messageListenerType**

Message listener type.

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.ConnectorInboundRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/getSchema**

The resource supports the following methods:

- [POST](#)

## POST

Get the schema for RA configuration based on the version that is provided. Return null if the version is not found. The current supported version is "1.0"

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**version**

String

Type: string

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections**

This resource manages a collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}**

This resource manages a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ConnectorInboundRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=MDBRuntimes

This resource's MDBRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MessageDrivenEJBRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume **rel**=action **title**=resume

This resource's resume action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend **rel**=action **title**=suspend

This resource's suspend action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=poolRuntime

This resource's poolRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=resources

This resource's resources collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=timerRuntime

This resource's timerRuntime singleton resource.

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConn

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=transactionRuntime

This resource's transactionRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime**

This resource manages a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool **rel**=action **title**=initializePool

This resource's initializePool action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/poolRuntime/initializePool**

The resource supports the following methods:

- [POST](#)

## POST

Instructs the Pool to initialize itself to its configured startup time size.

This is a synchronous and will wait until the pool is initialized before returning.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resources/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes the specific type of MDB by calling start on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## **POST**

Suspends the specific type of MDB by calling stop on the JMS Connection.

### **Roles**

Admin

### **Response Body**

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime**

This resource manages a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.EJBTimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers **rel**=action  
**title**=activateDisabledTimers

This resource's activateDisabledTimers action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/timerRuntime/activateDisabledTimers**

The resource supports the following methods:

- [POST](#)

## **POST**

Activate any temporarily disabled timers.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime**

This resource manages a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.EJBTransactionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/inboundConnections/{name}/MDBRuntimes/{name}/transactionRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

**Type:** int

### **props**

Properties to pass on to the RA or null

**Type:** `java.util.Properties`

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

Resumes all activities of this resource adapter.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspend a particular type of activity for this resource adapter

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/suspendAll**

The resource supports the following methods:

- [POST](#)



## POST

Resumes all activities of this resource adapter.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime  
**rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/capacityRuntime  
**rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/minThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntime/requestClassRuntime rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/RAs/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resume**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Resumes the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/resumeAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Resumes all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the specified type of activity for all RAs

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

### **props**

Properties to pass on to the RA or null

Type: `java.util.Properties`

## Response Body

Contains an empty JSON object.

## POST

Suspends the specified type of activity for all RAs.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **type**

int The type of activity(ies), see `weblogic.connector.extensions.Suspendable`

Type: int

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/connectorServiceRuntime/suspendAll**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **props**

Properties to be passed to the resource adapters or null

**Type:** java.util.Properties

## Response Body

Contains an empty JSON object.

## POST

Suspends all activities of all resource adapters.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdown**

The resource supports the following methods:

- [POST](#)



## POST

Force shutdown the partition. Causes the partition to reject new requests and fail pending requests.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceShutdownResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

Force shutdown the resource group. Causes the resource group to reject new requests and fail pending requests.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspend**

The resource supports the following methods:

- [POST](#)

## POST

Transitions the partition from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are transitioned to admin mode. This forcefully suspends the partition and transitions it to `ADMIN` state.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/forceSuspendResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

Transitions the resource group from `RUNNING` to `ADMIN` state forcefully cancelling inflight work.

Work that cannot be cancelled is dropped. Applications are brought into the admin mode. This forcefully suspends the resource group and transitions it `ADMIN` state.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/getRgState**

The resource supports the following methods:

- [POST](#)



## POST

The current state of the named resource group MBean

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
the resource group name  
Type: string

### Response Body

Contains a JSON object with a string return field.

---

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/halt

The resource supports the following methods:

- [POST](#)

## **POST**

Halts the partition.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime**

This resource manages a [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCPartitionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans](#)  
[rel=JDBCDataSourceRuntimeMBeans](#)

This resource's JDBCDataSourceRuntimeMBeans collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans](#)  
[rel=JDBCMultiDataSourceRuntimeMBeans](#)

This resource's JDBCMultiDataSourceRuntimeMBeans collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) [rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)  
[rel=parent](#)

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime](#) [rel=self](#)

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=JDBCDriverRuntime  
This resource's JDBCDriverRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=JDBCReplayStatisticsRuntimeMBean  
This resource's JDBCReplayStatisticsRuntimeMBean singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown **rel**=action **title**=asyncShutdown  
This resource's asyncShutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend **rel**=action **title**=asyncSuspend  
This resource's asyncSuspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache **rel**=action **title**=clearStatementCache  
This resource's clearStatementCache action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool **rel**=action **title**=dumpPool  
This resource's dumpPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile **rel**=action **title**=dumpPoolProfile  
This resource's dumpPoolProfile action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown **rel**=action **title**=forceShutdown  
This resource's forceShutdown action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend  
**rel**=action **title**=forceSuspend  
This resource's forceSuspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists  
**rel**=action **title**=poolExists  
This resource's poolExists action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset **rel**=action  
**title**=reset  
This resource's reset action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume  
**rel**=action **title**=resume  
This resource's resume action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink  
**rel**=action **title**=shrink  
This resource's shrink action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown  
**rel**=action **title**=shutdown  
This resource's shutdown action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start **rel**=action  
**title**=start  
This resource's start action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend  
**rel**=action **title**=suspend  
This resource's suspend action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool  
**rel**=action **title**=testPool  
This resource's testPool action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=canonical  
This resource.
- **rel**=lastTask  
This resource's lastTask reference to a weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=tasks

This resource's tasks collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncShutdown**

The resource supports the following methods:

- [POST](#)

## POST

Gracefully, asynchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

Setting `IgnoreInUseConnectionsEnabled` to `false` causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

#### **operationSecs**

The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use `Inactive Connection Timeout Seconds` if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: int

### Response Body

Contains a JSON object with a `weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/asyncSuspend**

The resource supports the following methods:

- [POST](#)

## POST

Asynchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: `java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later.` These connections remain in the pool and are not closed because the pool may be resumed.

Setting `IgnoreInUseConnectionsEnabled` to `false` causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`.

This is a privileged operation that can only be invoked by an authorized user.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

#### **operationSecs**

The number of seconds to allow the operation to run before stopping processing. If set to 0, the default is used. The default is to use `Inactive Connection Timeout Seconds` if set or 60 seconds. If you want a minimal timeout, set the value to 1. If you want no timeout, set it to a large value (not recommended).

Type: `int`

### Response Body

Contains a JSON object with a `weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean` reference return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/clearStatementCache**

The resource supports the following methods:

- [POST](#)



## POST

For each connection in the connection pool, clears the statement cache of Prepared and Callable Statements.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPool**

The resource supports the following methods:

- [POST](#)

## POST

Prints out information about all the connections in the connection pool in the data source.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/dumpPoolProfile**

The resource supports the following methods:

- [POST](#)

## **POST**

Prints out profile information about the data source.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceShutdown**

The resource supports the following methods:

- [POST](#)

## POST

Forcefully shuts down a data source that has a health state of `Running`, including forcing the disconnection of all current connection users.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/forceSuspend**

The resource supports the following methods:

- [POST](#)



## POST

Forcefully suspends a data source that has the health state of `Running`, including disconnecting all current connection users. All current connections are closed and recreated.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime**

This resource manages a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDriverRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCDriverRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean**

This resource manages a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics **rel**=action **title**=clearStatistics

This resource's clearStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics **rel**=action **title**=refreshStatistics

This resource's refreshStatistics action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/clearStatistics**

The resource supports the following methods:

- [POST](#)

## POST

Clear the statistics on all connections.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/refreshStatistics**

The resource supports the following methods:

- [POST](#)



## **POST**

Update the snapshot

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/JDBCReplayStatisticsRuntimeMBean/workManagerRuntimes/{name}/requestClassRuntime  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/poolExists**

The resource supports the following methods:

- [POST](#)

## POST

Specifies whether a data source with the given name exists.

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**poolName**

Name of the pool being looked for

**Type:** string

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/reset**

The resource supports the following methods:

- [POST](#)



## POST

Resets the connection pool in the data source by shutting down and recreating all available database connections in the pool.

Use when a data source is in the health state of `Unhealthy` and needs to be reinitialized.

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/resume**

The resource supports the following methods:

- [POST](#)

## POST

Restores all access to and operations on a data source that has a health state of Suspended

If successful, the health state is set to Running

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shrink**

The resource supports the following methods:

- [POST](#)

## POST

Shrinks the database connection pool in the data source to either the current number of reserved connections or the initial size of the connection pool, whichever is greater.

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/shutdown**

The resource supports the following methods:

- [POST](#)

## POST

Gracefully, synchronously shuts down a data source that has a health state of `Running`. A graceful (non-forced) datasource shutdown operation involves first gracefully suspending the data source and then releasing the associated resources including the connections. See the description above for details of gracefully suspending the datasource. After the datasource is gracefully suspended, all remaining in-use connections are closed and the datasource is marked as shut down.

If successful, the health state is set to `Shutdown`

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/start**

The resource supports the following methods:

- [POST](#)



## POST

Starts a data source that has a health state of Shutdown

If successful, the health state is set to Running

This is a privileged operation that can only be invoked by an authorized user.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

Synchronously, gracefully suspends a data source that has the health state of `Running` and disables existing connections. This operation immediately marks the data source as suspended and no further connections are created. Idle (not reserved) connections are marked as disabled. After a timeout period for the suspend operation, all remaining connections in the pool are marked as suspended and the following exception is thrown for any operations on the connection, indicating that the data source is suspended: `java.sql.SQLRecoverableException: Connection has been administratively disabled. Try later.` If graceful suspend is done as part of a graceful shutdown operation, connections are immediately closed when no longer reserved or at the end of the timeout period. If not done as part of a shutdown operation, these connections remain in the pool and are not closed because the pool may be resumed.

By default, the timeout period is 60 seconds. You can change the value of this timeout period by configuring or dynamically setting `Inactive Connection Timeout Seconds` to a non-zero value.

Setting `IgnoreInUseConnectionsEnabled` to false causes the operation to fail if in-use connections exist.

If successful, the health state is set to `Suspended`

This is a privileged operation that can only be invoked by an authorized user.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks**

This resource manages a collection of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}**

This resource manages a [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel **rel**=action **title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=subTasks  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)



## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel rel=action title=cancel](#)

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} rel=canonical](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks rel=parent](#)

The parent resource of this resource.

- [rel=parentTask](#)

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name} rel=self](#)

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/subTasks rel=subTasks](#)

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/tasks/{name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/testPool**

The resource supports the following methods:

- [POST](#)

## POST

Tests the connection pool in the data source by reserving and releasing a connection from it.

If the pool configuration attribute TestConnectionsOnReserve is enabled, the acquired connection is also tested as part of the reserve operation.

### Roles

Admin

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=workManagerRuntimes

This resource's workManagerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes**

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=capacityRuntime  
This resource's capacityRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=maxThreadsConstraintRuntime  
This resource's maxThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=minThreadsConstraintRuntime  
This resource's minThreadsConstraintRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=requestClassRuntime  
This resource's requestClassRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/capacityRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JDBCPartitionRuntime/JDBCMultiDataSourceRuntimeMBeans/{name}/workManagerRuntimes/{name}/requestClassRuntime **rel**=self

This resource.

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime

This resource manages a [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers rel=JMSServers](#)  
This resource's JMSServers collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections rel=connections](#)  
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections**

This resource manages a collection of [weblogic.management.runtime.JMSCConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}**

This resource manages a [weblogic.management.runtime.JMSCConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/destroy rel=action title=destroy](#)  
This resource's destroy action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name} rel=self](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions rel=sessions](#)  
This resource's sessions collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/destroy**

The resource supports the following methods:

- [POST](#)

## **POST**

Destroys server side context for the connection.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/sessions**

This resource manages a collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/connections/{name}/sessions/{name}**

This resource manages a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSSessionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSSessionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel=consumers**

This resource's consumers collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers](#) **rel=producers**

This resource's producers collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers**

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/connections/{name}/sessions/{name}/consumers/{name}**

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/consumers/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers**

This resource manages a collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/connections/{name}/sessions/{name}/producers/{name}**

This resource manages a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSProducerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSProducerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name}  
**rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/connections/{name}/sessions/{name}/producers/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers**

This resource manages a collection of [weblogic.management.runtime.JMSServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMServerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMServerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}**

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/closeCursor](#) **rel=action** **title=closeCursor**  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/forceCommit](#) **rel=action** **title=forceCommit**  
This resource's forceCommit action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/forceRollback](#) **rel=action** **title=forceRollback**  
This resource's forceRollback action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorEndPosition](#) **rel=action** **title=getCursorEndPosition**  
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorSize](#) **rel=action** **title=getCursorSize**  
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getCursorStartPosition](#) **rel=action** **title=getCursorStartPosition**  
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getMessages](#) **rel=action** **title=getMessages**  
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/getTransactionStatus](#) **rel=action** **title=getTransactionStatus**  
This resource's getTransactionStatus action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/pauseConsumption](#) **rel=action** **title=pauseConsumption**  
This resource's pauseConsumption action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/pauseInsertion](#) **rel=action** **title=pauseInsertion**

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/pauseProduction **rel**=action  
**title**=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeConsumption **rel**=action  
**title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeInsertion **rel**=action  
**title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/resumeProduction **rel**=action  
**title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=destinations

This resource's destinations collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=logRuntime

This resource's logRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations**

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations](#) **rel=self**

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/closeCursor](#) **rel=action**  
**title=closeCursor**  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber](#)  
**rel=action** **title=createDurableSubscriber**  
This resource's createDurableSubscriber action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/deleteMessages](#)  
**rel=action** **title=deleteMessages**  
This resource's deleteMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition](#)  
**rel=action** **title=getCursorEndPosition**  
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorSize](#) **rel=action**  
**title=getCursorSize**  
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition](#)  
**rel=action** **title=getCursorStartPosition**  
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/getMessages](#) **rel=action**  
**title=getMessages**  
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption](#)  
**rel=action** **title=pauseConsumption**  
This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=durableSubscribers  
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)



## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers**

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers  
**rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}**

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/sort rel=action title=sort](#)

This resource's sort action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} rel=canonical](#)

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action **title**=pauseConsumption

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion

This resource's pauseInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction

This resource's pauseProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption

This resource's resumeConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion

This resource's resumeInsertion action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction

This resource's resumeProduction action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers

This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}/destinationRuntime/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}/destinationRuntime/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)



## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/getCursorEndPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name }/destinationRuntime/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}/destinationRuntime/getCursorPosition**

The resource supports the following methods:

- [POST](#)



## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}/destinationRuntime/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/destinations/{name}/durableSubscribers/{name  
}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/getCursorEndPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)



## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/destinations/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/destinations/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/forceCommit**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be committed.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/forceRollback**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be rolled back.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorEndPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

**Type:** string

**timeoutSeconds**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### Response Body

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/getTransactionStatus**

The resource supports the following methods:

- [POST](#)

## POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains a JSON object with a int return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened **rel**=action  
**title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/forceLogRotation **rel**=action  
**title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption operation on all the destinations hosted by the JMS Server.

When the JMS Server is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the appearance of any messages on all the destinations of the JMS Server, that are result of the in-flight work completion on all the destinations hosted by this JMS Server.

### Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)



## POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes**

This resource manages a collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}**

This resource manages a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSSessionPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=JMSServer

This resource's JMSServer singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=connectionConsumers

This resource's connectionConsumers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionCons umers**

This resource manages a collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionCons umers/{name}**

This resource manages a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSConsumerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/connectionConsumers/{name} **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer**

This resource manages a [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JMSServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSServerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/closeCursor rel=action title=closeCursor](#)  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit rel=action title=forceCommit](#)  
This resource's forceCommit action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback rel=action title=forceRollback](#)  
This resource's forceRollback action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition rel=action title=getCursorPosition](#)  
This resource's getCursorPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize rel=action title=getCursorSize](#)  
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition rel=action title=getCursorPosition](#)  
This resource's getCursorPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages rel=action title=getMessages](#)  
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServerRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus rel=action title=getTransactionStatus](#)  
This resource's getTransactionStatus action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/pauseConsumption **rel**=action **title**=pauseConsumption  
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/destinations **rel**=destinations  
This resource's destinations collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/logRuntime **rel**=logRuntime  
This resource's logRuntime singleton resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer **rel**=parent  
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer  
**rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sessionPoolRuntimes **rel**=sessionPoolRuntimes

This resource's sessionPoolRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/close Cursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations**

This resource manages a collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor rel=action title=closeCursor](#)

This resource's closeCursor action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber rel=action title=createDurableSubscriber](#)

This resource's createDurableSubscriber action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages rel=action title=deleteMessages](#)

This resource's deleteMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorEndPosition rel=action title=getCursorEndPosition](#)

This resource's getCursorEndPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorSize rel=action title=getCursorSize](#)

This resource's getCursorSize action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getCursorStartPosition rel=action title=getCursorStartPosition](#)

This resource's getCursorStartPosition action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/getMessages rel=action title=getMessages](#)

This resource's getMessages action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption rel=action title=pauseConsumption](#)

This resource's pauseConsumption action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=durableSubscribers  
This resource's durableSubscribers collection resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/createDurableSubscriber**

The resource supports the following methods:

- [POST](#)

## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers**

This resource manages a collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}**

This resource manages a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition

This resource's getCursorEndPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition

This resource's getCursorStartPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=destinationRuntime

This resource's destinationRuntime singleton resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/deleteMessages**

The resource supports the following methods:

- [POST](#)



## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/durableSubscribers/{name}/destinationRuntime**

This resource manages a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JMSDestinationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor **rel**=action **title**=closeCursor

This resource's closeCursor action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/createDurableSubscriber **rel**=action **title**=createDurableSubscriber

This resource's createDurableSubscriber action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessages **rel**=action **title**=deleteMessages

This resource's deleteMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSize **rel**=action **title**=getCursorSize

This resource's getCursorSize action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorPosition **rel**=action **title**=getCursorPosition

This resource's getCursorPosition action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages **rel**=action **title**=getMessages

This resource's getMessages action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption **rel**=action **title**=pauseConsumption  
This resource's pauseConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion **rel**=action **title**=pauseInsertion  
This resource's pauseInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduction **rel**=action **title**=pauseProduction  
This resource's pauseProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption **rel**=action **title**=resumeConsumption  
This resource's resumeConsumption action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion **rel**=action **title**=resumeInsertion  
This resource's resumeInsertion action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction **rel**=action **title**=resumeProduction  
This resource's resumeProduction action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/durableSubscribers **rel**=durableSubscribers  
This resource's durableSubscribers collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSServer/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/createDurable  
Subscriber**

The resource supports the following methods:

- [POST](#)



## POST

Creates a durable subscriber on the destination with the specified client ID and subscription name. A message selector and no-local flag may also be specified.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**ClientID**

An identifier that uniquely identifies a client connection.

Type: string

**subscriptionName**

The name used to identify this subscription.

Type: string

**selector**

Only messages with properties matching the message selector expression are delivered. A value of null or an empty string indicates that there is no message selector for the message consumer.

Type: string

**noLocal**

If set, inhibits the delivery of messages published by its own connection.

Type: boolean

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/deleteMessag  
es**

The resource supports the following methods:

- [POST](#)

## POST

Deletes the set of messages from the destination that are qualified by the specified JMS message selector.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**selector**

A JMS message selector to identify which messages to delete.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorEnd Position**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSiz  
e**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/getCursorSta  
rtPosition**

The resource supports the following methods:

- [POST](#)



## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/destinationRuntime/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/pauseProduct ion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/destinationRuntime/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/durableSubscribers/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/durableSubscribers/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti nations/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)



## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM  
SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/desti  
nations/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Queries messages on the queue according to the provided message selector and state bitmask and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **selector**

A valid JMS message selector.

**Type:** string

### **timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### **state**

A messaging kernel state bitmask. Refer to the messaging kernel MessageElement interface for a description of the various message states.

**Type:** int

## Response Body

Contains a JSON object with a string return field.

## POST

Queries messages on the queue according to the provided message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector.

**Type:** string

**timeout**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

**Response Body**

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the insertion on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/pauseProduction**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the production on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the insertion operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/resumeProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the production operations on the destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/destinations/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceCommit**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be committed.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/forceRollback**

The resource supports the following methods:

- [POST](#)

## POST

Causes the work associated with the specified transaction branch to be rolled back.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Returns a set of messages that are associated with a JMS transaction branch. Note that the result set is returned to the caller in the form of a message cursor that may contain messages from several destinations on this JMS server.

The timeout parameter specifies the amount of time in seconds for which the cursor is valid. Upon timeout expiration the cursor is invalidated and the associated resources released.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

**Type:** string

**timeoutSeconds**

The last access timeout for the cursor. The cursor resources will be reclaimed if it is not accessed within the specified time interval. A value of 0 indicates no timeout.

**Type:** int

### Response Body

Contains a JSON object with a string return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/getTransactionStatus**

The resource supports the following methods:

- [POST](#)

## POST

Given an Xid this method returns the JTA status of the associated JMS transaction branch.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**xid**

An Xid in string representation for a JMS transaction branch.

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the consumption operation on all the destinations hosted by the JMS Server.

When the JMS Server is paused for consumption, all of its destination's state is marked as "consumption paused" and all the new synchronous receive operations will block until the destination is resumed and there are messages available for consumption. All the synchronous receive with blocking timeout will block until the timeout happens during the consumption paused state.

All the asynchronous consumers attached to that destination will not get any messages delivered to them while the destination in "consumption paused" state.

After a successful consumption "pause" operation, the user has to explicitly "resume" the destination to allow for any further consume operations on that destination

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/pauseInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the appearance of any messages on all the destinations of the JMS Server, that are result of the in-flight work completion on all the destinations hosted by this JMS Server.

### Definition of In-Flight work

The definitions below are based on the current implementation of WebLogic JMS subsystem.

- In-flight messages associated with Producers
  - UN-BORN MESSAGES

Messages that are produced by the producer, with "birth time" (TimeToDeliver) set in future are called un-born messages and are counted as "pending" messages in the destination statistics and are not available for consumers yet.
  - UN-COMMITTED MESSAGES

These are the messages that are produced by the producer as part of the transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. These messages are also counted as "pending" messages in the destination statistics and are not available for consumption.
  - QUOTA BLOCKING SEND

These are the messages that are produced by the producers but are not able reach the destination because of (either message or byte or both) quota limit on the destination and the producers are willing to block for a specific period of time for the quota to be available. These messages are invisible to the system and are not counted against any of the destination statistics.
- In-flight messages associated with Consumers
  - UN-ACKNOWLEDGED (CLIENT ACK PENDING) MESSAGES

These are the messages that are successfully consumed by the clients using a "client acknowledge" session, and are awaiting acknowledgements from the clients. These are "pending messages" which will be removed from the destination/system when the acknowledgement is received.
  - UN-COMMITTED MESSAGES

These are the messages that are consumed (received) by the clients within a transaction (using either user transaction or transacted session) and the transaction is still not committed or rolled back. When the clients successfully commit the transaction the messages get removed from the system.
  - ROLLED BACK MESSAGES

These are the messages that are put back on the destination because of a successful rollback of transactional receive by the consumers. These messages might or might not be ready for consumption (re-delivered) to the clients immediately, depending on the redelivery parameters, RedeliveryDelay and/or RedeliveryDelayOverride and RedeliveryLimit configured on the associated JMSConnectionFactory and JMSDestination respectively.

If there is a redelivery delay configured, then for that "delay" duration, the messages are not available for consumption and are counted as "pending" in

the destination statistics and after the "delay" period, if the redelivery limit is not exceeded, then they are delivered (made available for consumption) on that destination and are counted as "current" messages in the destination statistics. If the redelivery limit exceeds, then those messages will be moved to the ErrorDestination, if one configured.

Another parameter that controls the availability of the rolled back messages is RedeliveryLimit.

- RECOVERED MESSAGES

These messages are similar to ROLLED BACK MESSAGES except that these messages appear on the queue because of an explicit call to session "recover" by the client.

- REDELIVERED MESSAGES

These are again similar to ROLLED BACK MESSAGES except that these messages may re-appear on the destination because of an un-successful delivery attempt to the client (consumer crash, close etc.).

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/paus eProduction**

The resource supports the following methods:

- [POST](#)



## POST

Pauses the new message production on all the destinations hosted by the JMSServer.

When the production paused, it would prevent any new produce operations from both new and existing producers attached to the destinations. When the destination is "resumed from production pause", all the new message production is allowed from both new and existing producers attached to that destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resu meConsumption**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the consumption operation on all the destinations hosted by the JMSServer.

The state of the destinations shall be marked as "consumption enabled" thus allowing all the "consuming" activity to continue normally.

Invoking this API on a JMSServer that is currently not in "consumption paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resu meInsertion**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the in-flight message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "insertion enabled" thus allowing all the messages from in-flight work completion are allowed to appear on the destinations.

Invoking this API on a JMSServer that is currently not in "insertion paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/resu meProduction**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the new message production operation on all the destinations hosted by the JMSServer. The state of the JMSServer shall be marked as "production enabled" thus allowing all the new "producing" activity to continue normally. Invoking this API on a JMSServer that is currently not in "production paused" state has no effect.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JM SRuntime/JMSServers/{name}/sessionPoolRuntimes/{name}/JMSServer/sort**

The resource supports the following methods:

- [POST](#)



## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JMSSRuntime/JMSServers/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the JMS header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor.

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The JMS header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime**

This resource manages a [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.JTAPartitionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#)  
**rel**=nonXAResourceRuntimeMBeans  
This resource's nonXAResourceRuntimeMBeans collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)  
**rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=self  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#)  
**rel**=transactionNameRuntimeMBeans  
This resource's transactionNameRuntimeMBeans collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans](#)  
**rel**=transactionResourceRuntimeMBeans  
This resource's transactionResourceRuntimeMBeans collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.NonXAResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/nonXAResourceRuntimeMBeans/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TransactionNameRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TransactionNameRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionNameRuntimeMBeans/{name}](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans**

This resource manages a collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTA APartitionRuntime/transactionResourceRuntimeMBeans/{name}**

This resource manages a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TransactionResourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/JTAPartitionRuntime/transactionResourceRuntimeMBeans/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes**

This resource manages a collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.LibraryRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.LibraryRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}**

This resource manages a [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LibraryRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LibraryRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel=referencingRuntimes**

This resource's referencingRuntimes collection resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes**

This resource manages a collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/libraryRuntimes/{name}/referencingRuntimes/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes**

This resource manages a collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MailSessionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MailSessionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MailSessionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MailSessionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/mailSessionRuntimes/{name}](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/maxThreadsConstraintRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes**

This resource manages a collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=self**  
This resource.

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}

This resource manages a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MessagingBridgeRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/messagingBridgeRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes**

This resource manages a collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/minThreadsConstraintRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime**

This resource manages a [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionResourceMetricsRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime**

This resource manages a [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PartitionWorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime](#) **rel=fairShareRuntime**  
This resource's fairShareRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel=minThreadsConstraintCapRuntime**  
This resource's minThreadsConstraintCapRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=self**  
This resource.

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime

This resource manages a [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PartitionFairShareRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/fairShareRuntime rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/maxThreadsConstraintRuntime](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime**

This resource manages a [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/partitionWorkManagerRuntime/minThreadsConstraintCapRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PathServiceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PathServiceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies](#) **rel=assemblies**  
This resource's assemblies collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies**

This resource manages a collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}**

This resource manages a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor **rel**=action  
**title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition  
**rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize **rel**=action  
**title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition  
**rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries **rel**=action  
**title**=getMapEntries  
This resource's getMapEntries action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove **rel**=action  
**title**=remove  
This resource's remove action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)



## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries**

The resource supports the following methods:

- [POST](#)

## POST

Returns all entries in a persistent map's assembly.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**timeout**

how many seconds till operatoin times out. Zero is an infinite timeout.

Type: int

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/pathServiceRuntimes/{name}/assemblies/{name}/remove**

The resource supports the following methods:

- [POST](#)

## POST

Remove the path service entry referenced by this object.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

the handle to the cursor

Type: string

**itemHandle**

the handle to a specific item in the cursor

Type: int

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes**

This resource manages a collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=connections**  
This resource's connections collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/persistentStoreRuntimes/{name}/connections/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes**

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/requestClassRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime**

This resource manages a [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ResourceManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=resourceRuntimes**  
This resource's resourceRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes**

This resource manages a collection of [weblogic.management.runtime.ResourceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ResourceRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.ResourceRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.ResourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ResourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ResourceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime](#) **rel=fairShareConstraintRuntime**

This resource's fairShareConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#) **rel=triggerRuntimes**

This resource's triggerRuntimes collection resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntime**

This resource manages a [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.FairShareConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntimeMBean **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/fairShareConstraintRuntimeMBean **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes**

This resource manages a collection of [weblogic.management.runtime.TriggerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TriggerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TriggerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.TriggerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TriggerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TriggerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}  
**rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes  
**rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resourceManagerRuntime/resourceRuntimes/{name}/triggerRuntimes/{name}  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resume**

The resource supports the following methods:

- [POST](#)



## POST

Resume a suspended partition. Allow new requests. This operation transitions the partition into `RUNNING` state.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/resumeResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

Resume suspended resource group. Allow new requests. This operation transitions the resource group into `RUNNING` state.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime**

This resource manages a [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.SAFRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents rel=agents](#)  
This resource's agents collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents**

This resource manages a collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}**

This resource manages a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding](#) **rel=action**  
**title=pauseForwarding**  
This resource's pauseForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming](#) **rel=action** **title=pauseIncoming**  
This resource's pauseIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving](#) **rel=action** **title=pauseReceiving**  
This resource's pauseReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding](#) **rel=action**  
**title=resumeForwarding**  
This resource's resumeForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming](#) **rel=action** **title=resumeIncoming**  
This resource's resumeIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving](#) **rel=action** **title=resumeReceiving**  
This resource's resumeReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel=conversations**  
This resource's conversations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime](#) **rel=logRuntime**  
This resource's logRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents](#) **rel=parent**  
The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=remoteEndpoints

This resource's remoteEndpoints collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations**

This resource manages a collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}**

This resource manages a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy](#) **rel**=action  
**title**=destroy

This resource's destroy action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/conversations/{name}/destroy**

The resource supports the following methods:

- [POST](#)

## POST

Destroys the conversation and purges all the messages.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseForwarding**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the sending agent on forwarding messages so that the agent will not forward messages but will accept new messages.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseIncoming**

The resource supports the following methods:

- [POST](#)

## **POST**

Pauses the sending agent on accepting new messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/pauseReceiving**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the receiving agent on receiving messages.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints**

This resource manages a collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}**

This resource manages a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor **rel**=action **title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll **rel**=action **title**=expireAll  
This resource's expireAll action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize **rel**=action **title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages **rel**=action **title**=getMessages  
This resource's getMessages action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding **rel**=action **title**=pauseForwarding  
This resource's pauseForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming **rel**=action **title**=pauseIncoming  
This resource's pauseIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge **rel**=action **title**=purge  
This resource's purge action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding **rel**=action **title**=resumeForwarding  
This resource's resumeForwarding action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming **rel**=action **title**=resumeIncoming  
This resource's resumeIncoming action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort **rel**=action **title**=sort  
This resource's sort action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll**

The resource supports the following methods:

- [POST](#)

## POST

All pending messages for a remote destination are processed according to the policy specified by the associated Error Handling configuration and then removed.

- When selected, `expireAll` is performed asynchronously by the server.
- Oracle recommends that the remote endpoint is paused for incoming messages prior to expiring messages. When all pending messages are processed and removed, the remote endpoint can be set to resume and accept new messages.
- The state of the `expireAll` operation can be determined by the `getOperationState` method.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)



## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Queries messages on the queue according to the message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. If the cursor expires, the associated resources are released.

### Roles

Admin, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector or SAF message selector.

**Type:** string

**timeout**

Specifies the amount of time the message cursor is valid. A value of 0 indicates the cursor does not expire.

**Type:** int

### Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding**

The resource supports the following methods:

- [POST](#)



## POST

Pauses the forwarding of messages for a remote endpoint. The agent accepts new messages but does not forward them.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}

## **POST**

Pauses a remote endpoint so that new messages are not accepted.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge**

The resource supports the following methods:

- [POST](#)

## POST

Destroys all conversations and purges all the pending messages for a remote destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding**

The resource supports the following methods:

- [POST](#)

/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}

## **POST**

Resumes the forwarding of messages for the remote endpoint.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SA FRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming**

The resource supports the following methods:

- [POST](#)



/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}

## **POST**

Resumes a remote endpoint so that new messages are accepted.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the SAF header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor on which to perform the sort operation

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The SAF header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeForwarding**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the sending agent for forwarding messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeIncoming**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the sending agent for accepting new messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/SAFRuntime/agents/{name}/resumeReceiving**

The resource supports the following methods:

- [POST](#)



## **POST**

Resumes the receiving agent for receiving messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdown**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

Gracefully shuts down the partition after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the partition is completing inflight work. For example, a `forceShutdown` command can be issued to quickly shutdown the partition if graceful shutdown is taking too long to complete.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **timeout**

Number of seconds to wait before aborting inflight work and shutting down the partition.

**Type:** int

### **ignoreSessions**

`true` indicates ignore pending HTTP sessions during inflight work handling.

**Type:** boolean

### **waitForAllSessions**

`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

**Type:** boolean

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the partition after handling inflight work.

POST

---

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**timeout**

timeout

Type: int

**ignoreSessions**

ignoreSessions

Type: boolean

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/shutdownResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

Gracefully shuts down the resource group after handling inflight work.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
resourceGroupName

Type: string

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the partition after handling inflight work. Optionally, ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown takes a long time.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
resourceGroupName

**Type:** string

**timeout**

Number of seconds to wait before aborting inflight work and shutting down the partition.

**Type:** int

**ignoreSessions**

true indicates ignore pending HTTP sessions during inflight work handling.

**Type:** boolean

**waitForAllSessions**

true indicates waiting for all HTTP sessions during inflight work handling; false indicates waiting for non-persisted HTTP sessions only.

**Type:** boolean

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the partition after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

**Type:** string

**timeout**

timeout

**Type:** int

**ignoreSessions**

ignoreSessions

**Type:** boolean

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroup**

The resource supports the following methods:

- [POST](#)



## POST

starts the resource group.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
The resource group name  
Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/startResourceGroupInAdmin**

The resource supports the following methods:

- [POST](#)

## POST

Starts the resource group in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. Non-admin users are denied access to applications and resources

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspend**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends the partition. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## POST

Transitions the partition from `RUNNING` to `ADMIN` state gracefully.

Applications are in admin mode. Inflight work is completed. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **timeout**

Seconds to wait for partition to transition gracefully. The `forceSuspend()` is called after timeout.

**Type:** int

### **ignoreSessions**

drop inflight HTTP sessions during graceful suspend

**Type:** boolean

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/suspendResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

**timeout**

timeout

Type: int

**ignoreSessions**

ignoreSessions

Type: boolean

## Response Body

Contains an empty JSON object.

## POST

Suspends resource group. Denies new requests except by privileged users. Allows pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. Non-admin users are denied access to applications and resources

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

POST

---

Type: string

### **Response Body**

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime**

This resource manages a [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFPartitionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#)  
**rel**=WLDFPartitionAccessRuntime  
This resource's WLDFPartitionAccessRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime](#)  
**rel**=WLDFPartitionHarvesterRuntime  
This resource's WLDFPartitionHarvesterRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime](#)  
**rel**=WLDFPartitionImageRuntime  
This resource's WLDFPartitionImageRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#)  
**rel**=WLDFWatchNotificationRuntime  
This resource's WLDFWatchNotificationRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#)  
**rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime**

This resource manages a [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=WLDFDataAccessRuntimes

This resource's WLDFDataAccessRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime](#) **rel**=action **title**=lookupWLDFDataAccessRuntime

This resource's lookupWLDFDataAccessRuntime action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes](#) **rel**=dataAccessRuntimes

This resource's dataAccessRuntimes collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes**

This resource manages a collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes](#)  
**rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}**

This resource manages a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor](#) **rel=action** **title=closeCursor**  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords](#) **rel=action** **title=deleteDataRecords**  
This resource's deleteDataRecords action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount](#) **rel=action** **title=getDataRecordCount**  
This resource's getDataRecordCount action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData](#) **rel=action** **title=hasMoreData**  
This resource's hasMoreData action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor](#) **rel=action** **title=openCursor**  
This resource's openCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}](#) **rel=self**  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Disposes of the cursor once the client has fetched all the records.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorName**

cursorName

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords**

The resource supports the following methods:

- [POST](#)

## POST

Delete records within the specified time range that match the specified query. If the query is null or empty, all records within the time range will be deleted.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Not all archives support a deletion feature. If not supported, this method will throw an `UnsupportedOperationException` exception.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**startTime**

Start time of the interval (inclusive)

Type: long

**endTime**

End time of the interval (exclusive)

Type: long

**queryString**

Query criterion

Type: string

### Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

The number of records that match the specified query and time range.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**startTime**

Start time of the interval (inclusive)

Type: long

**endTime**

End time of the interval (exclusive)

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a int return field.

## POST

The number of records that match the specified query.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**query**

Query expression

Type: string

## Response Body

Contains a JSON object with a int return field.

## POST

The number that match the specified query and record-ID range, and whose timestamp (if it is available) is earlier than the specified end time.

The end time is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**startRecordId**

Record id of the first record

Type: long

**endRecordId**

Look at records whose record-ids are smaller than specified endrecordId

Type: long

**endTime**

Look at records which were entered prior to endTime

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a int return field.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/hasMoreData**

The resource supports the following methods:

- [POST](#)



## POST

Determines whether the specified cursor has more data to be fetched.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorName**

cursorName

Type: string

### Response Body

Contains a JSON object with a boolean return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/dataAccessRuntimes/{name}/openCursor**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Opens a cursor with the specified timeout value, in milliseconds.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

### **query**

The query expression to filter the result set from the underlying diagnostic log.

Type: string

### **cursorTimeout**

The timeout interval after which the cursor will become invalid if not invoked.

Type: long

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor for records that meet the specified time range and query condition. The timeout value for the cursor is also specified.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

### **beginTimestamp**

beginTimestamp

Type: long

**endTimestamp**

endTimestamp

Type: long

**query**

query

Type: string

**cursorTimeout**

cursorTimeout

Type: long

**Response Body**

Contains a JSON object with a string return field.

**POST**

Opens a cursor on the server side for the query.

**Roles**

Admin, Deployer, Monitor, Operator

**Request Body**

Must contain a JSON object with the following fields:

**query**

The query expression to filter the result set from the underlying diagnostic log.

Type: string

**Response Body**

Contains a JSON object with a string return field.

**POST**

Opens a cursor with the specified query and time range.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

**Roles**

Admin, Deployer, Monitor, Operator

**Request Body**

Must contain a JSON object with the following fields:

**beginTimestamp**

beginTimestamp

Type: long

**endTimestamp**

endTimestamp

Type: long

**query**

query

Type: string

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor using the specified record-ID range, end timestamp, and query. The timeout value for the cursor is also specified.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**beginRecordId**

Record id of the first record (inclusive) in the result set

Type: long

**endRecordId**

Record id of the last record (exclusive) in the result set

Type: long

**endTimestamp**

Include only those records whose timestamp is earlier than this value

Type: long

**query**

Query criterion

Type: string

**cursorTimeout**

cursorTimeout

Type: long

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor with a given query and a record-id range.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**beginRecordId**

Record id of the first record (inclusive) in the result set

Type: long

**endRecordId**

Record id of the last record (exclusive) in the result set

Type: long

**endTimestamp**

Include only those records whose timestamp is earlier than this value

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a string return field.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/lookupWLDFDataAccessRuntime**

The resource supports the following methods:

- [POST](#)

## POST

An instance of a `WLDFDataAccessMBean` defined by its logical name. The name is constructed from the specific type of log data requested.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**logicalName**

logicalName

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDataAccessRuntimeMBean` reference return field.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntime**

This resource manages a collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimees/{name}**

This resource manages a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive](#) **rel**=action **title**=closeArchive

This resource's closeArchive action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive**

The resource supports the following methods:

- [POST](#)

POST

---

## **POST**

### **Roles**

Admin, Deployer, Monitor, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime**

This resource manages a [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionHarvesterRuntime](#) **rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime**

This resource manages a [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFPartitionImageRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage rel=action title=captureImage](#)  
This resource's captureImage action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks rel=action title=clearCompletedImageCaptureTasks](#)  
This resource's clearCompletedImageCaptureTasks action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages rel=action title=purgeCapturedImages](#)  
This resource's purgeCapturedImages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout rel=action title=resetImageLockout](#)  
This resource's resetImageLockout action resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks rel=imageCaptureTasks](#)  
This resource's imageCaptureTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/captureImage**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the configured lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

## POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**lockoutMinutes**

number of minutes before the next image capture request will be accepted

Type: int

## Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/clearCompletedImageCaptureTasks**

The resource supports the following methods:

- [POST](#)

POST

---

## POST

Removes all completed image capture tasks.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks**

This resource manages a collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks](#)  
**rel**=self

This resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}**  
**}**

This resource manages a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel](#) **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks](#) **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=subTasks

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel](#) **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=self

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=subTasks

This resource's subTasks collection resource.



---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFFPartitionRuntime/WLDFFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel**=self

This resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel](#) **rel=action** **title=cancel**

This resource's cancel action resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel=parent**

The parent resource of this resource.

- **rel=parentTask**

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks](#) **rel=subTasks**

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

### Roles

Admin

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/purgeCapturedImages**

The resource supports the following methods:

- [POST](#)

## POST

Delete captured images specified by the age criteria.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**age**

Purge diagnostic images older than specified age specified in the format Days:Hours:Minutes. If empty or null all existing image files on disk are purged. The hours and minutes components are optional.

**Type:** string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFPartitionImageRuntime/resetImageLockout**

The resource supports the following methods:

- [POST](#)

POST

---

## POST

Reset the lockout period, thus allowing image capture requests to be accepted.

### Roles

Admin

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime**

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel**=WLDFWatchJMXNotificationSource

This resource's WLDFWatchJMXNotificationSource singleton resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm](#) **rel**=action **title**=resetWatchAlarm

This resource's resetWatchAlarm action resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm**

The resource supports the following methods:

- [POST](#)

## POST

Resets a policy alarm.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**watchName**

the name of the policy to reset

Type: string

### Response Body

Contains an empty JSON object.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource**

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/WLDFPartitionRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource **rel**=self

This resource.

## /management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**

This resource's capacityRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**

This resource's maxThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**

This resource's minThreadsConstraintRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**

This resource's requestClassRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self

This resource.



---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/workManagerRuntimes/{name}/requestClassRuntime](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime**

This resource manages a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel=clusterRouting**  
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}](#) **el=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel=self**  
This resource.



## **/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting**

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/partitionRuntimes/{name}/wseeClusterFrontEndRuntime/clusterRouting](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes**

This resource manages a collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PathServiceRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.PathServiceRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PathServiceRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.PathServiceRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel**=assemblies  
This resource's assemblies collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies**

This resource manages a collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies](#) **rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}**

This resource manages a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.PSAssemblyRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor **rel**=action **title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorEndPosition **rel**=action **title**=getCursorEndPosition  
This resource's getCursorEndPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize **rel**=action **title**=getCursorSize  
This resource's getCursorSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition **rel**=action **title**=getCursorStartPosition  
This resource's getCursorStartPosition action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries **rel**=action **title**=getMapEntries  
This resource's getMapEntries action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove **rel**=action **title**=remove  
This resource's remove action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/getMapEntries**

The resource supports the following methods:

- [POST](#)

## POST

Returns all entries in a persistent map's assembly.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**timeout**

how many seconds till operatoin times out. Zero is an infinite timeout.

Type: int

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/pathServiceRuntimes/{name}/assemblies/{name}/remove**

The resource supports the following methods:

- [POST](#)

## POST

Remove the path service entry referenced by this object.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

the handle to the cursor

Type: string

**itemHandle**

the handle to a specific item in the cursor

Type: int

### Response Body

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/persistentStoreRuntimes

This resource manages a collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#)  
**rel**=self  
This resource.



## **/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}**

This resource manages a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.PersistentStoreRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel**=connections

This resource's connections collection resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections**

This resource manages a collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}**

This resource manages a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/persistentStoreRuntimes/{name}/connections/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/requestClassRuntimes**

This resource manages a collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RequestClassRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RequestClassRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#)  
**rel**=self

This resource.



## /management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/requestClassRuntimes/{name}](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/restartSSLChannels**

The resource supports the following methods:

- [POST](#)

## POST

Restart all SSL channels on which the server is listening. This could be necessary because of some change that the server is not aware of, for instance updates to the keystore.

### Roles

Admin

### Response Body

Contains an empty JSON object.

### Example

#### **Example 1 Invoke the restartSSLChannels Action**

This example uses the POST method to invoke the restartSSLChannels action.

#### Example Request

```
curl -v \  
--user admin:admin123 \  
-H X-Requested-By:MyClient \  
-H Accept:application/json \  
-H Content-Type:application/json \  
-d "{}" \  
-X POST  
http://localhost:7001/management/weblogic/latest/serverRuntime/restartSSLChannels
```

#### Example Response

```
HTTP/1.1 200 OK
```

```
Response Body:  
{}
```

## **/management/weblogic/{version}/serverRuntime/resume**

The resource supports the following methods:

- [POST](#)

## POST

Resume suspended server. Allow new requests. This operation transitions the server into `RUNNING` state.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/resumeResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

Resume suspended resource group. Allow new requests. This operation transitions the resource group into `RUNNING` state.

### Roles

Admin, Operator

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/SAFRuntime**

This resource manages a [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SAFRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)  
**rel**=agents  
This resource's agents collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#) **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/SAFRuntime/agents

This resource manages a collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/SAFRuntime/agents](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}**

This resource manages a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFAgentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SAFAgentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseForwarding rel=action title=pauseForwarding](#)  
This resource's pauseForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseIncoming rel=action title=pauseIncoming](#)  
This resource's pauseIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/pauseReceiving rel=action title=pauseReceiving](#)  
This resource's pauseReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeForwarding rel=action title=resumeForwarding](#)  
This resource's resumeForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeIncoming rel=action title=resumeIncoming](#)  
This resource's resumeIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeReceiving rel=action title=resumeReceiving](#)  
This resource's resumeReceiving action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations rel=conversations](#)  
This resource's conversations collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime rel=logRuntime](#)  
This resource's logRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints rel=remoteEndpoints](#)

This resource's remoteEndpoints collection resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}  
**rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations**

This resource manages a collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}**

This resource manages a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFConversationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.SAFConversationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy](#) **rel**=action **title**=destroy  
This resource's destroy action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}](#) **rel**=canonical  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations](#) **rel**=parent  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/conversations/{name}/destroy**

The resource supports the following methods:

- [POST](#)

## **POST**

Destroys the conversation and purges all the messages.

### **Roles**

Admin

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime**

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)



## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseForwarding**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the sending agent on forwarding messages so that the agent will not forward messages but will accept new messages.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseIncoming**

The resource supports the following methods:

- [POST](#)



## **POST**

Pauses the sending agent on accepting new messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/ pauseReceiving**

The resource supports the following methods:

- [POST](#)

## **POST**

Pauses the receiving agent on receiving messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints**

This resource manages a collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}**

This resource manages a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor](#) **rel=action** **title=closeCursor**  
This resource's closeCursor action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll](#) **rel=action** **title=expireAll**  
This resource's expireAll action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorEndPosition](#) **rel=action** **title=getCursorEndPosition**  
This resource's getCursorEndPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize](#) **rel=action** **title=getCursorSize**  
This resource's getCursorSize action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition](#) **rel=action** **title=getCursorStartPosition**  
This resource's getCursorStartPosition action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages](#) **rel=action** **title=getMessages**  
This resource's getMessages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding](#) **rel=action** **title=pauseForwarding**  
This resource's pauseForwarding action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming](#) **rel=action** **title=pauseIncoming**  
This resource's pauseIncoming action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge](#) **rel=action** **title=purge**  
This resource's purge action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding](#) **rel=action** **title=resumeForwarding**

This resource's resumeForwarding action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming **rel**=action **title**=resumeIncoming

This resource's resumeIncoming action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort **rel**=action **title**=sort

This resource's sort action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name} **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Releases the server-side resources associated with the cursor and removes the runtime MBean instance.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/expireAll**

The resource supports the following methods:

- [POST](#)

## POST

All pending messages for a remote destination are processed according to the policy specified by the associated Error Handling configuration and then removed.

- When selected, `expireAll` is performed asynchronously by the server.
- Oracle recommends that the remote endpoint is paused for incoming messages prior to expiring messages. When all pending messages are processed and removed, the remote endpoint can be set to resume and accept new messages.
- The state of the `expireAll` operation can be determined by the `getOperationState` method.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor end position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorSize**

The resource supports the following methods:

- [POST](#)

## POST

Returns the number of items in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.



## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getCursorStartPosition**

The resource supports the following methods:

- [POST](#)

## POST

Returns the cursor start position in the result set.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The cursor handle.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/getMessages**

The resource supports the following methods:

- [POST](#)

## POST

Queries messages on the queue according to the message selector and returns a message cursor representing the result set. The timeout parameter specifies the amount of time in seconds for which the cursor is valid. If the cursor expires, the associated resources are released.

### Roles

Admin, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**selector**

A valid JMS message selector or SAF message selector.

**Type:** string

**timeout**

Specifies the amount of time the message cursor is valid. A value of 0 indicates the cursor does not expire.

**Type:** int

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseForwarding**

The resource supports the following methods:

- [POST](#)

## POST

Pauses the forwarding of messages for a remote endpoint. The agent accepts new messages but does not forward them.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/pauseIncoming**

The resource supports the following methods:

- [POST](#)

## POST

Pauses a remote endpoint so that new messages are not accepted.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/purge**

The resource supports the following methods:

- [POST](#)

## POST

Destroys all conversations and purges all the pending messages for a remote destination.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeForwarding**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the forwarding of messages for the remote endpoint.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/resumeIncoming**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes a remote endpoint so that new messages are accepted.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/remoteEndpoints/{name}/sort**

The resource supports the following methods:

- [POST](#)

## POST

Sorts the entire message result set managed by the cursor according to the SAF header attributes specified. The cursor position is set to the new position of the message corresponding to the "start" location before the sort is performed. The method returns the new cursor position.

### Roles

Admin, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorHandle**

The handle of the cursor on which to perform the sort operation

**Type:** string

**start**

The location of the message before the sort that will be the first message returned after the sort. A value of -1 will place the cursor start position at the head of the new sort order.

**Type:** long

**fields**

The SAF header attributes on which to sort.

**Type:** array of string

**ascending**

Determines whether the sort of the corresponding fields element is in ascending or descending order.

**Type:** array of boolean

### Response Body

Contains a JSON object with a long return field.



## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeForwarding**

The resource supports the following methods:

- [POST](#)

## POST

Resumes the sending agent for forwarding messages.

### Roles

Admin, Operator

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeIncoming**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the sending agent for accepting new messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/SAFRuntime/agents/{name}/resumeReceiving**

The resource supports the following methods:

- [POST](#)

## **POST**

Resumes the receiving agent for receiving messages.

### **Roles**

Admin, Operator

### **Response Body**

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/search

The resource supports the following methods:

- [POST](#)

## **POST**

Search the serverRuntime tree.

### **Request Body**

The search request body includes the search criteria.

### **Response Body**

The search response includes the results of the search.



## **/management/weblogic/{version}/serverRuntime/serverChannelRuntimes**

This resource manages a collection of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.ServerChannelRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}

This resource manages a [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ServerChannelRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ServerChannelRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverChannelRuntimes/{name}](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/serverLogRuntime**

This resource manages a [weblogic.management.runtime.ServerLogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ServerLogRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ServerLogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpened](#) **rel**=action **title**=ensureLogOpened  
This resource's ensureLogOpened action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog](#) **rel**=action **title**=flushLog  
This resource's flushLog action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation](#) **rel**=action **title**=forceLogRotation  
This resource's forceLogRotation action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverLogRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverLogRuntime](#) **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/serverLogRuntime/ensureLogOpened

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/serverLogRuntime/flushLog**

The resource supports the following methods:

- [POST](#)

## POST

Flushes the buffer to the log file on disk.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/serverLogRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## POST

Forces the rotation of the underlying log immediately.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime**

This resource manages a [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.ServerSecurityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole](#) **rel**=action **title**=checkRole  
This resource's checkRole action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel**=defaultRealmRuntime  
This resource's defaultRealmRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes](#) **rel**=realmRuntimes  
This resource's realmRuntimes collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/checkRole**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Checks whether current Subject has the specified role.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **roleName**

Name of the role to check if the Subject has the specified role.

**Type:** string

## Response Body

Contains a JSON object with a boolean return field.

## POST

Checks whether current Subject has any of the required roles.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **roleNames**

Names of the roles to check if the Subject has one of the specified roles.

**Type:** array of string

## Response Body

Contains a JSON object with a boolean return field.



## /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime

This resource manages a [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RealmRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel=authenticatorRuntimes**  
This resource's authenticatorRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime](#) **rel=userLockoutManagerRuntime**  
This resource's userLockoutManagerRuntime singleton resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes**

This resource manages a collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name}**

This resource manages a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name}](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/authenticatorRuntimes/{name}](#) **rel**=self

This resource.

## /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime

This resource manages a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/clearLockout **rel**=action  
**title**=clearLockout  
This resource's clearLockout action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLastLoginFailure **rel**=action  
**title**=getLastLoginFailure  
This resource's getLastLoginFailure action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLoginFailureCount **rel**=action **title**=getLoginFailureCount  
This resource's getLoginFailureCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/isLockedOut **rel**=action  
**title**=isLockedOut  
This resource's isLockedOut action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime **rel**=self  
This resource.



---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/clearLockout**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Unlocks a user account.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains an empty JSON object.

## POST

Unlocks a user account.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLastLoginFailure**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns a string that indicates the time of the last invalid login for this user.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns a string that indicates the time of the last invalid login for this user.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/getLoginFailureCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the current count of login failures for a specific user. This value returns to

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the current count of login failures for a specific user. This value returns to

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/defaultRealmRuntime/userLockoutManagerRuntime/isLockedOut**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Indicates whether a user is locked out.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

Type: string

**identityDomain**

- The identity domain of the user. May be null.

Type: string

## Response Body

Contains a JSON object with a boolean return field.

## POST

Indicates whether a user is locked out.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

Type: string

## Response Body

Contains a JSON object with a boolean return field.



## /management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime

This resource manages a collection of [weblogic.management.runtime.RealmRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.RealmRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.RealmRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}**

This resource manages a [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.RealmRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.RealmRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntimes](#) **rel**=authenticatorRuntimes  
This resource's authenticatorRuntimes collection resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime](#) **rel**=userLockoutManagerRuntime  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/userLockoutManagerRuntime](#) **rel**=userLockoutManagerRuntime  
This resource's userLockoutManagerRuntime singleton resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/authenticatorRuntimes**

This resource manages a collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instances.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a list of [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntimes](#) **rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntime/{name}/authenticatorRuntimes](#) **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/authenticatorRuntimes/{name}**

This resource manages a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.AuthenticatorRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/authenticatorRuntimes/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/authenticatorRuntimes **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/authenticatorRuntimes/{name} **rel**=self

This resource.



## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realms/{name}/userLockoutManagerRuntime**

This resource manages a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.UserLockoutManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime/clearLockout **rel**=action **title**=clearLockout  
This resource's clearLockout action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure **rel**=action **title**=getLastLoginFailure  
This resource's getLastLoginFailure action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount **rel**=action **title**=getLoginFailureCount  
This resource's getLoginFailureCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime/isLockedOut **rel**=action **title**=isLockedOut  
This resource's isLockedOut action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realMRuntimes/{name}/userLockoutManagerRuntime **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/clearLockout**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Unlocks a user account.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains an empty JSON object.

## POST

Unlocks a user account.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLastLoginFailure**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns a string that indicates the time of the last invalid login for this user.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns a string that indicates the time of the last invalid login for this user.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/getLoginFailureCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the current count of login failures for a specific user. This value returns to

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the current count of login failures for a specific user. This value returns to

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

**Type:** string

**identityDomain**

- The identity domain of the user. May be null.

**Type:** string

## Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/serverSecurityRuntime/realmRuntimes/{name}/userLockoutManagerRuntime/isLockedOut**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Indicates whether a user is locked out.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

Type: string

**identityDomain**

- The identity domain of the user. May be null.

Type: string

## Response Body

Contains a JSON object with a boolean return field.

## POST

Indicates whether a user is locked out.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**userName**

- A user name. If the user does not exist, this method returns *false*.

Type: string

## Response Body

Contains a JSON object with a boolean return field.

## /management/weblogic/{version}/serverRuntime/shutdown

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

Gracefully shuts down the server after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a `forceShutdown` command can be issued to quickly shutdown the server if graceful shutdown takes a long time.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

### **timeout**

Number of seconds to wait before aborting inflight work and shutting down the server.

**Type:** int

### **ignoreSessions**

`true` indicates ignore pending HTTP sessions during inflight work handling.

**Type:** boolean

### **waitForAllSessions**

`true` indicates waiting for all HTTP sessions during inflight work handling; `false` indicates waiting for non-persisted HTTP sessions only.

**Type:** boolean

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the server after handling inflight work.

## Roles

Admin, Operator

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the server after handling inflight work.

This method is the same as calling: `shutdown(timeout, ignoreSessions, false);`

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**timeout**

timeout

Type: int

**ignoreSessions**

ignoreSessions

Type: boolean

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/shutdownResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

Gracefully shuts down the resource group after handling inflight work.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
resourceGroupName

Type: string

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the resource group after handling inflight work; optionally ignores pending HTTP sessions while handling inflight work.

The following inflight work is allowed to complete before shutdown:

- Pending transaction's and TLOG checkpoint
- Pending HTTP sessions
- Pending JMS work
- Pending work in the execute queues
- RMI requests with transaction context

Further administrative calls are accepted while the server is completing inflight work. For example a forceShutdown command can be issued to quickly shutdown the partition if graceful shutdown takes a long time.

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**  
resourceGroupName

**Type:** string

**timeout**

Number of seconds to wait before aborting inflight work and shutting down the partition.

**Type:** int

**ignoreSessions**

true indicates ignore pending HTTP sessions during inflight work handling.

**Type:** boolean

**waitForAllSessions**

true indicates waiting for all HTTP sessions during inflight work handling; false indicates waiting for non-persisted HTTP sessions only.

**Type:** boolean

## Response Body

Contains an empty JSON object.

## POST

Gracefully shuts down the resource group after handling inflight work.

This method is same to call: `shutdown(timeout, ignoreSessions, false);`

## Roles

Admin, Operator

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

**Type:** string

**timeout**

timeout

**Type:** int

**ignoreSessions**

ignoreSessions

**Type:** boolean

## Response Body

Contains an empty JSON object.



## /management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime

This resource manages a [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SingleSignOnServicesRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish](#) **rel**=action **title**=publish  
This resource's publish action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/singleSignOnServicesRuntime/publish**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Publishes SAML 2.0 meta-data for Web Browser SSO Profile

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**fileName**

Name of file to create; will silently overwrite existing file, if present

**Type:** string

## Response Body

Contains an empty JSON object.

## POST

Publishes SAML 2.0 meta-data for Web Browser SSO Profile

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**fileName**

Name of file to create

**Type:** string

**prohibitOverwrite**

If true, prohibits overwrite if the file already exists

**Type:** boolean

## Response Body

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/SNMPAgentRuntime

This resource manages a [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) instance.

### Roles

Admin, Deployer, Monitor, Operator

### Response Body

Contains a [weblogic.management.runtime.SNMPAgentRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache](#) **rel=action** **title=invalidateLocalizedKeyCache**  
This resource's invalidateLocalizedKeyCache action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule](#) **rel=action** **title=outputCustomMBeansMIBModule**  
This resource's outputCustomMBeansMIBModule action resource.
- [uri=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/invalidateLocalizedKeyCache**

The resource supports the following methods:

- [POST](#)

## POST

Immediately invalidates the cached security keys for the specified WebLogic Server user.

An SNMP security key is an encrypted version of an SNMP agent's engine ID and an authentication password or privacy password. WebLogic Server generates one security key for each entry that you create in the SNMP credential map. When a WebLogic Server SNMP agent receives an SNMPv3 request, it compares the key that is in the request with its WebLogic Server keys. If it finds a match, it processes the request. The SNMP agent also encodes these keys in its responses and notifications. (You configure which keys are encoded when you create a trap destination.)

Instead of regenerating the keys for each SNMPv3 communication, WebLogic Server caches the keys. To make sure that the cache contains the latest set of SNMP credentials, WebLogic Server periodically invalidates the cache. After the cache is invalidated, the next time an SNMP agent requests credentials, WebLogic Server regenerates the cache.

Note that making a change to the credential map does not automatically update the cache. Instead, the cache is updated only after it has been invalidated.

Instead of waiting for WebLogic Server to invalidate the cached entry for a key, you can invalidate it immediately.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**username**

Name of the user

Type: string

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/SNMPAgentRuntime/outputCustomMBeansMIBModule**

The resource supports the following methods:

- [POST](#)

## POST

Returns WebLogic Server's MIB module for custom MBeans as a `java.lang.String`. You can save the `String` to a file and then load the file into a MIB browser.

When you register custom MBeans in the WebLogic Server Runtime MBean Server, WebLogic Server adds entries to a runtime MIB module that it maintains for custom MBeans. For each custom MBean type, WebLogic Server adds a table to the MIB module. For each instance of the custom MBean, it adds a table row. While WebLogic Server does not persist the MIB module as a file or other data structure, the OIDs in the module remain constant across server sessions.

### Roles

Admin

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/startPartition**

---

The resource supports the following methods:

- [POST](#)

## POST

starts the partition.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**partitionName**

The resource group name

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/startPartitionInAdmin**

The resource supports the following methods:

- [POST](#)

## POST

starts the Partition in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**partitionName**

partitionName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/startResourceGroup**

The resource supports the following methods:

- [POST](#)

## POST

starts the resource group.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

The resource group name

Type: string

### Response Body

Contains an empty JSON object.



## **/management/weblogic/{version}/serverRuntime/startResourceGroupInAdmin**

The resource supports the following methods:

- [POST](#)

## POST

starts the resource group in ADMIN state. Applications and resources are fully available to administrators in ADMIN state. But non-admin users are denied access to applications and resources

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/suspend**

---

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspend server. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the server into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

## Roles

Admin

## Response Body

Contains an empty JSON object.

## POST

Transitions the server from `RUNNING` to `ADMIN` state gracefully.

Applications are in admin mode. Inflight work is completed. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **timeout**

Seconds to wait for server to transition gracefully. The server calls `forceSuspend()` after timeout.

**Type:** int

### **ignoreSessions**

drop inflight HTTP sessions during graceful suspend

**Type:** boolean

## Response Body

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/suspendResourceGroup

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Suspend resource group. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

**timeout**

timeout

Type: int

**ignoreSessions**

ignoreSessions

Type: boolean

## Response Body

Contains an empty JSON object.

## POST

Suspend resource group. Deny new requests (except by privileged users). Allow pending requests to complete. This operation transitions the partition into `ADMIN` state. Applications and resources are fully available to administrators in `ADMIN` state. But non-admin users are denied access to applications and resources

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**resourceGroupName**

resourceGroupName

Type: string

### **Response Body**

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/threadPoolRuntime

This resource manages a [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.ThreadPoolRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/threadPoolRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/threadPoolRuntime](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/timerRuntime**

This resource manages a [weblogic.management.runtime.TimerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TimerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TimerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/timerRuntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/timerRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WANReplicationRuntime**

This resource manages a [weblogic.management.runtime.WANReplicationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WANReplicationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WANReplicationRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase **rel**=action  
**title**=cleanupExpiredSessionsInTheDatabase  
This resource's cleanupExpiredSessionsInTheDatabase action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WANReplicationRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WANReplicationRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WANReplicationRuntime/cleanupExpiredSessionsInTheDatabase**

The resource supports the following methods:

- [POST](#)

## POST

Clean up expired sessions in the database

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/webServerRuntimes

This resource manages a collection of [weblogic.management.runtime.WebServerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WebServerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WebServerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)  
**rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WebServerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WebServerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WebServerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime](#) **rel**=logRuntime  
This resource's logRuntime singleton resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes](#)  
**rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime

This resource manages a [weblogic.management.runtime.LogRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.LogRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.LogRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened **rel**=action **title**=ensureLogOpened

This resource's ensureLogOpened action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog **rel**=action **title**=flushLog

This resource's flushLog action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation **rel**=action **title**=forceLogRotation

This resource's forceLogRotation action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime **rel**=self

This resource.

## **/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/ensureLogOpened**

The resource supports the following methods:

- [POST](#)

## POST

Ensures that that the output stream to the underlying is opened if it got closed previously due to errors.

### Roles

Admin

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/flushLog**

The resource supports the following methods:

- [POST](#)



## POST

Flushes the buffer to the log file on disk.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/webServerRuntimes/{name}/logRuntime/forceLogRotation**

The resource supports the following methods:

- [POST](#)

## **POST**

Forces the rotation of the underlying log immediately.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime

This resource manages a [weblogic.management.runtime.WLDFRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=WLDFAccessRuntime  
This resource's WLDFAccessRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) **rel**=WLDFArchiveRuntimes  
This resource's WLDFArchiveRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime](#) **rel**=WLDFControlRuntime  
This resource's WLDFControlRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime](#) **rel**=WLDFDebugPatchesRuntime  
This resource's WLDFDebugPatchesRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime](#) **rel**=WLDFHarvesterRuntime  
This resource's WLDFHarvesterRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime](#) **rel**=WLDFImageRuntime  
This resource's WLDFImageRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) **rel**=WLDFInstrumentationRuntimes  
This resource's WLDFInstrumentationRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) **rel**=WLDFWatchNotificationRuntime  
This resource's WLDFWatchNotificationRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=canonical  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime

This resource manages a [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFAccessRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=WLDFDataAccessRuntimes  
This resource's WLDFDataAccessRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime](#) **rel**=action  
**title**=lookupWLDFDataAccessRuntime  
This resource's lookupWLDFDataAccessRuntime action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=canonical  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=dataAccessRuntimes  
This resource's dataAccessRuntimes collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=parent  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes**

This resource manages a collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}**

This resource manages a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor](#) **rel**=action  
**title**=closeCursor  
This resource's closeCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords](#) **rel**=action  
**title**=deleteDataRecords  
This resource's deleteDataRecords action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount](#) **rel**=action  
**title**=getDataRecordCount  
This resource's getDataRecordCount action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData](#) **rel**=action  
**title**=hasMoreData  
This resource's hasMoreData action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor](#) **rel**=action  
**title**=openCursor  
This resource's openCursor action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/closeCursor**

The resource supports the following methods:

- [POST](#)

## POST

Disposes of the cursor once the client has fetched all the records.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorName**

cursorName

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/deleteDataRecords**

The resource supports the following methods:

- [POST](#)

## POST

Delete records within the specified time range that match the specified query. If the query is null or empty, all records within the time range will be deleted.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

Not all archives support a deletion feature. If not supported, this method will throw an `UnsupportedOperationException` exception.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**startTime**

Start time of the interval (inclusive)

Type: long

**endTime**

End time of the interval (exclusive)

Type: long

**queryString**

Query criterion

Type: string

## Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/getDataRecordCount**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)

## POST

The number of records that match the specified query and time range.

Start and end times are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**startTime**

Start time of the interval (inclusive)

Type: long

**endTime**

End time of the interval (exclusive)

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a int return field.

## POST

The number of records that match the specified query.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**query**

Query expression

Type: string

## Response Body

Contains a JSON object with a int return field.

## POST

The number that match the specified query and record-ID range, and whose timestamp (if it is available) is earlier than the specified end time.

The end time is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**startRecordId**

Record id of the first record

Type: long

**endRecordId**

Look at records whose record-ids are smaller than specified endrecordId

Type: long

**endTime**

Look at records which were entered prior to endTime

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/hasMoreData**

The resource supports the following methods:

- [POST](#)

## POST

Determines whether the specified cursor has more data to be fetched.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**cursorName**

cursorName

Type: string

### Response Body

Contains a JSON object with a boolean return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/dataAccessRuntimes/{name}/openCursor**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Opens a cursor with the specified timeout value, in milliseconds.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

### **query**

The query expression to filter the result set from the underlying diagnostic log.

**Type:** string

### **cursorTimeout**

The timeout interval after which the cursor will become invalid if not invoked.

**Type:** long

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor for records that meet the specified time range and query condition. The timeout value for the cursor is also specified.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

### **beginTimestamp**

beginTimestamp

**Type:** long

**endTimestamp**

endTimestamp

Type: long

**query**

query

Type: string

**cursorTimeout**

cursorTimeout

Type: long

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor on the server side for the query.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**query**

The query expression to filter the result set from the underlying diagnostic log.

Type: string

## Response Body

Contains a JSON object with a string return field.

## POST

Opens a cursor with the specified query and time range.

Timestamps are specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**beginTimestamp**

beginTimestamp

Type: long

**endTimestamp**

endTimestamp

Type: long

**query**

query

Type: string

**Response Body**

Contains a JSON object with a string return field.

**POST**

Opens a cursor using the specified record-ID range, end timestamp, and query. The timeout value for the cursor is also specified.

The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

**Roles**

Admin, Deployer, Monitor, Operator

**Request Body**

Must contain a JSON object with the following fields:

**beginRecordId**

Record id of the first record (inclusive) in the result set

Type: long

**endRecordId**

Record id of the last record (exclusive) in the result set

Type: long

**endTimestamp**

Include only those records whose timestamp is earlier than this value

Type: long

**query**

Query criterion

Type: string

**cursorTimeout**

cursorTimeout

Type: long

**Response Body**

Contains a JSON object with a string return field.

**POST**

Opens a cursor with a given query and a record-id range.



The timestamp is specified as the number of milliseconds elapsed since the epoch: Jan 1 1970 AD, 00:00:00 GMT.

The default cursor timeout period is 5 minutes.

## Roles

Admin, Deployer, Monitor, Operator

## Request Body

Must contain a JSON object with the following fields:

**beginRecordId**

Record id of the first record (inclusive) in the result set

Type: long

**endRecordId**

Record id of the last record (exclusive) in the result set

Type: long

**endTimestamp**

Include only those records whose timestamp is earlier than this value

Type: long

**query**

Query criterion

Type: string

## Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/lookupWLDFDataAccessRuntime**

The resource supports the following methods:

- [POST](#)

## POST

An instance of a WLDFDataAccessMBean defined by its logical name. The name is constructed from the specific type of log data requested.

### Roles

Admin, Deployer, Monitor, Operator

### Request Body

Must contain a JSON object with the following fields:

**logicalName**

logicalName

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDataAccessRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes**

This resource manages a collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFDataAccessRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive](#) **rel**=action  
**title**=closeArchive  
This resource's closeArchive action resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFAccessRuntime/WLDFDataAccessRuntimes/{name}/closeArchive**

The resource supports the following methods:

- [POST](#)



## **POST**

### **Roles**

Admin, Deployer, Monitor, Operator

### **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes**

This resource manages a collection of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFArchiveRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFArchiveRuntimes/{name} **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime**

This resource manages a [weblogic.management.runtime.WLDFControlRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFControlRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFControlRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel=systemResourceControls**  
This resource's systemResourceControls collection resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls**

This resource manages a collection of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel=self**

This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}**

This resource manages a [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime](#) **rel=harvesterManagerRuntime**

This resource's harvesterManagerRuntime singleton resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}](#) **rel=self**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime](#) **rel=watchManagerRuntime**

This resource's watchManagerRuntime singleton resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime**

This resource manages a [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime](#)  
**rel**=canonical

This resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}](#) **rel**=parent

The parent resource of this resource.

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/harvesterManagerRuntime](#) **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime**

This resource manages a [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFWatchManagerRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm **rel**=action **title**=resetWatchAlarm

This resource's resetWatchAlarm action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name} **rel**=parent

The parent resource of this resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime **rel**=self

This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFControlRuntime/systemResourceControls/{name}/watchManagerRuntime/resetWatchAlarm**

The resource supports the following methods:

- [POST](#)



## POST

Resets a policy alarm.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**watchName**

the name of the policy to reset

Type: string

### Response Body

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime

This resource manages a [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch](#) **rel=action** **title=activateDebugPatch**  
This resource's activateDebugPatch action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks](#) **rel=action** **title=clearDebugPatchTasks**  
This resource's clearDebugPatchTasks action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches](#) **rel=action** **title=deactivateAllDebugPatches**  
This resource's deactivateAllDebugPatches action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches](#) **rel=action** **title=deactivateDebugPatches**  
This resource's deactivateDebugPatches action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/showDebugPatchInfo](#) **rel=action** **title=showDebugPatchInfo**  
This resource's showDebugPatchInfo action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks](#) **rel=debugPatchTasks**  
This resource's debugPatchTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/activateDebugPatch**

The resource supports the following methods:

- [POST](#)

## POST

Activate specified debug patch, optionally within the scope of given application and module

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**patch**

Patch to be activated

**Type:** string

**application**

If not null, limit the scope of activation to specified application. If null, activate at system level.

**Type:** string

**module**

If not null and application is specified, limit the scope of activation within specified module within the application.

**Type:** string

**partitionName**

partitionName

**Type:** string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/clearDebugPatchTasks**

The resource supports the following methods:

- [POST](#)

## **POST**

Clear all completed debug patch activation/deactivation tasks

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateAllDebugPatches**

The resource supports the following methods:

- [POST](#)



## POST

Deactivate all active debug patches

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See *About Synchronous and Asynchronous Operations*.

### Roles

Admin

### Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/deactivateDebugPatches**

The resource supports the following methods:

- [POST](#)

## POST

Deactivate specified patches within the scope of given application and module.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See About Synchronous and Asynchronous Operations.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**patches**

Comma separated list of patches to be deactivated

Type: string

**application**

If not null, deactivate given patches within the scope of specified application. If null, deactivate at system level.

Type: string

**module**

If not null and application is specified, limit the scope of de-activation to specified module.

Type: string

**partitionName**

partitionName

Type: string

### Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean` reference return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks**

This resource manages a collection of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}**

This resource manages a [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel](#) **rel=action** **title=cancel**  
This resource's cancel action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks](#) **rel=parent**  
The parent resource of this resource.
- **rel=parentTask**  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks](#) **rel=subTasks**  
This resource's subTasks collection resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)



## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name} rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/cancel **rel**=action  
**title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks  
**rel**=subTasks  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks](#) **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

---

**/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/debugPatchTasks/{name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFDebugPatchesRuntime/showDebugPatchInfo**

The resource supports the following methods:

- [POST](#)

## POST

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**patch**  
Debug patch  
Type: string

### Response Body

Contains a JSON object with a string return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime**

This resource manages a [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFHarvesterRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFHarvesterRuntime](#) **rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime

This resource manages a [weblogic.management.runtime.WLDFImageRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFImageRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFImageRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/captureImage](#) **rel=action** **title=captureImage**  
This resource's captureImage action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/clearCompletedImageCaptureTasks](#) **rel=action** **title=clearCompletedImageCaptureTasks**  
This resource's clearCompletedImageCaptureTasks action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/purgeCapturedImages](#) **rel=action** **title=purgeCapturedImages**  
This resource's purgeCapturedImages action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/resetImageLockout](#) **rel=action** **title=resetImageLockout**  
This resource's resetImageLockout action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=imageCaptureTasks**  
This resource's imageCaptureTasks collection resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/captureImage**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Creates a diagnostic image in the specified destination directory, which can be specified either as a relative or absolute pathname. If relative, the path is relative to the server's logs directory.

If the directory does not exist, it is created. If the directory exists, it must be writable in order for image creation to proceed.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**destination**

absolute or relative directory path

Type: string

## Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

## POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the configured lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

## POST

Creates a diagnostic image in the specified destination directory, which can be specified either as a relative or absolute pathname. If relative, the path is relative to the server's `logs` directory.

If the directory does not exist, it is created. If the directory exists, it must be writable in order for image creation to proceed.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**destination**

absolute or relative path

**Type:** string

**lockoutMinutes**

number of minutes before next image capture request will be accepted

**Type:** int

## Response Body

Contains a JSON object with a `weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean` reference return field.

## POST

Creates a diagnostic image in the configured destination directory.

No additional image capture requests will be accepted until the specified lockout period has expired.

This method supports both asynchronous and best effort synchronous invocations. The behavior is controlled by the 'Prefer' header. See [About Synchronous and Asynchronous Operations](#).

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **lockoutMinutes**

number of minutes before the next image capture request will be accepted

Type: int

## Response Body

Contains a JSON object with a  
weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean reference  
return field.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/clearCompletedImageCaptureTasks**

The resource supports the following methods:

- [POST](#)



## **POST**

Removes all completed image capture tasks.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks**

This resource manages a collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}**

This resource manages a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/cancel](#) **rel=action** **title=cancel**  
This resource's cancel action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks](#) **rel=parent**  
The parent resource of this resource.
- **rel=parentTask**  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}](#) **rel=self**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks](#) **rel=subTasks**  
This resource's subTasks collection resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=self  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel **rel**=action  
**title**=cancel  
This resource's cancel action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks **rel**=parent  
The parent resource of this resource.
- **rel**=parentTask  
This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name} **rel**=self  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks  
This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks**

This resource manages a collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.TaskRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.TaskRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks](#) **rel=self**  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}**

This resource manages a [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.TaskRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.TaskRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel **rel**=action **title**=cancel

This resource's cancel action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=canonical

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks **rel**=parent

The parent resource of this resource.

- **rel**=parentTask

This resource's parentTask reference to a [weblogic.management.runtime.TaskRuntimeMBean](#) resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name} **rel**=self

This resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/subTasks **rel**=subTasks

This resource's subTasks collection resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/imageCaptureTasks/{name}/subTasks/{name}/subTasks/{name}/cancel**

The resource supports the following methods:

- [POST](#)

## POST

Attempts to cancel this task.

An exception is thrown to indicate failure to cancel the task. Not all tasks can be cancelled.

## Roles

Admin

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/purgeCapturedImages**

The resource supports the following methods:

- [POST](#)

## POST

Delete captured images specified by the age criteria.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**age**

Purge diagnostic images older than specified age specified in the format Days:Hours:Minutes. If empty or null all existing image files on disk are purged. The hours and minutes components are optional.

**Type:** string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFImageRuntime/resetImageLockout**

The resource supports the following methods:

- [POST](#)

## **POST**

Reset the lockout period, thus allowing image capture requests to be accepted.

## **Roles**

Admin

## **Response Body**

Contains an empty JSON object.

## /management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes

This resource manages a collection of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)



## GET

Get this collection of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) entities.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}**

This resource manages a [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFInstrumentationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodInvocationStatisticsData](#) **rel=action** **title=resetMethodInvocationStatisticsData**

This resource's [resetMethodInvocationStatisticsData](#) action resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodMemoryAllocationStatisticsData](#) **rel=action** **title=resetMethodMemoryAllocationStatisticsData**

This resource's [resetMethodMemoryAllocationStatisticsData](#) action resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}](#) **rel=self**

This resource.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodInvocationStatisticsData**

The resource supports the following methods:

- [POST](#)

## POST

Resets the nested MethodInvocationStatistics structure and reinitializes the underlying metrics.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**expr**

Expression conforming to the harvester syntax for the MethodInvocationStatistics property without the attribute name prefix.

**Type:** string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFInstrumentationRuntimes/{name}/resetMethodMemoryAllocationStatisticsData**

The resource supports the following methods:

- [POST](#)

## POST

Resets the nested MethodMemoryAllocationStatistics structure and reinitializes the underlying metrics.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**expr**

Expression conforming to the harvester syntax for the MethodMemoryAllocationStatistics property without the attribute name prefix.

Type: string

### Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime**

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#)  
[rel=WLDFWatchJMXNotificationSource](#)  
This resource's [WLDFWatchJMXNotificationSource](#) singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm](#) [rel=action](#) [title=resetWatchAlarm](#)  
This resource's [resetWatchAlarm](#) action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime](#)  
[rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) [rel=self](#)  
This resource.

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/resetWatchAlarm**

The resource supports the following methods:

- [POST](#)

## POST

Resets a policy alarm.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**watchName**

the name of the policy to reset

Type: string

### Response Body

Contains an empty JSON object.

---

## **/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource**

This resource manages a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=canonical**

This resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime](#) **rel=parent**

The parent resource of this resource.

- [uri=/management/weblogic/{version}/serverRuntime/WLDFRuntime/WLDFWatchNotificationRuntime/WLDFWatchJMXNotificationSource](#) **rel=self**

This resource.

---

## /management/weblogic/{version}/serverRuntime/workManagerRuntimes

This resource manages a collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

The resource supports the following methods:

- [GET](#)

## GET

Get this collection of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instances.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a list of [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entities.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}

This resource manages a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WorkManagerRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WorkManagerRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel=capacityRuntime**  
This resource's capacityRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel=maxThreadsConstraintRuntime**  
This resource's maxThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel=minThreadsConstraintRuntime**  
This resource's minThreadsConstraintRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime](#) **rel=requestClassRuntime**  
This resource's requestClassRuntime singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel=self**  
This resource.

## **/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime**

This resource manages a [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.CapacityRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.CapacityRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/capacityRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/maxThreadsConstraintRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime**

This resource manages a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.MinThreadsConstraintRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/minThreadsConstraintRuntime](#) **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime**

This resource manages a [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.RequestClassRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.RequestClassRuntimeMBean](#) entity.

This method can return the following links:

- **uri**=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name} **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/workManagerRuntimes/{name}/requestClassRuntime **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime**

This resource manages a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting rel=clusterRouting](#)  
This resource's clusterRouting singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime rel=self](#)  
This resource.

## /management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting

This resource manages a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeClusterRoutingRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting](#) **rel=canonical**  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime](#) **rel=parent**  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/wseeClusterFrontEndRuntime/clusterRouting](#) **rel=self**  
This resource.

---

## /management/weblogic/{version}/serverRuntime/wseeWsruntime

This resource manages a [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WseeWsruntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WseeWsruntimeMBean](#) entity.

This method can return the following links:

- **uri**=[/management/weblogic/{version}/serverRuntime/wseeWsruntime](#)  
**rel**=canonical  
This resource.
- **uri**=[/management/weblogic/{version}/serverRuntime](#) **rel**=parent  
The parent resource of this resource.
- **uri**=[/management/weblogic/{version}/serverRuntime/wseeWsruntime](#)  
**rel**=self  
This resource.

## /management/weblogic/{version}/serverRuntime/WTCRuntime

This resource manages a [weblogic.management.runtime.WTCRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)



## GET

Get this [weblogic.management.runtime.WTCRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WTCRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean](#) [rel=WTCStatisticsRuntimeMBean](#)  
This resource's WTCStatisticsRuntimeMBean singleton resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus](#) [rel=action](#) [title=getServiceStatus](#)  
This resource's getServiceStatus action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService](#) [rel=action](#) [title=resumeService](#)  
This resource's resumeService action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection](#) [rel=action](#) [title=startConnection](#)  
This resource's startConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection](#) [rel=action](#) [title=stopConnection](#)  
This resource's stopConnection action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService](#) [rel=action](#) [title=suspendService](#)  
This resource's suspendService action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime](#) [rel=canonical](#)  
This resource.
- [uri=/management/weblogic/{version}/serverRuntime](#) [rel=parent](#)  
The parent resource of this resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime](#) [rel=self](#)  
This resource.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/getServiceStatus**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Returns status of a specific imported service provided by the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **localAccessPoint**

The local access point name.

**Type:** string

### **remoteAccessPointList**

The comma separated remote access point names.

**Type:** string

### **svcName**

The resource name of imported or exported service/resource name.

**Type:** string

## Response Body

Contains a JSON object with a int return field.

## POST

Returns status of the Import and Export service/resource configured for the targeted WTC server with the specified service name. This service name is the resource name of the WTCImport and WTCEXport. As long as one of the directions is available the returned status will be available.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

## Response Body

Contains a JSON object with a int return field.

## POST

Returns status of the imported or exported service of the specified service name and provided by the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

**Type:** string

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

**isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

**Type:** boolean

## Response Body

Contains a JSON object with a int return field.

## POST

Returns status of the Import or Export service/resource configured for the targeted WTC server with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

**isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

**Type:** boolean

**Response Body**

Contains a JSON object with a int return field.

**POST**

Returns status of the imported and exported service of the specified service name and provided by the specified local access point. The service name is the resource name of the WTCImport and WTCEXport. As long as one of the directions is available then the returned status will be available.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

**Type:** string

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

**Response Body**

Contains a JSON object with a int return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/resumeService**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Resume all the Import or Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEExport.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **localAccessPoint**

The local access point name.

**Type:** string

### **svcName**

The resource name of imported or exported service/resource name.

**Type:** string

### **isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

**Type:** boolean

## Response Body

Contains an empty JSON object.

## POST

Resume all the Import and Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEExport.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

POST

---

**svcName**

The resource name of imported or exported service/resource name.

Type: string

**Response Body**

Contains an empty JSON object.

POST

Resume a specific Import service with the specified service name configured for the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

Type: string

**remoteAccessPointList**

The comma separated remote access point names.

Type: string

**svcName**

The resource name of imported or exported service/resource name.

Type: string

**Response Body**

Contains an empty JSON object.

POST

Resume all the Import and Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

Type: string



**svcName**

The resource name of imported or exported service/resource name.

Type: string

**Response Body**

Contains an empty JSON object.

**POST**

Resume all the Import or Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**svcName**

The resource name of imported or exported service/resource name.

Type: string

**isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

Type: boolean

**Response Body**

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/WTCRuntime/startConnection

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Attempt to start a connection between the specified local and remote domain access points.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **LDomAccessPointId**

The local domain access point id.

Type: string

### **RDomAccessPointId**

The remote domain access point id.

Type: string

## Response Body

Contains an empty JSON object.

## POST

Attempt to start connections between the specified local domain access point and all remote end points defined for the given local domain domain access point.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **LDomAccessPointId**

The local domain access point id.

Type: string

## Response Body

Contains an empty JSON object.

---

## /management/weblogic/{version}/serverRuntime/WTCRuntime/stopConnection

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Attempt to stop the connection between the specified local and remote domain access points.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **LdomAccessPointId**

The local domain access point id.

Type: string

### **RDomAccessPointId**

The remote domain access point id.

Type: string

## Response Body

Contains an empty JSON object.

## POST

Attempt to stop all remote connections configured for the given local access point id.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **LdomAccessPointId**

The local domain access point id.

Type: string

## Response Body

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/suspendService**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)
- [POST](#)

## POST

Suspend a specific Import service with the specified service name configured for the specified local access point and remote access point list. The service name is the resource name of the WTCImport and WTCEXport. The remote access point list is a comma separated list; for instance, "TDOM1,TDOM2".

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **localAccessPoint**

The local access point name.

**Type:** string

### **remoteAccessPointList**

The comma separated remote access point names.

**Type:** string

### **svcName**

The resource name of imported or exported service/resource name.

**Type:** string

## Response Body

Contains an empty JSON object.

## POST

Suspend all the Import or Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

**isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

**Type:** boolean

**Response Body**

Contains an empty JSON object.

**POST**

Suspend all the Import or Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

**Type:** string

**svcName**

The resource name of imported or exported service/resource name.

**Type:** string

**isImport**

The type of service indicate whether it is import or export. If true, then it is imported service, if false it is targeted for exported service.

**Type:** boolean

**Response Body**

Contains an empty JSON object.

**POST**

Suspend all the Import and Export services with the specified service name. This service name is the resource name of the WTCImport and WTCEXport.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:



**svcName**

The resource name of imported or exported service/resource name.

Type: string

**Response Body**

Contains an empty JSON object.

**POST**

Suspend all the Import and Export services with the specified service name configured for the specified local access point. The service name is the resource name of the WTCImport and WTCEXport.

**Roles**

Admin

**Request Body**

Must contain a JSON object with the following fields:

**localAccessPoint**

The local access point name.

Type: string

**svcName**

The resource name of imported or exported service/resource name.

Type: string

**Response Body**

Contains an empty JSON object.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean**

This resource manages a [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) instance.

The resource supports the following methods:

- [GET](#)

## GET

Get this [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) instance.

## Roles

Admin, Deployer, Monitor, Operator

## Response Body

Contains a [weblogic.management.runtime.WTCStatisticsRuntimeMBean](#) entity.

This method can return the following links:

- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionCommittedTotalCount](#) **rel=action**  
**title=getInTransactionCommittedTotalCount**  
This resource's `getInTransactionCommittedTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionRolledBackTotalCount](#) **rel=action**  
**title=getInTransactionRolledBackTotalCount**  
This resource's `getInTransactionRolledBackTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundFailReqTotalCount](#) **rel=action**  
**title=getInboundFailReqTotalCount**  
This resource's `getInboundFailReqTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundMessageTotalCount](#) **rel=action**  
**title=getInboundMessageTotalCount**  
This resource's `getInboundMessageTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundNWMessageTotalSize](#) **rel=action**  
**title=getInboundNWMessageTotalSize**  
This resource's `getInboundNWMessageTotalSize` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundSuccessReqTotalCount](#) **rel=action**  
**title=getInboundSuccessReqTotalCount**  
This resource's `getInboundSuccessReqTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionCommittedTotalCount](#) **rel=action**  
**title=getOutTransactionCommittedTotalCount**  
This resource's `getOutTransactionCommittedTotalCount` action resource.
- [uri=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionRolledBackTotalCount](#) **rel=action**  
**title=getOutTransactionRolledBackTotalCount**  
This resource's `getOutTransactionRolledBackTotalCount` action resource.

- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundFailReqTotalCount **rel**=action  
**title**=getOutboundFailReqTotalCount  
This resource's getOutboundFailReqTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundMessageTotalCount **rel**=action  
**title**=getOutboundMessageTotalCount  
This resource's getOutboundMessageTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundNWMessageTotalSize **rel**=action  
**title**=getOutboundNWMessageTotalSize  
This resource's getOutboundNWMessageTotalSize action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundSuccessReqTotalCount **rel**=action  
**title**=getOutboundSuccessReqTotalCount  
This resource's getOutboundSuccessReqTotalCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutstandingNWReqCount **rel**=action  
**title**=getOutstandingNWReqCount  
This resource's getOutstandingNWReqCount action resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean **rel**=canonical  
This resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime **rel**=parent  
The parent resource of this resource.
- **uri**=/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean **rel**=self  
This resource.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundFailReqTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of inbound non-conversational, non-CORBA request that return failure by specific exported service. If specified service is imported, the return value should be 0.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**svcName**

The service resource name.

Type: string

**IDomAccessPointId**

The local access point ID for this exported service.

Type: string

**isImport**

Should be false to get value for exported service.

Type: boolean

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundMessageTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the total number of inbound non-conversational, non-CORBA request messages received by this exported Service. If specified service is imported, the return value should be 0.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The service resource name.

**Type:** string

**IDomAccessPointId**

The local access point ID for this exported service.

**Type:** string

**isImport**

Should be false to get value for exported service.

**Type:** boolean

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the total number of inbound non-conversational, non-CORBA request messages received by this WTC connection. The WTC connection is identified by IDomAccessPointId and rDomAccessPointId pair.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

**Type:** string



**rDomAccessPointId**

The remote domain access point id.

Type: string

**Response Body**

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundNWMessageTotalSize**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the total message size of inbound non-conversational, non-CORBA messages received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **LDomAccessPointId**

The local domain access point id.

Type: string

### **RDomAccessPointId**

The remote domain access point id.

Type: string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the total size of inbound non-conversational, non-CORBA messages received by this exported Service. If specified service is imported, the return value should be 0.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

### **svcName**

The service resource name.

Type: string

### **IDomAccessPointId**

The local access point ID for this exported service.

Type: string

**isImport**

Should be false to get value for exported service.

Type: boolean

**Response Body**

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInboundSuccessReqTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of inbound non-conversational, non-CORBA request that successfully handled by specific exported service. If specified service is imported, the return value should be 0.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**svcName**

The service resource name.

Type: string

**IDomAccessPointId**

The local access point ID for this exported service.

Type: string

**isImport**

Should be false to get value for exported service.

Type: boolean

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionCommittedTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of inbound transactions committed on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

### Response Body

Contains a JSON object with a long return field.



---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getInTransactionRolledBackTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of inbound transactions rolled back on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundFailReqTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of outbound non-conversational, non-CORBA requests return failure by specific imported service. If specified service is exported, the return value should be 0.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**svcName**

The service name.

Type: string

**IDomAccessPointId**

The local access point ID.

Type: string

**rDomAccessPointIdList**

The remote access point ID list.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundMessageTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the total number of outbound non-conversational, non-CORBA messages send to this imported Service. If specified service is exported, the return value should be 0.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The service name.

Type: string

**IDomAccessPointId**

The local access point ID.

Type: string

**rDomAccessPointIdList**

The remote access point ID list.

Type: string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the total number of outbound non-conversational, non-CORBA messages received by this WTC connection. The WTC connection is identified by IDomAccessPointId and rDomAccessPointId pair.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

**Response Body**

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundNWMessageTotalSize**

The resource supports the following methods:

- [POST](#)



## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the total size of outbound non-conversational, non-CORBA messages send to this imported Service. If specified service is exported, the return value should be 0.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The service name.

Type: string

**IDomAccessPointId**

The local access point ID.

Type: string

**rDomAccessPointIdList**

The remote access point ID list.

Type: string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the total size of outbound non-conversational, non-CORBA messages received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**LDomAccessPointId**

The local domain access point id.

Type: string

**RDomAccessPointId**

The remote domain access point id.

Type: string

**Response Body**

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutboundSuccessReqTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of outbound non-conversational, non-CORBA requests successfully handled by specific imported service. If specified service is exported, the return value should be 0.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**svcName**

The service name.

Type: string

**IDomAccessPointId**

The local access point ID.

Type: string

**rDomAccessPointIdList**

The remote access point ID list.

Type: string

### Response Body

Contains a JSON object with a long return field.

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutstandingNWReqCount**

The resource supports the following methods:

- [POST](#)

## POST

The resource supports the following methods:

- [POST](#)
- [POST](#)

## POST

Returns the current number of outstanding inbound non-conversational, non-CORBA requests received on this WTC connection. The WTC connection is defined by LDomAccessPointId and RDomAccessPointId pair.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

## Response Body

Contains a JSON object with a long return field.

## POST

Returns the current number of outstanding non-conversational, non-CORBA requests for specific imported/exported service.

## Roles

Admin

## Request Body

Must contain a JSON object with the following fields:

**svcName**

The service name.

Type: string

**IDomAccessPointId**

Local access point.

Type: string

**rDomAccessPointIdList**

Remote Access Point ID List. If null, then the service is an exported service.

Type: string

**Response Body**

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionCommittedTotalCount**

The resource supports the following methods:

- [POST](#)



## POST

Returns the total number of outbound transaction committed on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

### Response Body

Contains a JSON object with a long return field.

---

## **/management/weblogic/{version}/serverRuntime/WTCRuntime/WTCStatisticsRuntimeMBean/getOutTransactionRolledBackTotalCount**

The resource supports the following methods:

- [POST](#)

## POST

Returns the total number of outbound transactions rolled backed on this WTC connection. The WTC connection is defined by IDomAccessPointId and rDomAccessPointId pair.

### Roles

Admin

### Request Body

Must contain a JSON object with the following fields:

**IDomAccessPointId**

The local domain access point id.

Type: string

**rDomAccessPointId**

The remote domain access point id.

Type: string

### Response Body

Contains a JSON object with a long return field.



The following sections describe the data models on which the REST resources operate. These data models describe the information exchanged in REST resources.

### **com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean**

This interface provides functionality to monitor the class redefinition process. It also provides methods to explicitly initiate class redefinition.

The properties of the `com.bea.wls.redef.runtime.ClassRedefinitionRuntimeMBean` entity are as follows:

**classRedefinitionCount**

Number of class redefinitions executed so far.

**Type:** int

**Constraints:** Read Only, Restart Required

**failedClassRedefinitionCount**

Number of failed redefinition operations since the application was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**processedClassesCount**

Number of classes processed since the application was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**totalClassRedefinitionTime**

Total time spent processing classes, in nano seconds since the application was deployed.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean

This interface provides functionality to monitor and control a class redefinition request.

The properties of the com.bea.wls.redef.runtime.ClassRedefinitionTaskRuntimeMBean entity are as follows:

**candidateClassesCount**

Estimated number of candidate classes to be redefined in the current change-list. Returns -1 if the number is not yet estimated.

**Type:** int

**Constraints:** Read Only, Restart Required

**completed**

This property indicates whether an asynchronous job has completed.

**Type:** boolean

**description**

A description of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**endTime**

This property indicates the time when the asynchronous job ended.

**Type:** java.util.Date

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**parentTask**

The task of which this task is a part.

A value of null indicates that this task is not a subtask.

**Type:** weblogic.management.runtime.TaskRuntimeMBean reference

**Constraints:** Read Only, Restart Required

**processedClassesCount**

Number of classes processed so far.

**Type:** int

**Constraints:** Read Only, Restart Required

**progress**

The progress of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**running**

Indicates whether the task is still running.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**startTime**

This property indicates the time when an asynchronous job was started.

**Type:** java.util.Date

**startTimeAsLong**

The time at which this task was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**systemTask**

Indicates whether this task was initiated by the server versus a user.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**taskError**

Returns an exception describing the error, if any, that occurred while performing this task.

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**taskStatus**

The status of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## java.lang.Throwable

This entity represents errors and exceptions.

The properties of the java.lang.Throwable entity are as follows:

**cause**

This property contains the stack trace of errors and exceptions.

**Type:** java.lang.Throwable

**message**

This property contains the reason why the error or exception was thrown.

**Type:** string

## java.util.Date

This entity represents a date as a string in ISO 8601 format, yyyy-MM-ddTHH:mm:ss.SSSX

## java.util.Properties

This entity represents a JSONObject with a property for each property in the properties object, where the key is the property's name the the value is a string containing the property's value.

## weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the weblogic.diagnostics.accessor.runtime.DataAccessRuntimeMBean entity are as follows:

**earliestAvailableTimestamp**

The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the earliest record in the diagnostic data log.

**Type:** long

**Constraints:** Read Only, Restart Required

**latestAvailableTimestamp**

The timestamp, in milliseconds, since Jan 1, 1970 AD, 00:00:00 GMT for the newest record in the diagnostic data log.

**Type:** long

**Constraints:** Read Only, Restart Required

**latestRecordId**

The latest known record ID for the underlying archive.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**timestampAvailable**

Returns true, if timestamp information is available with the underlying archive.

**Type:** boolean



**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.health.HealthState

This entity represents the health of the services that are in a WebLogic server domain. Selected subsystems within each WebLogic Server instance monitor their health status based on criteria specific to the subsystem.

The properties of the weblogic.health.HealthState entity are as follows:

**partitionName**

This property indicates the partition name for which the health state is reported.

**Type:** string

**state**

This property indicates the reported state as:

- OK - Service is healthy.
- WARN - Service could have problems in the future
- CRITICAL - Something must be done now to prevent service failure
- FAILED - Service has failed and must be restarted
- OVERLOADED - Service is functioning normally but there is too much work in it
- UNKNOWN - Service state cannot be determined

**Type:** string

**subsystemName**

This property indicates the service for which the health state is reported.

**Type:** string

**symptoms**

This property indicates the cause of the reported state.

**Type:** array of weblogic.health.Symptom

## weblogic.health.Symptom

This entity represents an observation reported by a service with its health state. A symptom can be used to determine the reason for the current health state of a WebLogic server.

The properties of the weblogic.health.Symptom entity are as follows:

**info**

This property provides additional information about the symptom if available.

**Type:** string

**instanceId**

This property represents an identifier for the symptom.

**Type:** string

**severity**

This property indicates a low, medium, or high severity level.

**Type:** string

**type**

This property represents the cause of the symptom (low memory, network error, stuck threads, and so on).

**Type:** string

## weblogic.management.rest.bean.model.CurrentUser

The authenticated user that is making the request.

The properties of the weblogic.management.rest.bean.model.CurrentUser entity are as follows:

**partitionId**

The ID of the partition where the component that is being invoked resides.

**Type:** string

**partitionName**

The human readable name of the partition ID.

**Type:** string

**user**

The login of the user making this request, if the user has been authenticated, or null if the user has not been authenticated.

**Type:** string

## weblogic.management.rest.bean.model.Version

A Version entity describes a version of the WebLogic Server resources.

The properties of the weblogic.management.rest.bean.model.Version entity are as follows:

**isLatest**

True if this is the default version.

**Type:** boolean

**lifecycle**

The lifecycle of this version: active or deprecated

**Type:** string

**version**

The name of this version.

**Type:** string

## weblogic.management.runtime.ApplicationRuntimeMBean

An application represents a Java EE enterprise application packaged in an EAR file or EAR exploded directory. The EAR file or directory contains a set of components such as WAR, EJB, and RAR connector components, each of which can be deployed on one or more targets. A target is a server or a cluster. Modules in the application can have one of the following states:

- UNPREPARED - Indicates that none of the modules in this application are currently prepared or active.
- PREPARED - Indicates that none of the modules in this application are currently prepared or active.
- ACTIVATED - Indicates that at least one module in this application is currently active.

ApplicationRuntimeMBean encapsulates runtime information about a deployed enterprise application.

The properties of the weblogic.management.runtime.ApplicationRuntimeMBean entity are as follows:

### **activeVersionState**

Specifies whether this application version is the currently active version.

An application can be the only version currently deployed, or it can have more than one version currently deployed, using the side-by-side deployment feature. If more than one version is deployed, only one version can be active. This attribute specifies the state the current application version is in.

An application can be in an INACTIVE state, which means that it has not been activated yet, or that there is more than one version of the application deployed (using side-by-side deployment) and this version is retiring.

An application can be in ACTIVE\_ADMIN state, which means that it is the currently active version for administrative channel requests.

An application can be in ACTIVE state, which means that it is the currently active version for normal (non-administrative) channel requests.

**Type:** int

**Constraints:** Read Only, Restart Required

### **applicationName**

The name of the application.

**Type:** string

**Constraints:** Read Only, Restart Required

### **applicationVersion**

The application's version identifier.

This is particularly useful, when using the side-by-side deployment feature, to differentiate between two different versions of the same application that are deployed at the same time.

**Type:** string

**Constraints:** Read Only, Restart Required

**healthState**

The HealthState MBean for the application.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**internal**

Indicates whether this application is an internal application. Such applications are not displayed in the console or persisted in the config.xml.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**overallHealthState**

The overall health of the application including that of some of the components that report health. Currently, only connector modules report health status and are the only ones considered in the overall health state of the application.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**partitionName**

The application's partition.

Returns the partition to which this application is deployed.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.AsyncReplicationRuntimeMBean**

This MBean provides runtime statistics for async replication in a WebLogic Cluster

The properties of the weblogic.management.runtime.AsyncReplicationRuntimeMBean entity are as follows:

**detailedSecondariesDistribution**

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**lastSessionsFlushTime**

The last time the sessions were flushed, in milliseconds since midnight, January 1, 1970 UTC

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**primaryCount**

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryCount**

Answer the number of object that the local server hosts as secondaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryServerDetails**

**Type:** string

**Constraints:** Read Only, Restart Required

**sessionsWaitingForFlushCount**

Number of sessions which are waiting to be flushed.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.AuthenticatorRuntimeMBean

This class is used to monitor and manage authentication provider runtime information.

The properties of the weblogic.management.runtime.AuthenticatorRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**providerName**

Returns name of this security provider.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.BatchJobRepositoryRuntimeMBean

The properties of the weblogic.management.runtime.BatchJobRepositoryRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.CapacityRuntimeMBean

Monitoring information for Capacity which defines the maximum number of requests that can be enqueued by all the work managers that share it.

The properties of the weblogic.management.runtime.CapacityRuntimeMBean entity are as follows:

**count**

Total number of requests that can be enqueued.

**Type:** int

**Constraints:** Read Only, Has Default Value: -1

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## **weblogic.management.runtime.ClassLoaderRuntimeMBean**

Provides methods for retrieving runtime information about class loading

The properties of the weblogic.management.runtime.ClassLoaderRuntimeMBean entity are as follows:

### **afterIndexingFindClassCount**

Type: long

Constraints: Read Only, Restart Required

### **afterIndexingFindClassTime**

Type: long

Constraints: Read Only, Restart Required

### **afterIndexingLoadClassCount**

Type: long

Constraints: Read Only, Restart Required

### **afterIndexingLoadClassTime**

Type: long

Constraints: Read Only, Restart Required

### **afterIndexingResourceCount**

Type: long

Constraints: Read Only, Restart Required

### **afterIndexingResourceTime**

Type: long

Constraints: Read Only, Restart Required

### **beforeIndexingFindClassCount**

Type: long

Constraints: Read Only, Restart Required

### **beforeIndexingFindClassTime**

Type: long

Constraints: Read Only, Restart Required

### **beforeIndexingLoadClassCount**

Type: long

Constraints: Read Only, Restart Required

### **beforeIndexingLoadClassTime**

Type: long

Constraints: Read Only, Restart Required

### **beforeIndexingResourceCount**

Type: long

**Constraints:** Read Only, Restart Required

**beforeIndexingResourceTime**

Type: long

**Constraints:** Read Only, Restart Required

**defineClassCount**

Type: long

**Constraints:** Read Only, Restart Required

**defineClassTime**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingFindClassCount**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingFindClassTime**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingLoadClassCount**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingLoadClassTime**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingResourceCount**

Type: long

**Constraints:** Read Only, Restart Required

**duringIndexingResourceTime**

Type: long

**Constraints:** Read Only, Restart Required

**findClassCount**

Type: long

**Constraints:** Read Only, Restart Required

**findClassTime**

Type: long

**Constraints:** Read Only, Restart Required

**indexingTime**

Type: long

**Constraints:** Read Only, Restart Required



**loadClassCount**

Type: long

Constraints: Read Only, Restart Required

**loadClassTime**

Type: long

Constraints: Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**parentDelegationCount**

Type: long

Constraints: Read Only, Restart Required

**parentDelegationTime**

Type: long

Constraints: Read Only, Restart Required

**resourceCount**

Type: long

Constraints: Read Only, Restart Required

**resourceTime**

Type: long

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## weblogic.management.runtime.ClusterRuntimeMBean

This class is used for monitoring a server's view of the members of a WebLogic cluster within a WebLogic domain.

The properties of the weblogic.management.runtime.ClusterRuntimeMBean entity are as follows:

**activeSingletonServices**

Returns an array of the names of the singleton services that are active on this server.

Type: array of string

Constraints: Read Only, Restart Required

**aliveServerCount**

Provides the current total number of alive servers in this cluster.

Returns the current total number of alive servers in this cluster.

**Type:** int

**Constraints:** Read Only, Restart Required

**detailedSecondariesDistribution**

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**foreignFragmentsDroppedCount**

Provides the number of fragments that originated in foreign domains or clusters which use the same multicast address.

Answer the number of fragments that originated in foreign domains/cluster that use the same multicast address.

**Type:** long

**Constraints:** Read Only, Restart Required

**fragmentsReceivedCount**

Provides the total number of messages received on this server from the cluster. This is applicable to both multicast and unicast message types.

**Type:** long

**Constraints:** Read Only, Restart Required

**fragmentsSentCount**

Returns the total number of message fragments sent from this server into the cluster. This is applicable to both multicast and unicast message types.

**Type:** long

**Constraints:** Read Only, Restart Required

**healthState**

Provides health information returned by the server self-health monitor service.

- HEALTH\_OK = 0, Server service is healthy.
- HEALTH\_WARN = 1, Service could have problems in the future. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH\_CRITICAL = 2, Something must be done now to prevent service failure. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH\_FAILED = 3, Service has failed - must be restarted. Check the server logs and the corresponding RuntimeMBean for more details.
- HEALTH\_OVERLOADED = 4, Service is functioning normally but there is too much work in it. CRITICAL and OVERLOADED are different. A subsystem is in the critical state when a part of it is malfunctioning, for example, stuck threads. An overloaded state means that there is more work assigned to the service than the configured threshold. A service might refuse more work in this state.
- LOW\_MEMORY\_REASON = "server is low on memory", Reason code that indicates that the server is low on memory. Administrators can configure low and

high thresholds for memory usage. The server health changes to OVERLOADED with this reason code if the low threshold is reached.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**multicastMessagesLostCount**

Provides the total number of in-coming multicast messages that were lost according to this server.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**primaryCount**

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**resendRequestsCount**

Provides the number of state-delta messages that had to be resent because a receiving server in the cluster missed a message.

Returns the number of state-delta messages that had to be resent because a receiving server in the cluster missed a message.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryCount**

Answer the number of object that the local server hosts as secondaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryServerDetails**

**Type:** string

**Constraints:** Read Only, Restart Required

**serverNames**

Provides the names of the servers in the cluster.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.CoherenceClusterRuntimeMBean

Coherence cluster run-time information.

The properties of the weblogic.management.runtime.CoherenceClusterRuntimeMBean entity are as follows:

**clusterName**

The name of the Coherence cluster.

**Type:** string

**Constraints:** Read Only, Restart Required

**clusterSize**

The size of the Coherence cluster.

**Type:** int

**Constraints:** Read Only, Restart Required

**licenseMode**

The license mode for the Coherence cluster. Possible values are Evaluation, Development, or Production.

**Type:** string

**Constraints:** Read Only, Restart Required

**members**

Identifiers for the available Coherence cluster members.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**version**

The Coherence cluster version.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ComponentRuntimeMBean

Base class for all runtime mbeans that provide status of running modules.

The properties of the `weblogic.management.runtime.ComponentRuntimeMBean` entity are as follows:

**deploymentState**

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

**Type:** int

**Constraints:** Read Only, Restart Required

**moduleId**

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean**

Concurrent Managed Objects Runtime information for the global/domain partition or a common partition.

The properties of the `weblogic.management.runtime.ConcurrentManagedObjectsRuntimeMBean` entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**rejectedLongRunningRequests**

The number of long-running requests that have been rejected by managed executor services and managed scheduled executor services in this partition on the current server.

**Type:** long

**Constraints:** Read Only, Restart Required

**rejectedNewThreadRequests**

The number of newThread method invocations that have been rejected by managed thread factories in this partition on the current server.

**Type:** long

**Constraints:** Read Only, Restart Required

**runningLongRunningRequests**

The number of running long-running requests submitted to managed executor services and managed scheduled executor services in this partition on the current server.

**Type:** int

**Constraints:** Read Only, Restart Required

**runningThreadsCount**

The number of running threads created by managed thread factories in this partition on the current server.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ConnectorComponentRuntimeMBean**

Generates notifications about the deployment state of resource adapters. (Each resource adapter is represented by an instance of `weblogic.management.configuration.ConnectorComponentMBean`.)

In 2-phase deployment, if a resource adapter's state is `PREPARED` then it has achieved the first phase of deployment (everything is set up and all that remains is to enable a reference to the adapter). When the resource adapter is in an `ACTIVATED` state, it has achieved the second phase of deployment, in which applications can obtain a reference to the adapter.

A server instance creates an instance of this interface when it creates an instance of `weblogic.management.configuration.ConnectorComponentMBean`

The properties of the `weblogic.management.runtime.ConnectorComponentRuntimeMBean` entity are as follows:

**EISResourceId**

Returns the EISResourceId for the component.

**Type:** string

**Constraints:** Read Only, Restart Required

**EISType**

Get the EIS type.

**Type:** string

**Constraints:** Read Only, Restart Required

**activeVersion**

Return true if this version is the active version. Returns true if this resource adapter is not versioned.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**activeVersionId**

Get the active version Id.

**Type:** string

**Constraints:** Read Only, Restart Required

**componentName**

Get the name of the connector component.

**Type:** string

**Constraints:** Read Only, Restart Required

**configuration**

Return the xml string representing the RA configuration. The xml corresponding to the latest schema is returned. The current supported version is "1.0"

**Type:** string

**Constraints:** Read Only, Restart Required

**configurationVersion**

Return the latest configuration version.

**Type:** string

**Constraints:** Read Only, Restart Required

**configuredProperties**

Gets a subset of the resource adapter descriptor information.

**Type:** java.util.Properties

**Constraints:** Read Only, Restart Required

**connectionPoolCount**

The number of connection pools.

**Type:** int

**Constraints:** Read Only, Restart Required

**deploymentState**

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

**Type:** int

**Constraints:** Read Only, Restart Required

**description**

Get the Description for the resource adapter.

**Type:** string

**Constraints:** Read Only, Restart Required

**descriptions**

Get the Descriptions for the resource adapter.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**healthState**

The HealthState mbean for the application.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**inboundConnectionsCount**

The number of inbound connections for the resource adapter.

**Type:** int

**Constraints:** Read Only, Restart Required

**jndiName**

Get the Jndi name of the resource adapter.

**Type:** string

**Constraints:** Read Only, Restart Required

**linkref**

Get the linkref.

**Type:** string

**Constraints:** Read Only, Restart Required

**moduleId**

Returns the identifier for this Component. The identifier is unique within the application.



Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**schema**

Get the latest schema for RA configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**specVersion**

Get the spec version.

**Type:** string

**Constraints:** Read Only, Restart Required

**state**

Get the state of the resource adapter.

**Type:** string

**Constraints:** Read Only, Restart Required

**suspendedState**

Gets the suspended state information of the resource adapter.

If getState() returns SUSPENDED then getSuspendedState() returns an integer describing which functions of the resource adapter are suspended: one or more of INBOUND, OUTBOUND or WORK (or ALL) or 0 for nothing suspended

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**vendorName**

Get the vendor name.

**Type:** string

**Constraints:** Read Only, Restart Required

**version**

Get the version.

**Type:** string

**Constraints:** Read Only, Restart Required

**versionId**

Get the version Id.

**Type:** string

**Constraints:** Read Only, Restart Required

**versioned**

Check if the resource adapter is versioned. Returns true if it is.

**Type:** boolean

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean

This class is used for monitoring a WebLogic Connector Connection Pool

The properties of the weblogic.management.runtime.ConnectorConnectionPoolRuntimeMBean entity are as follows:

**EISResourceId**

The EISResourceId of this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**MCFClassName**

Get the MCF class name.

**Type:** string

**Constraints:** Read Only, Restart Required

**activeConnectionsCurrentCount**

The current total active connections.

**Type:** int

**Constraints:** Read Only, Restart Required

**activeConnectionsHighCount**

The high water mark of active connections in this Connector Pool since the pool was instantiated.

**Type:** int

**Constraints:** Read Only, Restart Required

**averageActiveUsage**

The running average usage of created connections that are active in the Connector Pool since the pool was last shrunk.

**Type:** int

**Constraints:** Read Only, Restart Required

**capacityIncrement**

The initial capacity configured for this Connector connection pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**closeCount**

The number of connections that were closed for the connection pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionFactoryClassName**

The ConnectionFactoryName of this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**connectionFactoryName**

For 1.0 link-ref resource adapters only, the base resource adapter's connection factory name.

**Type:** string

**Constraints:** Read Only, Restart Required

**connectionsCreatedTotalCount**

The total number of Connector connections created in this Connector Pool since the pool is instantiated.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsDestroyedByErrorTotalCount**

Return the number of connections that were destroyed because an error event was received.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsDestroyedByShrinkingTotalCount**

Return the number of connections that were destroyed as a result of shrinking.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsDestroyedTotalCount**

The total number of Connector connections destroyed in this Connector Pool since the pool is instantiated.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsMatchedTotalCount**

The total number of times a request for a Connector connections was satisfied via the use of an existing created connection since the pool is instantiated.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsRejectedTotalCount**

The total number of rejected requests for a Connector connections in this Connector Pool since the pool is instantiated.

Type: int

Constraints: Read Only, Restart Required

**connectorEisType**

The EIS type of this Connector connection pool.

Type: string

Constraints: Read Only, Restart Required

**currentCapacity**

The PoolSize of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

**freeConnectionsCurrentCount**

The current total free connections.

Type: int

Constraints: Read Only, Restart Required

**freeConnectionsHighCount**

The high water mark of free connections in this Connector Pool since the pool was instantiated.

Type: int

Constraints: Read Only, Restart Required

**freePoolSizeHighWaterMark**

The FreePoolSizeHighWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

**freePoolSizeLowWaterMark**

The FreePoolSizeLowWaterMark of this Connector connection pool.

Type: long

Constraints: Read Only, Restart Required

**healthState**

The HealthState mbean for the application.

Type: weblogic.health.HealthState

Constraints: Read Only, Restart Required

**highestNumWaiters**

Gets the highest number of waiters.

Type: long

Constraints: Read Only, Restart Required

**initialCapacity**

The initial capacity configured for this Connector connection pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**key**

The configured Key for the Connection Factory using this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastShrinkTime**

Return the last time that the pool was shrunk.

**Type:** long

**Constraints:** Read Only, Restart Required

**logFileName**

The Log File used by the Resource Adapter for this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**logFileStreamOpened**

Gets the opened state of the log file stream represented by this instance.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**loggingEnabled**

Indicates whether logging is enabled for this Connector connection pool.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**managedConnectionFactoryClassName**

The ManagedConnectionFactoryName of this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**maxCapacity**

The maximum capacity configured for this Connector connection pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**numUnavailableCurrentCount**

Return the number of unavailable connections.

**Type:** int

**Constraints:** Read Only, Restart Required

**numUnavailableHighCount**

Return the highest unavailable number of connections at any given time.

**Type:** int

**Constraints:** Read Only, Restart Required

**numWaiters**

Gets the current number of waiters.

**Type:** long

**Constraints:** Read Only, Restart Required

**numWaitersCurrentCount**

Return the number of waiters.

**Type:** int

**Constraints:** Read Only, Restart Required

**poolName**

The configured Logical Name for the Connection Factory using this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**poolSizeHighWaterMark**

The PoolSizeHighWaterMark of this Connector connection pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**poolSizeLowWaterMark**

The PoolSizeLowWaterMark of this Connector connection pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**proxyOn**

Return a flag indicating if the proxy is on. Returns true if it is.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**recycledTotal**

The total number of Connector connections that have been recycled in this Connector Pool since the pool is instantiated.

**Type:** int

**Constraints:** Read Only, Restart Required

**runtimeTransactionSupport**

The real transaction support level in use at runtime.

**Type:** string

**Constraints:** Read Only, Restart Required

**shrinkCountDownTime**

The amount of time left (in minutes) until an attempt to shrink the pool will be made.

**Type:** int

**Constraints:** Read Only, Restart Required

**shrinkPeriodMinutes**

The Shrink Period (in minutes) of this Connector connection pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**shrinkingEnabled**

Specifies whether shrinking of this Connector connection pool is enabled.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**state**

Get the state of the pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**testable**

This indicates whether the connection pool is testable or not.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**transactionSupport**

The static transaction support level, either configured in ra.xml or in @Connector annotation, for the Resource Adapter for this Connector connection pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ConnectorConnectionRuntimeMBean

This class is used for monitoring individual WebLogic Connector connections

The properties of the weblogic.management.runtime.ConnectorConnectionRuntimeMBean entity are as follows:

**EISProductName**

Returns the EISProductName associated with the ManagedConnection's MetaData

**Type:** string

**Constraints:** Read Only, Restart Required

**EISProductVersion**

Returns the EISProductVersion associated with the ManagedConnection's MetaData.

**Type:** string

**Constraints:** Read Only, Restart Required

**activeHandlesCurrentCount**

The current total active connection handles for this connection.

**Type:** int

**Constraints:** Read Only, Restart Required

**activeHandlesHighCount**

The high water mark of active connection handles for this connection since the connection was created.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionFactoryClassName**

Returns the connection factory class name.

**Type:** string

**Constraints:** Read Only, Restart Required

**creationDurationTime**

Return the time taken to create the connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentlyInUse**

Indicates whether the connection is currently in use.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**deletable**

Indicates whether the connection can be closed manually through the console.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**handlesCreatedTotalCount**

The total number of connection handles created for this connection since the connection was created.

**Type:** int

**Constraints:** Read Only, Restart Required

**inTransaction**

Indicates whether the connection is currently in use in a transaction.

**Type:** boolean

**Constraints:** Read Only, Restart Required



**managedConnectionFactoryClassName**

Returns the managed connection factory class name.

**Type:** string

**Constraints:** Read Only, Restart Required

**maxConnections**

Returns the MaxConnections associated with the ManagedConnection's MetaData

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**reserveDurationTime**

Get the time taken to reserve this connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**reserveTime**

Return the last time the connection was reserved.

**Type:** long

**Constraints:** Read Only, Restart Required

**shared**

Indicates whether the connection is currently being shared by more than one invoker.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**transactionId**

Get the Transaction ID of the transaction that this connection is being used with.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**userName**

Returns the UserName associated with the ManagedConnection's MetaData

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ConnectorInboundRuntimeMBean

This class is used for monitoring inbound connections of resource adapters.

The properties of the weblogic.management.runtime.ConnectorInboundRuntimeMBean entity are as follows:

### **activationSpecClass**

The activation spec class.

**Type:** string

**Constraints:** Read Only, Restart Required

### **msgListenerType**

The message listener type.

**Type:** string

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **state**

Return the state of the Inbound connection. The values that are returned are : "Running" and "Suspended".

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ConnectorServiceRuntimeMBean

This interface defines the runtime information that can be accessed at a connector service level. Runtime information can be accessed at a per resource adapter level or at an overall level.

The properties of the weblogic.management.runtime.ConnectorServiceRuntimeMBean entity are as follows:

### **RACount**

Returns the number of resource adapters that have been deployed in the server. This count includes active RAs and Non-active RAs ( in the case of versioned RAs that are being replaced by a new version )

**Type:** int

**Constraints:** Read Only, Restart Required

**activeRACount**

Returns the number of resource adapters that are active.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean**

This class is used for monitoring Connector Work Manager of resource adapters.

The properties of the weblogic.management.runtime.ConnectorWorkManagerRuntimeMBean entity are as follows:

**activeLongRunningRequests**

Return The number of current active long-running work requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**completedLongRunningRequests**

The number of completed long-running work requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**maxConcurrentLongRunningRequests**

The maximum number of allowed concurrent long-running work requests. New work submission will be rejected if current running long-running work requests exceed the limit.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.EJBPoolRuntimeMBean

This interface contains accessor methods for all free pool runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBPoolRuntimeMBean entity are as follows:

### **accessTotalCount**

Provides a count of the total number of times an attempt was made to get an instance from the free pool.

**Type:** long

**Constraints:** Read Only, Restart Required

### **beansInUseCurrentCount**

Provides a count of the number of bean instances currently being used from the free pool.

**Type:** int

**Constraints:** Read Only, Restart Required

### **destroyedTotalCount**

Provides a count of the total number of times a bean instance from this pool was destroyed due to a non-application Exception being thrown from it.

**Type:** long

**Constraints:** Read Only, Restart Required

### **missTotalCount**

Provides a count of the total number of times a failed attempt was made to get an instance from the free pool. An Attempt to get a bean from the pool will fail if there are no available instances in the pool.

**Type:** long

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **pooledBeansCurrentCount**

Provides a count of the current number of available bean instances in the free pool.

**Type:** int

**Constraints:** Read Only, Restart Required

### **timeoutTotalCount**

Provides a count of the total number of Threads that have timed out waiting for an available bean instance from the free pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**waiterCurrentCount**

Provides a count of the number of Threads currently waiting for an available bean instance from the free pool.

**Type:** int

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.EJBTimerRuntimeMBean

This interface contains accessor methods for all EJB Timer runtime information collected for an EJB.

The properties of the weblogic.management.runtime.EJBTimerRuntimeMBean entity are as follows:

**activeTimerCount**

Provides the current number of active timers for this EJB

**Type:** int

**Constraints:** Read Only, Restart Required

**cancelledTimerCount**

Provides the total number of timers that have been explicitly cancelled for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**disabledTimerCount**

Provides the current number of timers temporarily disabled for this EJB

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**timeoutCount**

Provides the total number of successful timeout notifications that have been made for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.EJBTransactionRuntimeMBean**

This interface contains accessor methods for all transaction runtime information collected for an EJB.

The properties of the `weblogic.management.runtime.EJBTransactionRuntimeMBean` entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**transactionsCommittedTotalCount**

Provides a count of the total number of transactions that have been committed for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionsRolledBackTotalCount**

Provides a count of the total number of transactions that have been rolled back for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionsTimedOutTotalCount**

Provides a count of the total number of transactions that have timed out for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean**

This class is used for monitoring an XML Cache.

The properties of the `weblogic.management.runtime.EntityCacheCumulativeRuntimeMBean` entity are as follows:

**avgEntrySizeDiskPurged**

Provides the cumulative average size of entries that have been purged from the disk cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgEntrySizeMemoryPurged**

Provides the average size of the all the entries that have been purged from the memory.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPerEntryDiskSize**

Provides the current average size of the entries in the entity disk cache.

Returns the current average size of the entries in the entity disk cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPerEntryMemorySize**

Provides the current average size of the entries in the entity memory cache.

Returns the current average size of the entries in the entity memory cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPercentPersistent**

Provides the current average percentage of entries in the entity cache that have been persisted to the disk cache.

Returns current average percentage of entries in the entity cache that have been persisted to the disk cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPercentTransient**

Provides the current average percentage of entries in the entity cache that are transient, or have not been persisted.

Returns current average percentage of entries in the entity cache that are transient, or have not been persisted.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgTimeout**

Provides the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Returns the average amount of time that the entity cache has timed out when trying to retrieve an entity.

**Type:** double

**Constraints:** Read Only, Restart Required

**diskPurgesPerHour**

Provides cumulative average number of purges from the disk cache per hour.

**Type:** double

**Constraints:** Read Only, Restart Required

**maxEntryMemorySize**

Provides the current maximum size of the entries in the entity memory cache.

Returns the current maximum size of the entries in the entity memory cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**maxEntryTimeout**

Provides the largest timeout value for any current entry in the entity cache.

Returns the largest timeout value for any current entry in the entity cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**memoryPurgesPerHour**

Provides the cumulative average number of entries that have been purged from the entity cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**minEntryMemorySize**

Provides the current minimum size of the entries in the entity memory cache.

Returns the current minimum size of the entries in the entity memory cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**minEntryTimeout**

Provides the smallest timeout value for any current entry in the entity cache.

Returns the smallest timeout value for any current entry in the entity cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**mostRecentDiskPurge**

Provides the date of the most recent purge from the disk cache.

**Type:** java.util.Date

**Constraints:** Read Only, Restart Required

**mostRecentMemoryPurge**

Provides the date of the most recent purge of the entity cache.

**Type:** java.util.Date

**Constraints:** Read Only, Restart Required



**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**percentRejected**

Provides the cumulative percent of the potential entries to the entity cache that have been rejected.

**Type:** double

**Constraints:** Read Only, Restart Required

**totalCurrentEntries**

Provides a count of the total current number of entries in the entity cache.

Returns the total current number of entries in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalItemsDiskPurged**

Provides the total number of items that have been purged from the disk cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalItemsMemoryPurged**

Provides the cumulative number of items that have been purged from the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalNumberDiskPurges**

Provides a count of the total number of entries that have been purged from the disk cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalNumberMemoryPurges**

Provides the cumulative number of entries that have been purged from the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalNumberOfRejections**

Provides the cumulative total number of rejections of entries from the entity cache for the current session.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalNumberOfRenewals**

Provides a count of the cumulative number of entries that have been refreshed in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalPersistentCurrentEntries**

Provides a count of the total current number of entries in the cache that have been persisted to disk.

Returns the total current number of entries in the cache that have been persisted to disk.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSizeOfRejections**

Provides the cumulative total size of the rejections from the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalTransientCurrentEntries**

Provides a count of the total current number of transient (not yet persisted to disk) entries in the entity cache.

Returns the total current number of transient entries in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean**

This class is used for monitoring the size and usage of an XML Cache.

The properties of the `weblogic.management.runtime.EntityCacheCurrentStateRuntimeMBean` entity are as follows:

**avgPerEntryDiskSize**

Provides the current average size of the entries in the entity disk cache.

Returns the current average size of the entries in the entity disk cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPerEntryMemorySize**

Provides the current average size of the entries in the entity memory cache.

Returns the current average size of the entries in the entity memory cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPercentPersistent**

Provides the current average percentage of entries in the entity cache that have been persisted to the disk cache.

Returns current average percentage of entries in the entity cache that have been persisted to the disk cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgPercentTransient**

Provides the current average percentage of entries in the entity cache that are transient, or have not been persisted.

Returns current average percentage of entries in the entity cache that are transient, or have not been persisted.

**Type:** double

**Constraints:** Read Only, Restart Required

**avgTimeout**

Provides the average amount of time that the entity cache has timed out when trying to retrieve an entity.

Returns the average amount of time that the entity cache has timed out when trying to retrieve an entity.

**Type:** double

**Constraints:** Read Only, Restart Required

**diskUsage**

Provides the current size of the entity disk cache.

Returns the current size of the entity disk cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**maxEntryMemorySize**

Provides the current maximum size of the entries in the entity memory cache.

Returns the current maximum size of the entries in the entity memory cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**maxEntryTimeout**

Provides the largest timeout value for any current entry in the entity cache.

Returns the largest timeout value for any current entry in the entity cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**memoryUsage**

Provides the current size of the entity memory cache.

Returns current size of the entity memory cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**minEntryMemorySize**

Provides the current minimum size of the entries in the entity memory cache.

Returns the current minimum size of the entries in the entity memory cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**minEntryTimeout**

Provides the smallest timeout value for any current entry in the entity cache.

Returns the smallest timeout value for any current entry in the entity cache.

**Type:** double

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalCurrentEntries**

Provides a count of the total current number of entries in the entity cache.

Returns the total current number of entries in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalPersistentCurrentEntries**

Provides a count of the total current number of entries in the cache that have been persisted to disk.

Returns the total current number of entries in the cache that have been persisted to disk.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalTransientCurrentEntries**

Provides a count of the total current number of transient (not yet persisted to disk) entries in the entity cache.

Returns the total current number of transient entries in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ExecuteQueueRuntimeMBean**

This bean is used to monitor an execute queue and its associated thread pool.

The properties of the weblogic.management.runtime.ExecuteQueueRuntimeMBean entity are as follows:

### **executeThreadCurrentIdleCount**

The number of idle threads assigned to the queue.

**Type:** int

**Constraints:** Read Only, Restart Required

### **executeThreadTotalCount**

The total number of execute threads assigned to the queue.

**Type:** int

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **pendingRequestCurrentCount**

The number of waiting requests in the queue.

**Type:** int

**Constraints:** Read Only, Restart Required

### **pendingRequestOldestTime**

The time since the longest waiting request was placed in the queue.

**Type:** long

**Constraints:** Read Only, Restart Required

### **servicedRequestTotalCount**

The number of requests that have been processed by the queue.

**Type:** int

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.FairShareConstraintRuntimeMBean

The properties of the weblogic.management.runtime.FairShareConstraintRuntimeMBean entity are as follows:

**activated**

Returns true if trigger was successfully executed.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**initiated**

Returns true if trigger execution has begun.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**lastTimeExecuted**

Return last trigger execution date and time.

**Type:** java.util.Date

**Constraints:** Read Only, Restart Required

**name**

Return name of the Resource.

**Type:** string

**Constraints:** Read Only, Restart Required

**recourseActionEventsHistory**

Return details of trigger execution in the past.

**Type:** array of weblogic.management.runtime.RecourseActionEventVBean

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JDBCDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Data Source and its associated connection pool.

The properties of the weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity are as follows:

**activeConnectionsAverageCount**

Average number of active connections in this instance of the data source.

Active connections are connections in use by an application. This value is only valid if the resource is configured to allow shrinking.

**Type:** int

**Constraints:** Read Only, Restart Required

**activeConnectionsCurrentCount**

The number of connections currently in use by applications.

**Type:** int

**Constraints:** Read Only, Restart Required

**activeConnectionsHighCount**

Highest number of active database connections in this instance of the data source since the data source was instantiated.

Active connections are connections in use by an application.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionDelayTime**

The average amount of time, in milliseconds, that it takes to create a physical connection to the database.

The value is calculated as summary of all times to connect divided by the total number of connections.

**Type:** int

**Constraints:** Read Only, Restart Required

**connectionsTotalCount**

The cumulative total number of database connections created in this data source since the data source was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**currCapacity**

The current count of JDBC connections in the connection pool in the data source.

**Type:** int

**Constraints:** Read Only, Restart Required

**currCapacityHighCount**

Highest number of database connections available or in use (current capacity) in this instance of the data source since the data source was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**databaseProductName**

The product name of the database that this data source is connected to.

**Type:** string

**Constraints:** Read Only, Restart Required

**databaseProductVersion**

The product version of the database that this data source is connected to.

**Type:** string

**Constraints:** Read Only, Restart Required

**deploymentState**

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

**Type:** int

**Constraints:** Read Only, Restart Required

**driverName**

The product name of the JDBC driver that this data source is configured to use.

**Type:** string

**Constraints:** Read Only, Restart Required

**driverVersion**

The version of the JDBC driver that this data source is configured to use.

**Type:** string

**Constraints:** Read Only, Restart Required

**enabled**

Indicates whether the data source is enabled or disabled:

- true if the data source is enabled.
- false if the data source is disabled.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**failedReserveRequestCount**

The cumulative, running count of requests for a connection from this data source that could not be fulfilled.

**Type:** long

**Constraints:** Read Only, Restart Required

**failuresToReconnectCount**

The number of times that the data source attempted to refresh a database connection and failed.

Failures may occur when the database is unavailable or when the network connection to the database is interrupted.

**Type:** int

**Constraints:** Read Only, Restart Required



**highestNumAvailable**

Highest number of database connections that were idle and available to be used by an application at any time in this instance of the data source since the data source was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**highestNumUnavailable**

Highest number of database connections that were in use by applications or being tested by the system in this instance of the data source since the data source was deployed.

**Type:** int

**Constraints:** Read Only, Restart Required

**lastTask**

Get the last datasource Task

**Type:** weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean reference

**Constraints:** Read Only, Restart Required

**leakedConnectionCount**

The number of leaked connections. A leaked connection is a connection that was reserved from the data source but was not returned to the data source by calling `close()`

**Type:** int

**Constraints:** Read Only, Restart Required

**moduleId**

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**numAvailable**

The number of database connections that are currently idle and available to be used by applications in this instance of the data source.

**Type:** int

**Constraints:** Read Only, Restart Required

**numUnavailable**

The number of connections currently in use by applications or being tested in this instance of the data source.

**Type:** int

**Constraints:** Read Only, Restart Required

**prepStmtCacheAccessCount**

The cumulative, running count of the number of times that the statement cache was accessed.

**Type:** long

**Constraints:** Read Only, Restart Required

**prepStmtCacheAddCount**

The cumulative, running count of the number of statements added to the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements added to the caches for all connections in the connection pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**prepStmtCacheCurrentSize**

The number of prepared and callable statements currently cached in the statement cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements in the caches for all connections in the connection pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**prepStmtCacheDeleteCount**

The cumulative, running count of statements discarded from the cache.

Each connection in the connection pool has its own cache of statements. This number is the sum of the number of statements that were discarded from the caches for all connections in the connection pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**prepStmtCacheHitCount**

The cumulative, running count of the number of times that statements from the cache were used.

**Type:** int

**Constraints:** Read Only, Restart Required

**prepStmtCacheMissCount**

The number of times that a statement request could not be satisfied with a statement from the cache.

**Type:** int

**Constraints:** Read Only, Restart Required

**properties**

The list of properties for a data source that are passed to the JDBC driver when creating database connections.

This is a privileged operation that can only be invoked by an authorized user.

**Type:** java.util.Properties

**Constraints:** Read Only, Restart Required

**reserveRequestCount**

The cumulative, running count of requests for a connection from this data source.

**Type:** long

**Constraints:** Read Only, Restart Required

**state**

The current state of the data source.

Possible states are:

- **Running** - the data source is enabled (deployed and not *Suspended*). This is the normal state of the data source. This state includes conditions when the database server is not available and the data source is created (creation retry must be enabled) or when all connections have failed connection tests (on creation, on reserve, or periodic testing).
- **Suspended** - the data source has been disabled.
- **Shutdown** - the data source is shutdown and all database connections have been closed.
- **Overloaded** - all resources in pool are in use.
- **Unknown** - the data source state is unknown.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**versionJDBCDriver**

The driver class name of the JDBC driver used to create database connections.

**Type:** string

**Constraints:** Read Only, Restart Required

**waitSecondsHighCount**

The highest number of seconds that an application waited for a connection (the longest connection reserve wait time) from this instance of the connection pool since the connection pool was instantiated.

This value is updated when a completed `getConnection` request takes longer to return a connection than any previous request.

**Type:** int

**Constraints:** Read Only, Restart Required

**waitingForConnectionCurrentCount**

The number of connection requests waiting for a database connection.

**Type:** int

**Constraints:** Read Only, Restart Required

**waitingForConnectionFailureTotal**

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually failed to get a connection.

Waiting connection requests can fail for a variety of reasons, including waiting for longer than the `ConnectionReserveTimeoutSeconds`.

**Type:** long

**Constraints:** Read Only, Restart Required

**waitingForConnectionHighCount**

Highest number of application requests concurrently waiting for a connection from this instance of the data source.

**Type:** int

**Constraints:** Read Only, Restart Required

**waitingForConnectionSuccessTotal**

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection and eventually succeeded in getting a connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**waitingForConnectionTotal**

The cumulative, running count of requests for a connection from this data source that had to wait before getting a connection, including those that eventually got a connection and those that did not get a connection.

**Type:** long

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean**

The properties of the `weblogic.management.runtime.JDBCDataSourceTaskRuntimeMBean` entity are as follows:

**completed**

This property indicates whether an asynchronous job has completed.

**Type:** boolean

**description**

A description of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**endTime**

This property indicates the time when the asynchronous job ended.

**Type:** java.util.Date

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**parentTask**

The task of which this task is a part.

A value of null indicates that this task is not a subtask.

**Type:** weblogic.management.runtime.TaskRuntimeMBean reference

**Constraints:** Read Only, Restart Required

**progress**

The progress of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**running**

Indicates whether the task is still running.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**startTime**

This property indicates the time when an asynchronous job was started.

**Type:** java.util.Date

**startTimeAsLong**

The time at which this task was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**systemTask**

Indicates whether this task was initiated by the server versus a user.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**taskError**

Returns an exception describing the error, if any, that occurred while performing this task.

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**taskStatus**

The status of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JDBCDataSourceRuntimeMBean

This class maps to a JDBCDataSource JMO

The properties of the weblogic.management.runtime.JDBCDataSourceRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean

This class is used for monitoring a WebLogic JDBC Multi Data Source and its associated data sources.

The properties of the weblogic.management.runtime.JDBCMultiDataSourceRuntimeMBean entity are as follows:

**deploymentState**

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- UNPREPARED. State indicating at this module is neither prepared or active.
- PREPARED. State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- ACTIVATED. State indicating at this module is currently active.
- NEW. State indicating this module has just been created and is being initialized.

**Type:** int

**Constraints:** Read Only, Restart Required

**maxCapacity**

The maximum capacity of this multi data source. The maximum capacity is: - Maximum capacity of first available (not suspended) data source in the list, if the multi data source is using the FAILOVER algorithm (the `FailoverRequestIfBusy` flag is not set). - Sum of maximum capacities of all available (not suspended) data sources, if the multi data source is using other algorithms.

**Type:** int

**Constraints:** Read Only, Restart Required

**moduleId**

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JDBCPartitionRuntimeMBean

Partition monitoring of WebLogic JDBC resources

The properties of the `weblogic.management.runtime.JDBCPartitionRuntimeMBean` entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean

This class is used to get replay statistics for an Oracle replay datasource aggregated across all connections in the pool.

The properties of the `weblogic.management.runtime.JDBCReplayStatisticsRuntimeMBean` entity are as follows:

### **deploymentState**

The current deployment state of the module.

A module can be in one and only one of the following states. State can be changed via deployment or administrator console.

- **UNPREPARED.** State indicating at this module is neither prepared or active.
- **PREPARED.** State indicating at this module of this application is prepared, but not active. The classes have been loaded and the module has been validated.
- **ACTIVATED.** State indicating at this module is currently active.
- **NEW.** State indicating this module has just been created and is being initialized.

**Type:** int

**Constraints:** Read Only, Restart Required

### **failedReplayCount**

Obtains the number of replays that failed.

When replay fails, it rethrows the original `SQLRecoverableException` to the application, with the reason for the failure chained to that original exception. Application can call `getNextException` to retrieve the reason.

**Type:** long

**Constraints:** Read Only, Restart Required

### **moduleId**

Returns the identifier for this Component. The identifier is unique within the application.

Typical modules will use the URI for their id. Web Modules will return their context-root since the web-uri may not be unique within an EAR.

**Type:** string

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **replayDisablingCount**

Obtains the number of times that replay is disabled. When replay is disabled in the middle of a request, the remaining calls in that request are no longer protected by AC. In case an outage strikes one of those remaining calls, no replay will be attempted, and application simply gets an `SQLRecoverableException`.

**Type:** long



**Constraints:** Read Only, Restart Required

**successfulReplayCount**

Obtains the number of replays that succeeded. Successful replays mask the outages from applications.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCalls**

Obtains the total number of JDBC calls executed so far.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCallsAffectedByOutages**

Obtains the number of JDBC calls affected by outages. This includes both local calls and calls that involve roundtrip(s) to the database server.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCallsAffectedByOutagesDuringReplay**

Obtains the number of JDBC calls affected by outages in the middle of replay. Outages may be cascaded and strike a call multiple times when replay is ongoing. AC automatically reattempts replay when this happens, unless it reaches the maximum retry limit.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCallsTriggeringReplay**

Obtains the number of JDBC calls that triggered replay. Not all the calls affected by an outage trigger replay, because replay can be disabled for some requests.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCompletedRequests**

Obtains the total number of completed requests so far.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalProtectedCalls**

Obtains the total number of JDBC calls executed so far that are protected by AC.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalReplayAttempts**

Obtains the number of replay attempts. AC automatically reattempts when replay fails, so this number may exceed the number of JDBC calls that triggered replay.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalRequests**

Obtains the total number of successfully submitted requests so far.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JDBCServiceRuntimeMBean**

This class is used for monitoring a WebLogic JDBC service. It maps to a JDBCResource JMO.

The properties of the weblogic.management.runtime.JDBCServiceRuntimeMBean entity are as follows:

**healthState**

The health state of the JDBC subsystem.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JMSConnectionRuntimeMBean**

This class is used for monitoring a WebLogic JMS connection.

The properties of the weblogic.management.runtime.JMSConnectionRuntimeMBean entity are as follows:

**clientID**

The client ID for this connection.

**Type:** string

**Constraints:** Read Only, Restart Required

**clientIDPolicy**

The ClientIDPolicy on this connection or durable subscriber.

Values are:

- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular `ClientID`
- `weblogic.management.configuration.JMSConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any `ClientID`, even when other restricted or unrestricted connections already use the same `ClientID`

**Type:** string

**Constraints:** Read Only, Restart Required

#### **hostAddress**

The host address of the client JVM as a string.

**Type:** string

**Constraints:** Read Only, Restart Required

#### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

#### **sessionsCurrentCount**

The current number of sessions for this connection.

**Type:** long

**Constraints:** Read Only, Restart Required

#### **sessionsHighCount**

The peak number of sessions for this connection since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

#### **sessionsTotalCount**

The number of sessions on this connection since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

#### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JMSConsumerRuntimeMBean**

This class is used for monitoring a WebLogic JMS consumer.

The properties of the `weblogic.management.runtime.JMSConsumerRuntimeMBean` entity are as follows:

**active**

Indicates whether the consumer active. A consumer is active if it has a message listener set up or a synchronous receive in progress.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**bytesPendingCount**

The number of bytes pending (uncommitted and unacknowledged) by this consumer.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received by this consumer since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**clientID**

The client ID for this connection.

**Type:** string

**Constraints:** Read Only, Restart Required

**clientIDPolicy**

The ClientIDPolicy on this connection or durable subscriber.

Valid values are:

- `weblogic.management.configuration.JMSCConstants.CLIENT_ID_POLICY_RESTRICTED`: Only one connection that uses this policy exists in a cluster at any given time for a particular ClientID
- `weblogic.management.configuration.JMSCConstants.CLIENT_ID_POLICY_UNRESTRICTED`: Connections created using this policy can specify any ClientID, even when other restricted or unrestricted connections already use the same ClientID

**Type:** string

**Constraints:** Read Only, Restart Required

**destinationName**

The name of the destination for this consumer. In case of a distributed destination, it is the name of the distributed destination, instead of the member destination.

**Type:** string

**Constraints:** Read Only, Restart Required

**durable**

Indicates whether the consumer is durable.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**memberDestinationName**

The name of the destination for this consumer. In case of a distributed destination, it is the name of the member destination.

**Type:** string

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The number of messages pending (uncommitted and unacknowledged) by this consumer.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received by this consumer since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**selector**

The selector associated with this consumer, if any.

**Type:** string

**Constraints:** Read Only, Restart Required

**subscriptionSharingPolicy**

The Subscription Sharing Policy on this subscriber.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSDestinationRuntimeMBean

This class is used for monitoring a WebLogic JMS destination (topic or queue).

The properties of the weblogic.management.runtime.JMSDestinationRuntimeMBean entity are as follows:

**bytesCurrentCount**

The current number of bytes stored in the destination. This does not include the pending bytes.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesHighCount**

The peak number of bytes stored in the destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesPendingCount**

The number of pending bytes stored in the destination.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received in this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesThresholdTime**

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

**consumersCurrentCount**

The current number of consumers accessing this destination.

Type: long

Constraints: Read Only, Restart Required

**consumersHighCount**

The peak number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

**consumersTotalCount**

The total number of consumers accessing this destination since the last reset.

Type: long

Constraints: Read Only, Restart Required

**consumptionPaused**

Indicates the consumption Pause state of the destination.

Type: boolean

Constraints: Read Only, Restart Required

**consumptionPausedState**

The current consumption pause state of the destination.

Type: string

Constraints: Read Only, Restart Required

**destinationType**

The destination type, either

`weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_QUEUE` or `weblogic.management.configuration.JMSConstants.DESTINATION_TYPE_TOPIC` depending upon whether the destination is a queue or topic.

**Type:** string

**Constraints:** Read Only, Restart Required

**insertionPaused**

Indicates the InsertionPause state of the destination.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**insertionPausedState**

The current insertion pause state of the destination.

**Type:** string

**Constraints:** Read Only, Restart Required

**messagesCurrentCount**

The current number of messages in the destination. This does not include the pending messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesDeletedCurrentCount**

Returns the number of messages that have been deleted from the destination.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesHighCount**

The peak number of messages in the destination since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesMovedCurrentCount**

Returns the number of messages that have been moved from the destination.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The number of pending messages in the destination.

Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or that has been received and not committed or acknowledged.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received in this destination since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesThresholdTime**

The amount of time in the threshold condition since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**productionPaused**

Indicates the ProductionPause state of the destination.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**productionPausedState**

The current production pause state of the destination.

**Type:** string

**Constraints:** Read Only, Restart Required

**state**

The operational state of the destination as a String.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean**

This class is used for monitoring a WebLogic JMS durable subscriber.

The properties of the weblogic.management.runtime.JMSDurableSubscriberRuntimeMBean entity are as follows:

**active**

Indicates whether this subscription is being used by a durable subscriber.

**Type:** boolean

**Constraints:** Read Only, Restart Required



**bytesCurrentCount**

The number of bytes received by this durable subscriber.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesPendingCount**

The number of bytes pending by this durable subscriber.

**Type:** long

**Constraints:** Read Only, Restart Required

**clientID**

A unique client identifier for this durable subscriber.

**Note:** The client ID is not necessarily equivalent to the WebLogic Server username; that is, a name used to authenticate a user in the WebLogic security realm. You can set the client ID to the WebLogic Server username if it is appropriate for your JMS application.

**Type:** string

**Constraints:** Read Only, Restart Required

**clientIDPolicy**

The policy for the client identifier for this durable subscriber.

**Note:** The client ID policy is either `Restricted` or `Unrestricted`.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastMessagesReceivedTime**

The time when the last time a subscriber received a message from the subscription. The returned value is a standard java absolute time, which is measured in milliseconds since midnight, January 1, 1970 UTC

This returns the JMS durable subscription boot time if there were no messages that were successfully delivered to any subscriber on this subscription since the subscription was booted. We define the boot time of a durable subscription to be the time the subscription is originally created or recovered during a server reboot or jms migration, which ever is latest.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesCurrentCount**

The number of messages still available by this durable subscriber.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesDeletedCurrentCount**

Returns the number of messages that have been deleted from the destination.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesHighCount**

The peak number of messages for the durable subscriber since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesMovedCurrentCount**

Returns the number of messages that have been moved from the destination.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The number of messages pending (uncommitted and unacknowledged) by this durable subscriber.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received by the durable subscriber since that reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**noLocal**

Specifies whether this durable subscriber receives local messages that it has published.

To prevent this, set the `noLocal` parameter to `true`

**Type:** boolean

**Constraints:** Read Only, Restart Required

**selector**

The message selector defined for this durable subscriber.

**Type:** string

**Constraints:** Read Only, Restart Required

**subscribersCurrentCount**

The number of subscribers that currently share this subscription.

**Type:** int

**Constraints:** Read Only, Restart Required, Has Default Value: 0

**subscribersHighCount**

The highest number of subscribers that have shared this subscription at the same time since the creation or the last reboot of the subscription, which ever is later.

**Type:** int

**Constraints:** Read Only, Restart Required, Has Default Value: 0

**subscribersTotalCount**

The total number of subscribers that have accessed this subscription since the creation or the last reboot of the subscription, whichever is later.

**Type:** int

**Constraints:** Read Only, Restart Required, Has Default Value: 0

**subscriptionName**

The subscription name for this durable subscriber. This name must be unique for each client ID.

Valid durable subscription names cannot include the following characters: comma ",", equals "=", colon ":", asterisk "\*", percent "%", or question mark "?".

**Type:** string

**Constraints:** Read Only, Restart Required

**subscriptionSharingPolicy**

The SubscriptionSharingPolicy on this subscriber.

**Type:** string

**Constraints:** Read Only, Restart Required, Has Default Value: Exclusive

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSProducerRuntimeMBean

This class is used for monitoring a WebLogic JMS producer.

The properties of the weblogic.management.runtime.JMSProducerRuntimeMBean entity are as follows:

**bytesPendingCount**

The number of bytes pending (uncommitted and unacknowledged) by this producer.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesSentCount**

The number of bytes sent by this producer since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The number of messages pending (uncommitted and unacknowledged) by this producer.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesSentCount**

The number of messages sent by this producer since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSRuntimeMBean

This class is used for monitoring a WebLogic JMS service.

The properties of the weblogic.management.runtime.JMSRuntimeMBean entity are as follows:

**JMSServersCurrentCount**

The current number of JMS servers that are deployed on this WebLogic Server instance.

**Type:** long

**Constraints:** Read Only, Restart Required

**JMSServersHighCount**

The highest number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**JMSServersTotalCount**

The total number of JMS servers that were deployed on this WebLogic Server instance since this server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionsCurrentCount**

The current number of connections to WebLogic Server server.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionsHighCount**

The highest number of connections to this WebLogic Server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionsTotalCount**

The total number of connections made to this WebLogic Server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**healthState**

The health state of this JMS service.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSServerRuntimeMBean

This class is used for monitoring a WebLogic JMS server.

The properties of the weblogic.management.runtime.JMSServerRuntimeMBean entity are as follows:

**bytesCurrentCount**

The current number of bytes stored on this JMS server.

This number does not include the pending bytes.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesHighCount**

The peak number of bytes stored in the JMS server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesPageableCurrentCount**

Return the total number of bytes in all the messages that are currently available to be paged out, but which have not yet been paged out. The JMS server attempts to keep this number smaller than the "MessageBufferSize" parameter.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesPagedInTotalCount**

Return the total number of bytes that were read from the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

**bytesPagedOutTotalCount**

Return the total number of bytes that were written to the paging directory since the JMS server was started.

Type: long

Constraints: Read Only, Restart Required

**bytesPendingCount**

The current number of bytes pending (unacknowledged or uncommitted) stored on this JMS server.

Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received on this JMS server since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesThresholdTime**

The amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

**consumptionPaused**

Returns the current consumption paused state of the JMSServer as boolean value.

Type: boolean

Constraints: Read Only, Restart Required

**consumptionPausedState**

Returns the current consumption paused state of the JMSServer as string value.

Type: string

Constraints: Read Only, Restart Required

**destinationsCurrentCount**

The current number of destinations for this JMS server.

Type: long

Constraints: Read Only, Restart Required

**destinationsHighCount**

The peak number of destinations on this JMS server since the last reset.

Type: long

**Constraints:** Read Only, Restart Required

**destinationsTotalCount**

The number of destinations instantiated on this JMS server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**healthState**

The health state of this JMS server.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**insertionPaused**

Returns the current insertion paused state of the JMSServer as boolean value.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**insertionPausedState**

Returns the current insertion paused state of the JMSServer as string value.

**Type:** string

**Constraints:** Read Only, Restart Required

**messagesCurrentCount**

The current number of messages stored on this JMS server. This number does not include the pending messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesHighCount**

The peak number of messages stored in the JMS server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPageableCurrentCount**

Return the number of messages that are currently available for paging in this JMS server but have not yet been paged out. Note that due to internal implementation details, this count may be zero even if "PageableByteCurrentCount" is zero.

**Type:** int

**Constraints:** Read Only, Restart Required

**messagesPagedInTotalCount**

Return the total number of messages that were read from the paging directory since the JMS server was started.

**Type:** int

**Constraints:** Read Only, Restart Required

**messagesPagedOutTotalCount**

Return the total number of messages that were written to the paging directory since the JMS server was started.

**Type:** int

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The current number of messages pending (unacknowledged or uncommitted) stored on this JMS server.

Pending messages are over and above the current number of messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received on this destination since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesThresholdTime**

The amount of time in the threshold condition since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**pagingAllocatedIoBufferBytes**

See PersistentStoreRuntimeMBean.AllocatedIoBufferBytes

**Type:** long

**Constraints:** Read Only, Restart Required

**pagingAllocatedWindowBufferBytes**

See PersistentStoreRuntimeMBean.AllocatedWindowBufferBytes

**Type:** long

**Constraints:** Read Only, Restart Required

**pagingPhysicalWriteCount**

See PersistentStoreRuntimeMBean.PhysicalWriteCount

**Type:** long

**Constraints:** Read Only, Restart Required

**pendingTransactions**

Returns an array of Xids representing transaction branches that exist on this JMS server in the pending state, i.e. branches that have been prepared by the transaction manager but not yet committed or rolled back.

**Type:** array of string

**Constraints:** Read Only, Restart Required



**productionPaused**

Returns the current production paused state of the JMS Server as boolean value.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**productionPausedState**

Returns the current production paused state of the JMS Server as string value.

**Type:** string

**Constraints:** Read Only, Restart Required

**sessionPoolsCurrentCount**

The current number of session pools instantiated on this JMS server.

**Type:** long

**Constraints:** Read Only, Restart Required

**sessionPoolsHighCount**

The peak number of session pools instantiated on this JMS server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**sessionPoolsTotalCount**

The number of session pools instantiated on this JMS server since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactions**

Returns an array of Xids representing transaction branches that exist on this JMS server in any state.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSSessionPoolRuntimeMBean

This class is used for monitoring a WebLogic JMS session pool.

The properties of the weblogic.management.runtime.JMSSessionPoolRuntimeMBean entity are as follows:

**connectionConsumersCurrentCount**

The current number of connection consumers for this session pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionConsumersHighCount**

The peak number of simultaneous connection consumers for this session pool.

**Type:** long

**Constraints:** Read Only, Restart Required

**connectionConsumersTotalCount**

The total number of connection consumers made by this session pool since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JMSSessionRuntimeMBean

This class is used for monitoring a WebLogic JMS session.

The properties of the weblogic.management.runtime.JMSSessionRuntimeMBean entity are as follows:

**acknowledgeMode**

The acknowledge mode as one of the following:

- AUTO\_ACKNOWLEDGE
- CLIENT\_ACKNOWLEDGE
- DUPS\_OK\_ACKNOWLEDGE
- NO\_ACKNOWLEDGE

**Type:** string

**Constraints:** Read Only, Restart Required

**bytesPendingCount**

The number of bytes pending (uncommitted and unacknowledged) for this session.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received by this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesSentCount**

The number of bytes sent by this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**consumersCurrentCount**

The current number of consumers for this session.

**Type:** long

**Constraints:** Read Only, Restart Required

**consumersHighCount**

The peak number of consumers for this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**consumersTotalCount**

The number of consumers instantiated by this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

The number of messages pending (uncommitted and unacknowledged) for this session.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received by this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesSentCount**

The number of bytes sent by this session since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**producersCurrentCount**

The current number of producers for this session.

**Type:** long

**Constraints:** Read Only, Restart Required

**producersHighCount**

The peak number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

**producersTotalCount**

The number of producers for this session since the last reset.

Type: long

Constraints: Read Only, Restart Required

**transacted**

Indicates whether the session is transacted.

Type: boolean

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## weblogic.management.runtime.JTAPartitionRuntimeMBean

This interface is used for accessing transaction runtime characteristics within a WebLogic server.

The properties of the weblogic.management.runtime.JTAPartitionRuntimeMBean entity are as follows:

**activeTransactionsTotalCount**

The number of active transactions on the server.

Type: int

Constraints: Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**registeredNonXAResourceNames**

An array of NonXA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

**registeredResourceNames**

An array of XA resource names that are registered with the transaction manager.

Type: array of string

Constraints: Read Only, Restart Required

**secondsActiveTotalCount**

The total number of seconds that transactions were active for all committed transactions.

Type: long

Constraints: Read Only, Restart Required

**transactionAbandonedTotalCount**

The total number of transactions that were abandoned since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionCommittedTotalCount**

The total number of transactions committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionHeuristicsTotalCount**

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionLLRCommittedTotalCount**

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionNoResourcesCommittedTotalCount**

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionOneResourceOnePhaseCommittedTotalCount**

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionReadOnlyOnePhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackAppTotalCount**

The number of transactions that were rolled back due to an application error.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackResourceTotalCount**

The number of transactions that were rolled back due to a resource error.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackSystemTotalCount**

The number of transactions that were rolled back due to an internal system error.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackTimeoutTotalCount**

The number of transactions that were rolled back due to a timeout expiration.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackTotalCount**

The number of transactions that were rolled back since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTotalCount**

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedLoggedTotalCount**

The total number of two phase commit transactions that were committed with TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedNotLoggedTotalCount**

The total number of two phase committed transactions that were committed without TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JTARecoveryRuntimeMBean

This interface is used for accessing transaction runtime characteristics for recovered transactions that are associated with a particular Transaction Recovery Service.

The properties of the weblogic.management.runtime.JTARecoveryRuntimeMBean entity are as follows:

**active**

Indicates whether the Transaction Recovery Service is currently activated on this server.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**initialRecoveredTransactionTotalCount**

The total number of transactions that are recovered from the transaction log initially.

**Type:** int

**Constraints:** Read Only, Restart Required

**initialRecoveredUnloggedTransactionTotalCount**

The total number of transactions that are recovered from the no transaction log initially.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**recoveredTransactionCompletionPercent**

The percentage of transactions that are recovered from the transaction log initially.

**Type:** int

**Constraints:** Read Only, Restart Required

**recoveredUnloggedTransactionCompletionPercent**

The percentage of transactions that are recovered from the no transaction log initially.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JTARuntimeMBean

This interface is used for accessing transaction runtime characteristics within a WebLogic server.

The properties of the weblogic.management.runtime.JTARuntimeMBean entity are as follows:

### **activeTransactionsTotalCount**

The number of active transactions on the server.

**Type:** int

**Constraints:** Read Only, Restart Required

### **healthState**

The health state of the JTA subsystem. for state values.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **registeredNonXAResourceNames**

An array of NonXA resource names that are registered with the transaction manager.

**Type:** array of string

**Constraints:** Read Only, Restart Required

### **registeredResourceNames**

An array of XA resource names that are registered with the transaction manager.

**Type:** array of string

**Constraints:** Read Only, Restart Required

### **secondsActiveTotalCount**

The total number of seconds that transactions were active for all committed transactions.

**Type:** long

**Constraints:** Read Only, Restart Required

### **transactionAbandonedTotalCount**

The total number of transactions that were abandoned since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

### **transactionCommittedTotalCount**

The total number of transactions committed since the server was started.



Type: long

Constraints: Read Only, Restart Required

**transactionHeuristicsTotalCount**

The number of transactions that completed with a heuristic status since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionLLRCommittedTotalCount**

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionNoResourcesCommittedTotalCount**

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionOneResourceOnePhaseCommittedTotalCount**

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionReadOnlyOnePhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackAppTotalCount**

The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackResourceTotalCount**

The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackSystemTotalCount**

The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackTimeoutTotalCount**

The number of transactions that were rolled back due to a timeout expiration.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackTotalCount**

The number of transactions that were rolled back since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTotalCount**

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedLoggedTotalCount**

The total number of two phase commit transactions that were committed with TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedNotLoggedTotalCount**

The total number of two phase committed transactions that were committed without TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JVMRuntimeMBean

Provides methods for retrieving information about the Java Virtual Machine (JVM) within which the current server instance is running. You cannot change the JVM's operating parameters while the JVM is active. Instead, use the startup options that are described in the JVM's documentation.

The WebLogic JVM contains only one of these Runtime MBeans:

- If the JVM is an instance of a JRockit JDK, then the JVM contains `JRockitRuntimeMBean`

- Otherwise, it contains the `JVMRuntimeMBean`

The properties of the `weblogic.management.runtime.JVMRuntimeMBean` entity are as follows:

**OSName**

Returns the operating system on which the JVM is running.

The operating system on which the JVM is running.

**Type:** string

**Constraints:** Read Only, Restart Required

**OSVersion**

The version of the operating system on which the JVM is running.

**Type:** string

**Constraints:** Read Only, Restart Required

**heapFreeCurrent**

The current amount of memory (in bytes) that is available in the JVM heap.

**Type:** long

**Constraints:** Read Only, Restart Required

**heapFreePercent**

Percentage of the maximum memory that is free.

**Type:** int

**Constraints:** Read Only, Restart Required

**heapSizeCurrent**

The current size (in bytes) of the JVM heap.

**Type:** long

**Constraints:** Read Only, Restart Required

**heapSizeMax**

The maximum free memory configured for this JVM.

**Type:** long

**Constraints:** Read Only, Restart Required

**javaVMVendor**

Returns the vendor of the JVM.

The vendor of the JVM that this server runs.

system property `java.vm.vendor` is returned

**Type:** string

**Constraints:** Read Only, Restart Required

**javaVendor**

Returns the vendor of Java.

The vendor of Java that this server runs.

**Type:** string

**Constraints:** Read Only, Restart Required

**javaVersion**

The Java version of the JVM.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**threadStackDump**

JVM thread dump. Thread dump is available only on 1.5 VM

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**uptime**

The number of milliseconds that the Virtual Machine has been running.

**Type:** long

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JobRuntimeMBean

RuntimeMBean that provides information about a particular job.

The properties of the weblogic.management.runtime.JobRuntimeMBean entity are as follows:

**ID**

The unique ID corresponding to this job

**Type:** string

**Constraints:** Read Only, Restart Required

**description**

Get the description of the submitted `commonj.timers.TimerListener`. Returns `commonj.timers.TimerListener#toString`

**Type:** string

**Constraints:** Read Only, Restart Required

**lastLocalExecutionTime**

Returns the most recent execution time of this job in the local server. Note that multiple executions of the same job are load-balanced across the cluster and this time indicates when the job was last executed locally.

**Type:** long

**Constraints:** Read Only, Restart Required

**localExecutionCount**

Returns the number of times this job was executed locally. Job executions are load-balanced across the cluster. This count specifies the number of executions of the job in the local server.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**period**

Returns the specified periodicity of this job

**Type:** long

**Constraints:** Read Only, Restart Required

**state**

Returns the state of the task. A Job is either in running state or in cancelled state

**Type:** string

**Constraints:** Read Only, Restart Required

**timeout**

Returns when the job will be executed next

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JobSchedulerRuntimeMBean

RuntimeMBean that provides information about jobs scheduled with the Job Scheduler.

The properties of the weblogic.management.runtime.JobSchedulerRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JoltConnectionPoolRuntimeMBean**

This class is used for monitoring a WebLogic Jolt Connection Pool

The properties of the weblogic.management.runtime.JoltConnectionPoolRuntimeMBean entity are as follows:

**maxCapacity**

The maximum connections configured for this Jolt pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**poolName**

The configured name of this Jolt pool.

**Type:** string

**Constraints:** Read Only, Restart Required

**poolState**

The pool state as one of 'Active' 'Suspended'.

**Type:** string

**Constraints:** Read Only, Restart Required

**securityContextPropagation**

Indicates whether the security context is propagated.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.JoltConnectionRuntimeMBean**

This class is used for monitoring individual WebLogic Jolt connections

The properties of the weblogic.management.runtime.JoltConnectionRuntimeMBean entity are as follows:

**address**

The connection Address.

**Type:** string

**Constraints:** Read Only, Restart Required

**alive**

The Connection Alive indicator.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**errorCount**

The Request Error Count.

**Type:** int

**Constraints:** Read Only, Restart Required

**inTransaction**

The Connection in Transaction indicator.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**lastAccessTime**

The Last Access Date and Time.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**pendingRequestCount**

The Pending Request Count.

**Type:** int

**Constraints:** Read Only, Restart Required

**requestCount**

The Request Count.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.JoltConnectionServiceRuntimeMBean

This class is used for monitoring a WebLogic Jolt component

The properties of the weblogic.management.runtime.JoltConnectionServiceRuntimeMBean entity are as follows:

### **connectionPoolCount**

The number of configured Jolt connection pools.

**Type:** int

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.LibraryRuntimeMBean

RuntimeMBean for library deployments.

The properties of the weblogic.management.runtime.LibraryRuntimeMBean entity are as follows:

### **implementationVersion**

Returns the library implementation version. If not set, this value is null.

**Type:** string

**Constraints:** Read Only, Restart Required

### **libraryIdentifier**

Returns the library identifier.

The library identifier uniquely identifies this library version across all versions of all deployed applications and deployed libraries. If the library is not versioned, the library identifier is the same as the library name.

**Type:** string

**Constraints:** Read Only, Restart Required

### **libraryName**

Returns the library name.

**Type:** string

**Constraints:** Read Only, Restart Required



**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**partitionName**

The library's partition.

Returns the partition to which this library is deployed.

**Type:** string

**Constraints:** Read Only, Restart Required

**referenced**

Returns true if this library is referenced by one or more referencers. Typically, a library referencer is a deployed application.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**specificationVersion**

Returns the library specification version. If not set, this value is null.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.LogBroadcasterRuntimeMBean

This MBean broadcasts JMX notifications for each log message generated in the local WLS server. There is exactly one implementation of this MBean in each WLS server. JMX listeners can register to this MBean and receive log notifications. The type of the notification generated is `WebLogicLogNotification`

The properties of the `weblogic.management.runtime.LogBroadcasterRuntimeMBean` entity are as follows:

**messagesLogged**

The total number of log messages that this WebLogic Server instance has generated.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.LogRuntimeMBean

This interface defines the control operations for a log in the WebLogic Server.

The properties of the weblogic.management.runtime.LogRuntimeMBean entity are as follows:

**logFileStreamOpened**

Gets the opened state of the log file stream represented by this instance.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.MANAsyncReplicationRuntimeMBean

RuntimeMBean for MAN Asynchronous Replication

The properties of the weblogic.management.runtime.MANAsyncReplicationRuntimeMBean entity are as follows:

**activeServersInRemoteCluster**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**detailedSecondariesDistribution**

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**lastSessionsFlushTime**

The last time the sessions were flushed, in milliseconds since midnight, January 1, 1970 UTC

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**primaryCount**

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**remoteClusterReachable**

Answer if the remote cluster is reachable or not.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**secondaryCount**

Answer the number of object that the local server hosts as secondaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryServerDetails**

**Type:** string

**Constraints:** Read Only, Restart Required

**secondaryServerName**

Answer the name of the secondary server

**Type:** string

**Constraints:** Read Only, Restart Required

**sessionsWaitingForFlushCount**

Number of sessions which are waiting to be flushed.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.MANReplicationRuntimeMBean**

RuntimeMBean for MAN Replication

The properties of the weblogic.management.runtime.MANReplicationRuntimeMBean entity are as follows:

**activeServersInRemoteCluster**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**detailedSecondariesDistribution**

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**primaryCount**

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**remoteClusterReachable**

Answer if the remote cluster is reachable or not.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**secondaryCount**

Answer the number of object that the local server hosts as secondaries.

**Type:** long

**Constraints:** Read Only, Restart Required

**secondaryServerDetails**

**Type:** string

**Constraints:** Read Only, Restart Required

**secondaryServerName**

Answer the name of the secondary server

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.MailSessionRuntimeMBean

RuntimeMBean for JavaMail Sessions

The properties of the weblogic.management.runtime.MailSessionRuntimeMBean entity are as follows:

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean

ManagedExecutorService Runtime information. It can be the information of a partition level MES, an application level MES or a regular JSR236 MES.

The properties of the weblogic.management.runtime.ManagedExecutorServiceRuntimeMBean entity are as follows:

### **applicationName**

Get the name of the application this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

### **completedLongRunningRequests**

Total number of long running tasks which is successfully completed.

**Type:** long

**Constraints:** Read Only, Restart Required

### **completedShortRunningRequests**

Total number of short running tasks which is successfully completed.

**Type:** long

**Constraints:** Read Only, Restart Required

### **failedRequests**

Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

**Type:** long

**Constraints:** Read Only, Restart Required

### **moduleName**

Get the name of the module this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**partitionName**

Get the name of the partition this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**rejectedLongRunningRequests**

Total number of long running tasks rejected by max-concurrent-long-running-requests

**Type:** long

**Constraints:** Read Only, Restart Required

**rejectedShortRunningRequests**

Total number of short running tasks rejected by workmanager overload policy

**Type:** long

**Constraints:** Read Only, Restart Required

**runningLongRunningRequests**

Total number of long running tasks which is currently running.

**Type:** long

**Constraints:** Read Only, Restart Required

**submittedShortRunningRequests**

Total number of submitted short running tasks

**Type:** long

**Constraints:** Read Only, Restart Required

**submittedLongRunningRequests**

Total number of submitted long running tasks

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean**

ManagedScheduledExecutorService Runtime information. It can be the information of a partition level MSES, an application level MSES or a regular JSR236 MSES.

The properties of the weblogic.management.runtime.ManagedScheduledExecutorServiceRuntimeMBean entity are as follows:

**applicationName**

Get the name of the application this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**completedLongRunningRequests**

Total number of long running tasks which is successfully completed.

**Type:** long

**Constraints:** Read Only, Restart Required

**completedShortRunningRequests**

Total number of short running tasks which is successfully completed.

**Type:** long

**Constraints:** Read Only, Restart Required

**failedRequests**

Total number of tasks which terminated abnormally by throwing exception, including both long and short term tasks.

**Type:** long

**Constraints:** Read Only, Restart Required

**moduleName**

Get the name of the module this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**partitionName**

Get the name of the partition this ManagedExecutor is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**rejectedLongRunningRequests**

Total number of long running tasks rejected by max-concurrent-long-running-requests

**Type:** long

**Constraints:** Read Only, Restart Required

**rejectedShortRunningRequests**

Total number of short running tasks rejected by workmanager overload policy

**Type:** long

**Constraints:** Read Only, Restart Required

**runningLongRunningRequests**

Total number of long running tasks which is currently running.

**Type:** long

**Constraints:** Read Only, Restart Required

**submittedShortRunningRequests**

Total number of submitted short running tasks

**Type:** long

**Constraints:** Read Only, Restart Required

**submittedLongRunningRequests**

Total number of submitted long running tasks

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean**

ManagedThreadFactory Runtime information. It can be the information of a partition level MTF, an application level MTF or a regular JSR236 MTF.

The properties of the weblogic.management.runtime.ManagedThreadFactoryRuntimeMBean entity are as follows:

**applicationName**

Get the name of the application this ManagedThreadFactory is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**completedThreadsCount**

The number of completed threads.

**Type:** long

**Constraints:** Read Only, Restart Required

**moduleName**

Get the name of the module this ManagedThreadFactory is associated with

**Type:** string

**Constraints:** Read Only, Restart Required



**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**partitionName**

Get the name of the partition this ManagedThreadFactory is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**rejectedNewThreadRequests**

The number of newThread method invocations that have been rejected because the limit of running threads was exceeded.

**Type:** long

**Constraints:** Read Only, Restart Required

**runningThreadsCount**

The number of running threads.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean**

Runtime information for MaxThreadsConstraint

The properties of the weblogic.management.runtime.MaxThreadsConstraintRuntimeMBean entity are as follows:

**configuredCount**

The configured count, or maximum concurrency value.

**Type:** int

**Constraints:** Read Only, Restart Required

**count**

The current maximum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed maximum concurrency value based on configured RCM policies and actual thread usage by the partition

**Type:** int

**Constraints:** Read Only, Restart Required

**deferredRequests**

Number of requests that are denied a thread for execution because the constraint is exceeded.

**Type:** int

**Constraints:** Read Only, Restart Required

**executingRequests**

Number of requests that are currently executing.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.MessageDrivenEJBRuntimeMBean**

This interface contains accessor methods for all EJB runtime information collected for a Message Driven Bean.

The properties of the `weblogic.management.runtime.MessageDrivenEJBRuntimeMBean` entity are as follows:

**EJBName**

Provides the name for this EJB as defined in the `javax.ejb.EJB` annotation, or the `ejb-name` when \* using the `ejb-jar.xml` deployment descriptor.

**Type:** string

**Constraints:** Read Only, Restart Required

**JMSConnectionAlive**

Provides information about whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

Returns whether the Message Driven Bean is currently connected to the JMS destination it is mapped to.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**MDBStatus**

Provides the Message Driven Bean status. `MDBStatus` is used after the MDB is connected to the destination. `MDBStatus` can be `Running` or `Suspended`.

**Type:** string

**Constraints:** Read Only, Restart Required

**connectionStatus**

Provides the connection status for the Message Driven Bean. ConnectionStatus can be Connected or Reconnecting.

**Type:** string

**Constraints:** Read Only, Restart Required

**destination**

Provides a count of the Message Driven Bean destination

**Type:** string

**Constraints:** Read Only, Restart Required

**healthState**

The health state of this MDB.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**jmsClientID**

Provides a count of the Message Driven Bean jmsClientID

**Type:** string

**Constraints:** Read Only, Restart Required

**lastException**

Provides the last exception this MDB encountered

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**lastExceptionAsString**

Provides the last exception as String this MDB encountered

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**processedMessageCount**

Provides a count of the total number of messages processed by this Message Driven Bean.

**Type:** long

**Constraints:** Read Only, Restart Required

**suspendCount**

Provides a count of the total number of times this MDB is suspended by the user or the EJB container.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.MessagingBridgeRuntimeMBean**

This class is used for monitoring a WebLogic messaging bridge.

The properties of the `weblogic.management.runtime.MessagingBridgeRuntimeMBean` entity are as follows:

**description**

The reason, if the messaging bridge is not running.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**state**

The state of the messaging bridge.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.MigrationDataRuntimeMBean**

Runtime information about one past or ongoing migration.

The properties of the `weblogic.management.runtime.MigrationDataRuntimeMBean` entity are as follows:

**clusterMasterName**

Name of the server that acted as the cluster master for this migration.

**Type:** string

**Constraints:** Read Only, Restart Required

**clusterName**

Name of the server that acted as the cluster master for this migration.

**Type:** string

**Constraints:** Read Only, Restart Required

**machineMigratedFrom**

Machine from which the server was migrated from

**Type:** string

**Constraints:** Read Only, Restart Required

**machineMigratedTo**

Machine to which the server was migrated to or is in the process of being migrated to.

**Type:** string

**Constraints:** Read Only, Restart Required

**machinesAttempted**

Get all the machines attempted for migration.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**migrationEndTime**

End time of migration

**Type:** long

**Constraints:** Read Only, Restart Required

**migrationStartTime**

Start time of migration

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**serverName**

Name of the server migrated

**Type:** string

**Constraints:** Read Only, Restart Required

**status**

Name of the server migrated

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.MinThreadsConstraintRuntimeMBean

Monitoring information for MinThreadsConstraint

The properties of the weblogic.management.runtime.MinThreadsConstraintRuntimeMBean entity are as follows:

### **completedRequests**

Completed request count.

**Type:** long

**Constraints:** Read Only, Restart Required

### **configuredCount**

The configured count, or minimum concurrency value.

**Type:** int

**Constraints:** Read Only, Restart Required

### **count**

The current minimum concurrency value. This could be different from the configured value as Resource Consumption Management could dynamically reduce the allowed minimum concurrency value based on configured RCM policies and actual thread usage by the partition

**Type:** int

**Constraints:** Read Only, Restart Required

### **currentWaitTime**

The last measured time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

**Type:** long

**Constraints:** Read Only, Restart Required

### **executingRequests**

Number of requests that are currently executing.

**Type:** int

**Constraints:** Read Only, Restart Required

### **maxWaitTime**

The max time a request had to wait for a thread. Only requests whose execution is needed to satisfy the constraint are considered.

**Type:** long

**Constraints:** Read Only, Restart Required

### **mustRunCount**

Number of requests that must be executed to satisfy the constraint.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**outOfOrderExecutionCount**

Number of requests executed out of turn to satisfy this constraint.

**Type:** long

**Constraints:** Read Only, Restart Required

**partitionLimitReached**

Whether the partition-level minimum threads constraint limit has reached, which could cause the number of executing requests to be less than the configured value in this minimum threads constraint.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**pendingRequests**

Pending requests that are waiting for an available thread.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.NonXAResourceRuntimeMBean

This represents runtime statistical information about a NonXAResource

The properties of the weblogic.management.runtime.NonXAResourceRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**nonXAResourceName**

Returns the resource name.

**Type:** string

**Constraints:** Read Only, Restart Required

**transactionCommittedTotalCount**

The total number of transactions committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicsTotalCount**

The number of transactions that completed with a heuristic status since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackTotalCount**

The number of transactions that were rolled back since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTotalCount**

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PSAssemblyRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PSAssemblyRuntimeMBean entity are as follows:

**mapEntries**

Returns all entries in a persistent map's assembly.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required



## weblogic.management.runtime.PartitionFairShareRuntimeMBean

Monitoring information for PartitionFairShare

The properties of the weblogic.management.runtime.PartitionFairShareRuntimeMBean entity are as follows:

### **configuredFairShare**

The configured fair share value.

**Type:** int

**Constraints:** Read Only, Restart Required

### **fairShare**

The current fair share value. This could be different from the configured value as Resource Consumption Management could dynamically adjust the actual fair share value based on configured RCM policies and actual thread usage by the partition

**Type:** int

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **partitionAdjuster**

The multiplier to be used to adjust the priority of requests from the partition in the request queue.

**Type:** double

**Constraints:** Read Only, Restart Required

### **threadUse**

Total amount of thread use time in milliseconds used by the partition during the past period.

**Type:** long

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean

Monitoring information for PartitionMinThreadsConstraint

The properties of the weblogic.management.runtime.PartitionMinThreadsConstraintCapRuntimeMBean entity are as follows:

**executingRequests**

Number of requests that are currently executing.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**sumMinThreadsConstraints**

Sum of all configured minimum threads constraints in the partition. This is the number of threads that is needed in order to satisfy all configured minimum threads constraints in the partition if all of them have more than that amount of concurrent work requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean**

The runtime MBean interface for partition specific resource consumption metrics. The resource meters are added lazily for a partition. Therefore, the first time these metrics are queried, it might return zero values. Subsequent gets would return non-zero values based on the resource consumption. These metrics are applicable in the context of a partition since either server start or partition creation/restart, whichever was later.

The properties of the `weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean` entity are as follows:

**RCMMetricsDataAvailable**

Checks whether RCM metrics data is available for this partition.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**allocatedMemory**

Total allocated memory in bytes for the partition. This metric value increases monotonically over time, it never decreases. Retained memory should be used to get current net values.

**Type:** long

**Constraints:** Read Only, Restart Required

**cpuTimeNanos**

Total CPU time spent measured in nanoseconds in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**cpuUtilizationHistoricalData**

Returns a snapshot of the historical data for CPU usage for the partition. CPU Utilization percentage indicates the percentage of CPU utilized by a partition with respect to available CPU to Weblogic Server. Data is returned as a two-dimensional array for the CPU usage scoped to the partition over time. Each item in the array contains a tuple of [timestamp (long), cpuUsage(long)] values.

**Type:** array of array of long

**Constraints:** Read Only, Restart Required

**currentOpenFileCount**

Number of files currently open in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentOpenFileDescriptorCount**

Number of file descriptors currently open in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentOpenSocketCount**

Number of sockets currently open in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**fileBytesRead**

Total number of file bytes read in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**fileBytesWritten**

Total number of file bytes written in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**networkBytesRead**

Total number of bytes read from sockets for a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**networkBytesWritten**

Total number of bytes written to sockets for a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**retainedHeapHistoricalData**

Returns a snapshot of the historical data for retained heap memory usage for the partition. Data is returned as a two-dimensional array for the usage of retained heap scoped to the partition over time. Each item in the array contains a tuple of [timestamp (long), retainedHeap(long)] values.

**Type:** array of array of long

**Constraints:** Read Only, Restart Required

**threadCount**

Number of threads currently assigned to the partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalOpenedFileCount**

Total number of files opened in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalOpenedFileDescriptorCount**

Total number of file descriptors opened in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalOpenedSocketCount**

Total number of sockets opened in the context of a partition.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PartitionRuntimeMBean

Partition Runtime information.

The properties of the weblogic.management.runtime.PartitionRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**overallHealthState**

The aggregate health state of the partition as reported by components within the partition

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**partitionID**

Partition ID for this partition.

**Type:** string

**Constraints:** Read Only, Restart Required

**restartRequired**

Indicates whether the partition must be restarted in order to activate configuration changes.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**serverName**

The server associated with this configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**state**

The current state of the partition runtime MBean

**Type:** string

**Constraints:** Read Only, Restart Required

**subState**

The current substate of the partition runtime MBean

**Type:** string

**Constraints:** Read Only, Restart Required

**subsystemHealthStates**

An array of health states for major subsystems in the partition.

**Type:** array of weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**systemFileSystemRoot**

System file system root directory for this partition.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**userFileSystemRoot**

User file system root directory for this partition.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PartitionWorkManagerRuntimeMBean

Monitoring information for PartitionWorkManager

The properties of the weblogic.management.runtime.PartitionWorkManagerRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**overloadRejectedRequestsCount**

Number of requests rejected due to configured Shared Capacity for work managers have been reached.

**Type:** int

**Constraints:** Read Only, Restart Required

**pendingUserRequestCount**

The number of pending user requests in the priority queue. The priority queue contains requests from internal subsystems and users. This is just the count of all user requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**sharedCapacityForWorkManagers**

Maximum amount of requests that can be accepted in the priority queue. Note that a request with higher priority will be accepted in place of a lower priority request already in the queue even after the threshold is reached. The lower priority request is kept waiting in the queue till all high priority requests are executed. Also note that further enqueues of the low priority requests are rejected right away.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PathServiceRuntimeMBean

This interface is used for accessing a WebLogic path service entity

The properties of the weblogic.management.runtime.PathServiceRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PersistenceUnitRuntimeMBean

This class is used for monitoring JPA specific runtime stats. Base class for all runtime mbeans that provide status of running modules.

The properties of the weblogic.management.runtime.PersistenceUnitRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**persistenceUnitName**

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean

This class is used for monitoring a Persistent Store Connection.

The properties of the weblogic.management.runtime.PersistentStoreConnectionRuntimeMBean entity are as follows:

**createCount**

Number of create requests issued by this connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**deleteCount**

Number of delete requests issued by this connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**objectCount**

Number of objects contained in the connection.

**Type:** long

**Constraints:** Read Only, Restart Required

**readCount**

Number of read requests issued by this connection, including requests that occur during store initialization.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**updateCount**

Number of update requests issued by this connection.

**Type:** long

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.PersistentStoreRuntimeMBean**

This class is used for monitoring a Persistent Store.

The properties of the weblogic.management.runtime.PersistentStoreRuntimeMBean entity are as follows:

**allocatedIoBufferBytes**

The amount of off-heap (native) memory, in bytes, reserved for file store use.

When applicable, this is a multiple of the file store configurable attribute `IOBufferSize`. Applies to synchronous write policies `Direct-Write` and `Cache-Flush` policies

**Type:** long

**Constraints:** Read Only, Restart Required



**allocatedWindowBufferBytes**

The amount of off-heap (native) memory, in bytes, reserved for file store window buffer use.

Applies to synchronous write policies `Direct-Write-With-Cache` and `Disabled` but only when the native `wlfileio` library is loaded. See file store configurable attribute `MaxWindowBufferSize` for more information

**Type:** long

**Constraints:** Read Only, Restart Required

**createCount**

Number of create requests issued by this store.

**Type:** long

**Constraints:** Read Only, Restart Required

**deleteCount**

Number of delete requests issued by this store.

**Type:** long

**Constraints:** Read Only, Restart Required

**healthState**

Implement the `HealthFeedback` interface by returning the health state of this store.

**Type:** `weblogic.health.HealthState`

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**objectCount**

Number of objects contained in the store.

**Type:** long

**Constraints:** Read Only, Restart Required

**physicalWriteCount**

Number of times the store flushed its data to durable storage.

**Type:** long

**Constraints:** Read Only, Restart Required

**readCount**

Number of read requests issued by this store, including requests that occur during store initialization.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**updateCount**

Number of update requests issued by this store.

**Type:** long

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.QueryCacheRuntimeMBean

This interface contains accessor methods for all query cache runtime information collected for an EJB. The cache miss counts need some explaining. A query-cache miss can occur due to one of the following reasons:

- The query result was not found in the query-cache
- The query result has timed out
- A bean which satisfies the query was not found in the entity cache
- A query with relationship-caching turned on did not find the related-beans query result
- A query which loads multiple EJBs could not load one or more of them

To better aid tuning, there are separate counters provided for each of the last four of the above causes. The fifth counter is a total cache miss counter. This counter takes into account all five causes of a cache miss.

The properties of the weblogic.management.runtime.QueryCacheRuntimeMBean entity are as follows:

**cacheAccessCount**

Provides a count of the number of accesses of the query cache for this EJB.

Returns the number of accesses of the query cache for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**cacheHitCount**

Provides a count of the number of cache hits of the query cache for this EJB.

Returns the number of cache hits of the query cache for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**cacheMissByBeanEvictionCount**

Provides a count of the number of cache misses of the query cache for this EJB because corresponding beans were not found in the entity cache.

Returns the number of times a cache miss occurred for this EJB because corresponding beans were not found in the entity cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**cacheMissByDependentQueryMissCount**

Provides a count of the number of cache misses of the query cache for this EJB because a dependent query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a dependent query was not found in another EJB's query cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**cacheMissByRelatedQueryMissCount**

Provides a count of the number of cache misses of the query cache for this EJB because a related query was not found in another EJB's query cache.

Returns the number of times a cache miss occurred for this EJB because a related query was not found in another EJB's query cache.

**Type:** long

**Constraints:** Read Only, Restart Required

**cacheMissByTimeoutCount**

Provides a count of the number of cache misses of the query cache for this EJB due to query results timing out.

Returns the number of cache misses due to query result timeout for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalCacheMissCount**

Provides a count of the total number of cache misses of the query cache for this EJB.

Returns the total number of cache misses of the query cache for this EJB.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalCachedQueriesCount**

Provides a count of the total number of query results for this EJB currently in the query cache.

Returns the total number of query results for this EJB currently in the EJB cache.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.RealmRuntimeMBean

This class is used to monitor and manage per security realm runtime information.

The properties of the weblogic.management.runtime.RealmRuntimeMBean entity are as follows:

**name**

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's

`javax.management.ObjectName`

*Name=user-specified-name*

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.RequestClassRuntimeMBean

RequestClassRuntimeMBean presents runtime information about RequestClasses. A request class represents a class of work. Work using the same request class shares the same priority.

The properties of the weblogic.management.runtime.RequestClassRuntimeMBean entity are as follows:

**completedCount**

Total number of completions since server start

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**pendingRequestCount**

Number of requests waiting for a thread to become available.

**Type:** int

**Constraints:** Read Only, Restart Required

**requestClassType**

Returns the type of RequestClass. Either FAIR\_SHARE or RESPONSE\_TIME or CONTEXT

**Type:** string

**Constraints:** Read Only, Restart Required

**totalThreadUse**

Total amount of thread use time in millisecond's used by the request class since server start.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**virtualTimeIncrement**

Current priority of the request class. The priority is relative to other request class priorities. The priority is calculated dynamically frequently and can change.

**Type:** long

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ResourceManagerRuntimeMBean

The {@code ResourceManagerRuntimeMBean} holds runtime information about a Resource Manager that has been assigned to the current Domain Partition. The {@code ResourceManagerRuntimeMBean} is used for retrieving the runtime state (information about policy evaluation, current resource usage, recourse actions executed) of configured resource management policies established for the current Partition by a system administrator in the current server instance.

The properties of the weblogic.management.runtime.ResourceManagerRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ResourceRuntimeMBean

The {@code ResourceRuntimeMBean} holds runtime state about the policy evaluations that have been performed for a Resource type in the current Domain Partition in the current server instance.

The properties of the weblogic.management.runtime.ResourceRuntimeMBean entity are as follows:

**name**

The name of the policy defined for this resource as configured in the {@code ResourceManagerMBean} for this MBean's resource type `getResourceType()`.

**Type:** string

**Constraints:** Read Only, Restart Required

**resourceType**

The resource type associated with this MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**usage**

The current resource utilization of a Resource by the current Domain Partition, in the current Server instance.

To track or monitor resource consumption for a Domain Partition without creating resource consumption management policies, see `weblogic.management.runtime.PartitionResourceMetricsRuntimeMBean`.

**Type:** long

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.RuntimeMBean**

The tagging interface for all runtime MBeans.

The properties of the `weblogic.management.runtime.RuntimeMBean` entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.SAFAgentRuntimeMBean**

This class is used for monitoring a WebLogic SAF agent.

The properties of the `weblogic.management.runtime.SAFAgentRuntimeMBean` entity are as follows:

**bytesCurrentCount**

Returns the current number of bytes. This number does not include the pending bytes.

Type: long

Constraints: Read Only, Restart Required

**bytesHighCount**

Returns the peak number of bytes since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesPendingCount**

Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

Type: long

Constraints: Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesThresholdTime**

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

**conversationsCurrentCount**

Returns the current number of conversations

Type: long

Constraints: Read Only, Restart Required

**conversationsHighCount**

The peak number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

**conversationsTotalCount**

The total number of conversations since the last reset.

Type: long

Constraints: Read Only, Restart Required

**failedMessagesTotal**

Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

**healthState**

The health state of this JMS server.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**messagesCurrentCount**

Returns the current number of messages. This number includes the pending messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesHighCount**

Returns the peak number of messages since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesThresholdTime**

Returns the amount of time in the threshold condition since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**pausedForForwarding**

Indicates whether or not the sending agent is paused for forwarding at the current time.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**pausedForIncoming**

Indicates whether or not the sending agent is paused for incoming messages at the current time.

**Type:** boolean



**Constraints:** Read Only, Restart Required

**pausedForReceiving**

Indicates whether or not the receiving agent is paused for receiving at the current time.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**remoteEndpointsCurrentCount**

The current number of remote endpoints to which this SAF agent has been storing and forwarding messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**remoteEndpointsHighCount**

The peak number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**remoteEndpointsTotalCount**

The number of remote endpoints to which this SAF agent has been storing and forwarding messages since last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.SAFConversationRuntimeMBean

This class is used for monitoring a WebLogic SAF conversation.

The properties of the weblogic.management.runtime.SAFConversationRuntimeMBean entity are as follows:

**QOS**

The quality of service (QOS) for the SAF conversation.

The quality-of-service values are:

- weblogic.management.runtime.SAFConstants.QOS\_EXACTLY\_ONCE
- weblogic.management.runtime.SAFConstants.QOS\_ATLEAST\_ONCE
- weblogic.management.runtime.SAFConstants.QOS\_ATMOST\_ONCE

**Type:** string

**Constraints:** Read Only, Restart Required

**conversationName**

The name of the conversation.

**Type:** string

**Constraints:** Read Only, Restart Required

**destinationURL**

The URL of the destination.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean

This class is used for monitoring a WebLogic SAF remote endpoint

The properties of the weblogic.management.runtime.SAFRemoteEndpointRuntimeMBean entity are as follows:

**URL**

The URL of the remote endpoint.

**Type:** string

**Constraints:** Read Only, Restart Required

**bytesCurrentCount**

Returns the current number of bytes. This number does not include the pending bytes.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesHighCount**

Returns the peak number of bytes since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesPendingCount**

Returns the number of pending bytes. Pending bytes are over and above the current number of bytes.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesReceivedCount**

The number of bytes received since the last reset.

Type: long

Constraints: Read Only, Restart Required

**bytesThresholdTime**

Returns the amount of time in the threshold condition since the last reset.

Type: long

Constraints: Read Only, Restart Required

**downtimeHigh**

Specifies the longest time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

**downtimeTotal**

Specifies the total time, in seconds, that the remote endpoint has not been available since the last reset.

Type: long

Constraints: Read Only, Restart Required

**endpointType**

Specifies if the remote endpoint is a JMS or Web Services (WSRM) destination. The possible values are: weblogic.management.runtime.SAFConstants.JMS\_ENDPOINT or weblogic.management.runtime.SAFConstants.WS\_ENDPOINT.

Type: string

Constraints: Read Only, Restart Required

**failedMessagesTotal**

Returns the total number of messages that have failed to be forwarded since the last reset.

Type: long

Constraints: Read Only, Restart Required

**lastException**

Specifies the exception thrown when message forwarding failed.

Type: java.lang.Throwable

Constraints: Read Only, Restart Required

**lastTimeConnected**

Specifies the last time that the remote endpoint was connected.

Type: java.util.Date

Constraints: Read Only, Restart Required

**lastTimeFailedToConnect**

Specifies the last time that the remote endpoint failed to be connected.

Type: java.util.Date

**Constraints:** Read Only, Restart Required

**messagesCurrentCount**

Returns the current number of messages. This number includes the pending messages.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesHighCount**

Returns the peak number of messages since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesPendingCount**

Returns the number of pending messages. Pending messages are over and above the current number of messages. A pending message is one that has either been sent in a transaction and not committed, or been forwarded but has not been acknowledged.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesThresholdTime**

Returns the amount of time in the threshold condition since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**operationState**

Specifies the state of the most recent `ExpireAll` operation.

**Type:** string

**Constraints:** Read Only, Restart Required

**pausedForForwarding**

Indicates if the remote endpoint is currently not forwarding messages.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**pausedForIncoming**

Indicates if a remote endpoint is currently not accepting new messages.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**uptimeHigh**

Specifies the longest time, in seconds, that the remote endpoint has been available since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

**uptimeTotal**

Specifies the total time, in seconds, that the remote endpoint has been available since the last reset.

**Type:** long

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.SAFRuntimeMBean**

This class is used for monitoring a WebLogic SAF service.

The properties of the weblogic.management.runtime.SAFRuntimeMBean entity are as follows:

**healthState**

The health state of SAF service.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.SNMPAgentRuntimeMBean**

Runtime information for an SNMP agent that is running in the current WebLogic Server domain.

The properties of the weblogic.management.runtime.SNMPAgentRuntimeMBean entity are as follows:

**SNMPAgentName**

Gets the name of the SNMPAgent MBean configuration that is currently active. Returns null if no SNMPAgent configuration is currently active on this Server.

**Type:** string

**Constraints:** Read Only, Restart Required

**UDPListenPort**

The UDP port on which this SNMP agent is listening for incoming requests from SNMP managers.

SNMP agents can also communicate through the host server's TCP listen port (7001 by default) or through a TCP port that is configured by a custom network channel.

**Type:** int

**Constraints:** Read Only, Restart Required

**attributeChangeTrapCount**

The number of attribute change notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**counterMonitorTrapCount**

The number of counter monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**failedAuthenticationCount**

The number of requests that this agent has rejected because of incorrect user credentials.

**Type:** int

**Constraints:** Read Only, Restart Required

**failedAuthorizationCount**

The number of requests that this agent has rejected because an authenticated user does not have sufficient privileges to view the requested information. You use the WebLogic Server security realm to assign privileges to users.

**Type:** int

**Constraints:** Read Only, Restart Required

**failedEncryptionCount**

The number of requests that this agent has rejected because of incorrect privacy (encryption) credentials

**Type:** int

**Constraints:** Read Only, Restart Required

**gaugeMonitorTrapCount**

The number of gauge monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**logMessageTrapCount**

The number of log message notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**masterAgentXPort**

The port that this SNMP agent uses to communicate with subagents.

The agent uses subagents to provide access to custom MBeans (MBeans that you create and register) and to other Oracle software components. WebLogic Server SNMP agents do not enable users to register their own subagents.

**Type:** int

**Constraints:** Read Only, Restart Required

**monitorTrapCount**

The total number of all notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**running**

Indicates whether this SNMP agent is running.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**serverStartTrapCount**

The number of serverStart notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**serverStopTrapCount**

The number of serverShutdown notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**stringMonitorTrapCount**

The number of string monitor notifications that this SNMP agent has sent to all trap destinations since the agent's host server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ServerChannelRuntimeMBean

Runtime information for NetworkAccessPoints or "Channels".

The properties of the weblogic.management.runtime.ServerChannelRuntimeMBean entity are as follows:

**acceptCount**

The number of sockets that have been accepted on this channel. This includes sockets both past and present so gives a good idea of the connection rate to the server.

**Type:** long

**Constraints:** Read Only, Restart Required

**associatedVirtualTargetName**

Associated virtual-target name with this channel. This may be null.

**Type:** string

**Constraints:** Read Only, Restart Required

**bytesReceivedCount**

The total number of bytes received on this channel.

**Type:** long

**Constraints:** Read Only, Restart Required

**bytesSentCount**

The total number of bytes sent on this channel.

**Type:** long

**Constraints:** Read Only, Restart Required

**channelName**

The channel name of this channel.

**Type:** string

**Constraints:** Read Only, Restart Required

**connectionsCount**

The number of active connections and sockets associated with this channel.

**Type:** long

**Constraints:** Read Only, Restart Required

**messagesReceivedCount**

The number of messages received on this channel.

**Type:** long



**Constraints:** Read Only, Restart Required

**messagesSentCount**

The number of messages sent on this channel.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**publicURL**

The physical URL that this channel is listening on.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ServerLogRuntimeMBean

This interface defines the control operations for a log in the WebLogic Server.

The properties of the weblogic.management.runtime.ServerLogRuntimeMBean entity are as follows:

**logFileStreamOpened**

Gets the opened state of the log file stream represented by this instance.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ServerMigrationRuntimeMBean

ServerMigrationRuntimeMBean provides runtime monitoring information about the past migrations performed by this server as the cluster master. If this server was never the cluster master then no information would be available. This RuntimeMBean would be hosted on all cluster members and can be queried for the location of the cluster master which is just another peer in the cluster. JMX clients can make another call to the server hosting the cluster master functionality to get the migration history.

Please note that the migration history is not persisted and is lost when a server is shutdown.

The properties of the weblogic.management.runtime.ServerMigrationRuntimeMBean entity are as follows:

### **clusterMaster**

Is the current server the cluster master?

**Type:** boolean

**Constraints:** Read Only, Restart Required

### **clusterMasterName**

Returns the server name who is the cluster master. Migration history is only available from the cluster master.

**Type:** string

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ServerRuntimeMBean

Provides methods for retrieving runtime information about a server instance and for transitioning a server from one state to another.

The properties of the weblogic.management.runtime.ServerRuntimeMBean entity are as follows:

### **SSLListenPortEnabled**

Indicates whether the default SSL listen port is enabled on the server

**Type:** boolean

**Constraints:** Read Only, Restart Required

### **activationTime**

The time when the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**adminServer**

Indicates whether the server is an Administration Server.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**adminServerHost**

The address on which the Administration Server is listening for connections. For example, this might return the string: santiago

**Type:** string

**Constraints:** Read Only, Restart Required

**adminServerListenPort**

The port on which the Administration Server is listening for connections.

**Type:** int

**Constraints:** Read Only, Restart Required

**adminServerListenPortSecure**

Indicates whether the port that the server uses for administrative traffic is configured to use a secure protocol.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**administrationPortEnabled**

Indicates whether the administration port is enabled on the server

**Type:** boolean

**Constraints:** Read Only, Restart Required

**administrationURL**

The URL that the server and its clients use for administrative connections.

If no administration channel is enabled, then this method returns the URL for connections through the default channel. If the default channel is de-activated, this method returns the URL for a secure channel. If no secure channel is enabled, the method returns null.

The returned URL will be consistent with dynamic channel updates.

**Type:** string

**Constraints:** Read Only, Restart Required

**currentDirectory**

The absolute path of the directory from which the server was started.

This may be used in conjunction with other relative paths in ServerMBean to compute full paths.

**Type:** string

**Constraints:** Read Only, Restart Required

**currentMachine**

Return the machine on which the server is running. This will be different from the configuration if the server gets migrated automatically.

**Type:** string

**Constraints:** Restart Required

**defaultURL**

The URL that clients use to connect to this server's default network channel.

The returned value indicates the default protocol, listen address and listen port:

*protocol://listen-addresslisten-port*

Note: The default protocol, listen address and listen port are persisted in the domain's `config.xml` file, however when a server instance is started, command-line options can override these persisted values. This `getDefaultURL` method returns the URL values that are currently being used, not necessarily the values that are specified in `config.xml`

The returned URL will be consistent with dynamic channel updates.

**Type:** string

**Constraints:** Read Only, Restart Required

**healthState**

The health state of the server as reported by the server's self-health monitoring.

For example, the server can report if it is overloaded by too many requests, if it needs more memory resources, or if it will soon fail for other reasons.

**Type:** `weblogic.health.HealthState`

**Constraints:** Read Only, Restart Required

**listenPortEnabled**

Indicates whether the default listen port is enabled on the server.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**middlewareHome**

The Oracle Middleware installation directory.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**openSocketsCurrentCount**

The current number of sockets registered for socket muxing on this server.

**Type:** int

**Constraints:** Read Only, Restart Required

**overallHealthState**

Determine the overall health state of this server, taking into account the health of each of its subsystems.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**restartRequired**

Indicates whether the server must be restarted in order to activate configuration changes.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**serverClasspath**

Get the classpath for this server including domain/lib contents that are automatically picked up and appended to the classpath.

**Type:** string

**Constraints:** Read Only, Restart Required

**state**

The current life cycle state of this server.

For example, a server can be in a RUNNING state in which it can receive and process requests or in an ADMIN state in which it can receive only administrative requests.

**Type:** string

**Constraints:** Read Only, Restart Required

**stateVal**

Returns current state of the server as in integer.

weblogic.management.runtime.ServerStates has more information about the available server states

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**weblogicHome**

The directory where the WebLogic Server instance (server) is installed, without the trailing "/server".

**Type:** string

**Constraints:** Read Only, Restart Required

**weblogicVersion**

The version of this WebLogic Server instance (server).

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.ServerSecurityRuntimeMBean

This class is used for monitoring WebLogic Security Info.

The properties of the weblogic.management.runtime.ServerSecurityRuntimeMBean entity are as follows:

### **JACCEnabled**

Indicates whether JACC (Java Authorization Contract for Containers) was enabled on the commandline for the jvm hosting this server

**Type:** boolean

**Constraints:** Read Only, Restart Required, Has Default Value: false

### **name**

The user-specified name of this MBean instance.

This name is included as one of the key properties in the MBean's `javax.management.ObjectName`

`Name=user-specified-name`

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.SingleSignOnServicesRuntimeMBean

This interface is used to publish SAML 2.0 local site meta-data for single sign-on services.

The properties of the weblogic.management.runtime.SingleSignOnServicesRuntimeMBean entity are as follows:

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.TaskRuntimeMBean

Exposes monitoring information about an ongoing and potentially long-running administrative process. This should be taken to mean, at minimum, any OA&M

operation involving I/O. Examples include starting and stopping servers, deploying and undeploying applications, or migrating services.

An MBean operation of this sort should fork a separate thread to perform the actual work and immediately return an instance of `TaskRuntimeMBean` to the caller. The caller can then use this to track the task's progress as desired. Users can also query for all instances of `TaskRuntimeMBean` to get a summary of both currently-running and recently-completed tasks.

Instance of `TaskRuntimeMBean` continue to exist in the `MBeanServer` after the completion of the work they describe. They will eventually either be explicitly deregistered by the user, or removed by a scavenger process which periodically purges instances of `TaskRuntimeMBean` that have been completed for some time.

The properties of the `weblogic.management.runtime.TaskRuntimeMBean` entity are as follows:

**completed**

This property indicates whether an asynchronous job has completed.

**Type:** boolean

**description**

A description of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**endTime**

This property indicates the time when the asynchronous job ended.

**Type:** `java.util.Date`

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**parentTask**

The task of which this task is a part.

A value of `null` indicates that this task is not a subtask.

**Type:** `weblogic.management.runtime.TaskRuntimeMBean` reference

**Constraints:** Read Only, Restart Required

**progress**

The progress of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**running**

Indicates whether the task is still running.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**startTime**

This property indicates the time when an asynchronous job was started.

**Type:** java.util.Date

**startTimeAsLong**

The time at which this task was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**systemTask**

Indicates whether this task was initiated by the server versus a user.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**taskError**

Returns an exception describing the error, if any, that occurred while performing this task.

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**taskStatus**

The status of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.ThreadPoolRuntimeMBean**

This bean is used to monitor the self-tuning queue

The properties of the weblogic.management.runtime.ThreadPoolRuntimeMBean entity are as follows:

**completedRequestCount**

The number of completed requests in the priority queue.

**Type:** long

**Constraints:** Read Only, Restart Required

**executeThreadIdleCount**

The number of idle threads in the pool. This count does not include standby threads and stuck threads. The count indicates threads that are ready to pick up new work when it arrives

**Type:** int

**Constraints:** Read Only, Restart Required



**executeThreadTotalCount**

The total number of threads in the pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**healthState**

The health state of this pool.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**hoggingThreadCount**

The threads that are being held by a request right now. These threads will either be declared as stuck after the configured timeout or will return to the pool before that. The self-tuning mechanism will backfill if necessary.

**Type:** int

**Constraints:** Read Only, Restart Required

**minThreadsConstraintsCompleted**

Number of requests with min threads constraint picked up out of order for execution immediately since their min threads requirement was not met. This does not include the case where threads are idle during schedule.

**Type:** long

**Constraints:** Read Only, Restart Required

**minThreadsConstraintsPending**

Number of requests that should be executed now to satisfy the min threads requirement.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**overloadRejectedRequestsCount**

Number of requests rejected due to configured Shared Capacity for work managers have been reached.

**Type:** int

**Constraints:** Read Only, Restart Required

**pendingUserRequestCount**

The number of pending user requests in the priority queue. The priority queue contains requests from internal subsystems and users. This is just the count of all user requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**queueLength**

The number of pending requests in the priority queue. This is the total of internal system requests and user requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**sharedCapacityForWorkManagers**

Maximum amount of requests that can be accepted in the priority queue. Note that a request with higher priority will be accepted in place of a lower priority request already in the queue even after the threshold is reached. The lower priority request is kept waiting in the queue till all high priority requests are executed. Also note that further enqueues of the low priority requests are rejected right away.

**Type:** int

**Constraints:** Read Only, Restart Required

**standbyThreadCount**

The number of threads in the standby pool. Threads that are not needed to handle the present work load are designated as standby and added to the standby pool. These threads are activated when more threads are needed.

**Type:** int

**Constraints:** Read Only, Restart Required

**stuckThreadCount**

Number of stuck threads in the thread pool.

**Type:** int

**Constraints:** Read Only, Restart Required

**suspended**

Indicates if the RequestManager is suspended. A suspended manager will not dequeue work and dispatch threads till it is resumed.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**throughput**

The mean number of requests completed per second.

**Type:** double

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.TimerRuntimeMBean

This RuntimeMBean exposes information about all active timers present in the WebLogic timer implementation.

The properties of the weblogic.management.runtime.TimerRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.TransactionNameRuntimeMBean

This interface represents runtime statistics for a transaction name category.

The properties of the weblogic.management.runtime.TransactionNameRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**secondsActiveTotalCount**

The total number of seconds that transactions were active for all committed transactions.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionAbandonedTotalCount**

The total number of transactions that were abandoned since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionCommittedTotalCount**

The total number of transactions committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicsTotalCount**

The number of transactions that completed with a heuristic status since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionLLRCommittedTotalCount**

The total number of LLR transactions that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionName**

The transaction name.

Type: string

Constraints: Read Only, Restart Required

**transactionNoResourcesCommittedTotalCount**

The total number of transactions with no enlisted resources that were committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionOneResourceOnePhaseCommittedTotalCount**

The total number of transactions with only one enlisted resource that were one-phase committed since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionReadOnlyOnePhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were one-phase committed due to read-only optimization since the server was started.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackAppTotalCount**

The number of transactions that were rolled back due to an application error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackResourceTotalCount**

The number of transactions that were rolled back due to a resource error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackSystemTotalCount**

The number of transactions that were rolled back due to an internal system error.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackTimeoutTotalCount**

The number of transactions that were rolled back due to a timeout expiration.

Type: long

Constraints: Read Only, Restart Required

**transactionRolledBackTotalCount**

The number of transactions that were rolled back since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTotalCount**

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedLoggedTotalCount**

The total number of two phase commit transactions that were committed with TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedNotLoggedTotalCount**

The total number of two phase committed transactions that were committed without TLog since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTwoPhaseCommittedTotalCount**

The total number of transactions with more than one enlisted resource that were two-phase committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**weblogic.management.runtime.TransactionResourceRuntimeMBean**

This interface represents runtime statistics for a transactional resource.

The properties of the `weblogic.management.runtime.TransactionResourceRuntimeMBean` entity are as follows:

**healthState**

The health state of the Resource.

**Type:** `weblogic.health.HealthState`

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**resourceName**

The resource name.

**Type:** string

**Constraints:** Read Only, Restart Required

**transactionCommittedTotalCount**

The total number of transactions committed since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicCommitTotalCount**

The number of transactions for which this resource has returned a heuristic commit decision.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicHazardTotalCount**

The number of transactions for which this resource has reported a heuristic hazard decision.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicMixedTotalCount**

The number of transactions for which this resource has reported a heuristic mixed decision.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicRollbackTotalCount**

The number of transactions for which this resource has returned a heuristic rollback decision.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionHeuristicsTotalCount**

The number of transactions that completed with a heuristic status since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionRolledBackTotalCount**

The number of transactions that were rolled back since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**transactionTotalCount**

The total number of transactions processed. This total includes all committed, rolled back, and heuristic transaction completions since the server was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.TriggerRuntimeMBean

The `TriggerRuntimeMBean` holds runtime state (for the current Server instance) for a Trigger that has been configured in the Resource Consumption Management policy of the current Domain Partition.

The WebLogic Resource Consumption Management feature automatically initiates the configured recourse action of a Trigger when the Trigger's configured usage limits are exceeded by a Domain Partition. When a usage limit is exceeded, and the configured recourse action has been successfully executed, the Trigger is *Activated*.

When the current resource usage by the Domain Partition falls below the Trigger's configured usage limit, the feature automatically withdraws the recourse action where possible. When the current usage is below the configured usage limit, and the configured recourse action has been successfully withdrawn, the Trigger is said to be *not Activated*.

The MBean captures the following states for a Trigger when the current resource consumption usage by the Domain Partition exceeds or goes below the configured usage limit for the Domain Partition:

- Whether the Trigger is *Activated* (usage has exceeded the limit and the recourse action was successfully executed) or not
- The time when the last recourse action was executed successfully for the Trigger
- Whether a recourse action has been initiated in response to the resource usage by the Domain Partition exceeding the configured usage limits

The properties of the `weblogic.management.runtime.TriggerRuntimeMBean` entity are as follows:

**activated**

Indicates if the Trigger is *Activated*

**Type:** boolean

**Constraints:** Read Only, Restart Required

**initiated**

Indicates if a recourse action has been initiated for this Trigger as a result of the current resource usage by a Domain Partition exceeding its usage limit. A new `RecourseActionEventVBean` is added to the array returned by `getRecourseActionEventsHistory()`.

The kind of recourse action initiated (for example, a new recourse action or a withdrawal of an existing recourse action) can be determined through `RecourseActionEventVBean#isActive()`.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**lastTimeExecuted**

The `{@code Date}` when the last recourse action was successfully executed for the current Trigger.

**Type:** java.util.Date

**Constraints:** Read Only, Restart Required

**name**

The name of the Trigger, as configured in the Resource Consumption Management policy of the Domain Partition.

**Type:** string

**Constraints:** Read Only, Restart Required

**recourseActionEventsHistory**

A list of recourse action events that have been initiated and executed.

**Type:** array of weblogic.management.runtime.RecourseActionEventVBean

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.UnicastMessagingRuntimeMBean

Monitoring information when unicast messaging is turned on

The properties of the `weblogic.management.runtime.UnicastMessagingRuntimeMBean` entity are as follows:

**discoveredGroupLeaders**

Running group leader names

**Type:** array of string

**Constraints:** Read Only, Restart Required

**groups**

Formatted group list

**Type:** string

**Constraints:** Read Only, Restart Required

**localGroupLeaderName**

Name of the local group leader

**Type:** string



**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**remoteGroupsDiscoveredCount**

Returns the total groups discovered by this server

**Type:** int

**Constraints:** Read Only, Restart Required

**totalGroupsCount**

Total configured groups - running and not running

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.UserLockoutManagerRuntimeMBean

This class is used to monitor and manage per security realm user lockout information.

The properties of the weblogic.management.runtime.UserLockoutManagerRuntimeMBean entity are as follows:

**invalidLoginAttemptsTotalCount**

Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled. In a cluster, this method returns the number of invalid logins attempted that have occurred since the cluster has been started because all servers share login failure information.

**Type:** long

**Constraints:** Read Only, Restart Required

**invalidLoginUsersHighCount**

Returns the highest number of users with concurrent unexpired or uncleared invalid login attempts. Invalid login attempts expire as specified by `LockoutResetDuration`. This count is useful in determining whether the `LockoutCacheSize` needs to be modified.

**Type:** long

**Constraints:** Read Only, Restart Required

**lockedUsersCurrentCount**

Returns the number of users that are currently locked out of this server.

**Type:** long

**Constraints:** Read Only, Restart Required

**loginAttemptsWhileLockedTotalCount**

Returns the number of invalid logins attempted since this server has been started and lockouts have been enabled.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**unlockedUsersTotalCount**

Returns the number times users have been unlocked since this server has been started.

**Type:** long

**Constraints:** Read Only, Restart Required

**userLockoutTotalCount**

Returns the number of user lockouts that have occurred since this server has been started. In a cluster, this method returns the number of user lockouts that have occurred since the cluster has been started because all servers share login failure information.

**Type:** long

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WANReplicationRuntimeMBean

RuntimeMBean for WAN Replication

The properties of the weblogic.management.runtime.WANReplicationRuntimeMBean entity are as follows:

**detailedSecondariesDistribution**

Provides the names of the remote servers (such as myserver) for which the local server is hosting secondary objects. The name is appended with a number to indicate the number of secondaries hosted on behalf of that server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**numberOfSessionsFlushedToTheDatabase**

Type: long

Constraints: Read Only, Restart Required

**numberOfSessionsRetrievedFromTheDatabase**

Type: long

Constraints: Read Only, Restart Required

**primaryCount**

Provides the number of object that the local server hosts as primaries.

Answer the number of object that the local server hosts as primaries.

Type: long

Constraints: Read Only, Restart Required

**remoteClusterReachable**

Answer if the remote cluster is reachable or not.

Type: boolean

Constraints: Restart Required

**secondaryCount**

Answer the number of object that the local server hosts as secondaries.

Type: long

Constraints: Read Only, Restart Required

**secondaryServerDetails**

Type: string

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## weblogic.management.runtime.WLDFAccessRuntimeMBean

Use this interface to access the different types of diagnostic data generated by a server.

The properties of the weblogic.management.runtime.WLDFAccessRuntimeMBean entity are as follows:

**availableDiagnosticDataAccessorNames**

Type: array of string

Constraints: Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFArchiveRuntimeMBean

Use this interface to collect statistical information about the data archives maintained by WLDF. Information provided by this interface is common to all WLDF data archives.

The properties of the weblogic.management.runtime.WLDFArchiveRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**recordRetrievalTime**

**Type:** long

**Constraints:** Read Only, Restart Required

**recordSeekCount**

**Type:** long

**Constraints:** Read Only, Restart Required

**recordSeekTime**

**Type:** long

**Constraints:** Read Only, Restart Required

**retrievedRecordCount**

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFControlRuntimeMBean

This MBean acts as a factory for WLDFSystemResourceControlRuntimeMBeans

The properties of the weblogic.management.runtime.WLDFControlRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFDataAccessRuntimeMBean

Use this interface to access the specific type of diagnostic data from an underlying log for which this instance is created.

The properties of the weblogic.management.runtime.WLDFDataAccessRuntimeMBean entity are as follows:

**earliestAvailableTimestamp**

**Type:** long

**Constraints:** Read Only, Restart Required

**latestAvailableTimestamp**

**Type:** long

**Constraints:** Read Only, Restart Required

**latestRecordId**

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**timestampAvailable**

**Type:** boolean

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean

This interface provides monitoring over activation and deactivation tasks for dynamic debug patches

The properties of the weblogic.management.runtime.WLDFDebugPatchTaskRuntimeMBean entity are as follows:

**activationTask**

Type: boolean

Constraints: Read Only, Restart Required

**applicationName**

Type: string

Constraints: Read Only, Restart Required

**completed**

This property indicates whether an asynchronous job has completed.

Type: boolean

**description**

A description of this task.

Type: string

Constraints: Read Only, Restart Required

**endTime**

This property indicates the time when the asynchronous job ended.

Type: java.util.Date

**moduleName**

Type: string

Constraints: Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**parentTask**

The task of which this task is a part.

A value of null indicates that this task is not a subtask.

Type: weblogic.management.runtime.TaskRuntimeMBean reference

Constraints: Read Only, Restart Required

**patches**

Type: string

Constraints: Read Only, Restart Required

**progress**

The progress of this task.

Type: string

Constraints: Read Only, Restart Required

**running**

Indicates whether the task is still running.

Type: boolean

**Constraints:** Read Only, Restart Required

**startTime**

This property indicates the time when an asynchronous job was started.

**Type:** java.util.Date

**startTimeAsLong**

The time at which this task was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**systemTask**

Indicates whether this task was initiated by the server versus a user.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**taskError**

Returns an exception describing the error, if any, that occurred while performing this task.

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**taskStatus**

The status of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean

This interface provides functionality to activate/deactivate dynamic debug patches without requiring server restart. It is assumed that the WLDF instrumentation agent is enabled. This is an internal interface.

The properties of the weblogic.management.runtime.WLDFDebugPatchesRuntimeMBean entity are as follows:

**activeDebugPatches**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**availableDebugPatches**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean**

Provides statistical information relative to a particular configured Harvester instance, and a means to retrieve an on-demand snapshot of configured attribute values.

The properties of the `weblogic.management.runtime.WLDFHarvesterManagerRuntimeMBean` entity are as follows:

**averageSamplingTime**

The average amount of time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentDataSampleCount**

The number of collected data samples in the current snapshot.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentSnapshotElapsedTime**

The elapsed time, in nanoseconds, of a snapshot.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentSnapshotStartTime**

The start time, in milliseconds, of the latest archived snapshot.

**Type:** long

**Constraints:** Read Only, Restart Required

**maximumSamplingTime**

The maximum observed sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**minimumSamplingTime**

The minimum observed sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required



**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalDataSampleCount**

The number of configured data samples that have been collected and archived so far in this server session.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSamplingCycles**

The total number of periodic sampling cycles taken thus far.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSamplingTime**

The total amount of observed time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations, as well as metadata about harvestable and harvested attributes, types, and instances.

Harvestable means potentially available for harvesting; harvested means explicitly designated for harvesting. These terms apply to types, instances, and the attributes within those types. In addition, the interface provides access to sampling and snapshot statistics. All statistics are base on data collected during the current server session.

The properties of the weblogic.management.runtime.WLDFHarvesterRuntimeMBean entity are as follows:

**averageSamplingTime**

The average amount of time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

**knownHarvestableTypes**

The set of all known types, regardless of whether the types are currently configured for harvesting. The set includes the WebLogic Server MBeans, which are always present, plus any other types that can be discovered. MBeans that are not WebLogic Server MBeans will require instances to exist in order to discover the type.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**maximumSamplingTime**

The maximum sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**minimumSamplingTime**

The minimum sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalSamplingCycles**

The total number of sampling cycles taken thus far.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSamplingTime**

The total amount of time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean**

Exposes monitoring information about a potentially long-running request for the generation of a diagnostic image. Remote clients, as well as clients running within a server, can access this information.

weblogic.management.runtime.WLDFImageRuntimeMBean

WLDFImageRuntimeMBean supports operations to request the generation of a diagnostic image for capturing a running server's internal state information. These operations will fork a separate thread to perform the actual work and immediately return an instance of this MBean to the caller. The caller can then use that instance to track the task's progress.

The properties of the weblogic.management.runtime.WLDFImageCreationTaskRuntimeMBean entity are as follows:

**completed**

This property indicates whether an asynchronous job has completed.

**Type:** boolean

**description**

A description of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**endTime**

This property indicates the time when the asynchronous job ended.

**Type:** java.util.Date

**imageFileName**

Retrieve the name of the image file that was created. If the name is not yet known at the time this is called, this may return null.

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**parentTask**

The task of which this task is a part.

A value of null indicates that this task is not a subtask.

**Type:** weblogic.management.runtime.TaskRuntimeMBean reference

**Constraints:** Read Only, Restart Required

**progress**

The progress of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**running**

Indicates whether the task is still running.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**startTime**

This property indicates the time when an asynchronous job was started.

**Type:** java.util.Date

**startTimeAsLong**

The time at which this task was started.

**Type:** long

**Constraints:** Read Only, Restart Required

**systemTask**

Indicates whether this task was initiated by the server versus a user.

**Type:** boolean

**Constraints:** Read Only, Restart Required

**taskError**

Returns an exception describing the error, if any, that occurred while performing this task.

**Type:** java.lang.Throwable

**Constraints:** Read Only, Restart Required

**taskStatus**

The status of this task.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFImageRuntimeMBean

This interface controls diagnostic image creation, and provides access to run-time information about past and current diagnostic image capture requests.

The properties of the weblogic.management.runtime.WLDFImageRuntimeMBean entity are as follows:

**availableCapturedImages**

Returns a list of captured images that are available on the Server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**imageDir**

The default directory where the server stores captured diagnostic images.

**Type:** string

**Constraints:** Read Only, Restart Required

**imageTimeout**

The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFInstrumentationRuntimeMBean

This interface defines various methods for accessing runtime information about the diagnostic instrumentation system.

The properties of the weblogic.management.runtime.WLDFInstrumentationRuntimeMBean entity are as follows:

**callJoinpointCount**

The number of affected CALL joinpoints for all classes that were inspected. (CALL joinpoints are on the caller side.)

**Type:** int

**Constraints:** Read Only, Restart Required

**classweaveAbortCount**

Number of classes for which the class weaving aborted with some exceptional situation.

**Type:** int

**Constraints:** Read Only, Restart Required

**executionJoinpointCount**

The number of affected EXECUTION joinpoints for all classes that were inspected. (EXECUTION joinpoints are on the callee side.)

**Type:** int

**Constraints:** Read Only, Restart Required

**inspectedClassesCount**

The number of classes inspected for weaving (weaving is the insertion of diagnostic code).

**Type:** int

**Constraints:** Read Only, Restart Required

**maxWeavingTime**

For all classes, the weaving time in nanoseconds for the class that required the most time to process (includes the time spent both for inspection and for modification).

**Type:** long

**Constraints:** Read Only, Restart Required

**minWeavingTime**

For all classes, the weaving time in nanoseconds for the class that required the least time to process (includes the time spent both for inspection and for modification).

**Type:** long

**Constraints:** Read Only, Restart Required

**modifiedClassesCount**

The number of modified classes (classes where diagnostic code has been inserted).

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalWeavingTime**

For all classes, the total weaving time in nanoseconds for processing (includes the time spent both for inspection and for modification).

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean**

Use this interface to access the different types of diagnostic data generated by a partition.

The properties of the `weblogic.management.runtime.WLDFPartitionAccessRuntimeMBean` entity are as follows:

**availableDiagnosticDataAccessorNames**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean

Provides aggregated information about all active Harvester configurations for a partition.

The properties of the weblogic.management.runtime.WLDFPartitionHarvesterRuntimeMBean entity are as follows:

### **averageSamplingTime**

The average amount of time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

### **maximumSamplingTime**

The maximum sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

### **minimumSamplingTime**

The minimum sampling time, in nanoseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **totalSamplingCycles**

The total number of sampling cycles taken thus far.

**Type:** long

**Constraints:** Read Only, Restart Required

### **totalSamplingTime**

The total amount of time, in nanoseconds, spent in sampling cycles.

**Type:** long

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFPartitionImageRuntimeMBean

This interface controls diagnostic image creation, and provides access to run-time information about past and current diagnostic image capture requests.

The properties of the weblogic.management.runtime.WLDFPartitionImageRuntimeMBean entity are as follows:

**availableCapturedImages**

Returns a list of captured images that are available on the Server.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**imageDir**

The default directory where the server stores captured diagnostic images.

**Type:** string

**Constraints:** Read Only, Restart Required

**imageTimeout**

The default timeout period, in minutes, that the server uses to delay future diagnostic image-capture requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WLDFPartitionRuntimeMBean**

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFPartitionRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required



## weblogic.management.runtime.WLDFRuntimeMBean

This interface provides access to all the runtime MBeans for the WebLogic Diagnostic Framework (WLDF).

The properties of the weblogic.management.runtime.WLDFRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean

This MBean acts as a Runtime Control for a WLDF profile. An WLDF profile could either be a configured system resource or an external descriptor provided by a user at runtime.

The properties of the weblogic.management.runtime.WLDFSystemResourceControlRuntimeMBean entity are as follows:

**enabled**

is the descriptor enabled

**Type:** boolean

**Constraints:** Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFWatchManagerRuntimeMBean

Provides access to Policy and Action statistical data for the current instance of this server.

The properties of the weblogic.management.runtime.WLDFWatchManagerRuntimeMBean entity are as follows:

**activeAlarmWatches**

The names of active alarm policies.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**averageEventDataWatchEvaluationTime**

The average Instrumentation event data evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**averageHarvesterWatchEvaluationTime**

The average Harvester evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**averageLogWatchEvaluationTime**

The average Log evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentActiveAlarmsCount**

The number of active alarms of any type.

**Type:** int

**Constraints:** Read Only, Restart Required

**maximumActiveAlarmsCount**

The maximum number of active alarms at any one time.

**Type:** int

**Constraints:** Read Only, Restart Required

**maximumEventDataWatchEvaluationTime**

The maximum time spent evaluating EventData policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**maximumHarvesterWatchEvaluationTime**

The maximum time spent evaluating Harvester policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**maximumLogWatchEvaluationTime**

The maximum time spent evaluating Log policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**minimumEventDataWatchEvaluationTime**

The minimum time spent evaluating Log policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**minimumHarvesterWatchEvaluationTime**

The minimum time spent evaluating Harvester policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**minimumLogWatchEvaluationTime**

The minimum time spent evaluating Log policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**totalActiveAutomaticResetAlarms**

The total number of active automatically reset alarms.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalActiveManualResetAlarms**

The total number of active manually reset alarms.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalDIMGNotificationsPerformed**

The total number of Diagnostic Image actions fired. Diagnostic Image files are not true actions, but this records the number of image captures requested by the policy component.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalEventDataEvaluationCycles**

The total number of times Instrumentation event data policies have been evaluated.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalEventDataWatchEvaluations**

The total number of Instrumentation event data policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Instrumentation event data policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalEventDataWatchesTriggered**

The total number of Instrumentation event data policies that have evaluated to true and triggered actions.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedDIMGNotifications**

The total number of failed Diagnostic Image action requests.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedJMSNotifications**

The total number of failed JMS action attempts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedJMXNotifications**

The total number of failed JMX action attempts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedNotifications**

The total number of failed action requests.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedSMTPNotifications**

The total number of failed SMTP action attempts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalFailedSNMPNotifications**

The total number of failed SNMP action attempts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalHarvesterEvaluationCycles**

The total number of times the Harvester has invoked the Policy and Action component to evaluate Harvester policies. (This number corresponds to the number of sampling cycles.)

**Type:** long

**Constraints:** Read Only, Restart Required

**totalHarvesterWatchEvaluations**

The total number of Harvester policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Harvester policies.

Type: long

Constraints: Read Only, Restart Required

**totalHarvesterWatchesTriggered**

The total number of Harvester policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

**totalJMSNotificationsPerformed**

The total number of JMS actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

**totalJMXNotificationsPerformed**

The total number of JMX actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

**totalLogEvaluationCycles**

The total number of times Log policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

**totalLogWatchEvaluations**

The total number of Log policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Log policies.

Type: long

Constraints: Read Only, Restart Required

**totalLogWatchesTriggered**

The total number of Log policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

**totalNotificationsPerformed**

The total number of actions performed.

Type: long

Constraints: Read Only, Restart Required

**totalSMTPNotificationsPerformed**

The total number of SMTP actions successfully fired.

Type: long

Constraints: Read Only, Restart Required

**totalSNMPNotificationsPerformed**

The total number of SNMP actions successfully fired.

Type: long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean

Provides access to policy and action statistical data for the current instance of this server.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the `weblogic.management.runtime.WLDFWatchNotificationRuntimeMBean` entity are as follows:

**activeAlarmWatches**

The names of active alarm policies.

**Type:** array of string

**Constraints:** Read Only, Restart Required

**averageEventDataWatchEvaluationTime**

The average Instrumentation event data evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**averageHarvesterWatchEvaluationTime**

The average Harvester evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**averageLogWatchEvaluationTime**

The average Log evaluation cycle time, in milliseconds.

**Type:** long

**Constraints:** Read Only, Restart Required

**currentActiveAlarmsCount**

The number of active alarms of any type.

**Type:** int

**Constraints:** Read Only, Restart Required

**maximumActiveAlarmsCount**

The maximum number of active alarms at any one time.

**Type:** int

**Constraints:** Read Only, Restart Required

**maximumEventDataWatchEvaluationTime**

The maximum time spent evaluating EventData policies.

Type: long

Constraints: Read Only, Restart Required

**maximumHarvesterWatchEvaluationTime**

The maximum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

**maximumLogWatchEvaluationTime**

The maximum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

**minimumEventDataWatchEvaluationTime**

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

**minimumHarvesterWatchEvaluationTime**

The minimum time spent evaluating Harvester policies.

Type: long

Constraints: Read Only, Restart Required

**minimumLogWatchEvaluationTime**

The minimum time spent evaluating Log policies.

Type: long

Constraints: Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**totalActiveAutomaticResetAlarms**

The total number of active automatically reset alarms.

Type: long

Constraints: Read Only, Restart Required

**totalActiveManualResetAlarms**

The total number of active manually reset alarms.

Type: long

Constraints: Read Only, Restart Required

**totalDIMGNotificationsPerformed**

The total number of Diagnostic Image actions fired. Diagnostic Image files are not true actions, but this records the number of image captures requested by the policy component.

Type: long

Constraints: Read Only, Restart Required

**totalEventDataEvaluationCycles**

The total number of times Instrumentation event data policies have been evaluated.

Type: long

Constraints: Read Only, Restart Required

**totalEventDataWatchEvaluations**

The total number of Instrumentation event data policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Instrumentation event data policies.

Type: long

Constraints: Read Only, Restart Required

**totalEventDataWatchesTriggered**

The total number of Instrumentation event data policies that have evaluated to true and triggered actions.

Type: long

Constraints: Read Only, Restart Required

**totalFailedDIMGNotifications**

The total number of failed Diagnostic Image action requests.

Type: long

Constraints: Read Only, Restart Required

**totalFailedJMSNotifications**

The total number of failed JMS action attempts.

Type: long

Constraints: Read Only, Restart Required

**totalFailedJMXNotifications**

The total number of failed JMX action attempts.

Type: long

Constraints: Read Only, Restart Required

**totalFailedNotifications**

The total number of failed action requests.

Type: long

Constraints: Read Only, Restart Required

**totalFailedSMTPNotifications**

The total number of failed SMTP action attempts.

Type: long



**Constraints:** Read Only, Restart Required

**totalFailedSNMPNotifications**

The total number of failed SNMP action attempts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalHarvesterEvaluationCycles**

The total number of times the Harvester has invoked the Policy and Action component to evaluate Harvester policies. (This number corresponds to the number of sampling cycles.)

**Type:** long

**Constraints:** Read Only, Restart Required

**totalHarvesterWatchEvaluations**

The total number of Harvester policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Harvester policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalHarvesterWatchesTriggered**

The total number of Harvester policies that have evaluated to true and triggered actions.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalJMSNotificationsPerformed**

The total number of JMS actions successfully fired.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalJMXNotificationsPerformed**

The total number of JMX actions successfully fired.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalLogEvaluationCycles**

The total number of times Log policies have been evaluated.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalLogWatchEvaluations**

The total number of Log policies that have been evaluated. For each cycle, the Policy and Action component evaluates all of the enabled Log policies.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalLogWatchesTriggered**

The total number of Log policies that have evaluated to true and triggered actions.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalNotificationsPerformed**

The total number of actions performed.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSMTPNotificationsPerformed**

The total number of SMTP actions successfully fired.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSNMPNotificationsPerformed**

The total number of SNMP actions successfully fired.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean

Attaches an action listener in order to receive action events when a policy evaluates to true. Note that the listener will receive all actions; the caller must filter the output.

Unlike the deprecated WLDFWatchJMXNotificationRuntimeMBean, the action generated by this source is a Java Map object comprised of simple JDK types, and does not require a client dependency on any WLDF code.

Note: As of WebLogic Server 12.2.1, the terms *watch* and *notification* are replaced by *policy* and *action*, respectively. However, the definition of these terms has not changed.

The properties of the weblogic.management.runtime.WLDFWatchNotificationSourceRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WTCRuntimeMBean

This class is used to 1. query, stop, and start WTC connections. 2. query, suspend, and resume WTC imported and exported services. 3. retrieve statistics MBean relates to this WTC server. 4. query status of WTC server.

The properties of the weblogic.management.runtime.WTCRuntimeMBean entity are as follows:

### **WTCServerStartTime**

Returns the timestamp when WTC server starts.

**Type:** long

**Constraints:** Read Only, Restart Required

### **WTCServerStatus**

Returns the status of WTC server itself.

**Type:** string

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WTCStatisticsRuntimeMBean

This class is used to:

- query statistics of WTC connections.
- query statistics of WTC imported and exported services.

The properties of the weblogic.management.runtime.WTCStatisticsRuntimeMBean entity are as follows:

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WebServerRuntimeMBean

Describes a Web Server (HTTP Server)

The properties of the weblogic.management.runtime.WebServerRuntimeMBean entity are as follows:

### **defaultWebServer**

Indicates whether it is the default WebServer or a VirtualHost

**Type:** boolean

**Constraints:** Read Only, Restart Required

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

### **webServerName**

Provides the name of the WebServer.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WorkManagerRuntimeMBean

WorkManager Runtime information.

The properties of the weblogic.management.runtime.WorkManagerRuntimeMBean entity are as follows:

### **applicationName**

Get the name of the application this WorkManager is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

### **completedDaemonRequests**

The number of daemon requests that have been processed

**Type:** long

**Constraints:** Read Only, Restart Required

### **completedRequests**

The number of requests that have been processed, including daemon requests.

**Type:** long

**Constraints:** Read Only, Restart Required

**healthState**

Returns the HealthState mbean for the work manager.

**Type:** weblogic.health.HealthState

**Constraints:** Read Only, Restart Required

**moduleName**

Get the name of the module this WorkManager is associated with

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**partitionName**

Returns the name of the partition that the work manager is associated with.

**Type:** string

**Constraints:** Read Only, Restart Required

**pendingDaemonRequests**

The number of daemon requests in progress.

**Type:** int

**Constraints:** Read Only, Restart Required

**pendingRequests**

The number of waiting requests in the queue, including daemon requests.

**Type:** int

**Constraints:** Read Only, Restart Required

**stuckThreadCount**

The number of threads that are considered to be stuck on the basis of any stuck thread constraints.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean**

Describes Web Service operation state, such as deployment state and runtime statistics. The derived MBean determines whether this state is for a single operation or whether it is aggregated across operations.

This MBean can describe the operation(s) on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the `weblogic.management.runtime.WseeAggregatableBaseOperationRuntimeMBean` entity are as follows:

**dispatchTimeAverage**

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeHigh**

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeLow**

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeTotal**

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**errorCount**

Number of errors sending or receiving a request.

**Type:** int

**Constraints:** Read Only, Restart Required

**executionTimeAverage**

Average operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeHigh**

Longest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeLow**

Shortest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeTotal**

Total time for all operation executions.

**Type:** long

**Constraints:** Read Only, Restart Required

**invocationCount**

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

**Type:** int

**Constraints:** Read Only, Restart Required

**lastError**

Last error that occurred processing a request.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastErrorTime**

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**lastInvocationTime**

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseError**

Last response error to arrive for this client/service (or null if no errors have occurred).

**Type:** string

**Constraints:** Read Only, Restart Required

**lastResponseErrorTime**

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseTime**

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**responseCount**

Total number of responses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseErrorCount**

Total number of errors from responses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseTimeAverage**

Average response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeHigh**

Longest response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeLow**

Lowest response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeTotal**

Total time for all responses generated from operation invocations.

**Type:** long



**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WseeBaseOperationRuntimeMBean**

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service. Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds.

The properties of the `weblogic.management.runtime.WseeBaseOperationRuntimeMBean` entity are as follows:

**dispatchTimeAverage**

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeHigh**

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeLow**

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeTotal**

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**errorCount**

Number of errors sending or receiving a request.

**Type:** int

**Constraints:** Read Only, Restart Required

**executionTimeAverage**

Average operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeHigh**

Longest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeLow**

Shortest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeTotal**

Total time for all operation executions.

**Type:** long

**Constraints:** Read Only, Restart Required

**invocationCount**

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

**Type:** int

**Constraints:** Read Only, Restart Required

**lastError**

Last error that occurred processing a request.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastErrorTime**

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**lastInvocationTime**

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseError**

Last response error to arrive for this client/service (or null if no errors have occurred).

**Type:** string

**Constraints:** Read Only, Restart Required

**lastResponseErrorTime**

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseTime**

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**operationName**

Name of the operation for which runtime information is being provided.

**Type:** string

**Constraints:** Read Only, Restart Required

**responseCount**

Total number of responses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseErrorCount**

Total number of errors from responses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseTimeAverage**

Average response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeHigh**

Longest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

**responseTimeLow**

Lowest response time from the responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

**responseTimeTotal**

Total time for all responses generated from operation invocations.

Type: long

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## **weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean**

Encapsulates runtime information about a particular Web Service cluster front-end instance. This MBean represents a cluster front-end instance (e.g. HttpClusterServlet) that contains a cluster routing function.

The properties of the `weblogic.management.runtime.WseeClusterFrontEndRuntimeMBean` entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

Type: string

Constraints: Read Only, Restart Required

**type**

Returns the type of the MBean.

Type: string

Constraints: Read Only, Restart Required

## **weblogic.management.runtime.WseeClusterRoutingRuntimeMBean**

Encapsulates runtime information about a particular Web Service cluster routing instance (whether it be a front-end router or an in-place router).

The properties of the `weblogic.management.runtime.WseeClusterRoutingRuntimeMBean` entity are as follows:

**lastRoutingFailure**

The exception that caused the last routing failure, or null if no failures have occurred.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastRoutingFailureTime**

The time (in milliseconds since epoch) of the last routing failure (or 0 if no failures have occurred).

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**requestCount**

The number of requests (messages with no RelatesTo header) that have come through this front-end since the server started.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseCount**

The number of responses (messages with a RelatesTo header) that have come through this front-end since the server started.

**Type:** int

**Constraints:** Read Only, Restart Required

**routedRequestCount**

The number of requests that were routed to a specific server instance via routing information in the request (not just load balanced) since the server started.

**Type:** int

**Constraints:** Read Only, Restart Required

**routedResponseCount**

The number of responses that were routed to a specific server instance via routing information in the response (not just load balanced) since the server started.

**Type:** int

**Constraints:** Read Only, Restart Required

**routingFailureCount**

The number of times a message failed to be routed, since the server started.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseeHandlerRuntimeMBean

Provides runtime information about a SOAP message handler that has been associated with a Web service.

SOAP message handlers are used to intercept both the inbound (request) and outbound (response) SOAP messages so that extra processing can be done on the messages. Programmers specify SOAP message handlers for a Web Service using the `@SOAPMessageHandlers` and `@HandlerChain JWS` annotations.

The properties of the `weblogic.management.runtime.WseeHandlerRuntimeMBean` entity are as follows:

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseeMcRuntimeMBean

Describes the state of MakeConnection pending message lists

The properties of the `weblogic.management.runtime.WseeMcRuntimeMBean` entity are as follows:

### **name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

### **type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseeOperationRuntimeMBean

Describes the state of a particular Web Service operation, such as deployment state and runtime statistics about the execution of the operation.

This MBean can describe the operation on a web service client or service. Request statistics relate to outgoing requests on a client or incoming requests on a service.

Response statistics relate to an incoming response on a client or an outgoing response on a service.

Time values are reported in milliseconds

The properties of the weblogic.management.runtime.WseeOperationRuntimeMBean entity are as follows:

**dispatchTimeAverage**

Average operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeHigh**

Longest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeLow**

Shortest operation dispatch time for the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**dispatchTimeTotal**

Total time for all operation dispatches in the current measurement period.

Dispatch time refers to the time for WebLogic Server to process the invocation.

The measurement period typically starts when WebLogic Server is first started.

**Type:** long

**Constraints:** Read Only, Restart Required

**errorCount**

Number of errors sending or receiving a request.

**Type:** int

**Constraints:** Read Only, Restart Required

**executionTimeAverage**

Average operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeHigh**

Longest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeLow**

Shortest operation execution time.

**Type:** long

**Constraints:** Read Only, Restart Required

**executionTimeTotal**

Total time for all operation executions.

**Type:** long

**Constraints:** Read Only, Restart Required

**invocationCount**

Total number of operation invocations in the current measurement period.

The measurement period typically starts when WebLogic Server is first started.

**Type:** int

**Constraints:** Read Only, Restart Required

**lastError**

Last error that occurred processing a request.

**Type:** string

**Constraints:** Read Only, Restart Required

**lastErrorTime**

Time on WebLogic Server of the last error for a request (sending or receiving) was detected expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**lastInvocationTime**

Time of the last operation request to be sent or received (or 0 if no requests have been sent or received).

**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseError**

Last response error to arrive for this client/service (or null if no errors have occurred).

**Type:** string

**Constraints:** Read Only, Restart Required

**lastResponseErrorTime**

Time on WebLogic Server of the last error sending or receiving a response (or 0 if no failures have occurred) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.



**Type:** long

**Constraints:** Read Only, Restart Required

**lastResponseTime**

Time on WebLogic Server of the last response to arrive for this client/service (or 0 if no responses have been received) expressed as the number of milliseconds since midnight, January 1, 1970 UTC.

**Type:** long

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**operationName**

Name of the operation for which runtime information is being provided.

**Type:** string

**Constraints:** Read Only, Restart Required

**policyAttachmentSupport**

Get attachment support for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectName**

Get subject name for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectResourcePattern**

The policySubject parameter must uniquely identify what application, module, service, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used: /{domain}/{instance}/{app}/WEBs|EJBs/{module}/WEBSERVICES/{service}/PORTs/{port}/OPERATIONS/{operation}

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectType**

Get subject type for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**responseCount**

Total number of oresponses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseErrorCount**

Total number of errors from responses generated from operation invocations.

**Type:** int

**Constraints:** Read Only, Restart Required

**responseTimeAverage**

Average response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeHigh**

Longest response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeLow**

Lowest response time from the responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**responseTimeTotal**

Total time for all responses generated from operation invocations.

**Type:** long

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WseePolicyRuntimeMBean**

Specifies runtime information about the WS-Policy files that are available for the Web Service.

Web Services can have one or more WS-Policy files associated with the endpoint itself or its operations; the WS-Policy files specify configuration options for Web Service message-level security (encryption and digital signatures) and reliable SOAP messaging.

Programmers can use the @Policy JWS annotation to associate a WS-Policy file to a Web Service at development time. Administrators can also associate additional WS-Policy files at runtime.

The properties of the weblogic.management.runtime.WseePolicyRuntimeMBean entity are as follows:

**availablePolicies**

**Type:** array of string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseePortPolicyRuntimeMBean

Describes the Web service security policy state of a particular Web service port.

The properties of the weblogic.management.runtime.WseePortPolicyRuntimeMBean entity are as follows:

**authenticationSuccesses**

Total number of authentication successes detected for this port. Only incoming message processing can add to the success count.

**Type:** int

**Constraints:** Read Only, Restart Required

**authenticationViolations**

Total number of authentication violations generated for this port. Only incoming message processing can add to the violation count.

**Type:** int

**Constraints:** Read Only, Restart Required

**authorizationSuccesses**

Total number of authorization successes detected for this port.

**Type:** int

**Constraints:** Read Only, Restart Required

**authorizationViolations**

Total number of authorization violations generated for this port.

**Type:** int

**Constraints:** Read Only, Restart Required

**confidentialitySuccesses**

Total number of confidentiality successes generated for this port. Both outgoing and incoming message processing can add to the success count.

**Type:** int

**Constraints:** Read Only, Restart Required

**confidentialityViolations**

Total number of confidentiality violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

**Type:** int

**Constraints:** Read Only, Restart Required

**integritySuccesses**

Total number of integrity successes generated for this port. Both outgoing and incoming message processing can add to the success count.

**Type:** int

**Constraints:** Read Only, Restart Required

**integrityViolations**

Total number of integrity violations generated for this port. Both outgoing and incoming message processing can add to the violation count.

**Type:** int

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**policyFaults**

Total number of policy faults generated for this port.

**Type:** int

**Constraints:** Read Only, Restart Required

**totalSecurityFaults**

Total number of security faults and violations generated for this port.

**Type:** int

**Constraints:** Read Only, Restart Required

**totalViolations**

Total number of authentication, integrity, and confidentiality violations. Both outgoing and incoming message processing can add to the violation count.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## **weblogic.management.runtime.WseePortRuntimeMBean**

Describes the state of a particular Web Service port.

The properties of the weblogic.management.runtime.WseePortRuntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**policyAttachmentSupport**

Get attachment support for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**policyFaults**

Total number of policy faults.

**Type:** int

**Constraints:** Read Only, Restart Required

**policySubjectAbsolutePortableExpression**

The policySubject AbsolutePortableExpression This is the WSM ResourcePattern AbsolutePortableExpression string

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectName**

Get subject name for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectResourcePattern**

The policySubject parameter must uniquely identify what application, module, service or reference-name, and port (port or operation for WLS Policy) is targeted. The syntax currently used by JRF (see [JRF ATTACHMENT POINT]) for J2EE Webservice Endpoints will be used:

Endpoints will be used:

`/ {domain} / {instance} / {app} / WEBS | EJBs / {module} / WEBSERVICES / {service} | {reference-name} / PORTs / {port}`

**Type:** string

**Constraints:** Read Only, Restart Required

**policySubjectType**

Get subject type for this port MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**portName**

Name of this port.

This attribute corresponds to the "name" attribute of the "port" element in the WSDL that describes the Web service. Programmers specify the name of the port using the

portName attribute of the @WLXXXTransport annotation, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

**Type:** string

**Constraints:** Read Only, Restart Required

**startTime**

Date and time that the Web service endpoint started.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSecurityFaults**

Total number of security faults and violations.

**Type:** int

**Constraints:** Read Only, Restart Required

**transportProtocolType**

Transport protocol used to invoke this Web service, such as HTTP, HTTPS, or JMS.

This attribute determines the transport that is published in the endpoint address section of the WSDL of the Web Service. Programmers specify the transport by the type of @WLXXXTransport JWS annotation they specify, where XXX refers to the type of transport (HTTP, HTTPS, or JMS).

Programmers can also use the WLXXXTransport child element of the jwsc Ant task to specify this attribute.

**Type:** string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseeV2RuntimeMBean

Encapsulates runtime information about a particular Web Service. The name attribute of this MBean will be the value of the webservice-description-name element in webservices.xml

The properties of the weblogic.management.runtime.WseeV2RuntimeMBean entity are as follows:

**URI**

Specifies the URI of this Web service.

This attribute corresponds to the final part of the endpoint address in the WSDL that describes the Web Services. It is specified at development time for JAX-RPC services using the serviceURI attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services, this can be set during compilation.

**Type:** string

**Constraints:** Read Only, Restart Required

**contextPath**

Specifies the context path of this web service.

This attribute corresponds to the initial part of the endpoint address in the WSDL that describes the Web Service. It is specified at development time in JAX-RPC services using the contextPath attribute of the @WLXXXTransport JWS annotation, where XXX refers to the transport, such as HTTP, HTTPS, or JMS. For JAX-WS services the context path is set either during compilation of the service, or by the module (web or EJB) hosting the service.

**Type:** string

**Constraints:** Read Only, Restart Required

**implementationType**

Specifies the implementation type of this service.

Valid values include: JAX-WS 2.0 JAX-RPC 1.1

**Type:** string

**Constraints:** Read Only, Restart Required

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**policyFaults**

Total number of faults generated by security policy handler.

**Type:** int

**Constraints:** Read Only, Restart Required

**serviceName**

Specifies the qualified name of this Web service.

This attribute is calculated based on actual MBean type and of the form:

WseeRuntimeMBean: <app name>#<app version>!<service name>.

WseeV2RuntimeMBean: <app name>#<app version>!<web WAR name or EJB JAR name>!<service name>.

**Type:** string

**Constraints:** Read Only, Restart Required

**startTime**

Date and time that the Web service starts.

**Type:** long

**Constraints:** Read Only, Restart Required

**totalSecurityFaults**

Total number of faults generated by this endpoint.

**Type:** int

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required

**webserviceDescriptionName**

webservice description name for this webservice

**Type:** string

**Constraints:** Read Only, Restart Required

## weblogic.management.runtime.WseeWsruntimeMBean

Encapsulates runtime information about WS-RM functionality. If this MBean is parented by a WseePortRuntimeMBean instance, this MBean represents WS-RM resources contained in a particular Web Service or web service client. If this MBean is parented by ServerRuntimeMBean, this MBean represents WS-RM resources for the entire server/VM (spanning across applications, web services, clients, etc.)

The properties of the weblogic.management.runtime.WseeWsruntimeMBean entity are as follows:

**name**

The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration.

**Type:** string

**Constraints:** Read Only, Restart Required

**sequenceIds**

A list of sequence IDs representing active sequences being managed on the WS-RM destination (receiving side).

**Type:** array of string

**Constraints:** Read Only, Restart Required

**type**

Returns the type of the MBean.

**Type:** string

**Constraints:** Read Only, Restart Required